1. Introduction. [LDF 2006.10.18.]

2. Copyright and licenses. [LDF 2006.10.23.]

This document is part of the LDF Metadata Exchange Utilities, a package for metadata exchange. The LDF Metadata Exchange Utilities contain code from the the IWF Metadata Harvester, a package for metadata harvesting.

The following copyright notice applies to the contents of this document up to and including January 31, 2007:

Copyright © 2006, 2007 IWF Wissen und Medien gGmbH

The following copyright notice applies to all changes and additions to this document starting on February 1, 2007:

Copyright © 2007 Laurence D. Finston

The states of the files used for creating this document as of January 31, 2007 are stored in the revisions of these files with the symbolic tag "`LAST_IWF`" in the CVS repository for the LDF Metadata Exchange Utilities:
`http://cvs.savannah.nongnu.org/viewcvs/iwf-mdh/?root=iwf-mdh`
If necessary, changes and additions after this date can be determined by comparing these revisions with later ones using the GNU diffutils:
`http://www.gnu.org/software/diffutils/diffutils.html`

The author is Laurence D. Finston.

The LDF Metadata Exchange Utilities are free software; you can redistribute them and/or modify them under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

The LDF Metadata Exchange Utilities are distributed in the hope that they will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the section ⟨ GNU General Public License 751 ⟩ for more details.

You should have received a copy of the GNU General Public License along with the LDF Metadata Exchange Utilities; if not, write to the Free Software Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA

See the section ⟨ GNU Free Documentation License 752 ⟩ for the copying conditions that apply **to this document**.

You should have received a copy of the GNU Free Documentation License along with the LDF Metadata Exchange Utilities; if not, write to the Free Software Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA

The LDF Metadata Exchange Utilities are available for downloading from the following FTP server:
`ftp://ftp.gwdg.de/pub/gnu2/iwfmdh/`

Please send bug reports to `lfinsto1@gwdg.de`

The author can be contacted at:

Laurence D. Finston
Kreuzbergring 41
D-37075 Göttingen
Germany

Email: `lfinsto1@gwdg.de`
`s246794@stud.uni-goettingen.de`

3. Formatting commands. [LDF 2006.10.18.]
This section contains formatting commands. They don't appear in the TEX output of CWEAVE.

4. File Lists. [LDF 2006.10.18.]

5. Source Files. [LDF 2006.10.18.]

6. Logical and Hierarchical Order. [LDF 2006.10.18.]

⟨ `nonwin.web` 9 ⟩ ..... Main header file when using The GNU Compiler Collection
⟨ `stdafx.web` 22 ⟩ ..... Main header file when using Microsoft Visual Studio
⟨ `querytyp.web` 49 ⟩ ..... **Query_Type**
⟨ `qtgensql.web` 124 ⟩ ..... **Query_Type**::*generate_sql_string* definition
⟨ `dtsrctyp.web` 159 ⟩ ..... **Datasource_Type**
⟨ `dttmtype.web` 29 ⟩ ..... **Date_Time_Type**
⟨ `idtype.web` 188 ⟩ ..... **Id_Type**
⟨ `scnrtype.web` 213 ⟩ ..... **Scanner_Type**
⟨ `scanner.web` 249 ⟩ ..... Type declarations and the *yylex* function
⟨ `scantest.web` 729 ⟩ ..... The *_tmain* function when using Microsoft Visual Studio
⟨ `dbcrscan.web` 381 ⟩ ..... Dublin Core (XML) Scanner
⟨ `dbcrprsr.w` 363 ⟩ ..... Dublin Core (XML) Parser
⟨ `parser.w` 392 ⟩ ..... The parser
⟨ `main.web` 734 ⟩ ..... The *main* function when using The GNU Compiler Collection

7. Parser files. [LDF 2006.11.16.]

Log

[2006.11.16.] Added this section.

⟨ parser.w 392 ⟩ ..... The main parser input file.
⟨ grpstmnt.w 431 ⟩ ..... Group statements.
⟨ declrtns.w 434 ⟩ ..... Declarations.
⟨ variabls.w 455 ⟩ ..... Variables.
⟨ assign.w 479 ⟩ ..... Assignment.
⟨ commands.w 598 ⟩ ..... Commands.
⟨ dttmexp.w 658 ⟩ ..... Datetime expressions.
⟨ queryexp.w 612 ⟩ ..... Query expressions.
⟨ dtsrcexp.w 636 ⟩ ..... Datasource expressions.

8. Alphabetical Order. [LDF 2006.09.27.]

⟨ assign.w 479 ⟩ ..... Assignment.
⟨ commands.w 598 ⟩ ..... Commands.
⟨ dbcrprsr.w 363 ⟩ ..... Dublin Core (XML) Parser
⟨ dbcrscan.web 381 ⟩ ..... Dublin Core (XML) Scanner
⟨ declrtns.w 434 ⟩ ..... Declarations.
⟨ dtsrcexp.w 636 ⟩ ..... Datasource expressions.
⟨ dtsrctyp.web 159 ⟩ ..... **Datasource_Type**
⟨ dttmexp.w 658 ⟩ ..... Datetime expressions.
⟨ dttmtype.web 29 ⟩ ..... **Date_Time_Type**
⟨ grpstmnt.w 431 ⟩ ..... Group statements.
⟨ idtype.web 188 ⟩ ..... **Id_Type**
⟨ main.web 734 ⟩ ..... The *main* function when using The GNU Compiler Collection
⟨ nonwin.web 9 ⟩ ..... Main header file when using The GNU Compiler Collection
⟨ parser.w 392 ⟩ ..... The parser
⟨ qtgensql.web 124 ⟩ ..... **Query_Type**::*generate_sql_string* definition
⟨ queryexp.w 612 ⟩ ..... Query expressions.
⟨ querytyp.web 49 ⟩ ..... **Query_Type**
⟨ scanner.web 249 ⟩ ..... Type declarations and the *yylex* function
⟨ scantest.web 729 ⟩ ..... The *_tmain* function when using Microsoft Visual Studio
⟨ scnrtype.web 213 ⟩ ..... **Scanner_Type**
⟨ stdafx.web 22 ⟩ ..... Main header file when using Microsoft Visual Studio
⟨ variabls.w 455 ⟩ ..... Variables.

9. Non-Windows Code (`nonwin.web`). [LDF 2006.10.20.]

Log

[LDF 2006.10.20.] Created this file.

[LDF 2006.11.03.] Now including `unistd.h` in order to be be able to use *getopt*.

[LDF 2007.02.13.] Now including `pthread.h`.

⟨ `nonwin.web` 9 ⟩ ≡

```
static char id_string[] = "$Id: nonwin.web,v 1.6 2007/02/13 21:29:36 lfinsto1 Exp $";
```

This code is cited in sections 6 and 8.

This code is used in section 21.

10. Include files.

⟨ Include files 10 ⟩ ≡

```
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <sys/types.h>
#include <cmath>
#include <bitset>
#include <ios>
#include <iomanip>
#include <iostream>
#include <iosfwd>
#include <fstream>
#include <sstream>
#if 0    /* 1 */
#include <strstream>
#endif
#include <new>
#include <ctype.h>
#include <string.h>
#include <map>
#include <stack>
#include <vector>
#include <pthread.h>
#include <sys/types.h>
#include <sys/wait.h>
#include <unistd.h>
#include <time.h>
```

See also sections 24, 30, 50, 125, 160, 189, 214, 250, 364, 382, 393, 679, 730, and 735.

This code is used in sections 20, 21, 28, 47, 122, 158, 186, 211, 247, 361, 379, 390, 676, 728, 733, and 750.

11. Type declarations. [LDF 2006.10.20.]

Log

[LDF 2006.10.20.] Added this section.

12. Mutex_Type. [LDF 2006.10.20.]

Log

[LDF 2006.10.20.] Added this type declaration.

⟨ **Mutex_Type** declaration 12 ⟩ ≡
```
struct Mutex_Type {
  pthread_mutex_t inner_mutex;
  Mutex_Type(void)
  {
    pthread_mutex_init(&inner_mutex, 0);
  }
  ;
  ⟨ Declare Mutex_Type functions 13 ⟩
};
```
This code is used in sections 20 and 21.

13. Lock. [LDF 2007.02.13.]

Log

[LDF 2007.02.13.] Added this function.

⟨ Declare **Mutex_Type** functions 13 ⟩ ≡
```
int lock(void);
```
See also section 15.

This code is used in section 12.

14.

⟨ Define **Mutex_Type** functions 14 ⟩ ≡
```
int Mutex_Type::lock(void)
{
  return pthread_mutex_lock(&inner_mutex);
}
```
See also section 16.

This code is used in section 21.

15. Unlock. [LDF 2007.02.13.]

Log

[LDF 2007.02.13.] Added this function.

⟨ Declare **Mutex_Type** functions 13 ⟩ +≡
```
int unlock(void);
```

16.

```
⟨ Define Mutex_Type functions 14 ⟩ +≡
  int Mutex_Type::unlock(void)
  {
    return pthread_mutex_unlock(&inner_mutex);
  }
```

17. Forward declarations. [LDF 2006.10.31.]

Log

[2006.10.31.] Added this section.

```
⟨ Forward declarations 17 ⟩ ≡
  class Query_Type;
  typedef Query_Type *Query_Node;
  class Scanner_Type;
  typedef Scanner_Type *Scanner_Node;
```

See also sections 32, 52, 162, 191, 216, and 252.

This code is used in sections 20, 47, 48, 122, 123, 186, 187, 211, 212, 247, 248, 361, and 362.

18. extern declarations for global variables. [LDF 2006.10.19.]

Log

[LDF 2006.10.19.] Added this section.

[LDF 2006.11.23.] Added **extern** declarations of **ofstream** *tex_file_strm*, **Mutex_Type** *tex_mutex*, **unsigned short** *tex_file_ctr*, and **string** *tex_filename_str*.

[LDF 2006.11.30.] Added **extern** declaration of **const string** *copyright_tex_str*.

[LDF 2006.11.30.] Added **extern** declaration of **Mutex_Type** *time_mutex*.

```
⟨ extern declarations for global variables 18 ⟩ ≡
  extern Mutex_Type cerr_mutex;
  extern Mutex_Type cout_mutex;
  extern Mutex_Type time_mutex;
  extern ofstream tex_file_strm;
  extern Mutex_Type tex_mutex;
  extern unsigned short tex_file_ctr;
  extern string tex_filename_str;
  extern string copyright_tex_str;
  extern int yydebug;
```

See also section 25.

This code is used in sections 20 and 28.

19. Putting Non-Win together. [LDF 2006.10.20.]

20. This is what's written to `nonwin.h`.

⟨ `nonwin.hh` 20 ⟩ ≡
⟨ Include files 10 ⟩
using namespace std;
⟨ **Mutex_Type** declaration 12 ⟩
⟨ Forward declarations 17 ⟩
⟨ **extern** declarations for global variables 18 ⟩

21. This is what's compiled. [LDF 2007.02.13.]

⟨ nonwin.web 9 ⟩
⟨ Include files 10 ⟩

using namespace std;

⟨ **Mutex_Type** declaration 12 ⟩
⟨ Define **Mutex_Type** functions 14 ⟩

22. stdafx (stdafx.web). [LDF 2006.10.17.]

Log

[LDF 2006.10.17.] Created this file.

⟨ stdafx.web 22 ⟩ ≡
static char *id_string*[] = "$Id: stdafx.web,v 1.4 2007/02/11 16:35:37 lfinsto1 Exp $";
This code is cited in sections 6 and 8.
This code is used in section 27.

23. Preprocessor macro calls. [LDF 2006.10.17.]

⟨ Preprocessor macro calls 23 ⟩ ≡
```
#ifdef WIN_LDF
#pragma once
#endif
```
See also sections 31, 51, 161, 190, 215, 251, and 680.
This code is used in sections 28, 48, 123, 187, 212, 248, and 362.

24. Include files in stdafx.h. [LDF 2006.10.17.]

⟨ Include files 10 ⟩ +≡
```
#include <iostream>
#include <tchar.h>
#define _ATL_CSTRING_EXPLICIT_CONSTRUCTORS      /* einige CString-Konstruktoren sind explizit */
#ifndef VC_EXTRALEAN
#define VC_EXTRALEAN      /* Selten verwendete Teile der Windows-Header nicht einbinden */
#endif
#include <afx.h>
#include <afxwin.h>      /* MFC-Kern- und Standardkomponenten */
#include <afxext.h>      /* MFC-Erweiterungen */
#include <afxdtctl.h>
    /* MFC-Untersttzung fr allgemeine Steuerelemente von Internet Explorer 4 */
#ifndef _AFX_NO_AFXCMN_SUPPORT
#include <afxcmn.h>      /* MFC-Untersttzung fr allgemeine Windows-Steuerelemente */
#endif      /* _AFX_NO_AFXCMN_SUPPORT */
#define _ATL_CSTRING_EXPLICIT_CONSTRUCTORS      /* einige CString-Konstruktoren sind explizit */
#include <atlbase.h>
#include <stdio.h>
#include <stdlib.h>
#include <ios>
#include <iomanip>
#include <fstream>
#include <sstream>
#include <strstream>
```

```
#include <new>
#include <ctype.h>
#include <string.h>
#include <map>
#include <stack>
#include <vector>
#include <time.h>
#include <afxmt.h>
#include "scanner.h"
```

25. extern declarations for global variables. [LDF 2006.10.19.]

Log

[LDF 2006.10.19.] Added this section.

⟨ **extern** declarations for global variables 18 ⟩ +≡

```
  extern ofstream log_strm;
  extern CMutex log_strm_mutex;
  extern CMutex cerr_mutex;
  extern CMutex cout_mutex;
  extern ifstream in_strm;
```

26. Putting `stdafx.web` together.

27. This is what's compiled. [LDF Undated.]

```
#include "stdafx.h"
  ⟨ stdafx.web 22 ⟩
```

28. This is what's written to `stdafx.h`.

⟨ `stdafx.hh` 28 ⟩ ≡
  ⟨ Preprocessor macro calls 23 ⟩
  ⟨ Include files 10 ⟩
  ⟨ **extern** declarations for global variables 18 ⟩

29. Date_Time_Type (`dttmtype.web`). [LDF 2006.10.17.]

Log

[LDF 2006.10.31.] Created this file.

⟨ `dttmtype.web` 29 ⟩ ≡
  static char *id_string*[] = "$Id:␣dttmtype.web,v␣1.6␣2007/02/13␣20:38:51␣lfinsto1␣Exp␣$";
This code is cited in sections 6 and 8.
This code is used in section 47.

30. Include files.

⟨ Include files 10 ⟩ +≡
```
#include "localldf.h"
#ifdef NON_WIN_LDF
#include "nonwin.h"
#else
#include "stdafx.h"
#endif
#include "parser.hxx"
```

31. Preprocessor macro calls.

⟨ Preprocessor macro calls 23 ⟩ +≡
```
#ifdef WIN_LDF
#pragma once
#endif
```

32. Forward declarations. [LDF 2006.10.31.]

```
⟨ Forward declarations 17 ⟩ +≡
  class Query_Type;
  class Date_Time_Type;
  typedef Date_Time_Type *Date_Time_Node;
  namespace Scan_Parse {
    int datetime_assignment_func_0(void *v, Date_Time_Node &curr_date_time_node, int specifier, int
        op, void *val, int type);
    int datetime_assignment_func_1(void *v, Date_Time_Node &d, int op, void *&vec);
  };
```

33. class Date_Time_Type declaration. [LDF 2006.10.17.]

Log

!! BUG FIX: Made function declarations **public**.

[LDF 2006.12.18.] Added **friend** declaration for *yyparse*.

[LDF 2006.12.18.] Added **friend** declaration for **Scan_Parse** :: *datetime_assignment_func_0*.

[LDF 2006.12.18.] Added **friend** declaration for **Scan_Parse** :: *datetime_assignment_func_1*.

```
⟨ Declare class Date_Time_Type 33 ⟩ ≡
  class Date_Time_Type {
    friend class Query_Type;
    friend int Scan_Parse :: datetime_assignment_func_0(void *v, Date_Time_Node
        &curr_date_time_node, int specifier, int op, void *val, int type);
    friend int Scan_Parse :: datetime_assignment_func_1 (void *v, Date_Time_Node &d, int op, void
        *&vec);
    friend int yyparse(void *);
    friend ostream &operator≪(ostream & o, Date_Time_Type &d);
    short *year_range_begin;
    short *year_range_end;
    short *year;
    unsigned short *month;
    unsigned short *day;
    unsigned short *hour;
    unsigned short *minute;
    float *second;
  public: ⟨ Declare Date_Time_Type functions 36 ⟩
  };
```

This code is used in sections 47 and 48.

34. Date_Time_Type functions. [LDF 2006.10.31.]

Log

[2006.10.31.] Added this section.

---

35. Constructors and setting functions. [LDF 2006.10.31.]

Log

[2006.10.31.] Added this section.

---

36. Default constructor. [LDF 2006.10.31.]

Log

[2006.10.31.] Added this function.

⟨ Declare **Date_Time_Type** functions 36 ⟩ ≡

```
Date_Time_Type(void);
```

See also sections 38, 40, and 44.

This code is used in section 33.

37.

⟨ Define **Date_Time_Type** functions 37 ⟩ ≡

```
Date_Time_Type::Date_Time_Type(void)
{
  year_range_begin = 0;
  year_range_end = 0;
  year = 0;
  month = 0;
  day = 0;
  hour = 0;
  minute = 0;
  second = 0;
  return;
}    /* End of the default Date_Time_Type constructor definition. */
```

See also sections 39, 41, and 45.

This code is used in section 47.

38. Destructor. [LDF 2006.12.15.]

Log

[LDF 2006.12.15.] Added this function.

⟨ Declare **Date_Time_Type** functions 36 ⟩ +≡

```
~Date_Time_Type(void);
```

39.

```
⟨ Define Date_Time_Type functions 37 ⟩ +≡
  Date_Time_Type::~Date_Time_Type(void)
  {
    delete year_range_begin;
    delete year_range_end;
    delete year;
    delete month;
    delete day;
    delete hour;
    delete minute;
    delete second;
    return;
  }     /* End of the default Date_Time_Type destructor definition. */
```

40. Assignment. [LDF 2006.12.18.]

Log

[LDF 2006.12.18.] Added this function.

```
⟨ Declare Date_Time_Type functions 36 ⟩ +≡
  Date_Time_Node operator=(const Date_Time_Type &d);
```

41.

```
⟨ Define Date_Time_Type functions 37 ⟩ +≡
  Date_Time_Node Date_Time_Type::operator=(const Date_Time_Type &d)
  {
#if 0     /* 1 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
    stringstream temp_strm;
#ifdef DEBUG_OUTPUT
    temp_strm << "Entering␣`Date_Time_Type'␣assignment␣operator." << endl;
    cerr_mutex.lock();
    cerr << temp_strm.str();
    cerr_mutex.unlock();
    temp_strm.str("");
#endif
    if (this ≡ &d) {
#ifdef DEBUG_OUTPUT
      temp_strm << "In␣`Date_Time_Type::operator=(const␣Date_Time_Type&)':" << endl <<
          "Self-assignment.␣␣Returning␣`this'." << endl;
      cerr_mutex.lock();
      cerr << temp_strm.str();
      cerr_mutex.unlock();
      temp_strm.str("");
#endif
      return this;
    }
    if (year_range_begin ∧ d.year_range_begin) {
      *year_range_begin = *d.year_range_begin;
    }
    else if (year_range_begin ∧ ¬d.year_range_begin) {
      delete year_range_begin;
      year_range_begin = 0;
    }
    else if (¬year_range_begin ∧ d.year_range_begin) {
      year_range_begin = new short(*d.year_range_begin);
    }
    if (year_range_end ∧ d.year_range_end) {
      *year_range_end = *d.year_range_end;
    }
    else if (year_range_end ∧ ¬d.year_range_end) {
      delete year_range_end;
      year_range_end = 0;
    }
    else if (¬year_range_end ∧ d.year_range_end) {
      year_range_end = new short(*d.year_range_end);
    }
    if (year ∧ d.year) {
      *year = *d.year;
    }
    else if (year ∧ ¬d.year) {
```

```
    delete year;
    year = 0;
  }
  else if (¬year ∧ d.year) {
    year = new short(*d.year);
  }
  if (month ∧ d.month) {
    *month = *d.month;
  }
  else if (month ∧ ¬d.month) {
    delete month;
    month = 0;
  }
  else if (¬month ∧ d.month) {
    month = new unsigned short(*d.month);
  }
  if (day ∧ d.day) {
    *day = *d.day;
  }
  else if (day ∧ ¬d.day) {
    delete day;
    day = 0;
  }
  else if (¬day ∧ d.day) {
    day = new unsigned short(*d.day);
  }
  if (hour ∧ d.hour) {
    *hour = *d.hour;
  }
  else if (hour ∧ ¬d.hour) {
    delete hour;
    hour = 0;
  }
  else if (¬hour ∧ d.hour) {
    hour = new unsigned short(*d.hour);
  }
  if (minute ∧ d.minute) {
    *minute = *d.minute;
  }
  else if (minute ∧ ¬d.minute) {
    delete minute;
    minute = 0;
  }
  else if (¬minute ∧ d.minute) {
    minute = new unsigned short(*d.minute);
  }
  if (second ∧ d.second) {
    *second = *d.second;
  }
  else if (second ∧ ¬d.second) {
    delete second;
    second = 0;
```

```
    }
    else if (¬second ∧ d.second) {
      second = new float(*d.second);
    }
#ifdef DEBUG_OUTPUT
    temp_strm ≪ "Exiting␣‘Date_Time_Type’␣assignment␣operator." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    temp_strm.str("");
#endif
    return this;
  }    /* End of the default Date_Time_Type assignment operator definition. */
```

42. Output operator. [LDF 2006.12.18.]

Log

[LDF 2006.12.18.] Added this function.

⟨ Declare non-member functions for **Date_Time_Type** 42 ⟩ ≡

```
ostream & operator≪(ostream & o, Date_Time_Type &d);
```

This code is used in sections 47 and 48.

43.

```
⟨ Define non-member functions for Date_Time_Type 43 ⟩ ≡
  ostream & operator≪(ostream & o, Date_Time_Type &d)
  {
#if 0     /* 1 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
    stringstream temp_strm;
#ifdef DEBUG_OUTPUT
    temp_strm ≪ "Entering␣‘Date_Time_Type’␣output␣operator." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    temp_strm.str("");
#endif
    o ≪ "year_range_begin␣==␣";
    if (d.year_range_begin) o ≪ *d.year_range_begin;
    else o ≪ "NULL";
    o ≪ endl;
    o ≪ "year_range_end␣==␣";
    if (d.year_range_end) o ≪ *d.year_range_end;
    else o ≪ "NULL";
    o ≪ endl;
    o ≪ "year␣==␣";
    if (d.year) o ≪ *d.year;
    else o ≪ "NULL";
    o ≪ endl;
    o ≪ "month␣==␣";
    if (d.month) o ≪ *d.month;
    else o ≪ "NULL";
    o ≪ endl;
    o ≪ "day␣==␣";
    if (d.day) o ≪ *d.day;
    else o ≪ "NULL";
    o ≪ endl;
    o ≪ "hour␣==␣";
    if (d.hour) o ≪ *d.hour;
    else o ≪ "NULL";
    o ≪ endl;
    o ≪ "minute␣==␣";
    if (d.minute) o ≪ *d.minute;
    else o ≪ "NULL";
    o ≪ endl;
    o ≪ "second␣==␣";
    if (d.second) o ≪ *d.second;
    else o ≪ "NULL";
    o ≪ endl;
    return o;
  }     /* End of operator≪ definition. */
```

This code is used in section 47.

44. Show. [LDF 2006.12.15.]

Log

[2006.12.15.] Added this function.

⟨ Declare **Date_Time_Type** functions 36 ⟩ +≡
int *show*(**string** *s* = "'Date_Time_Type:'");

45.

```
⟨ Define Date_Time_Type functions 37 ⟩ +≡
  int Date_Time_Type::show(string s)
  {
    stringstream temp_strm;
    temp_strm ≪ s ≪ endl ≪ "`year_range_begin'␣␣==␣";
    if (year_range_begin ≡ 0) temp_strm ≪ "NULL";
    else temp_strm ≪ *static_cast⟨short *⟩(year_range_begin);
    temp_strm ≪ endl;
    temp_strm ≪ "`year_range_end'␣␣==␣";
    if (year_range_end ≡ 0) temp_strm ≪ "NULL";
    else temp_strm ≪ *static_cast⟨short *⟩(year_range_end);
    temp_strm ≪ endl;
    temp_strm ≪ "`year'␣␣==␣";
    if (year ≡ 0) temp_strm ≪ "NULL";
    else temp_strm ≪ *static_cast⟨short *⟩(year);
    temp_strm ≪ endl;
    temp_strm ≪ "`month'␣␣==␣";
    if (month ≡ 0) temp_strm ≪ "NULL";
    else temp_strm ≪ *static_cast⟨unsigned short *⟩(month);
    temp_strm ≪ endl;
    temp_strm ≪ "`day'␣␣==␣";
    if (day ≡ 0) temp_strm ≪ "NULL";
    else temp_strm ≪ *static_cast⟨unsigned short *⟩(day);
    temp_strm ≪ endl;
    temp_strm ≪ "`hour'␣␣==␣";
    if (hour ≡ 0) temp_strm ≪ "NULL";
    else temp_strm ≪ *static_cast⟨unsigned short *⟩(hour);
    temp_strm ≪ endl;
    temp_strm ≪ "`minute'␣␣==␣";
    if (minute ≡ 0) temp_strm ≪ "NULL";
    else temp_strm ≪ *static_cast⟨unsigned short *⟩(minute);
    temp_strm ≪ endl;
    temp_strm ≪ "`second'␣␣==␣";
    if (second ≡ 0) temp_strm ≪ "NULL";
    else temp_strm ≪ *static_cast⟨float *⟩(second);
    temp_strm ≪ endl;
    cerr ≪ temp_strm.str( );
    temp_strm.str("");
    return 0;
  }     /* End of the default Date_Time_Type::show definition. */
```

46. Putting Date_Time_Type together. [LDF 2006.10.31.]

47. This is what's compiled.

⟨Include files 10⟩
⟨`dttmtype.web` 29⟩

using namespace std;

⟨Forward declarations 17⟩
⟨Declare **class Date_Time_Type** 33⟩
⟨Declare non-member functions for **Date_Time_Type** 42⟩
⟨Define **Date_Time_Type** functions 37⟩
⟨Define non-member functions for **Date_Time_Type** 43⟩

48. This is what's written to `dttmtype.h`.

⟨ `dttmtype.hh` 48 ⟩ ≡
⟨ Preprocessor macro calls 23 ⟩
using namespace std;
⟨ Forward declarations 17 ⟩
⟨ Declare **class Date_Time_Type** 33 ⟩
⟨ Declare non-member functions for **Date_Time_Type** 42 ⟩

49. Query_Type (`querytyp.web`). [LDF 2006.10.17.]

Log

[LDF 2006.10.31.] Created this file.

⟨ `querytyp.web` 49 ⟩ ≡
static char *id_string*[] = "$Id: querytyp.web,v 1.7 2007/02/13 20:40:50 lfinsto1 Exp $";
This code is cited in sections 6 and 8.
This code is used in section 122.

50. Include files.

⟨ Include files 10 ⟩ +≡
```
#include "localldf.h"
#ifdef NON_WIN_LDF
#include "nonwin.h"
#else
#include "stdafx.h"
#endif
#include "parser.hxx"
#include "dttmtype.h"
#include "idtype.h"
#include "scnrtype.h"
#include "scanner.h"
```

51. Preprocessor macro calls.

⟨ Preprocessor macro calls 23 ⟩ +≡
```
#ifdef WIN_LDF
#pragma once
#endif
```

52. Forward declarations. [LDF 2006.11.02.]

Log

[2006.11.02.] Added this section.

⟨ Forward declarations 17 ⟩ +≡
class Scanner_Type;
typedef Scanner_Type ∗**Scanner_Node**;
class Query_Type;
typedef Query_Type ∗**Query_Node**;
class Id_Type;

typedef Id_Type *Id_Node;

53. class Query_Type declaration. . [LDF 2006.10.17.]
The forward declaration of **Query_Type** is needed in order to be able to define **Query_Node** using **typedef**. [LDF 2006.10.31.]

Log

[LDF 2006.10.31.] Added **typedef Query_Type *Query_Node**.

[LDF 2006.10.31.] Working on this declaration.

[LDF 2006.11.13.] Removed **Query_Node** *next*. It was redundant, since *and_node* serves the same purpose.

[LDF 2006.11.13.] Added **vector⟨unsigned short⟩** *target_types* and **static map⟨unsigned short, string⟩** *target_type_map*.

[LDF 2006.11.13.] Added **unsigned short** *field_type* and **static map⟨unsigned short, string⟩** *field_type_map*.

[LDF 2006.11.21.] Added **string** *name* and **Id_Node** *id_node*.

[LDF 2006.11.22.] Added **unsigned short** *query_ctr*.

[LDF 2006.12.12.] Changed **unsigned short** array *match_values* to the non-array **unsigned short** *match_value*.

[LDF 2006.12.12.] Added **static map⟨unsigned short, string⟩** *match_value_map*.

⟨ Declare **class Query_Type** 53 ⟩ ≡
class Query_Type;
typedef Query_Type *Query_Node; **class Query_Type** { ⟨ **friend** declarations for **class Query_Type** 55 ⟩
private: **unsigned short** *query_type*;
unsigned short *field_type*;
unsigned short *value_type*;
vector⟨unsigned short⟩ *target_types*;
static map⟨unsigned short, string⟩ *query_type_map*;
static map⟨unsigned short, string⟩ *field_type_map*;
static map⟨unsigned short, string⟩ *value_type_map*;
static map⟨unsigned short, string⟩ *target_type_map*;
static map⟨unsigned short, string⟩ *match_value_map*;
Id_Node *id_node*;
bool *negated*;
string *name*;
void **value*;
Query_Node *up*;
Query_Node *and_node*;
Query_Node *or_node*;
Query_Node *xor_node*;
unsigned short *match_value*;

See also section 54.

This code is used in sections 122 and 123.

54.

⟨ Declare **class Query_Type** 53 ⟩ +≡
  Scanner_Node *scanner_node*;
  unsigned short *query_ctr*;

public: ⟨ Declare **static Query_Type** constants 57 ⟩
  ⟨ Declare **static Query_Type** variables 78 ⟩
  ⟨ Declare **Query_Type** functions 86 ⟩
  } ;

55. friend declarations for class Query_Type. [LDF 2006.10.31.]

Log

[2006.10.31.] Added this section.

[LDF 2006.11.01.] Changed the name of **Scan_Parse** :: *start_local_query_func* to **Scan_Parse** :: *start_local_database_query_fu*
and the name of **Scan_Parse** :: *end_local_query_func* to **Scan_Parse** :: *end_query_func*.

[LDF 2006.11.01.] Added the **friend** declaration of **Scan_Parse** :: *declare_variable_func*.

[LDF 2006.11.01.] Added the **char** ∗*name* argument to **Scan_Parse** :: *declare_variable_func*.

[LDF 2006.11.02.] Changed the return value of **Scan_Parse** :: *declare_variable_func* from **int** to **Id_Node**.

[LDF 2006.11.02.] Added the **friend** declaration of **Scan_Parse** :: *variable_func*.

[LDF 2006.11.02.] Added the **friend** declaration of **Scan_Parse** :: *query_assignment_func_0*.

[LDF 2006.11.14.] Added the **friend** declaration of *yyparse*.

[LDF 2006.12.15.] Added the **friend** declaration of **Scan_Parse** :: *datetime_assignment_func_0*.

[LDF 2006.12.18.] Added the **friend** declaration of **Scan_Parse** :: *datetime_assignment_func_1*.

[LDF 2006.12.19.] Added the **friend** declaration of **Scan_Parse** :: *query_assignment_func_1*.

⟨ **friend** declarations for **class Query_Type** 55 ⟩ ≡
  friend int *yyparse*(**void** ∗);
  friend void ∗**Scan_Parse** :: *variable_func*(**void** ∗*v*, **char** ∗*name*);
  friend Id_Node Scan_Parse :: *declare_variable_func*(**void** ∗*v*, **const unsigned short** *type*, **char** ∗*name*);
  friend void ∗**Scan_Parse** :: *query_assignment_func_0*(**void** ∗*v*, **void** ∗*object*, **unsigned int** *assignment_type*, **unsigned int** *arg_0*, **unsigned int** *arg_1*, **void** ∗*value*, **bool** *negate*);
  friend int Scan_Parse :: *query_assignment_func_1*(**Scanner_Node** *scanner_node*, **Id_Node** &*curr_id_node*, **void** ∗&*field_specifier*, **int** *assignment_operator*, **int** *negation_optional*, **int** *match_term_optional*, **void** ∗&*v*, **int** *type*);
  friend int Scan_Parse :: *start_local_database_query_func*(**void** ∗*v*);
  friend int Scan_Parse :: *end_query_func*(**void** ∗*v*);
  friend int Scan_Parse :: *datetime_assignment_func_0*(**void** ∗*v*, **Date_Time_Node** &*curr_date_time_node*, **int** *specifier*, **int** *op*, **void** ∗*val*, **int** *type*);
  friend int Scan_Parse :: *datetime_assignment_func_1*(**void** ∗*v*, **Date_Time_Node** &*d*, **int** *op*, **void** ∗&*vec*);

This code is used in section 53.

56. Declare static Query_Type constants and variables. [LDF 2006.10.31.]

57. Types for *value_type*, *field_type*, *query_type*, and *target_type*. [LDF 2006.10.31.]

Log

[2006.10.31.] Added this section.

⟨ Declare **static Query_Type** constants 57 ⟩ ≡
```
static const unsigned short QUERY_TYPE_NULL_TYPE;
```
See also sections 59, 62, 64, 65, 66, 73, 75, and 82.

This code is used in section 54.

58.

⟨ Initialize **static Query_Type** constants 58 ⟩ ≡
```
const unsigned short Query_Type::QUERY_TYPE_NULL_TYPE = 0;
```
See also sections 60, 67, 68, 70, 71, 72, 74, 76, and 83.

This code is used in section 122.

59. Types for *query_type*. [LDF 2006.10.31.]

Log

[2006.10.31.] Added this section.

[LDF 2006.11.13.] Added **static const unsigned short** TOP_TYPE.

⟨ Declare **static Query_Type** constants 57 ⟩ +≡
```
static const unsigned short TOP_TYPE;
static const unsigned short AND_TYPE;
static const unsigned short OR_TYPE;
static const unsigned short XOR_TYPE;
```

60.

⟨ Initialize **static Query_Type** constants 58 ⟩ +≡
```
const unsigned short Query_Type::TOP_TYPE = 1;
const unsigned short Query_Type::AND_TYPE = 2;
const unsigned short Query_Type::OR_TYPE = 3;
const unsigned short Query_Type::XOR_TYPE = 4;
```

61. Types for *field_type*. [LDF 2006.11.13.]

Log

[LDF 2006.11.13.] Added this section with the declarations of AUTHOR_FIELD, CONTRIBUTOR_FIELD, TITLE_FIELD, and SUBJECT_FIELD.

[LDF 2006.12.05.] Added **static const unsigned short** CREATOR_FIELD.

[LDF 2006.12.07.] Added the **static const unsigned** *shorts* AUTHOR_SURNAME_FIELD, AUTHOR_GIVEN_NAME_FIELD, AUTHOR_PREFIX_FIELD, CONTRIBUTOR_SURNAME_FIELD, CONTRIBUTOR_GIVEN_NAME_FIELD, and CONTRIBUTOR_PREFIX_FI

[LDF 2006.12.12.] Added the **static const unsigned short** AUTHOR_SURNAME_FIELD,

[LDF 2006.12.12.] Added the **static const unsigned short** MAIN_CANONICAL_TITLE_FIELD.

[LDF 2006.12.12.] Added **static const unsigned** *shorts* to refer to additional tables from the OAI database (dc_test).

[LDF 2006.12.12.] Added **static const unsigned** *shorts* to refer to additional tables from the PICA database (PICA_DB).

62. Tables. [LDF 2006.12.13.]

⟨ Declare **static Query_Type** constants 57 ⟩ +≡

```
static const unsigned short ACCESS_NUMBER_FIELD;
static const unsigned short AUTHOR_FIELD;
static const unsigned short BIBLIOGRAPHIC_TYPE_FIELD;
static const unsigned short CALL_NUMBER_FIELD;
static const unsigned short CLASSIFICATION_FIELD;
static const unsigned short COMPANY_FIELD;
static const unsigned short CONTENT_SUMMARY_FIELD;
static const unsigned short CONTRIBUTOR_FIELD;
static const unsigned short CREATOR_FIELD;
static const unsigned short DATABASE_PROVIDER_FIELD;
static const unsigned short DESCRIPTION_FIELD;
static const unsigned short EXEMPLAR_PRODUCTION_NUMBER_FIELD;
static const unsigned short IDENTIFIER_FIELD;
static const unsigned short INSTITUTION_FIELD;
static const unsigned short LANGUAGE_FIELD;
static const unsigned short MAIN_CANONICAL_TITLE_FIELD;
static const unsigned short PERMUTATION_PATTERN_FIELD;
static const unsigned short PHYSICAL_DESCRIPTION_FIELD;
static const unsigned short PERSON_FIELD;
static const unsigned short PUBLISHER_FIELD;
static const unsigned short RECORD_FIELD;
static const unsigned short REMOTE_ACCESS_FIELD;
static const unsigned short RIGHTS_FIELD;
static const unsigned short SOURCE_FIELD;
static const unsigned short SUBJECT_FIELD;
static const unsigned short SUPERORDINATE_ENTITIES_FIELD;
static const unsigned short TITLE_FIELD;
static const unsigned short TYPE_FIELD;
```

63. Columns. [LDF 2006.12.13.]

64. Authors. [LDF 2006.12.13.]

⟨ Declare **static Query_Type** constants 57 ⟩ +≡
```
static const unsigned short AUTHOR_SURNAME_FIELD;
static const unsigned short AUTHOR_GIVEN_NAME_FIELD;
static const unsigned short AUTHOR_PREFIX_FIELD;
```

65. Contributors. [LDF 2006.12.14.]

⟨ Declare **static Query_Type** constants 57 ⟩ +≡
```
static const unsigned short CONTRIBUTOR_SURNAME_FIELD;
static const unsigned short CONTRIBUTOR_GIVEN_NAME_FIELD;
static const unsigned short CONTRIBUTOR_PREFIX_FIELD;
```

66. Records. [LDF 2006.12.14.]

⟨ Declare **static Query_Type** constants 57 ⟩ +≡
```
static const unsigned short RECORD_ID_FIELD;
static const unsigned short RECORD_ELN_ORIGINAL_ENTRY_FIELD;
static const unsigned short RECORD_ELN_MOST_RECENT_CHANGE_FIELD;
static const unsigned short RECORD_ELN_STATUS_CHANGE_FIELD;
static const unsigned short RECORD_IDENTIFICATION_NUMBER_FIELD;
static const unsigned short RECORD_DATE_ORIGINAL_ENTRY_FIELD;
static const unsigned short RECORD_DATE_MOST_RECENT_CHANGE_FIELD;
static const unsigned short RECORD_DATE_STATUS_CHANGE_FIELD;
static const unsigned short RECORD_SOURCE_ID_FIELD;
static const unsigned short RECORD_YEAR_APPEARANCE_BEGIN_FIELD;
static const unsigned short RECORD_YEAR_APPEARANCE_END_FIELD;
static const unsigned short RECORD_YEAR_APPEARANCE_RAK_WB_FIELD;
static const unsigned short RECORD_YEAR_APPEARANCE_ORIGINAL_FIELD;
```

67. Initialization. [LDF 2006.12.13.]

⟨ Initialize **static Query_Type** constants 58 ⟩ +≡

68. Tables. [LDF 2006.12.13.]

⟨ Initialize **static Query_Type** constants 58 ⟩ +≡

```
const unsigned short Query_Type::ACCESS_NUMBER_FIELD = 1;
const unsigned short Query_Type::AUTHOR_FIELD = 2;
const unsigned short Query_Type::BIBLIOGRAPHIC_TYPE_FIELD = 3;
const unsigned short Query_Type::CALL_NUMBER_FIELD = 4;
const unsigned short Query_Type::CLASSIFICATION_FIELD = 5;
const unsigned short Query_Type::COMPANY_FIELD = 6;
const unsigned short Query_Type::CONTENT_SUMMARY_FIELD = 7;
const unsigned short Query_Type::CONTRIBUTOR_FIELD = 8;
const unsigned short Query_Type::CREATOR_FIELD = 9;
const unsigned short Query_Type::DATABASE_PROVIDER_FIELD = 10;
const unsigned short Query_Type::DESCRIPTION_FIELD = 11;
const unsigned short Query_Type::EXEMPLAR_PRODUCTION_NUMBER_FIELD = 12;
const unsigned short Query_Type::IDENTIFIER_FIELD = 13;
const unsigned short Query_Type::INSTITUTION_FIELD = 14;
const unsigned short Query_Type::LANGUAGE_FIELD = 15;
const unsigned short Query_Type::MAIN_CANONICAL_TITLE_FIELD = 16;
const unsigned short Query_Type::PERMUTATION_PATTERN_FIELD = 17;
const unsigned short Query_Type::PERSON_FIELD = 18;
const unsigned short Query_Type::PHYSICAL_DESCRIPTION_FIELD = 19;
const unsigned short Query_Type::PUBLISHER_FIELD = 20;
const unsigned short Query_Type::RECORD_FIELD = 21;
const unsigned short Query_Type::REMOTE_ACCESS_FIELD = 22;
const unsigned short Query_Type::RIGHTS_FIELD = 23;
const unsigned short Query_Type::SOURCE_FIELD = 24;
const unsigned short Query_Type::SUPERORDINATE_ENTITIES_FIELD = 25;
const unsigned short Query_Type::TITLE_FIELD = 26;
const unsigned short Query_Type::SUBJECT_FIELD = 27;
const unsigned short Query_Type::TYPE_FIELD = 28;
```

69. Columns. [LDF 2006.12.13.]

70. Authors. [LDF 2006.12.13.]

⟨ Initialize **static Query_Type** constants 58 ⟩ +≡

```
const unsigned short Query_Type::AUTHOR_SURNAME_FIELD = 200;
const unsigned short Query_Type::AUTHOR_GIVEN_NAME_FIELD = 201;
const unsigned short Query_Type::AUTHOR_PREFIX_FIELD = 202;
```

71. Contributors. [LDF 2006.12.13.]

⟨ Initialize **static Query_Type** constants 58 ⟩ +≡

```
const unsigned short Query_Type::CONTRIBUTOR_SURNAME_FIELD = 203;
const unsigned short Query_Type::CONTRIBUTOR_GIVEN_NAME_FIELD = 204;
const unsigned short Query_Type::CONTRIBUTOR_PREFIX_FIELD = 205;
```

72. Records. [LDF 2006.12.14.]

⟨ Initialize **static Query_Type** constants 58 ⟩ +≡
```
const unsigned short Query_Type::RECORD_ID_FIELD = 500;
const unsigned short Query_Type::RECORD_ELN_ORIGINAL_ENTRY_FIELD = 501;
const unsigned short Query_Type::RECORD_ELN_MOST_RECENT_CHANGE_FIELD = 502;
const unsigned short Query_Type::RECORD_ELN_STATUS_CHANGE_FIELD = 503;
const unsigned short Query_Type::RECORD_IDENTIFICATION_NUMBER_FIELD = 504;
const unsigned short Query_Type::RECORD_DATE_ORIGINAL_ENTRY_FIELD = 505;
const unsigned short Query_Type::RECORD_DATE_MOST_RECENT_CHANGE_FIELD = 506;
const unsigned short Query_Type::RECORD_DATE_STATUS_CHANGE_FIELD = 507;
const unsigned short Query_Type::RECORD_SOURCE_ID_FIELD = 508;
const unsigned short Query_Type::RECORD_YEAR_APPEARANCE_BEGIN_FIELD = 509;
const unsigned short Query_Type::RECORD_YEAR_APPEARANCE_END_FIELD = 510;
const unsigned short Query_Type::RECORD_YEAR_APPEARANCE_RAK_WB_FIELD = 501;
const unsigned short Query_Type::RECORD_YEAR_APPEARANCE_ORIGINAL_FIELD = 512;
```

73. Types for *value_type*. [LDF 2006.10.31.]

Log

[2006.10.31.] Added this section.

⟨ Declare **static Query_Type** constants 57 ⟩ +≡
```
static const unsigned short INT_TYPE;
static const unsigned short FLOAT_TYPE;
static const unsigned short QUERY_TYPE_STRING_TYPE;
static const unsigned short DATE_TIME_TYPE;
```

74.

⟨ Initialize **static Query_Type** constants 58 ⟩ +≡
```
const unsigned short Query_Type::INT_TYPE = 1;
const unsigned short Query_Type::FLOAT_TYPE = 2;
const unsigned short Query_Type::QUERY_TYPE_STRING_TYPE = 3;
const unsigned short Query_Type::DATE_TIME_TYPE = 4;
```

75. Types for *target_types*. [LDF 2006.11.13.]

Log

[LDF 2006.11.13.] Added this section with the declarations of the **static const unsigned** *shorts* `LOCAL_DATABASE_TARGET` `LOCAL_SERVER_TARGET`, `REMOTE_DATABASE_TARGET`, and `REMOTE_SERVER_TARGET`.

⟨ Declare **static Query_Type** constants 57 ⟩ +≡
```
static const unsigned short LOCAL_DATABASE_TARGET;
static const unsigned short LOCAL_SERVER_TARGET;
static const unsigned short REMOTE_DATABASE_TARGET;
static const unsigned short REMOTE_SERVER_TARGET;
```

76.

⟨ Initialize **static Query_Type** constants 58 ⟩ +≡

```
const unsigned short Query_Type::LOCAL_DATABASE_TARGET = 1;
const unsigned short Query_Type::LOCAL_SERVER_TARGET = 2;
const unsigned short Query_Type::REMOTE_DATABASE_TARGET = 3;
const unsigned short Query_Type::REMOTE_SERVER_TARGET = 4;
```

77. Flags. [LDF 2006.12.13.]

Log

[2006.12.13.] Added this section.

⟨ Preprocessor macro definitions 77 ⟩ ≡

```
#define QUERY_TYPE_BITSET_SIZE 96
```

See also section 365.

This code is used in sections 122, 123, and 379.

78.

⟨ Declare **static Query_Type** variables 78 ⟩ ≡

```
static bitset < QUERY_TYPE_BITSET_SIZE > NULL_BITSET;
```

See also section 79.

This code is used in section 54.

79. Tables. [LDF 2006.12.13.]

⟨ Declare **static Query_Type** variables 78 ⟩ +≡

```
static bitset < QUERY_TYPE_BITSET_SIZE > ACCESS_NUMBER_FLAG;
static bitset < QUERY_TYPE_BITSET_SIZE > AUTHOR_FLAG;
static bitset < QUERY_TYPE_BITSET_SIZE > AUTHOR_SURNAME_FLAG;
static bitset < QUERY_TYPE_BITSET_SIZE > AUTHOR_GIVEN_NAME_FLAG;
static bitset < QUERY_TYPE_BITSET_SIZE > AUTHOR_PREFIX_FLAG;
static bitset < QUERY_TYPE_BITSET_SIZE > BIBLIOGRAPHIC_TYPE_FLAG;
static bitset < QUERY_TYPE_BITSET_SIZE > CALL_NUMBER_FLAG;
static bitset < QUERY_TYPE_BITSET_SIZE > CLASSIFICATION_FLAG;
static bitset < QUERY_TYPE_BITSET_SIZE > COMPANY_FLAG;
static bitset < QUERY_TYPE_BITSET_SIZE > CONTENT_SUMMARY_FLAG;
static bitset < QUERY_TYPE_BITSET_SIZE > CONTRIBUTOR_SURNAME_FLAG;
static bitset < QUERY_TYPE_BITSET_SIZE > CONTRIBUTOR_GIVEN_NAME_FLAG;
static bitset < QUERY_TYPE_BITSET_SIZE > CONTRIBUTOR_PREFIX_FLAG;
static bitset < QUERY_TYPE_BITSET_SIZE > CREATOR_FLAG;
static bitset < QUERY_TYPE_BITSET_SIZE > CONTRIBUTOR_FLAG;
static bitset < QUERY_TYPE_BITSET_SIZE > DATABASE_PROVIDER_FLAG;
static bitset < QUERY_TYPE_BITSET_SIZE > DESCRIPTION_FLAG;
static bitset < QUERY_TYPE_BITSET_SIZE > EXEMPLAR_PRODUCTION_NUMBER_FLAG;
static bitset < QUERY_TYPE_BITSET_SIZE > IDENTIFIER_FLAG;
static bitset < QUERY_TYPE_BITSET_SIZE > INSTITUTION_FLAG;
static bitset < QUERY_TYPE_BITSET_SIZE > LANGUAGE_FLAG;
static bitset < QUERY_TYPE_BITSET_SIZE > MAIN_CANONICAL_TITLE_FLAG;
static bitset < QUERY_TYPE_BITSET_SIZE > PERMUTATION_PATTERN_FLAG;
static bitset < QUERY_TYPE_BITSET_SIZE > PERSON_FLAG;
static bitset < QUERY_TYPE_BITSET_SIZE > PHYSICAL_DESCRIPTION_FLAG;
static bitset < QUERY_TYPE_BITSET_SIZE > PUBLISHER_FLAG;
static bitset < QUERY_TYPE_BITSET_SIZE > RECORD_FLAG;
static bitset < QUERY_TYPE_BITSET_SIZE > RECORD_ID_FLAG;
static bitset < QUERY_TYPE_BITSET_SIZE > RECORD_ELN_ORIGINAL_ENTRY_FLAG;
static bitset < QUERY_TYPE_BITSET_SIZE > RECORD_ELN_MOST_RECENT_CHANGE_FLAG;
static bitset < QUERY_TYPE_BITSET_SIZE > RECORD_ELN_STATUS_CHANGE_FLAG;
static bitset < QUERY_TYPE_BITSET_SIZE > RECORD_IDENTIFICATION_NUMBER_FLAG;
static bitset < QUERY_TYPE_BITSET_SIZE > RECORD_DATE_ORIGINAL_ENTRY_FLAG;
static bitset < QUERY_TYPE_BITSET_SIZE > RECORD_DATE_MOST_RECENT_CHANGE_FLAG;
static bitset < QUERY_TYPE_BITSET_SIZE > RECORD_DATE_STATUS_CHANGE_FLAG;
static bitset < QUERY_TYPE_BITSET_SIZE > RECORD_SOURCE_ID_FLAG;
static bitset < QUERY_TYPE_BITSET_SIZE > RECORD_YEAR_APPEARANCE_BEGIN_FLAG;
static bitset < QUERY_TYPE_BITSET_SIZE > RECORD_YEAR_APPEARANCE_END_FLAG;
static bitset < QUERY_TYPE_BITSET_SIZE > RECORD_YEAR_APPEARANCE_RAK_WB_FLAG;
static bitset < QUERY_TYPE_BITSET_SIZE > RECORD_YEAR_APPEARANCE_ORIGINAL_FLAG;
static bitset < QUERY_TYPE_BITSET_SIZE > REMOTE_ACCESS_FLAG;
static bitset < QUERY_TYPE_BITSET_SIZE > RIGHTS_FLAG;
static bitset < QUERY_TYPE_BITSET_SIZE > SOURCE_FLAG;
static bitset < QUERY_TYPE_BITSET_SIZE > SUBJECT_FLAG;
static bitset < QUERY_TYPE_BITSET_SIZE > SUPERORDINATE_ENTITIES_FLAG;
static bitset < QUERY_TYPE_BITSET_SIZE > TITLE_FLAG;
static bitset < QUERY_TYPE_BITSET_SIZE > TYPE_FLAG;
```

80.

⟨ Initialize **static Query_Type** variables 80 ⟩ ≡

```
bitset < QUERY_TYPE_BITSET_SIZE > Query_Type::NULL_BITSET;
bitset < QUERY_TYPE_BITSET_SIZE > Query_Type::ACCESS_NUMBER_FLAG;
bitset < QUERY_TYPE_BITSET_SIZE > Query_Type::AUTHOR_FLAG;
bitset < QUERY_TYPE_BITSET_SIZE > Query_Type::BIBLIOGRAPHIC_TYPE_FLAG;
bitset < QUERY_TYPE_BITSET_SIZE > Query_Type::CALL_NUMBER_FLAG;
bitset < QUERY_TYPE_BITSET_SIZE > Query_Type::CLASSIFICATION_FLAG;
bitset < QUERY_TYPE_BITSET_SIZE > Query_Type::COMPANY_FLAG;
bitset < QUERY_TYPE_BITSET_SIZE > Query_Type::CONTENT_SUMMARY_FLAG;
bitset < QUERY_TYPE_BITSET_SIZE > Query_Type::CREATOR_FLAG;
bitset < QUERY_TYPE_BITSET_SIZE > Query_Type::CONTRIBUTOR_FLAG;
bitset < QUERY_TYPE_BITSET_SIZE > Query_Type::DATABASE_PROVIDER_FLAG;
bitset < QUERY_TYPE_BITSET_SIZE > Query_Type::DESCRIPTION_FLAG;
bitset < QUERY_TYPE_BITSET_SIZE > Query_Type::EXEMPLAR_PRODUCTION_NUMBER_FLAG;
bitset < QUERY_TYPE_BITSET_SIZE > Query_Type::IDENTIFIER_FLAG;
bitset < QUERY_TYPE_BITSET_SIZE > Query_Type::INSTITUTION_FLAG;
bitset < QUERY_TYPE_BITSET_SIZE > Query_Type::LANGUAGE_FLAG;
bitset < QUERY_TYPE_BITSET_SIZE > Query_Type::MAIN_CANONICAL_TITLE_FLAG;
bitset < QUERY_TYPE_BITSET_SIZE > Query_Type::PERMUTATION_PATTERN_FLAG;
bitset < QUERY_TYPE_BITSET_SIZE > Query_Type::PERSON_FLAG;
bitset < QUERY_TYPE_BITSET_SIZE > Query_Type::PHYSICAL_DESCRIPTION_FLAG;
bitset < QUERY_TYPE_BITSET_SIZE > Query_Type::PUBLISHER_FLAG;
bitset < QUERY_TYPE_BITSET_SIZE > Query_Type::RECORD_FLAG;
bitset < QUERY_TYPE_BITSET_SIZE > Query_Type::RECORD_ID_FLAG;
bitset < QUERY_TYPE_BITSET_SIZE > Query_Type::RECORD_ELN_ORIGINAL_ENTRY_FLAG;
bitset < QUERY_TYPE_BITSET_SIZE > Query_Type::RECORD_ELN_MOST_RECENT_CHANGE_FLAG;
bitset < QUERY_TYPE_BITSET_SIZE > Query_Type::RECORD_ELN_STATUS_CHANGE_FLAG;
bitset < QUERY_TYPE_BITSET_SIZE > Query_Type::RECORD_IDENTIFICATION_NUMBER_FLAG;
bitset < QUERY_TYPE_BITSET_SIZE > Query_Type::RECORD_DATE_ORIGINAL_ENTRY_FLAG;
bitset < QUERY_TYPE_BITSET_SIZE > Query_Type::RECORD_DATE_MOST_RECENT_CHANGE_FLAG;
bitset < QUERY_TYPE_BITSET_SIZE > Query_Type::RECORD_DATE_STATUS_CHANGE_FLAG;
bitset < QUERY_TYPE_BITSET_SIZE > Query_Type::RECORD_SOURCE_ID_FLAG;
bitset < QUERY_TYPE_BITSET_SIZE > Query_Type::RECORD_YEAR_APPEARANCE_BEGIN_FLAG;
bitset < QUERY_TYPE_BITSET_SIZE > Query_Type::RECORD_YEAR_APPEARANCE_END_FLAG;
bitset < QUERY_TYPE_BITSET_SIZE > Query_Type::RECORD_YEAR_APPEARANCE_RAK_WB_FLAG;
bitset < QUERY_TYPE_BITSET_SIZE > Query_Type::RECORD_YEAR_APPEARANCE_ORIGINAL_FLAG;
bitset < QUERY_TYPE_BITSET_SIZE > Query_Type::REMOTE_ACCESS_FLAG;
bitset < QUERY_TYPE_BITSET_SIZE > Query_Type::RIGHTS_FLAG;
bitset < QUERY_TYPE_BITSET_SIZE > Query_Type::SOURCE_FLAG;
bitset < QUERY_TYPE_BITSET_SIZE > Query_Type::SUBJECT_FLAG;
bitset < QUERY_TYPE_BITSET_SIZE > Query_Type::SUPERORDINATE_ENTITIES_FLAG;
bitset < QUERY_TYPE_BITSET_SIZE > Query_Type::TITLE_FLAG;
bitset < QUERY_TYPE_BITSET_SIZE > Query_Type::TYPE_FLAG;
bitset < QUERY_TYPE_BITSET_SIZE > Query_Type::AUTHOR_SURNAME_FLAG;
bitset < QUERY_TYPE_BITSET_SIZE > Query_Type::AUTHOR_GIVEN_NAME_FLAG;
bitset < QUERY_TYPE_BITSET_SIZE > Query_Type::AUTHOR_PREFIX_FLAG;
bitset < QUERY_TYPE_BITSET_SIZE > Query_Type::CONTRIBUTOR_SURNAME_FLAG;
bitset < QUERY_TYPE_BITSET_SIZE > Query_Type::CONTRIBUTOR_GIVEN_NAME_FLAG;
bitset < QUERY_TYPE_BITSET_SIZE > Query_Type::CONTRIBUTOR_PREFIX_FLAG;
```

See also section 81.

This code is used in section 122.

81. Initialize static Query_Type variables. [LDF 2006.10.31.]

Log

[2006.10.31.] Added this section.

[LDF 2006.11.13.] Added declaration of *target_type_map*.

[LDF 2006.11.13.] Added declaration of *field_type_map*.

[LDF 2006.12.12.] Added declaration of *match_value_map*.

⟨ Initialize **static Query_Type** variables 80 ⟩ +≡
```
map⟨unsigned short, string⟩ Query_Type::query_type_map;
map⟨unsigned short, string⟩ Query_Type::field_type_map;
map⟨unsigned short, string⟩ Query_Type::value_type_map;
map⟨unsigned short, string⟩ Query_Type::target_type_map;
map⟨unsigned short, string⟩ Query_Type::match_value_map;
```

82. Constants for *match_value*. [LDF 2006.12.11.]

Log

[LDF 2006.12.11.] Added this section with the declarations of the **static const unsigned** *shorts* `LIKE_VALUE` and `FREETEXT_VALUE`.

[LDF 2006.12.12.] Added **unsigned short** `CONTAINS_VALUE`.

⟨ Declare **static Query_Type** constants 57 ⟩ +≡
```
static const unsigned short CONTAINS_VALUE;
static const unsigned short FREETEXT_VALUE;
static const unsigned short LIKE_VALUE;
```

83.

⟨ Initialize **static Query_Type** constants 58 ⟩ +≡
```
const unsigned short Query_Type::CONTAINS_VALUE = 1;
const unsigned short Query_Type::FREETEXT_VALUE = 2;
const unsigned short Query_Type::LIKE_VALUE = 3;
```

84. Query_Type functions. [LDF 2006.10.31.]

Log

[2006.10.31.] Added this section.

85. Constructor and setting functions. [LDF 2006.10.31.]

86. Default constructor. [LDF 2006.10.31.]

Log

[2006.10.31.] Added this function.

⟨ Declare **Query_Type** functions 86 ⟩ ≡
```
Query_Type(void);
```
See also sections 88, 90, 95, 99, 101, 105, 110, 114, and 115.

This code is used in section 54.

87.

⟨ Define **Query_Type** functions 87 ⟩ ≡
```
Query_Type::Query_Type(void)
{
  query_type = QUERY_TYPE_NULL_TYPE;
  field_type = QUERY_TYPE_NULL_TYPE;
  value_type = QUERY_TYPE_NULL_TYPE;
  negated = false;
  id_node = 0;
  value = 0;
  up = 0;
  and_node = 0;
  or_node = 0;
  xor_node = 0;
  query_ctr = 0;
  match_value = QUERY_TYPE_NULL_TYPE;
  scanner_node = 0;
  return;
}    /* End of default Query_Type constructor definition. */
```
See also sections 89, 91, 92, 93, 94, 96, 97, 98, 100, 102, 103, 104, 106, 107, 108, 111, 112, 113, 116, 117, 118, 119, 120, 127, 128, 129, 130, 131, 132, 133, 134, 135, 136, 137, 138, 139, 140, 141, 142, 144, 145, 146, 147, 148, 149, 150, 151, 152, 153, 154, 155, and 156.

This code is used in sections 122 and 158.

88. Set. [LDF 2006.10.31.]

Log

[2006.10.31.] Added this function.

[LDF 2006.11.13.] Added **unsigned short** *ffield* and *ttarget* arguments. Made all arguments optional, except the first one, i.e., *qquery_type*.

⟨ Declare **Query_Type** functions 86 ⟩ +≡
```
int set(unsigned short qquery_type, unsigned short ffield_type = 0, unsigned short
    vvalue_type = 0, unsigned short ttarget_type = 0, bool nnegated = false, void
    *vvalue = 0, Query_Node uup = 0, Query_Node aand_node = 0, Query_Node
    oor_node = 0, Query_Node xxor_node = 0, Scanner_Node sscanner_node = 0);
```

89.

⟨ Define **Query_Type** functions 87 ⟩ +≡

```
int Query_Type::set(unsigned short qquery_type, unsigned short ffield_type, unsigned short
        vvalue_type, unsigned short target_type, bool nnegated, void *vvalue, Query_Node uup,
        Query_Node aand_node, Query_Node oor_node, Query_Node xxor_node, Scanner_Node
        sscanner_node)
{
  match_value = QUERY_TYPE_NULL_TYPE;
  return 0;
}    /* End of Query_Type::set definition. */
```

90. Destructor. [LDF 2006.10.31.]

To Do

[LDF 2006.12.12.] Change the way some *values* are handled, depending on the *field_type*. I've added dummy code for new fields that assumes that all of the associated values are pointers to **string**. This will probably not be the case.

Log

[2006.10.31.] Added this function.

[LDF 2006.11.14.] [LDF 2006.11.14.] !! BUG FIX: No longer writing debugging output to *scanner_node→log_strm*. This caused a "General Protection Fault" using GCC under Windows XP.

[LDF 2006.12.12.] Added code to account for additional **static const unsigned** *shorts* that refer to tables in the OAI database (dc_test).

[LDF 2006.12.12.] Added code to account for the tokens that refer to additional tables in the PICA database (PICA_DB).

⟨ Declare **Query_Type** functions 86 ⟩ +≡

```
~Query_Type(void);
```

91.

⟨ Define **Query_Type** functions 87 ⟩ +≡

```
Query_Type::~Query_Type(void){
#if 0    /* 1 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
    stringstream temp_strm;
#ifdef DEBUG_OUTPUT
    temp_strm << "Entering␣`Query_Type'␣destructor." << endl;
    cerr_mutex.lock();
    cerr << temp_strm.str();
    cerr_mutex.unlock();
    temp_strm.str("");
#endif
```

92. Please note that the **Query_Node** *up* isn't deleted! [LDF 2006.11.03.]

To Do

[LDF 2006.11.03.] Cast *value* to correct type and delete it.

```
⟨ Define Query_Type functions 87 ⟩ +≡
  up = 0;
  if (value ≠ 0) {
    if (field_type ≡ ACCESS_NUMBER_FIELD ∨ field_type ≡ AUTHOR_FIELD ∨ field_type ≡
          BIBLIOGRAPHIC_TYPE_FIELD ∨ field_type ≡ CALL_NUMBER_FIELD ∨ field_type ≡
          CLASSIFICATION_FIELD ∨ field_type ≡ COMPANY_FIELD ∨ field_type ≡
          CONTENT_SUMMARY_FIELD ∨ field_type ≡ CONTRIBUTOR_FIELD ∨ field_type ≡
          CREATOR_FIELD ∨ field_type ≡ DATABASE_PROVIDER_FIELD ∨ field_type ≡
          DESCRIPTION_FIELD ∨ field_type ≡ EXEMPLAR_PRODUCTION_NUMBER_FIELD ∨ field_type ≡
          IDENTIFIER_FIELD∨field_type ≡ INSTITUTION_FIELD∨field_type ≡ LANGUAGE_FIELD∨field_type ≡
          MAIN_CANONICAL_TITLE_FIELD ∨ field_type ≡ PERMUTATION_PATTERN_FIELD ∨ field_type ≡
          PERSON_FIELD ∨ field_type ≡ PHYSICAL_DESCRIPTION_FIELD ∨ field_type ≡
          PUBLISHER_FIELD∨field_type ≡ RECORD_FIELD∨field_type ≡ REMOTE_ACCESS_FIELD∨field_type ≡
          RIGHTS_FIELD ∨ field_type ≡ SOURCE_FIELD ∨ field_type ≡ SUBJECT_FIELD ∨ field_type ≡
          SUPERORDINATE_ENTITIES_FIELD ∨ field_type ≡ TITLE_FIELD ∨ field_type ≡
          TYPE_FIELD ∨ field_type ≡ AUTHOR_SURNAME_FIELD ∨ field_type ≡
          AUTHOR_GIVEN_NAME_FIELD ∨ field_type ≡ AUTHOR_PREFIX_FIELD ∨ field_type ≡
          CONTRIBUTOR_SURNAME_FIELD ∨ field_type ≡ CONTRIBUTOR_GIVEN_NAME_FIELD ∨ field_type ≡
          CONTRIBUTOR_PREFIX_FIELD ∨ field_type ≡ RECORD_IDENTIFICATION_NUMBER_FIELD) {
      delete static_cast⟨string ∗⟩(value);
    }
    else if (field_type ≡ RECORD_ID_FIELD∨field_type ≡ RECORD_ELN_ORIGINAL_ENTRY_FIELD∨field_type ≡
          RECORD_ELN_MOST_RECENT_CHANGE_FIELD ∨ field_type ≡
          RECORD_ELN_STATUS_CHANGE_FIELD ∨ field_type ≡ RECORD_SOURCE_ID_FIELD ∨ field_type ≡
          RECORD_YEAR_APPEARANCE_BEGIN_FIELD ∨ field_type ≡ RECORD_YEAR_APPEARANCE_END_FIELD ∨
          field_type ≡ RECORD_YEAR_APPEARANCE_RAK_WB_FIELD ∨ field_type ≡
          RECORD_YEAR_APPEARANCE_ORIGINAL_FIELD) {
      delete static_cast⟨int ∗⟩(value);
    }
    else if (field_type ≡ RECORD_DATE_ORIGINAL_ENTRY_FIELD ∨ field_type ≡
          RECORD_DATE_MOST_RECENT_CHANGE_FIELD ∨ field_type ≡ RECORD_DATE_STATUS_CHANGE_FIELD)
      {
      delete static_cast⟨Date_Time_Node⟩(value);
    }
  }     /∗ if (value ≠ 0) ∗/
  value = 0;
  delete and_node;
  and_node = 0;
  delete or_node;
  or_node = 0;
  delete xor_node;
  xor_node = 0;
```

93.

⟨ Define **Query_Type** functions 87 ⟩ +≡

```
#ifdef DEBUG_OUTPUT
  temp_strm ≪ "Exiting␣'Query_Type'␣destructor." ≪ endl;
  cerr_mutex.lock( );
  cerr ≪ temp_strm.str( );
  cerr_mutex.unlock( );
  temp_strm.str("");
#endif
```

94. DO NOT delete *scanner_node*! [LDF 2006.10.31.]

⟨ Define **Query_Type** functions 87 ⟩ +≡

```
  scanner_node = 0;
  return; }      /* End of ~Query_Type definition. */
```

95. Assignment. [LDF 2006.11.15.]

Log

[2006.11.15.] Added this function.

⟨ Declare **Query_Type** functions 86 ⟩ +≡

```
  Query_Node operator=(const Query_Type &q);
```

96.

```
⟨ Define Query_Type functions 87 ⟩ +≡
  Query_Node Query_Type::operator=(const Query_Type &q){
#if 0     /* 1 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
      stringstream temp_strm;
      scanner_node = q.scanner_node;
      query_ctr = q.query_ctr;
#ifdef DEBUG_OUTPUT
      temp_strm << "Entering␣`Query_Type::operator=(const␣Query_Type)'." << endl;
      cerr_mutex.lock();
      cerr << temp_strm.str();
      cerr_mutex.unlock();
      if (scanner_node) scanner_node->log_strm << temp_strm.str();
      temp_strm.str("");
#endif
      if (this ≡ &q) {
#ifdef DEBUG_OUTPUT
        temp_strm << "In␣`Query_Type::operator=(const␣Query_Type)':" << endl <<
            "Self-assignment.␣␣Returning␣`this'." << endl;
        cerr_mutex.lock();
        cerr << temp_strm.str();
        cerr_mutex.unlock();
        if (scanner_node) scanner_node->log_strm << temp_strm.str();
        temp_strm.str("");
#endif
        return this;
      }
```

97.

Log

[LDF 2006.11.21.] Added this section. Now setting *name* to *q.name*.

```
⟨ Define Query_Type functions 87 ⟩ +≡
  name = q.name;
  if (value ≠ 0 ∧ value_type ≠ q.value_type) {
    if (value_type ≡ Query_Type::QUERY_TYPE_STRING_TYPE) {
      delete static_cast⟨string *⟩(value);
    }
    else if (value_type ≡ Query_Type::INT_TYPE) {
      delete static_cast⟨int *⟩(value);
    }
    else if (value_type ≡ Query_Type::FLOAT_TYPE) {
      delete static_cast⟨float *⟩(value);
    }
    else if (value_type ≡ Query_Type::DATE_TIME_TYPE) {
      delete static_cast⟨Date_Time_Node⟩(value);
    }
    value = 0;
  }     /* if (value ≠ 0 ∧ value_type ≠ q.value_type) */
  query_type = q.query_type;
  field_type = q.field_type;
  value_type = q.value_type;
  negated = q.negated;
  target_types.clear();
  for (vector⟨unsigned short⟩::const_iterator iter = q.target_types.begin(); iter ≠ q.target_types.end();
       ++iter) target_types.push_back(*iter);
  if (q.value ≠ 0 ∧ value_type ≡ QUERY_TYPE_STRING_TYPE) {
    if (value ≡ 0) value = static_cast⟨void *⟩(new string);
    *static_cast⟨string *⟩(value) = *static_cast⟨string *⟩(q.value);
  }     /* if */
  else if (q.value ≠ 0 ∧ value_type ≡ INT_TYPE) {
    if (value ≡ 0) value = static_cast⟨void *⟩(new int);
    *static_cast⟨int *⟩(value) = *static_cast⟨int *⟩(q.value);
  }
  else if (q.value ≠ 0 ∧ value_type ≡ FLOAT_TYPE) {
    if (value ≡ 0) value = static_cast⟨void *⟩(new float);
    *static_cast⟨float *⟩(value) = *static_cast⟨float *⟩(q.value);
  }
  else if (q.value ≠ 0 ∧ value_type ≡ DATE_TIME_TYPE) {
    if (value ≡ 0) value = static_cast⟨void *⟩(new Date_Time_Type);
    *static_cast⟨Date_Time_Node⟩(value) = *static_cast⟨Date_Time_Node⟩(q.value);
  }
  else {
    value_type = QUERY_TYPE_NULL_TYPE;
    value = 0;
  }
  scanner_node = q.scanner_node;
  delete and_node;
```

```
  and_node = 0;
  delete or_node;
  or_node = 0;
  delete xor_node;
  xor_node = 0;
  if (q.and_node) {
    and_node = new Query_Type;
    *and_node = *q.and_node;
    and_node->up = this;
  }
  if (q.or_node) {
    or_node = new Query_Type;
    *or_node = *q.or_node;
    or_node->up = this;
  }
  if (q.xor_node) {
    xor_node = new Query_Type;
    *xor_node = *q.xor_node;
    xor_node->up = this;
  }
#ifdef DEBUG_OUTPUT
  temp_strm << "Exiting `Query_Type::operator=(const Query_Type)'." << endl;
  cerr_mutex.lock();
  cerr << temp_strm.str();
  cerr_mutex.unlock();
  if (scanner_node) scanner_node->log_strm << temp_strm.str();
  temp_strm.str("");
#endif
```

98.

⟨ Define **Query_Type** functions 87 ⟩ +≡
```
match_value = q.match_value;
return this; }      /* End of Query_Type::operator=(const Query_Type q) definition. */
```

99. Initialize type maps. [LDF 2006.10.31.]

Log

[2006.10.31.] Added this function.

[LDF 2006.11.13.] Added code for initializing *target_type_map*.

[LDF 2006.11.13.] Added code for initializing *field_type_map*.

[LDF 2006.12.12.] Added code for `MAIN_CANONICAL_TITLE_FIELD`.

[LDF 2006.12.12.] Added code for initializing *match_value_map*.

[LDF 2006.12.12.] Added code for additional **static const unsigned** *shorts* that refer to tables in the OAI database (dc_test).

[LDF 2006.12.12.] Added code to account for for additional **static const unsigned** *shorts* that refer to tables in the PICA database (PICA_DB).

⟨ Declare **Query_Type** functions 86 ⟩ +≡
```
static int initialize_type_maps(void);
```

100.

```
⟨ Define Query_Type functions 87 ⟩ +≡
  int Query_Type::initialize_type_maps(void)
  {
    query_type_map[QUERY_TYPE_NULL_TYPE] = "QUERY_TYPE_NULL_TYPE";
    query_type_map[TOP_TYPE] = "TOP_TYPE";
    query_type_map[AND_TYPE] = "AND_TYPE";
    query_type_map[OR_TYPE] = "OR_TYPE";
    query_type_map[XOR_TYPE] = "XOR_TYPE";
    field_type_map[QUERY_TYPE_NULL_TYPE] = "QUERY_TYPE_NULL_TYPE";
    field_type_map[ACCESS_NUMBER_FIELD] = "ACCESS_NUMBER_FIELD";
    field_type_map[AUTHOR_FIELD] = "AUTHOR_FIELD";
    field_type_map[AUTHOR_SURNAME_FIELD] = "AUTHOR_SURNAME_FIELD";
    field_type_map[AUTHOR_GIVEN_NAME_FIELD] = "AUTHOR_GIVEN_NAME_FIELD";
    field_type_map[AUTHOR_PREFIX_FIELD] = "AUTHOR_PREFIX_FIELD";
    field_type_map[BIBLIOGRAPHIC_TYPE_FIELD] = "BIBLIOGRAPHIC_TYPE_FIELD";
    field_type_map[CALL_NUMBER_FIELD] = "CALL_NUMBER_FIELD";
    field_type_map[CLASSIFICATION_FIELD] = "CLASSIFICATION_FIELD";
    field_type_map[COMPANY_FIELD] = "COMPANY_FIELD";
    field_type_map[CONTENT_SUMMARY_FIELD] = "CONTENT_SUMMARY_FIELD";
    field_type_map[CONTRIBUTOR_FIELD] = "CONTRIBUTOR_FIELD";
    field_type_map[CONTRIBUTOR_SURNAME_FIELD] = "CONTRIBUTOR_SURNAME_FIELD";
    field_type_map[CONTRIBUTOR_GIVEN_NAME_FIELD] = "CONTRIBUTOR_GIVEN_NAME_FIELD";
    field_type_map[CONTRIBUTOR_PREFIX_FIELD] = "CONTRIBUTOR_PREFIX_FIELD";
    field_type_map[CREATOR_FIELD] = "CREATOR_FIELD";
    field_type_map[DATABASE_PROVIDER_FIELD] = "DATABASE_PROVIDER_FIELD";
    field_type_map[DESCRIPTION_FIELD] = "DESCRIPTION_FIELD";
    field_type_map[EXEMPLAR_PRODUCTION_NUMBER_FIELD] = "EXEMPLAR_PRODUCTION_NUMBER_FIELD";
    field_type_map[IDENTIFIER_FIELD] = "IDENTIFIER_FIELD";
    field_type_map[INSTITUTION_FIELD] = "INSTITUTION_FIELD";
    field_type_map[LANGUAGE_FIELD] = "LANGUAGE_FIELD";
    field_type_map[MAIN_CANONICAL_TITLE_FIELD] = "MAIN_CANONICAL_TITLE_FIELD";
    field_type_map[PERMUTATION_PATTERN_FIELD] = "PERMUTATION_PATTERN_FIELD";
    field_type_map[PERSON_FIELD] = "PERSON_FIELD";
    field_type_map[PHYSICAL_DESCRIPTION_FIELD] = "PHYSICAL_DESCRIPTION_FIELD";
    field_type_map[PUBLISHER_FIELD] = "PUBLISHER_FIELD";
    field_type_map[RECORD_FIELD] = "RECORD_FIELD";
    field_type_map[RECORD_IDENTIFICATION_NUMBER_FIELD] = "RECORD_IDENTIFICATION_NUMBER_FIELD";
    field_type_map[RECORD_DATE_MOST_RECENT_CHANGE_FIELD] =
        "RECORD_DATE_MOST_RECENT_CHANGE_FIELD";
    field_type_map[RECORD_DATE_ORIGINAL_ENTRY_FIELD] = "RECORD_DATE_ORIGINAL_ENTRY_FIELD";
    field_type_map[RECORD_DATE_STATUS_CHANGE_FIELD] = "RECORD_DATE_STATUS_CHANGE_FIELD";
    field_type_map[RECORD_ELN_STATUS_CHANGE_FIELD] = "RECORD_ELN_STATUS_CHANGE_FIELD";
    field_type_map[REMOTE_ACCESS_FIELD] = "REMOTE_ACCESS_FIELD";
    field_type_map[RIGHTS_FIELD] = "RIGHTS_FIELD";
    field_type_map[SOURCE_FIELD] = "SOURCE_FIELD";
    field_type_map[SUBJECT_FIELD] = "SUBJECT_FIELD";
    field_type_map[SUPERORDINATE_ENTITIES_FIELD] = "SUPERORDINATE_ENTITIES_FIELD";
    field_type_map[TITLE_FIELD] = "TITLE_FIELD";
    field_type_map[TYPE_FIELD] = "TYPE_FIELD";
    value_type_map[QUERY_TYPE_NULL_TYPE] = "QUERY_TYPE_NULL_TYPE";
    value_type_map[INT_TYPE] = "INT_TYPE";
```

```
    value_type_map[FLOAT_TYPE] = "FLOAT_TYPE";
    value_type_map[QUERY_TYPE_STRING_TYPE] = "QUERY_TYPE_STRING_TYPE";
    value_type_map[DATE_TIME_TYPE] = "DATE_TIME_TYPE";
    target_type_map[LOCAL_DATABASE_TARGET] = "LOCAL_DATABASE_TARGET";
    target_type_map[LOCAL_SERVER_TARGET] = "LOCAL_SERVER_TARGET";
    target_type_map[REMOTE_DATABASE_TARGET] = "REMOTE_DATABASE_TARGET";
    target_type_map[REMOTE_SERVER_TARGET] = "REMOTE_SERVER_TARGET";
    match_value_map[QUERY_TYPE_NULL_TYPE] = "QUERY_TYPE_NULL_TYPE";
    match_value_map[CONTAINS_VALUE] = "CONTAINS_VALUE";
    match_value_map[FREETEXT_VALUE] = "FREETEXT_VALUE";
    match_value_map[LIKE_VALUE] = "LIKE_VALUE";
    return 0;
  }     /* End of Query_Type::initialize_type_maps definition. */
```

101. Initialize flags. [LDF 2006.12.13.]

Log

[2006.12.13.] Added this function.

⟨ Declare **Query_Type** functions 86 ⟩ +≡

```
  static int initialize_flags(void);
```

102.

⟨ Define **Query_Type** functions 87 ⟩ +≡

```
  int Query_Type::initialize_flags(void){ int shift_value = 0;
```

103.

⟨ Define **Query_Type** functions 87 ⟩ +≡

```
ACCESS_NUMBER_FLAG = 1;
ACCESS_NUMBER_FLAG <<= shift_value++;
AUTHOR_FLAG = 1;
AUTHOR_FLAG <<= shift_value++;
AUTHOR_SURNAME_FLAG = 1;
AUTHOR_SURNAME_FLAG <<= shift_value++;
AUTHOR_GIVEN_NAME_FLAG = 1;
AUTHOR_GIVEN_NAME_FLAG <<= shift_value++;
AUTHOR_PREFIX_FLAG = 1;
AUTHOR_PREFIX_FLAG <<= shift_value++;
BIBLIOGRAPHIC_TYPE_FLAG = 1;
BIBLIOGRAPHIC_TYPE_FLAG <<= shift_value++;
CALL_NUMBER_FLAG = 1;
CALL_NUMBER_FLAG <<= shift_value++;
CLASSIFICATION_FLAG = 1;
CLASSIFICATION_FLAG <<= shift_value++;
COMPANY_FLAG = 1;
COMPANY_FLAG <<= shift_value++;
CONTENT_SUMMARY_FLAG = 1;
CONTENT_SUMMARY_FLAG <<= shift_value++;
CONTRIBUTOR_FLAG = 1;
CONTRIBUTOR_FLAG <<= shift_value++;
CONTRIBUTOR_SURNAME_FLAG = 1;
CONTRIBUTOR_SURNAME_FLAG <<= shift_value++;
CONTRIBUTOR_GIVEN_NAME_FLAG = 1;
CONTRIBUTOR_GIVEN_NAME_FLAG <<= shift_value++;
CONTRIBUTOR_PREFIX_FLAG = 1;
CONTRIBUTOR_PREFIX_FLAG <<= shift_value++;
CREATOR_FLAG = 1;
CREATOR_FLAG <<= shift_value++;
DATABASE_PROVIDER_FLAG = 1;
DATABASE_PROVIDER_FLAG <<= shift_value++;
DESCRIPTION_FLAG = 1;
DESCRIPTION_FLAG <<= shift_value++;
EXEMPLAR_PRODUCTION_NUMBER_FLAG = 1;
EXEMPLAR_PRODUCTION_NUMBER_FLAG <<= shift_value++;
IDENTIFIER_FLAG = 1;
IDENTIFIER_FLAG <<= shift_value++;
INSTITUTION_FLAG = 1;
INSTITUTION_FLAG <<= shift_value++;
LANGUAGE_FLAG = 1;
LANGUAGE_FLAG <<= shift_value++;
MAIN_CANONICAL_TITLE_FLAG = 1;
MAIN_CANONICAL_TITLE_FLAG <<= shift_value++;
PERMUTATION_PATTERN_FLAG = 1;
PERMUTATION_PATTERN_FLAG <<= shift_value++;
PERSON_FLAG = 1;
PERSON_FLAG <<= shift_value++;
PHYSICAL_DESCRIPTION_FLAG = 1;
PHYSICAL_DESCRIPTION_FLAG <<= shift_value++;
```

```
PUBLISHER_FLAG = 1;
PUBLISHER_FLAG ≪= shift_value++;
RECORD_FLAG = 1;
RECORD_FLAG ≪= shift_value++;
RECORD_ID_FLAG = 1;
RECORD_ID_FLAG ≪= shift_value++;
RECORD_ELN_ORIGINAL_ENTRY_FLAG = 1;
RECORD_ELN_ORIGINAL_ENTRY_FLAG ≪= shift_value++;
RECORD_ELN_MOST_RECENT_CHANGE_FLAG = 1;
RECORD_ELN_MOST_RECENT_CHANGE_FLAG ≪= shift_value++;
RECORD_ELN_STATUS_CHANGE_FLAG = 1;
RECORD_ELN_STATUS_CHANGE_FLAG ≪= shift_value++;
RECORD_IDENTIFICATION_NUMBER_FLAG = 1;
RECORD_IDENTIFICATION_NUMBER_FLAG ≪= shift_value++;
RECORD_DATE_ORIGINAL_ENTRY_FLAG = 1;
RECORD_DATE_ORIGINAL_ENTRY_FLAG ≪= shift_value++;
RECORD_DATE_MOST_RECENT_CHANGE_FLAG = 1;
RECORD_DATE_MOST_RECENT_CHANGE_FLAG ≪= shift_value++;
RECORD_DATE_STATUS_CHANGE_FLAG = 1;
RECORD_DATE_STATUS_CHANGE_FLAG ≪= shift_value++;
RECORD_SOURCE_ID_FLAG = 1;
RECORD_SOURCE_ID_FLAG ≪= shift_value++;
RECORD_YEAR_APPEARANCE_BEGIN_FLAG = 1;
RECORD_YEAR_APPEARANCE_BEGIN_FLAG ≪= shift_value++;
RECORD_YEAR_APPEARANCE_END_FLAG = 1;
RECORD_YEAR_APPEARANCE_END_FLAG ≪= shift_value++;
RECORD_YEAR_APPEARANCE_RAK_WB_FLAG = 1;
RECORD_YEAR_APPEARANCE_RAK_WB_FLAG ≪= shift_value++;
RECORD_YEAR_APPEARANCE_ORIGINAL_FLAG = 1;
RECORD_YEAR_APPEARANCE_ORIGINAL_FLAG ≪= shift_value++;
REMOTE_ACCESS_FLAG = 1;
REMOTE_ACCESS_FLAG ≪= shift_value++;
RIGHTS_FLAG = 1;
RIGHTS_FLAG ≪= shift_value++;
SOURCE_FLAG = 1;
SOURCE_FLAG ≪= shift_value++;
SUBJECT_FLAG = 1;
SUBJECT_FLAG ≪= shift_value++;
SUPERORDINATE_ENTITIES_FLAG = 1;
SUPERORDINATE_ENTITIES_FLAG ≪= shift_value++;
TITLE_FLAG = 1;
TITLE_FLAG ≪= shift_value++;
TYPE_FLAG = 1;
TYPE_FLAG ≪= shift_value++;
```

104. Error handling. `QUERY_TYPE_BITSET_SIZE` too small. [LDF 2006.12.13.]

```
⟨ Define Query_Type functions 87 ⟩ +≡
  if (shift_value > QUERY_TYPE_BITSET_SIZE) {
    cerr ≪ "ERROR!␣␣In␣'Query_Type::initialize_flags':" ≪ endl ≪
        "'shift_value'␣>␣'QUERY_TYPE_BITSET_SIZE'." ≪ endl ≪
        "Increase␣the␣size␣of␣'QUERY_TYPE_BITSET_SIZE'." ≪ endl ≪
        "Exiting␣function␣with␣return␣value␣1." ≪ endl ≪ "Type␣<RETURN>␣to␣continue:␣";
    getchar( );
    return 1;
  }     /* if (shift_value > QUERY_TYPE_BITSET_SIZE) */
  return 0; }     /* Query_Type::initialize_flags */
```

105. Set field specifier. [LDF 2006.11.15.]

Log

[2006.11.15.] Added this function.

[LDF 2006.12.12.] Added code for `MAIN_CANONICAL_TITLE_FIELD`.

[LDF 2006.12.12.] Added code for more **static const unsigned** *shorts* that refer to tables in the OAI database (dc_test).

[LDF 2006.12.12.] Added code for more **static const unsigned** *shorts* that refer to tables in the PICA database (PICA_DB).

[LDF 2006.12.13.] Changed the name of this function from *set_field_type* to *set_field_specifier*.

```
⟨ Declare Query_Type functions 86 ⟩ +≡
  int set_field_specifier(void *v, bool traverse = false, Scanner_Node sscanner_node = 0);
```

106.

```
⟨ Define Query_Type functions 87 ⟩ +≡
  int Query_Type::set_field_specifier(void *v, bool traverse, Scanner_Node sscanner_node){
#if 0     /* 1 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
      stringstream temp_strm; deque < int > *field_specifier = static_cast ⟨ deque < int >*> (v);
      unsigned int table = (*field_specifier)[0];
      unsigned int column;
      if (table ≡ ACCESS_NUMBER) field_type = ACCESS_NUMBER_FIELD;
      else if (table ≡ AUTHOR) {
        if (field_specifier→size( ) ≡ 1) field_type = AUTHOR_FIELD;
        else      /* field_specifier→size( ) ≠ 1 */
        {
          column = (*field_specifier)[1];
          if (column ≡ SURNAME) field_type = AUTHOR_SURNAME_FIELD;
          else if (column ≡ GIVEN_NAME) field_type = AUTHOR_GIVEN_NAME_FIELD;
          else if (column ≡ PREFIX) field_type = AUTHOR_PREFIX_FIELD;
        }     /* else (field_specifier→size( ) ≠ 1) */
      }     /* else if (table ≡ AUTHOR) */
      else if (table ≡ BIBLIOGRAPHIC_TYPE) field_type = BIBLIOGRAPHIC_TYPE_FIELD;
      else if (table ≡ CALL_NUMBER) field_type = CALL_NUMBER_FIELD;
      else if (table ≡ CLASSIFICATION) field_type = CLASSIFICATION_FIELD;
      else if (table ≡ COMPANY) field_type = COMPANY_FIELD;
      else if (table ≡ CONTENT_SUMMARY) field_type = CONTENT_SUMMARY_FIELD;
      else if (table ≡ CONTRIBUTOR) {
        if (field_specifier→size( ) ≡ 1) field_type = CONTRIBUTOR_FIELD;
        else      /* (field_specifier→size( ) ≠ 1) */
        {
          column = (*field_specifier)[1];
          if (column ≡ SURNAME) field_type = CONTRIBUTOR_SURNAME_FIELD;
          else if (column ≡ GIVEN_NAME) field_type = CONTRIBUTOR_GIVEN_NAME_FIELD;
          else if (column ≡ PREFIX) field_type = CONTRIBUTOR_PREFIX_FIELD;
        }     /* else ((field_specifier→size( ) ≠ 1)) */
      }     /* else if (table ≡ CONTRIBUTOR) */
      else if (table ≡ CREATOR) field_type = CREATOR_FIELD;
      else if (table ≡ DATABASE_PROVIDER) field_type = DATABASE_PROVIDER_FIELD;
      else if (table ≡ DESCRIPTION) field_type = DESCRIPTION_FIELD;
      else if (table ≡ EXEMPLAR_PRODUCTION_NUMBER)
        field_type = EXEMPLAR_PRODUCTION_NUMBER_FIELD;
      else if (table ≡ IDENTIFIER) field_type = IDENTIFIER_FIELD;
      else if (table ≡ INSTITUTION) field_type = INSTITUTION_FIELD;
      else if (table ≡ LANGUAGE) field_type = LANGUAGE_FIELD;
      else if (table ≡ MAIN_CANONICAL_TITLE) field_type = MAIN_CANONICAL_TITLE_FIELD;
      else if (table ≡ PERMUTATION_PATTERN) field_type = PERMUTATION_PATTERN_FIELD;
      else if (table ≡ PERSON) field_type = PERSON_FIELD;
      else if (table ≡ PHYSICAL_DESCRIPTION) field_type = PHYSICAL_DESCRIPTION_FIELD;
      else if (table ≡ PUBLISHER) field_type = PUBLISHER_FIELD;
```

107. *table* ≡ RECORD.

Log

[2006.12.14.] Added this section.

```
⟨ Define Query_Type functions 87 ⟩ +≡
  else
    if (table ≡ RECORD) {
      if (field_specifier→size( ) ≡ 1) field_type = RECORD_FIELD;
      else      /* (field_specifier→size( ) ≠ 1) */
      {
        column = (*field_specifier)[1];
        if (column ≡ ID) field_type = RECORD_ID_FIELD;
        else if (column ≡ ELN_ORIGINAL_ENTRY) field_type = RECORD_ELN_ORIGINAL_ENTRY_FIELD;
        else if (column ≡ ELN_MOST_RECENT_CHANGE)
          field_type = RECORD_ELN_MOST_RECENT_CHANGE_FIELD;
        else if (column ≡ ELN_STATUS_CHANGE) field_type = RECORD_ELN_STATUS_CHANGE_FIELD;
        else if (column ≡ IDENTIFICATION_NUMBER)
          field_type = RECORD_IDENTIFICATION_NUMBER_FIELD;
        else if (column ≡ DATE_ORIGINAL_ENTRY) field_type = RECORD_DATE_ORIGINAL_ENTRY_FIELD;
        else if (column ≡ DATE_MOST_RECENT_CHANGE)
          field_type = RECORD_DATE_MOST_RECENT_CHANGE_FIELD;
        else if (column ≡ DATE_STATUS_CHANGE) field_type = RECORD_DATE_STATUS_CHANGE_FIELD;
        else if (column ≡ SOURCE_ID) field_type = RECORD_SOURCE_ID_FIELD;
        else if (column ≡ YEAR_APPEARANCE_BEGIN)
          field_type = RECORD_YEAR_APPEARANCE_BEGIN_FIELD;
        else if (column ≡ YEAR_APPEARANCE_END) field_type = RECORD_YEAR_APPEARANCE_END_FIELD;
        else if (column ≡ YEAR_APPEARANCE_RAK_WB)
          field_type = RECORD_YEAR_APPEARANCE_RAK_WB_FIELD;
        else if (column ≡ YEAR_APPEARANCE_ORIGINAL)
          field_type = RECORD_YEAR_APPEARANCE_ORIGINAL_FIELD;
      }     /* else ((field_specifier→size( ) ≠ 1)) */
    }     /* else if (table ≡ RECORD) */
```

108.

```
⟨ Define Query_Type functions 87 ⟩ +≡
  else
    if (table ≡ REMOTE_ACCESS) field_type = REMOTE_ACCESS_FIELD;
    else if (table ≡ RIGHTS) field_type = RIGHTS_FIELD;
    else if (table ≡ SOURCE) field_type = SOURCE_FIELD;
    else if (table ≡ SUBJECT) field_type = SUBJECT_FIELD;
    else if (table ≡ SUPERORDINATE_ENTITIES) field_type = SUPERORDINATE_ENTITIES_FIELD;
    else if (table ≡ TITLE) field_type = TITLE_FIELD;
    else if (table ≡ TYPE) field_type = TYPE_FIELD;
    else if (table ≡ CONTRIBUTOR_SURNAME) field_type = CONTRIBUTOR_SURNAME_FIELD;
    else if (table ≡ CONTRIBUTOR_GIVEN_NAME) field_type = CONTRIBUTOR_GIVEN_NAME_FIELD;
    else if (table ≡ CONTRIBUTOR_PREFIX) field_type = CONTRIBUTOR_PREFIX_FIELD;
    else field_type = QUERY_TYPE_NULL_TYPE;
  if (traverse) {
    if (and_node) and_node→set_field_specifier(v, true, scanner_node);
    if (or_node) or_node→set_field_specifier(v, true, scanner_node);
    if (xor_node) xor_node→set_field_specifier(v, true, scanner_node);
  }
  return 0;
#undef DEBUG_OUTPUT
  }     /* End of Query_Type::set_field_specifier definition. */
```

109. Functions for generating strings. [LDF 2006.11.21.]

Log

[LDF 2006.11.21.] Added this section.

110. Generate TEX string. [LDF 2006.11.21.]

Log

[2006.11.21.] Added this function.

```
⟨ Declare Query_Type functions 86 ⟩ +≡
  string generate_tex_string(Scanner_Node scanner_node, stringstream *tex_strm);
```

111.

```
⟨ Define Query_Type functions 87 ⟩ +≡
  string Query_Type::generate_tex_string(Scanner_Node scanner_node, stringstream *tex_strm){
#if 0     /* 1 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
      stringstream temp_strm;
#ifdef DEBUG_OUTPUT
      temp_strm << "Entering `Query_Type::generate_tex_string'." << endl <<
          "`query_ctr' == " << query_ctr << endl;
      cerr_mutex.lock();
      cerr << temp_strm.str();
      cerr_mutex.unlock();
      if (scanner_node ≠ 0) scanner_node→log_strm << temp_strm.str();
      temp_strm.str("");
#endif
```

112.

```
⟨ Define Query_Type functions 87 ⟩ +≡
  if (query_ctr ≡ 0) *tex_strm ≪ "\\setbox\\namebox=\\hbox{" ≪ name ≪ "}" ≪ endl;
  *tex_strm ≪ "\\setbox\\querytypebox=\\hbox{" ≪ query_type_map[query_type] ≪ "}" ≪ endl;
  *tex_strm ≪ "\\setbox\\fieldtypebox=\\hbox{" ≪ field_type_map[field_type] ≪ "}" ≪ endl;
  *tex_strm ≪ "\\setbox\\valuetypebox=\\hbox{" ≪ value_type_map[value_type] ≪ "}" ≪ endl;
  *tex_strm ≪ "\\setbox\\targettypesbox=\\hbox{";
  if (target_types.size() ≤ 0) *tex_strm ≪ "QUERY_TYPE_NULL_TYPE";
  else if (target_types.size() ≡ 1) {
    *tex_strm ≪ target_type_map[target_types[0]];
  }
  else {
    *tex_strm ≪ "\\vbox{";
    int i = 0;
    for (vector⟨unsigned short⟩::iterator iter = target_types.begin(); iter ≠ target_types.end();
        ++iter) {
      if (i++ > 0) *tex_strm ≪ "%" ≪ endl;
      *tex_strm ≪ "\\hbox{" ≪ target_type_map[*iter] ≪ "}";
    }    /* for */
    *tex_strm ≪ "}";
  }    /* else */
  *tex_strm ≪ "}" ≪ endl;
  if (value_type ≡ QUERY_TYPE_STRING_TYPE) {
    *tex_strm ≪ "\\setbox\\valuebox=\\hbox{" ≪ *static_cast⟨string *⟩(value) ≪ "}" ≪ endl;
  }
  else if (value_type ≡ INT_TYPE) {
    *tex_strm ≪ "\\setbox\\valuebox=\\hbox{" ≪ *static_cast⟨int *⟩(value) ≪ "}" ≪ endl;
  }
  else if (value_type ≡ FLOAT_TYPE) {
    *tex_strm ≪ "\\setbox\\valuebox=\\hbox{" ≪ *static_cast⟨float *⟩(value) ≪ "}" ≪ endl;
  }
  else if (value_type ≡ DATE_TIME_TYPE) { *tex_strm ≪ "\\setbox\\valuebox=\\hbox{" ≪
      "Date\\_Time" # if 0    /* 1 */
  *static_cast⟨Date_Time_Node⟩(value) # endif ≪ "}" ≪ endl; } *tex_strm ≪ "\\upctr=";
  if (up) *tex_strm ≪ up→query_ctr;
  else *tex_strm ≪ "0";
  *tex_strm ≪ endl;
  *tex_strm ≪ "\\andctr=";
  if (and_node) *tex_strm ≪ and_node→query_ctr;
  else *tex_strm ≪ "0";
  *tex_strm ≪ endl;
  *tex_strm ≪ "\\orctr=";
  if (or_node) *tex_strm ≪ or_node→query_ctr;
  else *tex_strm ≪ "0";
  *tex_strm ≪ endl;
  *tex_strm ≪ "\\xorctr=";
  if (or_node) *tex_strm ≪ xor_node→query_ctr;
  else *tex_strm ≪ "0";
  *tex_strm ≪ endl;
  *tex_strm ≪ "%" ≪ endl ≪ "\\chart{" ≪ query_ctr ≪ "}{" ≪ negated ≪ "}" ≪ endl ≪ "%" ≪ endl;
  if (and_node) {
```

```
    *tex_strm ≪ "\\vskip\\queryskip\n%\n";
    *tex_strm ≪ "\\vskip\\ht\\targettypesbox\n" ≪ "\\vskip\\dp\\targettypesbox\n" ≪ "%\n";
    and_node→generate_tex_string(scanner_node, tex_strm);
  }
  if (or_node) {
    *tex_strm ≪ "\\vskip\\queryskip\n%\n";
    *tex_strm ≪ "\\vskip\\ht\\targettypesbox\n" ≪ "\\vskip\\dp\\targettypesbox\n" ≪ "%\n";
    or_node→generate_tex_string(scanner_node, tex_strm);
  }
  if (xor_node) {
    *tex_strm ≪ "\\vskip\\queryskip\n%\n";
    *tex_strm ≪ "\\vskip\\ht\\targettypesbox\n" ≪ "\\vskip\\dp\\targettypesbox\n" ≪ "%\n";
    xor_node→generate_tex_string(scanner_node, tex_strm);
  }
```

113. Return string. [LDF 2006.11.21.]

```
⟨ Define Query_Type functions 87 ⟩ +≡
#ifdef DEBUG_OUTPUT
  temp_strm ≪ "Exiting␣`Query_Type::generate_tex_string'." ≪ endl;
  cerr_mutex.lock();
  cerr ≪ temp_strm.str();
  cerr_mutex.unlock();
  if (scanner_node ≠ 0) scanner_node→log_strm ≪ temp_strm.str();
  temp_strm.str("");
#endif
  return tex_strm→str(); }      /* Query_Type::generate_tex_string */
```

114. Generate SQL string. [LDF 2006.12.01.]

Log

[LDF 2006.12.01.] Added this function.

[LDF 2006.12.12.] Added code for `MAIN_CANONICAL_TITLE_FLAG`.

[LDF 2006.12.12.] Added code to account for **static const unsigned** *shorts* that refer to additional tables in the OAI database (dc_test).

[LDF 2006.12.14.] Moved the definition of this function from this file (`querytyp.web`) to `qtgensql.web`.

⟨ Declare **Query_Type** functions 86 ⟩ +≡

int *generate_sql_string*(**Scanner_Node** *scanner_node*, **int** *database_type*, **stringstream** ∗*sql_strm*, **stringstream** ∗*select_strm*, **stringstream** ∗*from_strm*, **stringstream** ∗*where_strm_0*, **stringstream** ∗*where_strm_1*, **bool** ∗*first_select*, **bool** ∗*first_from*, **bool** ∗*first_where*, *bitset* < `QUERY_TYPE_BITSET_SIZE` > ∗*field_flags*, **string** ∗*return_str*);

115. Show. [LDF 2006.10.31.]

As well as simply showing the **Query_Type** object, this function is meant to serve as an example of traversing it. This is somewhat complicated, because of all of the **Query_Nodes** it contains, and the complex way in which they're linked. [LDF 2006.10.31.]

The **Scanner_Node** *scanner_node* data member of the **Query_Type** object may already be non-null. However, *show* has an optional **Scanner_Node** argument, just in case it doesn't. [LDF 2006.10.31.]

Log

[2006.10.31.] Added this function.

[LDF 2006.11.14.] Added the optional **int** *level_ctr* argument with default 0.

[LDF 2006.12.12.] Added code to account for additional fields that refer to tables in the PICA database (PICA_DB).

⟨ Declare **Query_Type** functions 86 ⟩ +≡

int *show*(**string** *s* = `"'Query_Type':\n"`, **Scanner_Node** *sscanner_node* = 0);

116.

⟨ Define **Query_Type** functions 87 ⟩ +≡

int **Query_Type** :: *show*(**string** *s*, **Scanner_Node** *sscanner_node*){ **stringstream** *temp_strm*;

if (*scanner_node* ≡ 0 ∧ *sscanner_node* ≠ 0) *scanner_node* = *sscanner_node*;

117. *query_type*, *field_type*, *value_type*, and *target_type*. [LDF 2006.10.31.]

Log

[LDF 2006.11.13.] Added code for showing *target_types*.

[LDF 2006.11.21.] Now showing *name*.

[LDF 2006.12.12.] Added code to account for **static const unsigned** *shorts* that refer to additional tables in the OAI database (dc_test).

```
⟨ Define Query_Type functions 87 ⟩ +≡
  temp_strm ≪ "`name'␣==␣" ≪ name ≪ endl ≪ "`query_type'␣==␣" ≪ query_type_map[query_type] ≪
      endl ≪ "`field_type'␣==␣" ≪ field_type_map[field_type] ≪ endl ≪ "`value_type'␣==␣" ≪
      value_type_map[value_type] ≪ endl ≪ "`match_value'␣==␣" ≪ match_value_map[match_value] ≪
      endl;
  int i = 0;
  for (vector⟨unsigned short⟩::iterator iter = target_types.begin(); iter ≠ target_types.end(); ++iter)
    temp_strm ≪ "`target_types[" ≪ i++ ≪ "]'␣==␣" ≪ target_type_map[*iter] ≪ endl;
  if (value ≠ 0) {
    if (field_type ≡ ACCESS_NUMBER_FIELD)
      temp_strm ≪ "Access_Number␣==␣" ≪ *static_cast⟨string *⟩(value) ≪ endl;
    else if (field_type ≡ AUTHOR_FIELD)
      temp_strm ≪ "Author␣==␣" ≪ *static_cast⟨string *⟩(value) ≪ endl;
    else if (field_type ≡ BIBLIOGRAPHIC_TYPE_FIELD)
      temp_strm ≪ "Bibliographic_Type␣==␣" ≪ *static_cast⟨string *⟩(value) ≪ endl;
    else if (field_type ≡ CALL_NUMBER_FIELD)
      temp_strm ≪ "Call_Number␣==␣" ≪ *static_cast⟨string *⟩(value) ≪ endl;
    else if (field_type ≡ CLASSIFICATION_FIELD)
      temp_strm ≪ "Classification␣==␣" ≪ *static_cast⟨string *⟩(value) ≪ endl;
    else if (field_type ≡ COMPANY_FIELD)
      temp_strm ≪ "Company␣==␣" ≪ *static_cast⟨string *⟩(value) ≪ endl;
    else if (field_type ≡ CONTENT_SUMMARY_FIELD)
      temp_strm ≪ "Content_Summary␣==␣" ≪ *static_cast⟨string *⟩(value) ≪ endl;
    else if (field_type ≡ CONTRIBUTOR_FIELD)
      temp_strm ≪ "Contributor␣==␣" ≪ *static_cast⟨string *⟩(value) ≪ endl;
    else if (field_type ≡ CREATOR_FIELD)
      temp_strm ≪ "Creator␣==␣" ≪ *static_cast⟨string *⟩(value) ≪ endl;
    else if (field_type ≡ DATABASE_PROVIDER_FIELD)
      temp_strm ≪ "Database_Provider␣==␣" ≪ *static_cast⟨string *⟩(value) ≪ endl;
    else if (field_type ≡ DESCRIPTION_FIELD)
      temp_strm ≪ "Description␣==␣" ≪ *static_cast⟨string *⟩(value) ≪ endl;
    else if (field_type ≡ EXEMPLAR_PRODUCTION_NUMBER_FIELD)
      temp_strm ≪ "Exemplar_Production_Number␣==␣" ≪ *static_cast⟨string *⟩(value) ≪ endl;
    else if (field_type ≡ IDENTIFIER_FIELD)
      temp_strm ≪ "Identifier␣==␣" ≪ *static_cast⟨string *⟩(value) ≪ endl;
    else if (field_type ≡ INSTITUTION_FIELD)
      temp_strm ≪ "Institution␣==␣" ≪ *static_cast⟨string *⟩(value) ≪ endl;
    else if (field_type ≡ LANGUAGE_FIELD)
      temp_strm ≪ "Language␣==␣" ≪ *static_cast⟨string *⟩(value) ≪ endl;
    else if (field_type ≡ MAIN_CANONICAL_TITLE_FIELD)
      temp_strm ≪ "Main_Canonical_Title_␣==␣" ≪ *static_cast⟨string *⟩(value) ≪ endl;
```

```
else if (field_type ≡ PERMUTATION_PATTERN_FIELD)
  temp_strm ≪ "Permutation_Pattern␣==␣" ≪ *static_cast⟨string *⟩(value) ≪ endl;
else if (field_type ≡ PERSON_FIELD)
  temp_strm ≪ "Person␣==␣" ≪ *static_cast⟨string *⟩(value) ≪ endl;
else if (field_type ≡ PHYSICAL_DESCRIPTION_FIELD)
  temp_strm ≪ "Physical_Description␣==␣" ≪ *static_cast⟨string *⟩(value) ≪ endl;
else if (field_type ≡ PUBLISHER_FIELD)
  temp_strm ≪ "Publisher␣==␣" ≪ *static_cast⟨string *⟩(value) ≪ endl;
else if (field_type ≡ RECORD_FIELD)
  temp_strm ≪ "Record␣==␣" ≪ *static_cast⟨string *⟩(value) ≪ endl;
else if (field_type ≡ RECORD_ID_FIELD)
  temp_strm ≪ "Record␣ID␣==␣" ≪ *static_cast⟨int *⟩(value) ≪ endl;
else if (field_type ≡ RECORD_ELN_ORIGINAL_ENTRY_FIELD)
  temp_strm ≪ "Record_Eln_Original_Entry_Field␣==␣" ≪ *static_cast⟨int *⟩(value) ≪ endl;
else if (field_type ≡ RECORD_ELN_MOST_RECENT_CHANGE_FIELD)
  temp_strm ≪ "Record_Eln_Most_Recent_Change_Field␣==␣" ≪ *static_cast⟨int
      *⟩(value) ≪ endl;
else if (field_type ≡ RECORD_ELN_STATUS_CHANGE_FIELD)
  temp_strm ≪ "Record_Eln_Status_Change_Field␣==␣" ≪ *static_cast⟨int *⟩(value) ≪ endl;
else if (field_type ≡ RECORD_IDENTIFICATION_NUMBER_FIELD)
  temp_strm ≪ "Record_Identification_Number_Field␣==␣" ≪ *static_cast⟨string
      *⟩(value) ≪ endl;
else if (field_type ≡ RECORD_SOURCE_ID_FIELD)
  temp_strm ≪ "Record_Source_Id_Field␣==␣" ≪ *static_cast⟨int *⟩(value) ≪ endl;
else if (field_type ≡ RECORD_YEAR_APPEARANCE_BEGIN_FIELD)
  temp_strm ≪ "Record_Year_Appearance_Begin_Field␣==␣" ≪ *static_cast⟨int *⟩(value) ≪ endl;
else if (field_type ≡ RECORD_YEAR_APPEARANCE_END_FIELD)
  temp_strm ≪ "Record_Year_Appearance_End_Field␣==␣" ≪ *static_cast⟨int *⟩(value) ≪ endl;
else if (field_type ≡ RECORD_YEAR_APPEARANCE_RAK_WB_FIELD)
  temp_strm ≪ "Record_Year_Appearance_Rak_Wb_Field␣==␣" ≪ *static_cast⟨int
      *⟩(value) ≪ endl;
else if (field_type ≡ RECORD_YEAR_APPEARANCE_ORIGINAL_FIELD)
  temp_strm ≪ "Record_Year_Appearance_Original_Field␣==␣" ≪ *static_cast⟨int
      *⟩(value) ≪ endl;
else if (field_type ≡ RECORD_DATE_STATUS_CHANGE_FIELD)
  temp_strm ≪ "Record_Date_Status_Change_Field:" ≪ endl ≪
      *static_cast⟨Date_Time_Node⟩(value) ≪ endl;
else if (field_type ≡ RECORD_DATE_ORIGINAL_ENTRY_FIELD)
  temp_strm ≪ "Record_Date_Original_Entry_Field:" ≪ endl ≪
      *static_cast⟨Date_Time_Node⟩(value) ≪ endl;
else if (field_type ≡ RECORD_DATE_MOST_RECENT_CHANGE_FIELD)
  temp_strm ≪ "Record_Date_Most_Recent_Change_Field␣==␣" ≪ endl ≪
      *static_cast⟨Date_Time_Node⟩(value) ≪ endl;
else if (field_type ≡ REMOTE_ACCESS_FIELD)
  temp_strm ≪ "Remote_Access␣==␣" ≪ *static_cast⟨string *⟩(value) ≪ endl;
else if (field_type ≡ RIGHTS_FIELD)
  temp_strm ≪ "Rights␣==␣" ≪ *static_cast⟨string *⟩(value) ≪ endl;
else if (field_type ≡ SOURCE_FIELD)
  temp_strm ≪ "Source␣==␣" ≪ *static_cast⟨string *⟩(value) ≪ endl;
else if (field_type ≡ SUBJECT_FIELD)
  temp_strm ≪ "Subject␣==␣" ≪ *static_cast⟨string *⟩(value) ≪ endl;
```

```
    else if (field_type ≡ SUPERORDINATE_ENTITIES_FIELD)
      temp_strm ≪ "Superordinate_Entities␣==␣" ≪ *static_cast⟨string *⟩(value) ≪ endl;
    else if (field_type ≡ TITLE_FIELD)
      temp_strm ≪ "Title␣==␣" ≪ *static_cast⟨string *⟩(value) ≪ endl;
    else if (field_type ≡ TYPE_FIELD)
      temp_strm ≪ "Type␣==␣" ≪ *static_cast⟨string *⟩(value) ≪ endl;
    else temp_strm ≪ "Can't␣show␣this␣field␣yet." ≪ endl;
  }    /* if (value ≠ 0) */
  else {
    temp_strm ≪ "'value'␣␣==␣0." ≪ endl;
  }
  if (up ∧ up→value ∧ up→value_type ≡ QUERY_TYPE_STRING_TYPE) {
    temp_strm ≪ "'up->value'␣==␣" ≪ *static_cast⟨string *⟩(up→value) ≪ endl;
  }
```

118. Output the contents of *temp_strm*. [LDF 2006.10.31.]

```
⟨ Define Query_Type functions 87 ⟩ +≡
  cerr_mutex.lock( );
  cerr ≪ temp_strm.str( );
  cerr_mutex.unlock( );
  temp_strm.str("");
  if (scanner_node ≠ 0 ∧ scanner_node→log_strm.is_open( )) scanner_node→log_strm ≪ temp_strm;
```

119. Show subsidiary nodes recursively. [LDF 2006.11.14.]

Log

[2006.11.14.] Added this section.

```
⟨ Define Query_Type functions 87 ⟩ +≡
  if (and_node ≠ 0) {
    temp_strm ≪ "***␣‘and_node’␣****" ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    temp_strm.str("");
    if (scanner_node ≠ 0 ∧ scanner_node→log_strm.is_open()) scanner_node→log_strm ≪ temp_strm;
    and_node→show("‘and_node’:", sscanner_node);
  }
  if (or_node ≠ 0) {
    temp_strm ≪ "***␣‘or_node’␣****" ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    temp_strm.str("");
    if (scanner_node ≠ 0 ∧ scanner_node→log_strm.is_open()) scanner_node→log_strm ≪ temp_strm;
    or_node→show("‘or_node’:", sscanner_node);
  }
  if (xor_node ≠ 0) {
    temp_strm ≪ "***␣‘xor_node’␣****" ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    temp_strm.str("");
    if (scanner_node ≠ 0 ∧ scanner_node→log_strm.is_open()) scanner_node→log_strm ≪ temp_strm;
    xor_node→show("‘xor_node’:", sscanner_node);
  }
  temp_strm ≪ "*******" ≪ endl;
  cerr_mutex.lock();
  cerr ≪ temp_strm.str();
  cerr_mutex.unlock();
  temp_strm.str("");
```

120.

```
⟨ Define Query_Type functions 87 ⟩ +≡
  return 0; }      /* End of Query_Type::show definition. */
```

121. Putting Query_Type together. [LDF 2006.10.31.]

122. This is what's compiled.

⟨Include files 10⟩
⟨`querytyp.web` 49⟩

using namespace std;
using namespace Scan_Parse;

⟨Preprocessor macro definitions 77⟩
⟨Forward declarations 17⟩
⟨Declare **class Query_Type** 53⟩
⟨Initialize **static Query_Type** constants 58⟩
⟨Initialize **static Query_Type** variables 80⟩
⟨Define **Query_Type** functions 87⟩

123. This is what's written to `querytyp.h`.

```
⟨ querytyp.hh 123 ⟩ ≡
#ifndef QUERYTYP_KNOWN
#define QUERYTYP_KNOWN 1
  ⟨ Preprocessor macro definitions 77 ⟩
  ⟨ Preprocessor macro calls 23 ⟩
  using namespace std;
  ⟨ Forward declarations 17 ⟩
  ⟨ Declare class Query_Type 53 ⟩
#endif    /* QUERYTYP_KNOWN is defined. */
```

124. Query_Type::*generate_sql_string* definition (`qtgensql.web`). [LDF 2006.12.14.]

Log

[LDF 2006.12.14.] Created this file.

```
⟨ qtgensql.web 124 ⟩ ≡
  static char id_string[] = "$Id: qtgensql.web,v 1.6 2007/02/13 20:40:08 lfinsto1 Exp $";
```

This code is cited in sections 6 and 8.

This code is used in section 158.

125. Include files.

```
⟨ Include files 10 ⟩ +≡
#include "localldf.h"
#ifdef NON_WIN_LDF
#include "nonwin.h"
#else
#include "stdafx.h"
#endif
#include "parser.hxx"
#include "dttmtype.h"
#include "idtype.h"
#include "scnrtype.h"
#include "scanner.h"
#include "querytyp.h"
```

126. Generate SQL string. [LDF 2006.12.01.]

Log

[LDF 2006.12.01.] Added this function.

[LDF 2006.12.12.] Added code for `MAIN_CANONICAL_TITLE_FLAG`.

[LDF 2006.12.12.] Added code to account for **static const unsigned** *shorts* that refer to additional tables in the OAI database (dc_test).

[LDF 2006.12.14.] Moved the definition of this function from `querytyp.web` to this file (`qtgensql.web`).

127.

```
⟨ Define Query_Type functions 87 ⟩ +≡
  int Query_Type::generate_sql_string(Scanner_Node scanner_node, int database_type, stringstream
        *sql_strm, stringstream *select_strm, stringstream *from_strm, stringstream
        *where_strm_0, stringstream *where_strm_1, bool *first_select, bool *first_from, bool
        *first_where, bitset < QUERY_TYPE_BITSET_SIZE > *field_flags, string *return_str){
#if 0     /* 14g */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
    stringstream temp_strm;
    stringstream date_strm;
#ifdef DEBUG_OUTPUT
    temp_strm << "Entering␣`Query_Type::generate_sql_string'." << endl <<
        "`query_ctr'␣==␣" << query_ctr << endl << "`database_type'␣==␣" <<
        token_map[database_type] << endl << "`query_type'␣==␣" << query_type_map[query_type] <<
        endl << "`*first_select'␣==␣" << *first_select << endl << "`*first_where'␣==␣" <<
        *first_where << endl << "`*first_from␣==␣" << *first_from << endl << "`query_ctr'␣==␣" <<
        query_ctr << endl;
    cerr_mutex.lock();
    cerr << temp_strm.str();
    cerr_mutex.unlock();
    if (scanner_node ≠ 0) scanner_node→log_strm << temp_strm.str();
    temp_strm.str("");
    getchar();
#endif
```

128. Set match operator string. [LDF 2006.12.12.]

Log

[2006.12.12.] Added this declaration.

```
⟨ Define Query_Type functions 87 ⟩ +≡
  string match_str;
  if (match_value ≡ QUERY_TYPE_NULL_TYPE) match_str = "=";
  else if (match_value ≡ CONTAINS_VALUE) match_str = "contains";
  else if (match_value ≡ FREETEXT_VALUE) match_str = "freetext";
  else if (match_value ≡ LIKE_VALUE) match_str = "like";
  else {
    temp_strm << "WARNING!␣␣In␣`Query_Type::generate_sql_string':" << endl <<
        "`match_value'␣has␣invalid␣value:␣␣" << match_value << endl <<
        "Will␣use␣`='␣as␣the␣match␣operator." << endl;
    cerr_mutex.lock();
    cerr << temp_strm.str();
    cerr_mutex.unlock();
    if (scanner_node ≠ 0) scanner_node→log_strm << temp_strm.str();
    temp_strm.str("");
  }
```

129. Set *query_type_str*. [LDF 2006.12.06.]

```
⟨ Define Query_Type functions 87 ⟩ +≡
  string query_type_str;
```

130. Set parenthesis strings. [LDF 2006.12.14.]

```
⟨ Define Query_Type functions 87 ⟩ +≡
  string open_parenthesis_str;
  string close_parenthesis_str;
  if (and_node ∨ or_node ∨ xor_node) {
    open_parenthesis_str = "(";
    close_parenthesis_str = ")";
  }
  else {
    open_parenthesis_str = "";
    close_parenthesis_str = "";
  }
  if (query_type ≡ AND_TYPE) query_type_str = "and";
  else if (query_type ≡ OR_TYPE) query_type_str = "or";
  else if (query_type ≡ XOR_TYPE) {
    if (database_type ≡ OAI) {
      temp_strm ≪ "ERROR!␣␣In␣‘Query_Type::generate_sql_string’:" ≪ endl ≪
          "‘query_type’␣==␣‘XOR_TYPE’␣and␣‘database_type’␣==␣‘OAI’." ≪
          endl ≪ "This␣combination␣of␣types␣is␣not␣allowed." ≪ endl ≪
          "Exiting␣function␣unsuccessfully␣with␣return␣value␣1." ≪ endl;
      cerr_mutex.lock();
      cerr ≪ temp_strm.str();
      cerr_mutex.unlock();
      scanner_node→log_strm ≪ temp_strm.str();
      temp_strm.str("");
      *return_str = "";
      return 1;
    }     /* if (database_type ≡ OAI) */
    query_type_str = "xor";
  }     /* else if (query_type ≡ XOR_TYPE) */
  if (negated) query_type_str += "␣not";
```

131.

```
⟨ Define Query_Type functions 87 ⟩ +≡
  if (query_ctr ≡ 0) *select_strm ≪ "select␣" ≪ endl;
#if 0     /* 1 */
  cerr ≪ "‘field_type’␣==␣" ≪ field_type_map[field_type] ≪ endl;
#endif
```

132. AUTHOR_SURNAME_FIELD. Pica Only. [LDF 2006.12.06.]

```
⟨ Define Query_Type functions 87 ⟩ +≡
  if (field_type ≡ AUTHOR_SURNAME_FIELD ∧ database_type ≡ PICA) {
    if (*first_select) {
      *select_strm ≪ "RAUT.record_id";
      *first_select = false;
    }
    if ((*field_flags & AUTHOR_FLAG) ≡ NULL_BITSET) {
      *select_strm ≪ ",␣AUT.author_id" ≪ endl;
    }
    if ((*field_flags & AUTHOR_SURNAME_FLAG) ≡ NULL_BITSET) {
      *select_strm ≪ ",␣AUT.author_surname" ≪ endl;
    }
    if (*first_from) *from_strm ≪ "from␣";
    else if ((*field_flags & AUTHOR_FLAG) ≡ NULL_BITSET) {
      *from_strm ≪ ",␣";
    }
    *first_from = false;
    if ((*field_flags & AUTHOR_FLAG) ≡ NULL_BITSET) {
      *from_strm ≪ "Authors␣as␣AUT,␣Records_Authors␣as␣RAUT" ≪ endl;
    }
    if (*first_where) *where_strm_0 ≪ "where␣" ≪ endl;
    else {
      *where_strm_0 ≪ query_type_str ≪ "␣" ≪ open_parenthesis_str;
    }
    *first_where = false;
    *where_strm_0 ≪ "AUT.author_surname␣" ≪ match_str ≪ "␣'" ≪ *static_cast⟨string
        *⟩(value) ≪ "'␣";
    if ((*field_flags & AUTHOR_FLAG) ≡ NULL_BITSET) {
      *where_strm_1 ≪ "and␣RAUT.author_id␣=␣AUT.author_id" ≪ endl;
    }
    *field_flags |= AUTHOR_SURNAME_FLAG;
    *field_flags |= AUTHOR_FLAG;
  }     /* if (field_type ≡ AUTHOR_SURNAME_FIELD ∧ database_type ≡ PICA) */
```

133. AUTHOR_GIVEN_NAME_FIELD. Pica Only. [LDF 2006.12.13.]

```
⟨ Define Query_Type functions 87 ⟩ +≡
  else
    if (field_type ≡ AUTHOR_GIVEN_NAME_FIELD ∧ database_type ≡ PICA) {
      if (*first_select) {
        *select_strm ≪ "RAUT.record_id";
        *first_select = false;
      }
      if ((*field_flags & AUTHOR_FLAG) ≡ NULL_BITSET) {
        *select_strm ≪ ",␣AUT.author_id" ≪ endl;
      }
      if ((*field_flags & AUTHOR_GIVEN_NAME_FLAG) ≡ NULL_BITSET) {
        *select_strm ≪ ",␣AUT.author_given_name" ≪ endl;
      }
      if (*first_from) *from_strm ≪ "from␣";
      else if ((*field_flags & AUTHOR_FLAG) ≡ NULL_BITSET) {
        *from_strm ≪ ",␣";
      }
      *first_from = false;
      if ((*field_flags & AUTHOR_FLAG) ≡ NULL_BITSET) {
        *from_strm ≪ "Authors␣as␣AUT,␣Records_Authors␣as␣RAUT" ≪ endl;
      }
      if (*first_where) *where_strm_0 ≪ "where␣" ≪ endl;
      else {
        *where_strm_0 ≪ query_type_str ≪ "␣" ≪ open_parenthesis_str;
      }
      *first_where = false;
      *where_strm_0 ≪ "AUT.author_given_name␣" ≪ match_str ≪ "␣'" ≪ *static_cast⟨string
          *⟩(value) ≪ "'␣";
      if ((*field_flags & AUTHOR_FLAG) ≡ NULL_BITSET) {
        *where_strm_1 ≪ "and␣RAUT.author_id␣=␣AUT.author_id" ≪ endl;
      }
      *field_flags |= AUTHOR_GIVEN_NAME_FLAG;
      *field_flags |= AUTHOR_FLAG;
    }     /* else if (field_type ≡ AUTHOR_GIVEN_NAME_FIELD ∧ database_type ≡ PICA) */
```

134. AUTHOR_PREFIX_FIELD. Pica Only. [LDF 2006.12.13.]

```
⟨ Define Query_Type functions 87 ⟩ +≡
  else
    if (field_type ≡ AUTHOR_PREFIX_FIELD ∧ database_type ≡ PICA) {
      if (*first_select) {
        *select_strm ≪ "RAUT.record_id";
        *first_select = false;
      }
      if ((*field_flags & AUTHOR_FLAG) ≡ NULL_BITSET) {
        *select_strm ≪ ",␣AUT.author_id" ≪ endl;
      }
      if ((*field_flags & AUTHOR_PREFIX_FLAG) ≡ NULL_BITSET) {
        *select_strm ≪ ",␣AUT.author_prefix" ≪ endl;
      }
      if (*first_from) *from_strm ≪ "from␣";
      else if ((*field_flags & AUTHOR_FLAG) ≡ NULL_BITSET) {
        *from_strm ≪ ",␣";
      }
      *first_from = false;
      if ((*field_flags & AUTHOR_FLAG) ≡ NULL_BITSET) {
        *from_strm ≪ "Authors␣as␣AUT,␣Records_Authors␣as␣RAUT" ≪ endl;
      }
      if (*first_where) *where_strm_0 ≪ "where␣" ≪ endl;
      else {
        *where_strm_0 ≪ query_type_str ≪ "␣" ≪ open_parenthesis_str;
      }
      *first_where = false;
      *where_strm_0 ≪ "AUT.author_prefix␣" ≪ match_str ≪ "␣'" ≪ *static_cast⟨string
          *⟩(value) ≪ "'␣";
      if ((*field_flags & AUTHOR_FLAG) ≡ NULL_BITSET) {
        *where_strm_1 ≪ "and␣RAUT.author_id␣=␣AUT.author_id" ≪ endl;
      }
      *field_flags |= AUTHOR_PREFIX_FLAG;
      *field_flags |= AUTHOR_FLAG;
    }     /* else if (field_type ≡ AUTHOR_PREFIX_FIELD ∧ database_type ≡ PICA) */
```

135. CONTRIBUTOR_SURNAME_FIELD. Pica Only. [LDF 2006.12.14.]

```
⟨ Define Query_Type functions 87 ⟩ +≡
  if (field_type ≡ CONTRIBUTOR_SURNAME_FIELD ∧ database_type ≡ PICA) {
    if (*first_select) {
      *select_strm ≪ "RCNTRB.record_id";
      *first_select = false;
    }
    if ((*field_flags & CONTRIBUTOR_FLAG) ≡ NULL_BITSET) {
      *select_strm ≪ ",␣CNTRB.contributor_id" ≪ endl;
    }
    if ((*field_flags & CONTRIBUTOR_SURNAME_FLAG) ≡ NULL_BITSET) {
      *select_strm ≪ ",␣CNTRB.contributor_surname" ≪ endl;
    }
    if (*first_from) *from_strm ≪ "from␣";
    else if ((*field_flags & CONTRIBUTOR_FLAG) ≡ NULL_BITSET) {
      *from_strm ≪ ",␣";
    }
    *first_from = false;
    if ((*field_flags & CONTRIBUTOR_FLAG) ≡ NULL_BITSET) {
      *from_strm ≪ "Contributors␣as␣CNTRB,␣Records_Contributors␣as␣RCNTRB" ≪ endl;
    }
    if (*first_where) *where_strm_0 ≪ "where␣" ≪ endl;
    else {
      *where_strm_0 ≪ query_type_str ≪ "␣" ≪ open_parenthesis_str;
    }
    *first_where = false;
    *where_strm_0 ≪ "CNTRB.contributor_surname␣" ≪ match_str ≪ "␣'" ≪ *static_cast⟨string
        *⟩(value) ≪ "'␣";
    if ((*field_flags & CONTRIBUTOR_FLAG) ≡ NULL_BITSET) {
      *where_strm_1 ≪ "and␣RCNTRB.contributor_id␣=␣CNTRB.contributor_id" ≪ endl;
    }
    *field_flags |= CONTRIBUTOR_SURNAME_FLAG;
    *field_flags |= CONTRIBUTOR_FLAG;
  }     /* if (field_type ≡ CONTRIBUTOR_SURNAME_FIELD ∧ database_type ≡ PICA) */
```

136. CONTRIBUTOR_GIVEN_NAME_FIELD. Pica Only. [LDF 2006.12.14.]

```
⟨ Define Query_Type functions 87 ⟩ +≡
  else
    if (field_type ≡ CONTRIBUTOR_GIVEN_NAME_FIELD ∧ database_type ≡ PICA) {
      if (*first_select) {
        *select_strm ≪ "RCNTRB.record_id";
        *first_select = false;
      }
      if ((*field_flags & CONTRIBUTOR_FLAG) ≡ NULL_BITSET) {
        *select_strm ≪ ",␣CNTRB.contributor_id" ≪ endl;
      }
      if ((*field_flags & CONTRIBUTOR_GIVEN_NAME_FLAG) ≡ NULL_BITSET) {
        *select_strm ≪ ",␣CNTRB.contributor_given_name" ≪ endl;
      }
      if (*first_from) *from_strm ≪ "from␣";
      else if ((*field_flags & CONTRIBUTOR_FLAG) ≡ NULL_BITSET) {
        *from_strm ≪ ",␣";
      }
      *first_from = false;
      if ((*field_flags & CONTRIBUTOR_FLAG) ≡ NULL_BITSET) {
        *from_strm ≪ "Contributors␣as␣CNTRB,␣Records_Contributors␣as␣RCNTRB" ≪ endl;
      }
      if (*first_where) *where_strm_0 ≪ "where␣" ≪ endl;
      else {
        *where_strm_0 ≪ query_type_str ≪ "␣" ≪ open_parenthesis_str;
      }
      *first_where = false;
      *where_strm_0 ≪ "CNTRB.contributor_given_name␣" ≪ match_str ≪ "␣'" ≪ *static_cast⟨string
          *⟩(value) ≪ "'␣";
      if ((*field_flags & CONTRIBUTOR_FLAG) ≡ NULL_BITSET) {
        *where_strm_1 ≪ "and␣RCNTRB.contributor_id␣=␣CNTRB.contributor_id" ≪ endl;
      }
      *field_flags |= CONTRIBUTOR_GIVEN_NAME_FLAG;
      *field_flags |= CONTRIBUTOR_FLAG;
    }     /* else if (field_type ≡ CONTRIBUTOR_GIVEN_NAME_FIELD ∧ database_type ≡ PICA) */
```

137. CONTRIBUTOR_PREFIX_FIELD. Pica Only. [LDF 2006.12.14.]

```
⟨ Define Query_Type functions 87 ⟩ +≡
  else
    if (field_type ≡ CONTRIBUTOR_PREFIX_FIELD ∧ database_type ≡ PICA) {
      if (*first_select) {
        *select_strm ≪ "RCNTRB.record_id";
        *first_select = false;
      }
      if ((*field_flags & CONTRIBUTOR_FLAG) ≡ NULL_BITSET) {
        *select_strm ≪ ",␣CNTRB.contributor_id" ≪ endl;
      }
      if ((*field_flags & CONTRIBUTOR_PREFIX_FLAG) ≡ NULL_BITSET) {
        *select_strm ≪ ",␣CNTRB.contributor_prefix" ≪ endl;
      }
      if (*first_from) *from_strm ≪ "from␣";
      else if ((*field_flags & CONTRIBUTOR_FLAG) ≡ NULL_BITSET) {
        *from_strm ≪ ",␣";
      }
      *first_from = false;
      if ((*field_flags & CONTRIBUTOR_FLAG) ≡ NULL_BITSET) {
        *from_strm ≪ "Contributors␣as␣CNTRB,␣Records_Contributors␣as␣RCNTRB" ≪ endl;
      }
      if (*first_where) *where_strm_0 ≪ "where␣" ≪ endl;
      else {
        *where_strm_0 ≪ query_type_str ≪ "␣" ≪ open_parenthesis_str;
      }
      *first_where = false;
      *where_strm_0 ≪ "CNTRB.contributor_prefix␣" ≪ match_str ≪ "␣'" ≪ *static_cast⟨string
          *⟩(value) ≪ "'␣";
      if ((*field_flags & CONTRIBUTOR_FLAG) ≡ NULL_BITSET) {
        *where_strm_1 ≪ "and␣RCNTRB.contributor_id␣=␣CNTRB.contributor_id" ≪ endl;
      }
      *field_flags |= CONTRIBUTOR_PREFIX_FLAG;
      *field_flags |= CONTRIBUTOR_FLAG;
    }     /* else if (field_type ≡ CONTRIBUTOR_PREFIX_FIELD ∧ database_type ≡ PICA) */
```

138. OAI. [LDF 2006.12.06.]

```
⟨ Define Query_Type functions 87 ⟩ +≡
  else
    if (field_type ≡ CONTRIBUTOR_FIELD ∧ database_type ≡ OAI) {
      if (*first_select) {
        *select_strm ≪ "RCN.record_id";
        *first_select = false;
      }
      if ((*field_flags & CONTRIBUTOR_FLAG) ≡ NULL_BITSET)
        *select_strm ≪ ",␣CN.contributor_id,␣CN.dc_contributor" ≪ endl;
      if (*first_from) *from_strm ≪ "from␣";
      else if ((*field_flags & CONTRIBUTOR_FLAG) ≡ NULL_BITSET) *from_strm ≪ ",␣";
      *first_from = false;
      if ((*field_flags & CONTRIBUTOR_FLAG) ≡ NULL_BITSET)
        *from_strm ≪ "Contributors␣as␣CN,␣Records_Contributors␣as␣RCN" ≪ endl;
      if (*first_where) *where_strm_0 ≪ "where␣";
      else {
        *where_strm_0 ≪ query_type_str ≪ "␣" ≪ open_parenthesis_str;
      }
      *first_where = false;
      *where_strm_0 ≪ "CN.dc_contributor␣" ≪ match_str ≪ "␣'" ≪ *static_cast⟨string
          *⟩(value) ≪ "'␣";
      if ((*field_flags & CONTRIBUTOR_FLAG) ≡ NULL_BITSET)
        *where_strm_1 ≪ "and␣RCN.contributor_id␣=␣CN.contributor_id" ≪ endl;
      *field_flags |= CONTRIBUTOR_FLAG;
    }     /* else if (field_type ≡ CONTRIBUTOR_FIELD ∧ database_type ≡ OAI) */
```

139. Creator. OAI only. [LDF 2006.12.06.]

```
⟨ Define Query_Type functions 87 ⟩ +≡
  else
  if (field_type ≡ CREATOR_FIELD ∧ database_type ≡ OAI) {
    if (*first_select) {
      *select_strm ≪ "RC.record_id";
      *first_select = false;
    }
    if ((*field_flags & CREATOR_FLAG) ≡ NULL_BITSET)
      *select_strm ≪ ",␣C.creator_id,␣C.dc_creator" ≪ endl;
    if (*first_from) *from_strm ≪ "from␣";
    else if ((*field_flags & CREATOR_FLAG) ≡ NULL_BITSET) *from_strm ≪ ",␣";
    *first_from = false;
    if ((*field_flags & CREATOR_FLAG) ≡ NULL_BITSET)
      *from_strm ≪ "Creators␣as␣C,␣Records_Creators␣as␣RC" ≪ endl;
    if (*first_where) *where_strm_0 ≪ "where␣" ≪ endl;
    else {
      *where_strm_0 ≪ query_type_str ≪ "␣" ≪ open_parenthesis_str;
    }
    *first_where = false;
    *where_strm_0 ≪ "C.dc_creator␣" ≪ match_str ≪ "␣'" ≪ *static_cast⟨string *⟩(value) ≪ "'␣";
    if ((*field_flags & CREATOR_FLAG) ≡ NULL_BITSET)
      *where_strm_1 ≪ "and␣RC.creator_id␣=␣C.creator_id" ≪ endl;
    *field_flags |= CREATOR_FLAG;
  }     /* else if (field_type ≡ CREATOR_FIELD ∧ database_type ≡ OAI) */
  else if (field_type ≡ TITLE_FIELD) {
```

140. OAI. [LDF 2006.12.12.]

Log

[2006.12.11.] Added this section.

```
⟨ Define Query_Type functions 87 ⟩ +≡
  if (database_type ≡ OAI) {
    if (*first_select) {
      *select_strm ≪ "T.record_id";
      *first_select = false;
    }
    if ((*field_flags & TITLE_FLAG) ≡ NULL_BITSET)
      *select_strm ≪ ",␣T.title_id,␣T.dc_title" ≪ endl;
    if (*first_from) *from_strm ≪ "from␣";
    else if ((*field_flags & TITLE_FLAG) ≡ NULL_BITSET) *from_strm ≪ ",␣";
    *first_from = false;
    if ((*field_flags & TITLE_FLAG) ≡ NULL_BITSET)
      *from_strm ≪ "Titles␣as␣T,␣Records␣as␣REC" ≪ endl;
    if (*first_where) *where_strm_0 ≪ "where␣" ≪ endl;
    else {
      *where_strm_0 ≪ query_type_str ≪ "␣" ≪ open_parenthesis_str;
    }
    *first_where = false;
    *where_strm_0 ≪ "T.dc_title␣" ≪ match_str ≪ "␣'" ≪ *static_cast⟨string *⟩(value) ≪ "'␣";
    if ((*field_flags & TITLE_FLAG) ≡ NULL_BITSET)
      *where_strm_1 ≪ "and␣T.record_id␣=␣REC.record_id" ≪ endl;
    *field_flags |= TITLE_FLAG;
  }    /* if (database_type ≡ OAI) */
  }    /* else if (field_type ≡ TITLE_FIELD) */
```

141. Main canonical title (Pica). [LDF 2006.12.12.]

Log

[LDF 2006.12.12.] Added this section.

```
⟨ Define Query_Type functions 87 ⟩ +≡
  else if (field_type ≡ MAIN_CANONICAL_TITLE_FIELD) {
```

142. PICA. [LDF 2006.12.12.]

Log

[LDF 2006.12.12.] Added this section.

```
⟨ Define Query_Type functions 87 ⟩ +≡
  if (database_type ≡ PICA) {
    if (*first_select) {
      *select_strm ≪ "RMT.record_id";
      *first_select = false;
    }
    if ((*field_flags & MAIN_CANONICAL_TITLE_FLAG) ≡ NULL_BITSET)
      *select_strm ≪ ",␣MT.main_title_id,␣MT.main_canonical_title" ≪ endl;
    if (*first_from) *from_strm ≪ "from␣";
    else if ((*field_flags & MAIN_CANONICAL_TITLE_FLAG) ≡ NULL_BITSET) *from_strm ≪ ",␣";
    *first_from = false;
    if ((*field_flags & MAIN_CANONICAL_TITLE_FLAG) ≡ NULL_BITSET)
      *from_strm ≪ "Main_Titles␣as␣MT,␣Records_Main_Titles␣as␣RMT" ≪ endl;
    if (*first_where) *where_strm_0 ≪ "where␣" ≪ endl;
    else {
      *where_strm_0 ≪ query_type_str ≪ "␣" ≪ open_parenthesis_str;
    }
    *first_where = false;
    *where_strm_0 ≪ "MT.main_canonical_title␣" ≪ match_str ≪ "␣'" ≪ *static_cast⟨string
        *⟩(value) ≪ "'␣";
    if ((*field_flags & MAIN_CANONICAL_TITLE_FLAG) ≡ NULL_BITSET)
      *where_strm_1 ≪ "and␣RMT.main_title_id␣=␣MT.main_title_id" ≪ endl;
    *field_flags |= MAIN_CANONICAL_TITLE_FLAG;
  }     /* if (database_type ≡ PICA) */
  }     /* else if (field_type ≡ MAIN_CANONICAL_TITLE_FIELD) */
```

143. Record. [LDF 2006.12.14.]

Log

[2006.12.14.] Added this section.

144. Record ID. [LDF 2006.12.14.]

Log

[2006.12.14.] Added this section.

```
⟨ Define Query_Type functions 87 ⟩ +≡
  else
    if (field_type ≡ RECORD_ID_FIELD ∧ database_type ≡ PICA) {
      if (*first_select) {
        *select_strm ≪ "REC.record_id" ≪ endl;
        *first_select = false;
      }
      else if ((*field_flags & RECORD_ID_FLAG) ≡ NULL_BITSET) {
        *select_strm ≪ ",␣REC.record_id" ≪ endl;
      }
      if (*first_from) *from_strm ≪ "from␣";
      else if ((*field_flags & RECORD_FLAG) ≡ NULL_BITSET) {
        *from_strm ≪ ",␣";
      }
      *first_from = false;
      if ((*field_flags & RECORD_FLAG) ≡ NULL_BITSET) {
        *from_strm ≪ "Records␣as␣REC" ≪ endl;
      }
      if (*first_where) *where_strm_0 ≪ "where␣" ≪ endl;
      else {
        *where_strm_0 ≪ query_type_str ≪ "␣" ≪ open_parenthesis_str;
      }
      *first_where = false;
      *where_strm_0 ≪ "REC.record_id␣" ≪ match_str ≪ "␣" ≪ *static_cast⟨int *⟩(value) ≪ "␣";
      *field_flags |= RECORD_ID_FLAG;
      *field_flags |= RECORD_FLAG;
    }     /* else if (field_type ≡ RECORD_ID_FIELD ∧ database_type ≡ PICA) */
```

145. Record ELN Original Entry. [LDF 2006.12.14.]

Log

[2006.12.14.] Added this section.

```
⟨ Define Query_Type functions 87 ⟩ +≡
  else
    if (field_type ≡ RECORD_ELN_ORIGINAL_ENTRY_FIELD ∧ database_type ≡ PICA) {
      if (∗first_select) {
        ∗select_strm ≪ "REC.record_id";
        ∗first_select = false;
      }
      if ((∗field_flags & RECORD_ELN_ORIGINAL_ENTRY_FLAG) ≡ NULL_BITSET) {
        ∗select_strm ≪ ",␣REC.eln_original_entry" ≪ endl;
      }
      if (∗first_from) ∗from_strm ≪ "from␣";
      else if ((∗field_flags & RECORD_FLAG) ≡ NULL_BITSET) {
        ∗from_strm ≪ ",␣";
      }
      ∗first_from = false;
      if ((∗field_flags & RECORD_FLAG) ≡ NULL_BITSET) {
        ∗from_strm ≪ "Records␣as␣REC" ≪ endl;
      }
      if (∗first_where) ∗where_strm_0 ≪ "where␣" ≪ endl;
      else {
        ∗where_strm_0 ≪ query_type_str ≪ "␣" ≪ open_parenthesis_str;
      }
      ∗first_where = false;
      ∗where_strm_0 ≪ "REC.eln_original_entry␣" ≪ match_str ≪ "␣" ≪ ∗static_cast⟨int
          ∗⟩(value) ≪ "␣";
      ∗field_flags |= RECORD_ELN_ORIGINAL_ENTRY_FLAG;
      ∗field_flags |= RECORD_FLAG;
    }     /∗ else if (field_type ≡ RECORD_ELN_ORIGINAL_ENTRY_FIELD ∧ database_type ≡ PICA) ∗/
```

146. Record ELN Most Recent Change. [LDF 2006.12.14.]

Log

[2006.12.14.] Added this section.

```
⟨ Define Query_Type functions 87 ⟩ +≡
  else
    if (field_type ≡ RECORD_ELN_MOST_RECENT_CHANGE_FIELD ∧ database_type ≡ PICA) {
      if (*first_select) {
        *select_strm ≪ "REC.record_id";
        *first_select = false;
      }
      if ((*field_flags & RECORD_ELN_MOST_RECENT_CHANGE_FLAG) ≡ NULL_BITSET) {
        *select_strm ≪ ",␣REC.eln_most_recent_change" ≪ endl;
      }
      if (*first_from) *from_strm ≪ "from␣";
      else if ((*field_flags & RECORD_FLAG) ≡ NULL_BITSET) {
        *from_strm ≪ ",␣";
      }
      *first_from = false;
      if ((*field_flags & RECORD_FLAG) ≡ NULL_BITSET) {
        *from_strm ≪ "Records␣as␣REC" ≪ endl;
      }
      if (*first_where) *where_strm_0 ≪ "where␣" ≪ endl;
      else {
        *where_strm_0 ≪ query_type_str ≪ "␣" ≪ open_parenthesis_str;
      }
      *first_where = false;
      *where_strm_0 ≪ "REC.eln_most_recent_change␣" ≪ match_str ≪ "␣" ≪ *static_cast⟨int
          *⟩(value) ≪ "␣";
      *field_flags |= RECORD_ELN_MOST_RECENT_CHANGE_FLAG;
      *field_flags |= RECORD_FLAG;
    }     /* else if (field_type ≡ RECORD_ELN_MOST_RECENT_CHANGE_FIELD ∧ database_type ≡ PICA) */
```

147. Record ELN Status Change. [LDF 2006.12.15.]

Log

[LDF 2006.12.15.] Added this section.

```
⟨ Define Query_Type functions 87 ⟩ +≡
  else
    if (field_type ≡ RECORD_ELN_STATUS_CHANGE_FIELD ∧ database_type ≡ PICA) {
      if (*first_select) {
        *select_strm ≪ "REC.record_id";
        *first_select = false;
      }
      if ((*field_flags & RECORD_ELN_STATUS_CHANGE_FLAG) ≡ NULL_BITSET) {
        *select_strm ≪ ",␣REC.eln_status_change" ≪ endl;
      }
      if (*first_from) *from_strm ≪ "from␣";
      else if ((*field_flags & RECORD_FLAG) ≡ NULL_BITSET) {
        *from_strm ≪ ",␣";
      }
      *first_from = false;
      if ((*field_flags & RECORD_FLAG) ≡ NULL_BITSET) {
        *from_strm ≪ "Records␣as␣REC" ≪ endl;
      }
      if (*first_where) *where_strm_0 ≪ "where␣" ≪ endl;
      else {
        *where_strm_0 ≪ query_type_str ≪ "␣" ≪ open_parenthesis_str;
      }
      *first_where = false;
      *where_strm_0 ≪ "REC.eln_status_change␣" ≪ match_str ≪ "␣" ≪ *static_cast⟨int
          *⟩(value) ≪ "␣";
      *field_flags |= RECORD_ELN_STATUS_CHANGE_FLAG;
      *field_flags |= RECORD_FLAG;
    }     /* else if (field_type ≡ RECORD_ELN_STATUS_CHANGE_FIELD ∧ database_type ≡ PICA) */
```

148. Record Identification Number. [LDF 2006.12.15.]

Log

[LDF 2006.12.15.] Added this section.

```
⟨ Define Query_Type functions 87 ⟩ +≡
  else
    if (field_type ≡ RECORD_IDENTIFICATION_NUMBER_FIELD ∧ database_type ≡ PICA) {
      if (*first_select) {
        *select_strm ≪ "REC.record_id";
        *first_select = false;
      }
      if ((*field_flags & RECORD_IDENTIFICATION_NUMBER_FLAG) ≡ NULL_BITSET) {
        *select_strm ≪ ",␣REC.identification_number" ≪ endl;
      }
      if (*first_from) *from_strm ≪ "from␣";
      else if ((*field_flags & RECORD_FLAG) ≡ NULL_BITSET) {
        *from_strm ≪ ",␣";
      }
      *first_from = false;
      if ((*field_flags & RECORD_FLAG) ≡ NULL_BITSET) {
        *from_strm ≪ "Records␣as␣REC" ≪ endl;
      }
      if (*first_where) *where_strm_0 ≪ "where␣" ≪ endl;
      else {
        *where_strm_0 ≪ query_type_str ≪ "␣" ≪ open_parenthesis_str;
      }
      *first_where = false;
      *where_strm_0 ≪ "REC.identification_number␣" ≪ match_str ≪ "␣'" ≪ *static_cast⟨string
          *⟩(value) ≪ "'␣";
      *field_flags |= RECORD_IDENTIFICATION_NUMBER_FLAG;
      *field_flags |= RECORD_FLAG;
    }     /* else if (field_type ≡ RECORD_IDENTIFICATION_NUMBER_FIELD ∧ database_type ≡ PICA) */
```

149. Record Date Status Change. [LDF 2006.12.19.]

Log

[LDF 2006.12.19.] Added this section.

```
⟨ Define Query_Type functions 87 ⟩ +≡
  else
    if (field_type ≡ RECORD_DATE_STATUS_CHANGE_FIELD ∧ database_type ≡ PICA) {
      if (*first_select) {
        *select_strm ≪ "REC.record_id";
        *first_select = false;
      }
      if ((*field_flags & RECORD_DATE_STATUS_CHANGE_FLAG) ≡ NULL_BITSET) {
        *select_strm ≪ ",␣REC.date_status_change" ≪ endl;
      }
      if (*first_from) *from_strm ≪ "from␣";
      else if ((*field_flags & RECORD_FLAG) ≡ NULL_BITSET) {
        *from_strm ≪ ",␣";
      }
      *first_from = false;
      if ((*field_flags & RECORD_FLAG) ≡ NULL_BITSET) {
        *from_strm ≪ "Records␣as␣REC" ≪ endl;
      }
      if (*first_where) *where_strm_0 ≪ "where␣" ≪ endl;
      else {
        *where_strm_0 ≪ query_type_str ≪ "␣" ≪ open_parenthesis_str;
      }
      *first_where = false;
      Date_Time_Node d = static_cast⟨Date_Time_Node⟩(value);
      date_strm.str("");
      *where_strm_0 ≪ "REC.date_status_change␣" ≪ match_str ≪ "␣convert(datetime,␣'";
      if (d→year) *where_strm_0 ≪ setfill('0') ≪ right ≪ setw(4) ≪ *d→year;
      else *where_strm_0 ≪ "0000";
      *where_strm_0 ≪ "-";
      if (d→month) *where_strm_0 ≪ setfill('0') ≪ right ≪ setw(2) ≪ *d→month;
      else *where_strm_0 ≪ "00";
      *where_strm_0 ≪ "-";
      if (d→day) *where_strm_0 ≪ setfill('0') ≪ right ≪ setw(2) ≪ *d→day;
      else *where_strm_0 ≪ "00";
      *where_strm_0 ≪ "␣";
      if (d→hour) *where_strm_0 ≪ setfill('0') ≪ right ≪ setw(2) ≪ *d→hour;
      else *where_strm_0 ≪ "00";
      *where_strm_0 ≪ ":";
      if (d→minute) *where_strm_0 ≪ setfill('0') ≪ right ≪ setw(2) ≪ *d→minute;
      else *where_strm_0 ≪ "00";
      *where_strm_0 ≪ ":";
      if (d→second) {
        if (*d→second < 10) *where_strm_0 ≪ "0";
        *where_strm_0 ≪ fixed ≪ setprecision(3) ≪ *d→second;
      }
      else *where_strm_0 ≪ "00.000";
```

```
    *where_strm_0 ≪ "',␣121)";
    *field_flags |= RECORD_DATE_STATUS_CHANGE_FLAG;
    *field_flags |= RECORD_FLAG;
  }    /* else if (field_type ≡ RECORD_DATE_STATUS_CHANGE_FIELD ∧ database_type ≡ PICA) */
```

150. Subject. [LDF Undated.]

```
⟨ Define Query_Type functions 87 ⟩ +≡
  else if (field_type ≡ SUBJECT_FIELD) {
```

151.

Log

[2006.12.12.] Added this section.

```
⟨ Define Query_Type functions 87 ⟩ +≡
  if (database_type ≡ PICA) {
    if (*first_select) {
      *select_strm ≪ "RS.record_id";
      *first_select = false;
    }
    if ((*field_flags & SUBJECT_FLAG) ≡ NULL_BITSET)
      *select_strm ≪ ",␣S.subject_id,␣S.subject" ≪ endl;
    if (*first_from) *from_strm ≪ "from␣";
    else if ((*field_flags & SUBJECT_FLAG) ≡ NULL_BITSET) *from_strm ≪ ",␣";
    *first_from = false;
    if ((*field_flags & SUBJECT_FLAG) ≡ NULL_BITSET)
      *from_strm ≪ "Subjects␣as␣S,␣Records_Subjects␣as␣RS" ≪ endl;
    if (*first_where) *where_strm_0 ≪ "where␣" ≪ endl;
    else {
      *where_strm_0 ≪ query_type_str ≪ "␣" ≪ open_parenthesis_str;
    }
    *first_where = false;
    *where_strm_0 ≪ "S.subject␣" ≪ match_str ≪ "␣'" ≪ *static_cast⟨string *⟩(value) ≪ "'␣";
    if ((*field_flags & SUBJECT_FLAG) ≡ NULL_BITSET)
      *where_strm_1 ≪ "and␣RS.subject_id␣=␣S.subject_id" ≪ endl;
    *field_flags |= SUBJECT_FLAG;
  }    /* if (database_type ≡ PICA) */
```

152.

```
⟨ Define Query_Type functions 87 ⟩ +≡
  if (database_type ≡ OAI) {
    if (*first_select) {
      *select_strm ≪ "RS.record_id";
      *first_select = false;
    }
    if ((*field_flags & SUBJECT_FLAG) ≡ NULL_BITSET)
      *select_strm ≪ ",␣S.subject_id,␣S.dc_subject" ≪ endl;
    if (*first_from) *from_strm ≪ "from␣";
    else if ((*field_flags & SUBJECT_FLAG) ≡ NULL_BITSET) *from_strm ≪ ",␣";
    *first_from = false;
    if ((*field_flags & SUBJECT_FLAG) ≡ NULL_BITSET)
      *from_strm ≪ "Subjects␣as␣S,␣Records_Subjects␣as␣RS" ≪ endl;
    if (*first_where) *where_strm_0 ≪ "where␣" ≪ endl;
    else {
      *where_strm_0 ≪ query_type_str ≪ "␣" ≪ open_parenthesis_str;
    }
    *first_where = false;
    *where_strm_0 ≪ "S.dc_subject␣" ≪ match_str ≪ "␣'" ≪ *static_cast⟨string *⟩(value) ≪ "'␣";
    if ((*field_flags & SUBJECT_FLAG) ≡ NULL_BITSET)
      *where_strm_1 ≪ "and␣RS.subject_id␣=␣S.subject_id" ≪ endl;
    *field_flags |= SUBJECT_FLAG;
  }     /* if (database_type ≡ OAI) */
  }     /* else if (field_type ≡ SUBJECT_FIELD) */
  temp_strm ≪ "`value_type'␣==␣" ≪ value_type_map[value_type] ≪ endl;
  temp_strm ≪ "`target_types'␣==␣";
  if (target_types.size() ≤ 0) temp_strm ≪ "QUERY_TYPE_NULL_TYPE";
  else if (target_types.size() ≡ 1) {
    temp_strm ≪ target_type_map[target_types[0]];
  }
  else {
    int i = 0;
    for (vector⟨unsigned short⟩::iterator iter = target_types.begin(); iter ≠ target_types.end();
         ++iter) {
      if (i++ > 0) temp_strm ≪ endl ≪ "--" ≪ endl;
      temp_strm ≪ target_type_map[*iter];
    }     /* for */
  }     /* else */
  temp_strm ≪ endl;
  if (value_type ≡ QUERY_TYPE_STRING_TYPE) {
    temp_strm ≪ *static_cast⟨string *⟩(value) ≪ endl;
    if (value_type ≡ QUERY_TYPE_STRING_TYPE) ;
#if 0     /* 1 */
    *sql_strm ≪ *static_cast⟨string *⟩(value) ≪ "␣";
#endif
  }
  if (up) temp_strm ≪ "`up'␣==␣" ≪ up→query_ctr;
  else temp_strm ≪ "`up'␣==␣0";
  temp_strm ≪ endl;
  if (and_node) {
    temp_strm ≪ "`and'␣==␣" ≪ and_node→query_ctr;
```

```
  }
  else temp_strm ≪ "‘and_node’␣==␣0";
  temp_strm ≪ endl;
  if (or_node) {
    temp_strm ≪ "‘or’␣==␣" ≪ or_node→query_ctr;
  }
  else temp_strm ≪ "‘or_node’␣==␣0";
  temp_strm ≪ endl;
  if (or_node) {
    temp_strm ≪ "‘xor’␣==␣" ≪ xor_node→query_ctr;
  }
  else temp_strm ≪ "‘xor_node’␣==␣0";
  temp_strm ≪ endl;
  if (and_node) {
    temp_strm ≪ "‘and_node’␣==␣" ≪ endl;
    ∗where_strm_0 ≪ endl;
    and_node→generate_sql_string(scanner_node, database_type, sql_strm, select_strm, from_strm,
        where_strm_0, where_strm_1, first_select, first_from, first_where, field_flags, return_str);
  }
  if (or_node) {
    temp_strm ≪ "‘or_node’␣==␣" ≪ endl;
    ∗where_strm_0 ≪ endl;
    or_node→generate_sql_string(scanner_node, database_type, sql_strm, select_strm, from_strm,
        where_strm_0, where_strm_1, first_select, first_from, first_where, field_flags, return_str);
  }
  if (xor_node) {
    temp_strm ≪ "‘xor_node’␣==␣" ≪ endl;
    ∗where_strm_0 ≪ endl;
    xor_node→generate_sql_string(scanner_node, database_type, sql_strm, select_strm, from_strm,
        where_strm_0, where_strm_1, first_select, first_from, first_where, field_flags, return_str);
  }
```

153.

⟨ Define **Query_Type** functions 87 ⟩ +≡

```
  if (query_ctr > 0) ∗where_strm_0 ≪ close_parenthesis_str;
```

154. Write streams to ∗*sql_strm*. [LDF 2006.12.05.]

⟨ Define **Query_Type** functions 87 ⟩ +≡

```
  if (query_ctr ≡ 0) {
    ∗sql_strm ≪ select_strm→str() ≪ from_strm→str() ≪ where_strm_0→str() ≪ endl ≪
        where_strm_1→str();
  }
```

155. Print debuggging output to terminal. [LDF 2006.12.05.]

⟨ Define **Query_Type** functions 87 ⟩ +≡

```
  if (query_ctr ≡ 0) temp_strm ≪ endl ≪ "‘sql_strm->str()’␣==␣" ≪ endl ≪ sql_strm→str() ≪
        endl ≪ "Enter␣<RETURN>␣to␣continue:␣";
```

156. Store string and return. [LDF 2006.12.01.]

```
⟨ Define Query_Type functions 87 ⟩ +≡
#ifdef DEBUG_OUTPUT
  temp_strm ≪ "Exiting␣‘Query_Type::generate_sql_string’." ≪ endl;
  cerr_mutex.lock( );
  cerr ≪ temp_strm.str( );
  cerr_mutex.unlock( );
  if (scanner_node ≠ 0) scanner_node→log_strm ≪ temp_strm.str( );
  temp_strm.str("");
#endif
  *return_str = sql_strm→str( );
  return 0; }      /* Query_Type::generate_sql_string */
```

157. Putting Query_Type::*generate_sql_string* together. [LDF 2006.10.31.]

158. This is what's compiled.

⟨ Include files 10 ⟩
⟨ qtgensql.web 124 ⟩

```
using namespace std;
using namespace Scan_Parse;
```

⟨ Define **Query_Type** functions 87 ⟩

159. datasource_type (dtsrctyp.web). [LDF 2006.12.08.]

Log

[LDF 2006.12.08.] Created this file.

⟨ dtsrctyp.web 159 ⟩ ≡

```
static char id_string[] = "$Id: dtsrctyp.web,v 1.7 2007/02/13 20:38:06 lfinsto1 Exp $";
```

This code is cited in sections 6 and 8.

This code is used in section 186.

160. Include files.

⟨ Include files 10 ⟩ +≡

```
#include "localldf.h"
#ifdef NON_WIN_LDF
#include "nonwin.h"
#else
#include "stdafx.h"
#endif
#include "parser.hxx"
#include "dttmtype.h"
#include "idtype.h"
#include "scnrtype.h"
#include "scanner.h"
```

161. Preprocessor macro calls.

⟨ Preprocessor macro calls 23 ⟩ +≡

```
#ifdef WIN_LDF
#pragma once
#endif
```

162. Forward declarations. [LDF 2006.12.08.]

Log

[LDF 2006.12.08.] Added this section.

⟨ Forward declarations 17 ⟩ +≡

```
class Scanner_Type;
typedef Scanner_Type *Scanner_Node;
class Datasource_Type;
typedef Datasource_Type *Datasource_Node;
class Id_Type;
typedef Id_Type *Id_Node;
```

163. class datasource_type declaration. . [LDF 2006.12.08.]
The forward declaration of **Datasource_Type** is needed in order to be able to define **Datasource_Node** using **typedef**. [LDF 2006.12.08.]

Log

Added this section.

⟨ Declare **class Datasource_Type** 163 ⟩ ≡
```
class Datasource_Type;
typedef Datasource_Type *Datasource_Node;
class Datasource_Type {
  ⟨ friend declarations for class Datasource_Type 164 ⟩
private: unsigned short type;
  static map⟨unsigned short, string⟩ datasource_type_map;
  string name;
  void *value;
  Scanner_Node scanner_node;
public: ⟨ Declare static Datasource_Type constants 165 ⟩
  ⟨ Declare Datasource_Type functions 171 ⟩
};
```
This code is used in sections 186 and 187.

164. friend declarations for class datasource_type. [LDF 2006.12.08.]

Log

[LDF 2006.12.08.] Added this section.

⟨ **friend** declarations for **class Datasource_Type** 164 ⟩ ≡
```
friend int yyparse(void *);
```
This code is used in section 163.

165. Declare static datasource_type constants. [LDF 2006.12.08.]

Log

[LDF 2006.12.08.] Added this section with the declaration of `DATASOURCE_TYPE_NULL_TYPE`.

[LDF 2006.12.08.] Added the declarations of `DBT_TYPE`, `GBV_GVK_TYPE`, `TIMMS_TYPE`, and `DATASOURCE_FILE_TYPE`.

⟨ Declare **static Datasource_Type** constants 165 ⟩ ≡
```
static const unsigned short DATASOURCE_TYPE_NULL_TYPE;
static const unsigned short DBT_TYPE;
static const unsigned short GBV_GVK_TYPE;
static const unsigned short TIMMS_TYPE;
static const unsigned short DATASOURCE_FILE_TYPE;
```
See also section 168.
This code is used in section 163.

166.

⟨ Initialize **static Datasource_Type** constants 166 ⟩ ≡
```
const unsigned short Datasource_Type::DATASOURCE_TYPE_NULL_TYPE = 0;
const unsigned short Datasource_Type::DBT_TYPE = 1;
const unsigned short Datasource_Type::GBV_GVK_TYPE = 2;
const unsigned short Datasource_Type::TIMMS_TYPE = 3;
const unsigned short Datasource_Type::DATASOURCE_FILE_TYPE = 4;
```
This code is used in section 186.

167. Initialize static Datasource_Type variables. [LDF 2006.12.08.]

Log

[LDF 2006.12.08.] Added this section with the declaration of *datasource_type_map*.

⟨ Initialize **static Datasource_Type** variables 167 ⟩ ≡
```
map⟨unsigned short, string⟩ Datasource_Type::datasource_type_map;
```
This code is used in section 186.

168. Types for *datasource_type*. [LDF 2006.12.08.]

Log

[LDF 2006.12.08.] Added this section.

[LDF 2006.11.13.] Added **static const unsigned short** `TOP_TYPE`.

⟨ Declare **static Datasource_Type** constants 165 ⟩ +≡

169. datasource_type functions. [LDF 2006.12.08.]

Log

[LDF 2006.12.08.] Added this section.

170. Constructor and setting functions. [LDF 2006.12.08.]

171. Default constructor. [LDF 2006.12.08.]

Log

[LDF 2006.12.08.] Added this function.

⟨ Declare **Datasource_Type** functions 171 ⟩ ≡
```
Datasource_Type(void);
```
See also sections 173, 175, 179, 181, and 183.
This code is used in section 163.

172.

```
⟨ Define Datasource_Type functions 172 ⟩ ≡
  Datasource_Type::Datasource_Type(void)
  {
    cerr ≪ "Entering␣‘Datasource_Type::Datasource_Type(void)’." ≪ endl;
    return;
  }     /* End of default Datasource_Type constructor definition. */
```

See also sections 174, 176, 177, 178, 180, 182, and 184.

This code is used in section 186.

173. Set. [LDF 2006.12.08.]

Log

[LDF 2006.12.08.] Added this function.

```
⟨ Declare Datasource_Type functions 171 ⟩ +≡
  int set(unsigned short datasource_type, Scanner_Node sscanner_node = 0);
```

174.

```
⟨ Define Datasource_Type functions 172 ⟩ +≡
  int Datasource_Type::set(unsigned short datasource_type, Scanner_Node sscanner_node)
  {
    return 0;
  }     /* End of Datasource_Type::set definition. */
```

175. Destructor. [LDF 2006.12.08.]

Log

[LDF 2006.12.08.] Added this function.

```
⟨ Declare Datasource_Type functions 171 ⟩ +≡
  ~Datasource_Type(void);
```

176.

```
⟨ Define Datasource_Type functions 172 ⟩ +≡
  Datasource_Type::~Datasource_Type(void){
#if 0     /* 1 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
      stringstream temp_strm;
#ifdef DEBUG_OUTPUT
      temp_strm ≪ "Entering␣‘Datasource_Type’␣destructor." ≪ endl;
      cerr_mutex.lock();
      cerr ≪ temp_strm.str();
      cerr_mutex.unlock();
      temp_strm.str("");
#endif
```

177.

```
⟨ Define Datasource_Type functions 172 ⟩ +≡
#ifdef DEBUG_OUTPUT
  temp_strm ≪ "Exiting␣‘Datasource_Type’␣destructor." ≪ endl;
  cerr_mutex.lock( );
  cerr ≪ temp_strm.str( );
  cerr_mutex.unlock( );
  temp_strm.str("");
#endif
```

178. DO NOT delete *scanner_node*! [LDF 2006.12.08.]

```
⟨ Define Datasource_Type functions 172 ⟩ +≡
  scanner_node = 0;
  return; }      /* End of ~Datasource_Type definition. */
```

179. Assignment. [LDF 2006.12.08.]

Log

[LDF 2006.12.08.] Added this function.

```
⟨ Declare Datasource_Type functions 171 ⟩ +≡
  Datasource_Node operator=(const Datasource_Type &d);
```

180.

```
⟨ Define Datasource_Type functions 172 ⟩ +≡
  Datasource_Node Datasource_Type::operator=(const Datasource_Type &d)
  {
#if 0     /* 1 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
    stringstream temp_strm;
    scanner_node = d.scanner_node;
#ifdef DEBUG_OUTPUT
    temp_strm << "Entering ‘Datasource_Type::operator=(const Datasource_Type)’." << endl;
    cerr_mutex.lock();
    cerr << temp_strm.str();
    cerr_mutex.unlock();
    if (scanner_node) scanner_node->log_strm << temp_strm.str();
    temp_strm.str("");
#endif
    if (this ≡ &d) {
#ifdef DEBUG_OUTPUT
      temp_strm << "In ‘Datasource_Type::operator=(const Datasource_Type)’:" << endl <<
          "Self-assignment.  Returning ‘this’." << endl;
      cerr_mutex.lock();
      cerr << temp_strm.str();
      cerr_mutex.unlock();
      if (scanner_node) scanner_node->log_strm << temp_strm.str();
      temp_strm.str("");
#endif
      return this;
    }     /* if (this ≡ &d) */
    type = d.type;
#ifdef DEBUG_OUTPUT
    temp_strm << "Exiting ‘Datasource_Type::operator=(const Datasource_Type)’." << endl;
    cerr_mutex.lock();
    cerr << temp_strm.str();
    cerr_mutex.unlock();
    if (scanner_node) scanner_node->log_strm << temp_strm.str();
    temp_strm.str("");
#endif
    return this;
  }     /* End of Datasource_Type::operator=(const Datasource_Type d) definition. */
```

181. Initialize type maps. [LDF 2006.12.08.]

Log

[LDF 2006.12.08.] Added this function.

[LDF 2006.12.08.] Added code for `DBT_TYPE`, `GBV_GVK_TYPE`, `TIMMS_TYPE`, and `DATASOURCE_FILE_TYPE`.

```
⟨ Declare Datasource_Type functions 171 ⟩ +≡
```

static int *initialize_type_maps*(**void**);

182.

⟨ Define **Datasource_Type** functions 172 ⟩ +≡

```
int Datasource_Type::initialize_type_maps(void)
{
  datasource_type_map[DATASOURCE_TYPE_NULL_TYPE] = "DATASOURCE_TYPE_NULL_TYPE";
  datasource_type_map[DBT_TYPE] = "DBT_TYPE";
  datasource_type_map[GBV_GVK_TYPE] = "GBV_GVK_TYPE";
  datasource_type_map[TIMMS_TYPE] = "TIMMS_TYPE";
  datasource_type_map[DATASOURCE_FILE_TYPE] = "DATASOURCE_FILE_TYPE";
  return 0;
}    /* End of Datasource_Type::initialize_type_maps definition. */
```

183. Show. [LDF 2006.12.08.]

Log

[LDF 2006.12.08.] Added this function.

⟨ Declare **Datasource_Type** functions 171 ⟩ +≡

```
int show(string s = "'Datasource_Type':\n", Scanner_Node sscanner_node = 0);
```

184.

⟨ Define **Datasource_Type** functions 172 ⟩ +≡

```
int Datasource_Type::show(string s, Scanner_Node sscanner_node)
{
  stringstream temp_strm;
  if (scanner_node ≡ 0 ∧ sscanner_node ≠ 0) scanner_node = sscanner_node;
  temp_strm ≪ s ≪ endl ≪ "'type' == " ≪ datasource_type_map[type] ≪ " (" ≪ type ≪ ")" ≪ endl;
  cerr_mutex.lock();
  cerr ≪ temp_strm.str();
  cerr_mutex.unlock();
  temp_strm.str("");
  if (scanner_node ≠ 0 ∧ scanner_node→log_strm.is_open()) scanner_node→log_strm ≪ temp_strm;
  return 0;
}    /* End of Datasource_Type::show definition. */
```

185. Putting datasource_type together. [LDF 2006.12.08.]

186. This is what's compiled.

⟨ Include files 10 ⟩
⟨ dtsrctyp.web 159 ⟩

```
using namespace std;
using namespace Scan_Parse;
```

⟨ Forward declarations 17 ⟩
⟨ Declare **class Datasource_Type** 163 ⟩
⟨ Initialize **static Datasource_Type** constants 166 ⟩
⟨ Initialize **static Datasource_Type** variables 167 ⟩
⟨ Define **Datasource_Type** functions 172 ⟩

187. This is what's written to `dtsrctyp.h`.

```
⟨ dtsrctyp.hh 187 ⟩ ≡
#ifndef DTSRCTYP_KNOWN
#define DTSRCTYP_KNOWN 1
  ⟨ Preprocessor macro calls 23 ⟩
  using namespace std;
  ⟨ Forward declarations 17 ⟩
  ⟨ Declare class Datasource_Type 163 ⟩
#endif    /* DTSRCTYP_KNOWN is defined. */
```

188. id_type (`idtype.web`). [LDF 2006.11.01.]

Log

[LDF 2006.11.01.] Created this file.

```
⟨ idtype.web 188 ⟩ ≡
  static char id_string[] = "$Id: idtype.web,v 1.6 2007/02/13 20:39:05 lfinsto1 Exp $";
```

This code is cited in sections 6 and 8.

This code is used in section 211.

189. Include files.

```
⟨ Include files 10 ⟩ +≡
#include "localldf.h"
#ifdef NON_WIN_LDF
#include "nonwin.h"
#else
#include "stdafx.h"
#endif
#include "dttmtype.h"
#include "parser.hxx"
#include "scnrtype.h"
#include "querytyp.h"
```

190. Preprocessor macro calls.

```
⟨ Preprocessor macro calls 23 ⟩ +≡
#ifdef WIN_LDF
#pragma once
#endif
```

191. Forward declarations. [LDF 2006.10.31.]

```
⟨ Forward declarations 17 ⟩ +≡
  class Scanner_Type;
  typedef Scanner_Type *Scanner_Node;
  struct Id_Type;
  typedef Id_Type *Id_Node;
```

192. struct id_type declaration. [LDF 2006.10.17.]

Log

[LDF 2006.11.21.] Added **unsigned short** *subtype*. It's needed for *strings*.

[LDF 2006.12.01.] Added **static map⟨unsigned short, string⟩** *subtype_map*.

```
⟨ Declare struct Id_Type 192 ⟩ ≡
  struct Id_Type {
    friend class Scanner_Type;
    string name;
    void *value;
    unsigned short type;
    unsigned short subtype;
    Id_Node up;
    Id_Node left;
    Id_Node right;
    static map⟨unsigned short, string⟩ subtype_map;
    Scanner_Node scanner_node;
    ⟨ Declare Id_Type functions 199 ⟩
    ⟨ Declare static Id_Type constants 193 ⟩
  };
```

This code is used in sections 211 and 212.

193. static Id_Type constants.

Log

[2006.11.21.] Added this section with the declarations of the **static const unsigned** *shorts* `TEX_STRING_TYPE`, `SQL_STRING_TYPE`, and `PQF_STRING_TYPE`. These types must be declared in **struct Id_Type**, because the Standard C++ library type **string** is used to represent the **string** type in the Scantest language.

```
⟨ Declare static Id_Type constants 193 ⟩ ≡
  static const unsigned short TEX_STRING_TYPE;
  static const unsigned short SQL_STRING_TYPE;
  static const unsigned short PQF_STRING_TYPE;
```

This code is used in section 192.

194.

Log

[2006.11.21.] Added this section with the initializations of Added this section with the declarations of the **static const unsigned** *shorts* `TEX_STRING_TYPE`, `SQL_STRING_TYPE`, and `PQF_STRING_TYPE`.

⟨ Initialize **static Id_Type** constants 194 ⟩ ≡
```
const unsigned short Id_Type::TEX_STRING_TYPE = 1;
const unsigned short Id_Type::SQL_STRING_TYPE = 2;
const unsigned short Id_Type::PQF_STRING_TYPE = 3;
```
This code is used in section 211.

195. Declare **static Id_Type** variables. [LDF 2006.12.01.]
Id_Type :: *subtype_map* needs to be declared outside of the class declaration. It is initialized in the function *initialize_subtype_map*, which is called in *main*. [LDF 2006.12.01.]

Log

[2006.12.01.] Added this section.

⟨ Declare **static Id_Type** variables 195 ⟩ ≡
```
map⟨unsigned short, string⟩ Id_Type::subtype_map;
```
This code is used in section 211.

196. id_type functions. [LDF 2006.11.01.]

Log

[LDF 2006.11.01.] Added this section.

197. Constructors and setting functions. [LDF 2006.11.01.]

Log

[LDF 2006.11.01.] Added this section.

198. Default constructor. [LDF 2006.11.01.]

Log

[2006.10.31.] Added this function.

[LDF 2006.11.02.] Now setting **Scanner_Node** *scanner_node* = 0.

199.

⟨ Declare **Id_Type** functions 199 ⟩ ≡
```
Id_Type(void);
```
See also sections 202, 205, and 208.

This code is used in section 192.

200.

```
⟨ Define Id_Type functions 200 ⟩ ≡
  Id_Type::Id_Type(void)
  {
    name = "";
    value = 0;
    type = 0;
    subtype = 0;
    up = 0;
    left = 0;
    right = 0;
    scanner_node = 0;
    return;
  }     /* End of the default Id_Type constructor definition. */
```

See also sections 203, 206, and 209.

This code is used in section 211.

201. Destructor. [LDF 2006.11.02.]

Log

[LDF 2006.11.02.] Added this function.

202.

```
⟨ Declare Id_Type functions 199 ⟩ +≡
  ~Id_Type(void);
```

203.

```
⟨ Define Id_Type functions 200 ⟩ +≡
  Id_Type::~Id_Type(void)
  {
#if 0     /* 1 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
    stringstream temp_strm;
#ifdef DEBUG_OUTPUT
    temp_strm << "Entering␣`~Id_Type'." << endl << "`name'␣==␣`" << name << "'" << endl <<
        "`type'␣==␣`" << Scan_Parse::token_map[type] << "'" << endl;
    cerr_mutex.lock();
    cerr << temp_strm.str();
    cerr_mutex.unlock();
    if (scanner_node ≠ 0) scanner_node→log_strm << temp_strm.str();
    temp_strm.str("");
#endif
    if (type ≡ QUERY_TYPE) {
      delete static_cast⟨Query_Node⟩(value);
      value = 0;
    }
    delete left;
    delete right;
#ifdef DEBUG_OUTPUT
    temp_strm << "Exiting␣`~Id_Type'." << endl;
    cerr_mutex.lock();
    cerr << temp_strm.str();
    cerr_mutex.unlock();
    if (scanner_node ≠ 0) scanner_node→log_strm << temp_strm.str();
    temp_strm.str("");
#endif
    return;
#undef DEBUG_OUTPUT
  }     /* End of ~Id_Type definition. */
```

204. Initialize *subtype_map*. [LDF 2006.12.01.]

Log

[LDF 2006.12.01.] Added this function.

205.

```
⟨ Declare Id_Type functions 199 ⟩ +≡
  static int initialize_subtype_map(Scanner_Node s = 0);
```

206.

```
⟨ Define Id_Type functions 200 ⟩ +≡
  int Id_Type::initialize_subtype_map(Scanner_Node s)
  {
#if 0     /* 1 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
    stringstream temp_strm;
#ifdef DEBUG_OUTPUT
    temp_strm << "Entering␣`Id_Type::initialize_subtype_map'." << endl;
    cerr_mutex.lock();
    cerr << temp_strm.str();
    cerr_mutex.unlock();
    if (s ≠ 0) s→log_strm << temp_strm.str();
    temp_strm.str("");
#endif
    Id_Type::subtype_map[TEX_STRING_TYPE] = "TEX_STRING_TYPE";
    Id_Type::subtype_map[SQL_STRING_TYPE] = "SQL_STRING_TYPE";
    Id_Type::subtype_map[PQF_STRING_TYPE] = "PQF_STRING_TYPE";
#ifdef DEBUG_OUTPUT
    temp_strm << "Exiting␣`Id_Type::initialize_subtype_map'." << endl;
    cerr_mutex.lock();
    cerr << temp_strm.str();
    cerr_mutex.unlock();
    if (s ≠ 0) s→log_strm << temp_strm.str();
    temp_strm.str("");
#endif
    return 0;
#undef DEBUG_OUTPUT
  }     /* End of Id_Type::initialize_subtype_map definition. */
```

207. Show. [LDF 2006.11.02.]

Log

[2006.11.02.] Added this function.

208.

```
⟨ Declare Id_Type functions 199 ⟩ +≡
  int show(string = "");
```

209.

```
⟨ Define Id_Type functions 200 ⟩ +≡
  int Id_Type::show(string s)
  {
#if 0     /* 1 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
    stringstream temp_strm;
    if (s ≡ "") s = "`Id_Type:'";
    temp_strm ≪ s ≪ endl ≪ "`name' == `" ≪ name ≪ "'" ≪ endl ≪ "`type' == `" ≪
        Scan_Parse::token_map[type] ≪ "'" ≪ endl ≪ "`subtype' == " ≪ subtype_map[subtype] ≪
        endl;
    if (value ≡ 0) temp_strm ≪ "`value' == 0" ≪ endl;
    else temp_strm ≪ "`value' != 0" ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    if (scanner_node ≠ 0) scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#ifdef DEBUG_OUTPUT
    temp_strm ≪ "Exiting `Id_Type::show'." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    if (scanner_node ≠ 0) scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    return 0;
#undef DEBUG_OUTPUT
  }     /* End of Id_Type::show definition. */
```

210. Putting id_type together. [LDF 2006.11.01.]

211. This is what's compiled.

```
⟨ Include files 10 ⟩
⟨ idtype.web 188 ⟩
using namespace std;
⟨ Forward declarations 17 ⟩
⟨ Declare struct Id_Type 192 ⟩
⟨ Initialize static Id_Type constants 194 ⟩
⟨ Declare static Id_Type variables 195 ⟩
⟨ Define Id_Type functions 200 ⟩
```

212. This is what's written to `idtype.h`.

⟨ `idtype.hh` 212 ⟩ ≡
```
⟨ Preprocessor macro calls 23 ⟩
using namespace std;
⟨ Forward declarations 17 ⟩
⟨ Declare struct Id_Type 192 ⟩
```

213. Scanner_Type (`scnrtype.web`). [LDF 2006.10.17.]

Log

[LDF 2006.10.31.] Created this file.

⟨ `scnrtype.web` 213 ⟩ ≡
```
static char id_string[] = "$Id: scnrtype.web,v 1.6 2007/02/13 20:41:41 lfinsto1 Exp $";
```
This code is cited in sections 6 and 8.

This code is used in section 247.

214. Include files.

⟨ Include files 10 ⟩ +≡
```
#include "localldf.h"
#ifdef NON_WIN_LDF
#include "nonwin.h"
#else
#include "stdafx.h"
#endif
#include "parser.hxx"
#include "dttmtype.h"
#include "idtype.h"
#include "scanner.h"
#include "querytyp.h"
#include "dtsrctyp.h"
```

215. Preprocessor macro calls.

⟨ Preprocessor macro calls 23 ⟩ +≡
```
#ifdef WIN_LDF
#pragma once
#endif
```

216. Forward declarations. [LDF 2006.11.02.]

Log

[2006.11.02.] Added this section.

⟨ Forward declarations 17 ⟩ +≡
```
class Scanner_Type;
typedef Scanner_Type *Scanner_Node;
class Query_Type;
typedef Query_Type *Query_Node;
class Id_Type;
```

typedef Id_Type *Id_Node;

217. struct Token_Type declaration. [LDF 2006.11.02.]

Log

[2006.11.02.] Added this declaration.

[LDF 2006.11.02.] Added constructor.

⟨ Declare **struct Token_Type** 217 ⟩ ≡

```
struct Token_Type {
  unsigned int type;
  YYSTYPE value;
  ⟨ Declare Token_Type functions 219 ⟩
};
```

This code is used in sections 247 and 248.

218. Token_Type functions. [LDF 2006.11.02.]

Log

[2006.11.02.] Added this section.

219. Default Constructor. [LDF 2006.11.02.]

Log

[2006.11.02.] Added this function.

⟨ Declare **Token_Type** functions 219 ⟩ ≡

```
Token_Type(void);
```

See also section 221.

This code is used in section 217.

220.

⟨ Define **Token_Type** functions 220 ⟩ ≡

```
Token_Type::Token_Type(void)
{
  type = 0;
  value.int_value = 0;
  return;
}
```

See also section 222.

This code is used in section 247.

221. Non-Default Constructor. [LDF 2006.11.02.]

Log

[2006.11.02.] Added this function.

⟨ Declare **Token_Type** functions 219 ⟩ +≡
Token_Type(**unsigned int** *ttype*, `YYSTYPE`*vvalue*);

222.

⟨ Define **Token_Type** functions 220 ⟩ +≡
Token_Type :: **Token_Type**(**unsigned int** *ttype*, YYSTYPE*vvalue*): *type*(*ttype*), *value*(*vvalue*)
{
return;
}

223. class Scanner_Type declaration. This is the type passed to the functions *yylex* and *yyparse* as a parameter. [LDF 2006.10.17.]

Log

[LDF 2006.10.31.] Added **typedef Scanner_Type** ∗**Scanner_Node**.

[LDF 2006.10.31.] Working on this declaration.

[LDF 2006.11.02.] Added **Query_Node** *curr_query*.

[LDF 2006.11.03.] Added **vector**⟨**float**⟩ *float_vector*.

⟨ Declare **class Scanner_Type** 223 ⟩ ≡
class Scanner_Type { ⟨ **friend** declarations for **Scanner_Type** 224 ⟩
char *in_filename*[128];
char *log_filename*[128];
ifstream *in_strm*;
map⟨**string**, **Id_Type** ∗⟩ *id_map*; *stack* < **Token_Type** > *token_stack*;
vector⟨**float**⟩ *float_vector*;
public: **ofstream** *log_strm*;
⟨ Declare **Scanner_Type** functions 230 ⟩
} ;
This code is used in sections 247 and 248.

224. friend declarations for Scanner_Type. [LDF 2006.10.31.]

Log

[2006.10.31.] Added this section.

⟨ **friend** declarations for **Scanner_Type** 224 ⟩ ≡
friend int *main*(**int**, **char** ∗[]); **friend int** *yylex* (YYSTYPE ∗ , **void** ∗) ;
friend int *yyparse*(**void** ∗);
See also section 226.
This code is used in section 223.

225. friend declarations for parser rule functions. [LDF 2006.10.31.]

Log

[2006.10.31.] Added this section.

226. friend declarations for functions for group statements. [LDF 2006.10.31.]

Log

[2006.10.31.] Added this section with the **friend** declarations for **Scan_Parse** :: *start_local_query_func* and **Scan_Parse** :: *end_local_query_func*.

[LDF 2006.11.01.] Changed the name of **Scan_Parse** :: *start_local_query_func* to **Scan_Parse** :: *start_local_database_query_fu* and the name of **Scan_Parse** :: *end_local_query_func* to **Scan_Parse** :: *end_query_func*.

[LDF 2006.11.01.] Added the **friend** declaration of **Scan_Parse** :: *declare_variable_func*.

[LDF 2006.11.01.] Added the **char** ∗*name* argument to **Scan_Parse** :: *declare_variable_func*.

[LDF 2006.11.02.] Changed the return value of **Scan_Parse** :: *declare_variable_func* from **int** to **void** ∗.

[LDF 2006.11.02.] Added the **friend** declaration of **Scan_Parse** :: *variable_func*.

[LDF 2006.11.02.] Added the **friend** declaration of **Scan_Parse** :: *query_assignment_func_0*.

[LDF 2006.12.15.] Added the **friend** declaration of **Scan_Parse** :: *datetime_assignment_func_0*.

[LDF 2006.12.18.] Added the **friend** declaration of **Scan_Parse** :: *datetime_assignment_func_1*.

[LDF 2006.12.19.] Added the **friend** declaration of **Scan_Parse** :: *query_assignment_func_1*.

⟨ **friend** declarations for **Scanner_Type** 224 ⟩ +≡

```
friend void *Scan_Parse::variable_func(void *v, char *name);
friend Id_Node Scan_Parse::declare_variable_func(void *v, const unsigned short type, char
    *name);
friend void *Scan_Parse::query_assignment_func_0(void *v, void *object, unsigned int
    assignment_type, unsigned int arg_0, unsigned int arg_1, void *value, bool negate);
friend int Scan_Parse::query_assignment_func_1(Scanner_Node scanner_node, Id_Node
    &curr_id_node, void *&field_specifier, int assignment_operator, int negation_optional, int
    match_term_optional, void *&v, int type);
friend int Scan_Parse::start_local_database_query_func(void *v);
friend int Scan_Parse::end_query_func(void *v);
friend int Scan_Parse::datetime_assignment_func_0(void *v, Date_Time_Node
    &curr_date_time_node, int specifier, int op, void *val, int type);
friend int Scan_Parse::datetime_assignment_func_1(void *v, Date_Time_Node &d, int op, void
    *&vec);
```

227. Scanner_Type functions. [LDF 2006.10.31.]

Log

[2006.10.31.] Added this section.

228. Constructors and setting functions. [LDF 2006.10.31.]

Log

[2006.10.31.] Added this section.

229. Default constructor. [LDF 2006.10.31.]

Log

[2006.10.31.] Added this function.

[LDF 2006.11.02.] Now initializing **Query_Node** *query_node* to 0.

230.

```
⟨ Declare Scanner_Type functions 230 ⟩ ≡
  Scanner_Type(void);
```

See also sections 232, 234, and 236.

This code is used in section 223.

231.

```
⟨ Define Scanner_Type functions 231 ⟩ ≡
  Scanner_Type::Scanner_Type(void)
  {
    return;
  }     /* End of the default Scanner_Type constructor definition. */
```

See also sections 233, 235, 237, 238, 239, 240, 241, 242, 243, 244, and 245.

This code is used in section 247.

232. Destructor. [LDF 2006.11.02.]

Log

[LDF 2006.11.02.] Added this function.

```
⟨ Declare Scanner_Type functions 230 ⟩ +≡
  ~Scanner_Type(void);
```

233.

```
⟨ Define Scanner_Type functions 231 ⟩ +≡
  Scanner_Type::~Scanner_Type(void)
  {
#if 0     /* 1 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
    stringstream temp_strm;
#ifdef DEBUG_OUTPUT
    temp_strm << "Entering␣`~Scanner_Node'." << endl;
    cerr_mutex.lock();
    cerr << temp_strm.str();
    cerr_mutex.unlock();
    if (log_strm.is_open()) log_strm << temp_strm.str();
    temp_strm.str("");
#endif
    for (map⟨string, Id_Type *⟩::iterator iter = id_map.begin(); iter ≠ id_map.end(); ++iter) {
      delete iter→second;
    }
    id_map.clear();
    in_strm.close();
#ifdef DEBUG_OUTPUT
    temp_strm << "Exiting␣`~Scanner_Node'." << endl;
    cerr_mutex.lock();
    cerr << temp_strm.str();
    cerr_mutex.unlock();
    if (log_strm.is_open()) log_strm << temp_strm.str();
    temp_strm.str("");
#endif
    log_strm.close();
    return;
#undef DEBUG_OUTPUT
  }     /* End of the ~Scanner_Type definition. */
```

234. Initialize *id_map*. [LDF 2006.11.02.]

Log

[LDF 2006.11.02.] Added this function.

[LDF 2006.11.14.] Removed the code that declared a variable `"curr_query"` and set *this→curr_query* to point to it. I now plan to use *curr_query* for parsing subqueries.

```
⟨ Declare Scanner_Type functions 230 ⟩ +≡
  int initialize_id_map(void);
```

235.

```
⟨ Define Scanner_Type functions 231 ⟩ +≡
  int Scanner_Type::initialize_id_map(void)
  {
#if 0     /* 1 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
    stringstream temp_strm;
#ifdef DEBUG_OUTPUT
    temp_strm << "Entering␣`Scanner_Node::initialize_id_map'." << endl;
    cerr_mutex.lock();
    cerr << temp_strm.str();
    cerr_mutex.unlock();
    if (log_strm.is_open()) log_strm << temp_strm.str();
    temp_strm.str("");
#endif
#ifdef DEBUG_OUTPUT
    temp_strm << "Exiting␣`Scanner_Node::initialize_id_map'." << endl;
    cerr_mutex.lock();
    cerr << temp_strm.str();
    cerr_mutex.unlock();
    if (log_strm.is_open()) log_strm << temp_strm.str();
    temp_strm.str("");
#endif
    return 0;
#undef DEBUG_OUTPUT
  }     /* End of the Scanner_Type::initialize_id_map definition. */
```

236. Lookup. [LDF 2006.11.03.]

Log

[LDF 2006.11.03.] Added this function.

```
⟨ Declare Scanner_Type functions 230 ⟩ +≡
  Id_Node lookup(char *name, bool create = false, unsigned int type = NULL_TYPE);
```

237.

```
⟨ Define Scanner_Type functions 231 ⟩ +≡
  Id_Node Scanner_Type::lookup(char *name, bool create, unsigned int type){
#if 0     /* 1 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
      stringstream temp_strm;
#ifdef DEBUG_OUTPUT
      temp_strm ≪ "Entering ‘Scanner_Node::lookup’." ≪ endl;
      cerr_mutex.lock();
      cerr ≪ temp_strm.str();
      cerr_mutex.unlock();
      log_strm ≪ temp_strm.str();
      temp_strm.str("");
#endif
      Id_Node curr_id_node;
      map⟨string, Id_Node⟩::iterator iter = id_map.find(name);
      if (iter ≡ id_map.end()) {
        curr_id_node = 0;
      }
      else     /* iter ≠ id_map.end() */
      { curr_id_node = iter→second;
```

238. WARNING: *type* ≠ *curr_id_node→type*. [LDF 2006.11.03.]

```
⟨ Define Scanner_Type functions 231 ⟩ +≡
  if (type ≠ curr_id_node→type) {
    temp_strm ≪ "WARNING! In ‘Scanner_Node::lookup’:" ≪ endl ≪
        "‘type’ == ‘" ≪ Scan_Parse::token_map[type] ≪ "’ is not the same as " ≪
        "‘curr_id_node->type’ == ‘" ≪ Scan_Parse::token_map[curr_id_node→type] ≪ "’." ≪
        endl ≪ "Setting ‘type’ to ‘" ≪ Scan_Parse::token_map[curr_id_node→type] ≪
        "’ and continuing." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    log_strm ≪ temp_strm.str();
    temp_strm.str("");
    type = curr_id_node→type;
  }     /* if (type ≠ curr_id_node→type) */
```

239.

```
⟨ Define Scanner_Type functions 231 ⟩ +≡
  }     /* else (iter ≠ id_map.end()) */
```

240. *name* doesn't refer to an array. [LDF 2006.11.03.]

```
⟨ Define Scanner_Type functions 231 ⟩ +≡
  if (strchr(name, '¥') ≡ 0) {
    if (curr_id_node ≠ 0) return curr_id_node;
    else if (create ≡ true) {
      curr_id_node = new Id_Type;
      curr_id_node→name = name;
      curr_id_node→type = type;
      id_map[name] = curr_id_node;
      return curr_id_node;
    }
    else      /* curr_id_node ≡ 0 and create ≡ false */
    {
#ifdef DEBUG_OUTPUT
      temp_strm ≪ "In␣‘Scanner_Node::lookup’:" ≪ "‘name’␣not␣found␣in␣‘id_map’␣and␣‘creat\
          e’␣==␣0." ≪ endl ≪ "Exiting␣function␣with␣return␣value␣0.";
      cerr_mutex.lock();
      cerr ≪ temp_strm.str();
      cerr_mutex.unlock();
      log_strm ≪ temp_strm.str();
      temp_strm.str("");
#endif
      return 0;
    }     /* else (curr_id_node ≡ 0 and create ≡ false) */
  }     /* if (strchar(name, '¥') ≡ 0) */
```

241. *name* refers to an array. [LDF 2006.11.03.]

```
⟨ Define Scanner_Type functions 231 ⟩ +≡
  else      /* strchar(name, '¥') ≠ 0 */
  { stringstream curr_name_strm;
  string curr_name;
  {     /* Beginning of group */
    int j = 0;
    for (int i = 0; i < strlen(name); ++i) {
      if (name[i] ≡ '¥') curr_name_strm ≪ '[' ≪ float_vector[j++] ≪ ']';
      else curr_name_strm ≪ name[i];
    }     /* for */
  }     /* End of group */
  curr_name = curr_name_strm.str();
#ifdef DEBUG_OUTPUT
  temp_strm ≪ "‘curr_name’␣==␣" ≪ curr_name ≪ endl;
  cerr_mutex.lock();
  cerr ≪ temp_strm.str();
  cerr_mutex.unlock();
  log_strm ≪ temp_strm.str();
  temp_strm.str("");
#endif
```

242. No elements on array. [LDF 2006.11.03.]

```
⟨ Define Scanner_Type functions 231 ⟩ +≡
  if (curr_id_node→left ≡ 0) {
#ifdef DEBUG_OUTPUT
  temp_strm ≪ "‘" ≪ name ≪ "’␣refers␣to␣an␣empty␣array." ≪ endl;
  cerr_mutex.lock();
  cerr ≪ temp_strm.str();
  cerr_mutex.unlock();
  log_strm ≪ temp_strm.str();
  temp_strm.str("");
#endif
```

243. *create* ≡ *false*. Return 0. [LDF 2006.11.03.]

```
⟨ Define Scanner_Type functions 231 ⟩ +≡
  if (create ≡ false) {
#ifdef DEBUG_OUTPUT
    temp_strm ≪ "‘create’␣==␣‘false’.␣␣Returning␣0." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    return 0;
  }    /* if (create ≡ false) */
```

244. *create* ≡ *true*. Create array element. [LDF 2006.11.03.]

```
⟨ Define Scanner_Type functions 231 ⟩ +≡
  else    /* create ≡ true */
  {
#ifdef DEBUG_OUTPUT
    temp_strm ≪ "Creating␣array␣element␣for␣‘" ≪ curr_name ≪ "’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    curr_id_node→left = new Id_Type;
    curr_id_node→left→name = curr_name;
    curr_id_node→left→type = type;
    curr_id_node→left→up = curr_id_node;
    return curr_id_node→left;
  }    /* else (create ≡ true) */
  }    /* if (curr_id_node→left ≡ 0) */
```

245. Array isn't empty. Traverse the tree. [LDF 2006.11.03.]

```
⟨ Define Scanner_Type functions 231 ⟩ +≡
  else      /* curr_id_node→left ≠ 0 */
  {
#ifdef DEBUG_OUTPUT
    temp_strm ≪ "‘" ≪ name ≪ "’ array isn’t empty.  " ≪ "Traversing." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    curr_id_node = curr_id_node→left;
    for ( ; ; ) {
      if (curr_name ≡ curr_id_node→name) {
#ifdef DEBUG_OUTPUT
        temp_strm ≪ "‘" ≪ curr_name ≪ "’ exists.  Returning it." ≪ endl;
        cerr_mutex.lock();
        cerr ≪ temp_strm.str();
        cerr_mutex.unlock();
        log_strm ≪ temp_strm.str();
        temp_strm.str("");
#endif
        return curr_id_node;
      }     /* if (curr_name ≡ curr_id_node→name) */
      else if (curr_name.compare(curr_id_node→name) < 0) {
#ifdef DEBUG_OUTPUT
        temp_strm ≪ "‘" ≪ curr_name ≪ "’ < ‘" ≪ curr_id_node→name ≪ "’.  " ≪
            "Traversing the tree leftwards." ≪ endl;
        cerr_mutex.lock();
        cerr ≪ temp_strm.str();
        cerr_mutex.unlock();
        log_strm ≪ temp_strm.str();
        temp_strm.str("");
#endif
        if (curr_id_node→left ≠ 0) {
#ifdef DEBUG_OUTPUT
          temp_strm ≪ "‘" ≪ curr_id_node→name ≪ "->left’ exists.  " ≪ "Continuing." ≪ endl;
          cerr_mutex.lock();
          cerr ≪ temp_strm.str();
          cerr_mutex.unlock();
          log_strm ≪ temp_strm.str();
          temp_strm.str("");
#endif
          curr_id_node = curr_id_node→left;
          continue;
        }
        else      /* curr_id_node→left ≡ 0 */
        {
#ifdef DEBUG_OUTPUT
          temp_strm ≪ "‘" ≪ curr_id_node→name ≪ "->left’ doesn’t exist." ≪ endl;
          cerr_mutex.lock();
```

```
            cerr ≪ temp_strm.str();
            cerr_mutex.unlock();
            log_strm ≪ temp_strm.str();
            temp_strm.str("");
#endif
            if (create ≡ true) {
#ifdef DEBUG_OUTPUT
              temp_strm ≪ "Creating␣new␣‘Id_Node’␣for␣‘" ≪ curr_name ≪ "’." ≪ endl;
              cerr_mutex.lock();
              cerr ≪ temp_strm.str();
              cerr_mutex.unlock();
              log_strm ≪ temp_strm.str();
              temp_strm.str("");
#endif
              curr_id_node→left = new Id_Type;
              curr_id_node→left→name = curr_name;
              curr_id_node→left→type = type;
              curr_id_node→left→up = curr_id_node;
              return curr_id_node→left;
            }     /* if (create ≡ true) */
            else      /* create ≡ false */
            {
#ifdef DEBUG_OUTPUT
              temp_strm ≪ "‘create’␣==␣‘false’.␣␣" ≪ "Not␣creating␣new␣‘Id_Node’␣for␣‘" ≪
                  curr_name ≪ "’.␣␣Returning␣0." ≪ endl;
              cerr_mutex.lock();
              cerr ≪ temp_strm.str();
              cerr_mutex.unlock();
              log_strm ≪ temp_strm.str();
              temp_strm.str("");
#endif
              return 0;
            }     /* else (create ≡ false) */
          }     /* else (curr_id_node→left ≡ 0) */
        }     /* else if (curr_name.compare(curr_id_node→name) < 0) */
        else if (curr_name.compare(curr_id_node→name) > 0) {
#ifdef DEBUG_OUTPUT
          temp_strm ≪ "‘" ≪ curr_name ≪ "’␣>␣‘" ≪ curr_id_node→name ≪ "’.␣␣" ≪
              "Traversing␣the␣tree␣rightwards." ≪ endl;
          cerr_mutex.lock();
          cerr ≪ temp_strm.str();
          cerr_mutex.unlock();
          log_strm ≪ temp_strm.str();
          temp_strm.str("");
#endif
          if (curr_id_node→right ≠ 0) {
#ifdef DEBUG_OUTPUT
            temp_strm ≪ "‘" ≪ curr_id_node→name ≪ "->right’␣exists.␣␣" ≪ "Continuing." ≪ endl;
            cerr_mutex.lock();
            cerr ≪ temp_strm.str();
            cerr_mutex.unlock();
            log_strm ≪ temp_strm.str();
```

```
        temp_strm.str("");
#endif
        curr_id_node = curr_id_node→right;
        continue;
      }     /* if (curr_id_node→right ≠ 0) */
      else      /* curr_id_node→right ≡ 0 */
      {
#ifdef DEBUG_OUTPUT
        temp_strm ≪ "‘" ≪ curr_id_node→name ≪ "->right’␣doesn’t␣exist." ≪ endl;
        cerr_mutex.lock();
        cerr ≪ temp_strm.str();
        cerr_mutex.unlock();
        log_strm ≪ temp_strm.str();
        temp_strm.str("");
#endif
        if (create ≡ true) {
#ifdef DEBUG_OUTPUT
          temp_strm ≪ "Creating␣new␣‘Id_Node’␣for␣‘" ≪ curr_name ≪ "’." ≪ endl;
          cerr_mutex.lock();
          cerr ≪ temp_strm.str();
          cerr_mutex.unlock();
          log_strm ≪ temp_strm.str();
          temp_strm.str("");
#endif
          curr_id_node→right = new Id_Type;
          curr_id_node→right→name = curr_name;
          curr_id_node→right→type = type;
          curr_id_node→right→up = curr_id_node;
          return curr_id_node→right;
        }     /* if (create ≡ true) */
        else      /* create ≡ false */
        {
#ifdef DEBUG_OUTPUT
          temp_strm ≪ "‘create’␣==␣‘false’.␣␣" ≪ "Not␣creating␣new␣‘Id_Node’␣for␣‘" ≪
              curr_name ≪ "’.␣␣Returning␣0." ≪ endl;
          cerr_mutex.lock();
          cerr ≪ temp_strm.str();
          cerr_mutex.unlock();
          log_strm ≪ temp_strm.str();
          temp_strm.str("");
#endif
          return 0;
        }     /* else (create ≡ false) */
      }     /* else (curr_id_node→right ≡ 0) */
    }     /* else if (curr_name.compare(curr_id_node→name) > 0) */
  }     /* for */
}     /* else (curr_id_node→left ≠ 0) */
}     /* else (strchar(name, '¥') ≠ 0) */
#ifdef DEBUG_OUTPUT
temp_strm ≪ "Exiting␣‘Scanner_Node::lookup’." ≪ endl;
cerr_mutex.lock();
cerr ≪ temp_strm.str();
```

```
  cerr_mutex.unlock();
  log_strm ≪ temp_strm.str();
  temp_strm.str("");
#endif
  return 0;
#undef DEBUG_OUTPUT
  }     /* End of Scanner_Type::lookup definition. */
```

246. Putting Scanner_Type together. [LDF 2006.10.31.]

247. This is what's compiled.

```
⟨ Include files 10 ⟩
⟨ scnrtype.web 213 ⟩
using namespace std;
⟨ Forward declarations 17 ⟩
⟨ Declare struct Token_Type 217 ⟩
⟨ Declare class Scanner_Type 223 ⟩
⟨ Define Token_Type functions 220 ⟩
⟨ Define Scanner_Type functions 231 ⟩
```

248. This is what's written to `scnrtype.h`.

```
⟨ scnrtype.hh 248 ⟩ ≡
#ifndef SCNRTYPE_KNOWN
#define SCNRTYPE_KNOWN 1
  ⟨ Preprocessor macro calls 23 ⟩
  using namespace std;
#include "scanner.h"
  using namespace Scan_Parse;
  ⟨ Forward declarations 17 ⟩
  ⟨ Declare struct Token_Type 217 ⟩
  ⟨ Declare class Scanner_Type 223 ⟩
#endif    /* SCNRTYPE_KNOWN is defined. */
```

249. Scanning (`scanner.web`). [LDF 2006.10.17.]

Log

[LDF 2006.10.17.] Created this file.

```
⟨ scanner.web 249 ⟩ ≡
  static char id_string[] = "$Id: scanner.web,v 1.6 2007/02/13 20:41:04 lfinsto1 Exp $";
```

This code is cited in sections 6 and 8.

This code is used in section 361.

250. Include files.

```
⟨ Include files 10 ⟩ +≡
#include "localldf.h"
#ifdef NON_WIN_LDF
#include "nonwin.h"
#else
#include "stdafx.h"
#endif
#include "parser.hxx"
#include "dttmtype.h"
#include "idtype.h"
#include "scnrtype.h"
```

251. Preprocessor macro calls.

```
⟨ Preprocessor macro calls 23 ⟩ +≡
#ifdef WIN_LDF
#pragma once
#endif
```

252. Forward declarations. [LDF 2006.11.02.]

Log

[2006.11.02.] Added this section.

```
⟨ Forward declarations 17 ⟩ +≡
  class Scanner_Type;
```

```
typedef Scanner_Type *Scanner_Node;
class Query_Type;
typedef Query_Type *Query_Node;
class Id_Type;
typedef Id_Type *Id_Node;
class Date_Time_Type;
typedef Date_Time_Type *Date_Time_Node;
```

253. Type declarations for the scanner. [LDF 2006.10.17.]

254. Declare namespace Scan_Parse. [LDF 2006.10.17.]

255. Declaration with initializations for compiliation. [LDF 2006.10.19.]

Log

[LDF 2006.10.19.] Added this section.

[LDF 2006.11.01.] Removed **const unsigned int** `COLLECTING_ARGUMENT`. Changed **const unsigned int** `COLLECTING_KEYWORD` to `COLLECTING_ID`.

[LDF 2006.11.02.] Added **extern const unsigned int** `COLLECTING_INTEGER` and **extern const unsigned int** `COLLECTING_FLOAT`.

⟨ Declare namespace **Scan_Parse** 255 ⟩ ≡

```
namespace Scan_Parse {
  extern const unsigned int NULL_STATE = 0;
  extern const unsigned int COLLECTING_ID = 1;
  extern const unsigned int COLLECTING_STRING = 2;
  extern const unsigned int COLLECTING_INTEGER = 3;
  extern const unsigned int COLLECTING_FLOAT = 4;
  ⟨ Declare struct Keyword_Type 261 ⟩
  ⟨ Declare keyword_map 263 ⟩
  ⟨ Declare token_map 266 ⟩
  ⟨ Declare Scan_Parse functions 268 ⟩
}   /* End of namespace Scan_Parse declaration. */
```

This code is used in section 361.

256. extern declaration of namespace Scan_Parse. [LDF 2006.10.19.]

⟨ **extern** declaration of namespace **Scan_Parse** 256 ⟩ ≡

```
namespace Scan_Parse {
```

See also sections 258 and 259.

This code is used in section 362.

257. Constants. [LDF 2006.10.19.]

258. Scanner state ("start conditions"). [LDF 2006.10.19.]

```
⟨ extern declaration of namespace Scan_Parse 256 ⟩ +≡
  extern const unsigned int NULL_STATE;
  extern const unsigned int COLLECTING_ID;
  extern const unsigned int COLLECTING_STRING;
  extern const unsigned int COLLECTING_INTEGER;
  extern const unsigned int COLLECTING_FLOAT;
```

259.

```
⟨ extern declaration of namespace Scan_Parse 256 ⟩ +≡
  struct Keyword_Type;
  ⟨ extern keyword_map declaration 264 ⟩
  ⟨ extern token_map declaration 267 ⟩
  ⟨ Declare Scan_Parse functions 268 ⟩
  }     /* End of extern declaration of namespace Scan_Parse. */
```

260. Keywords. [LDF 2006.10.19.]

261. Declare struct Keyword_Type. [LDF Undated.]

Log

[LDF 2006.11.01.] Tried to change **Keyword_Type** from a **struct** to a **class**, but it didn't work.

```
⟨ Declare struct Keyword_Type 261 ⟩ ≡
  struct Keyword_Type {
    string name;
    int value;
    string value_name;
  };
```

This code is used in section 255.

262. Keyword map. [LDF 2006.10.19.]

Log

[LDF 2006.10.19.] Added this section.

263. Declare *keyword_map*. [LDF 2006.10.19.]

```
⟨ Declare keyword_map 263 ⟩ ≡
  map⟨string, Keyword_Type *⟩ keyword_map;
```

This code is used in section 255.

264. **extern** declaration of *keyword_map* for the header file. [LDF 2006.10.19.]

⟨ **extern** *keyword_map* declaration 264 ⟩ ≡
  extern map⟨**string**, **Keyword_Type** ∗⟩ *keyword_map*;

This code is used in section 259.

265. **Token map.** [LDF 2006.11.01.]

Log

[LDF 2006.11.01.] Added this section.

266. **Declare** *token_map*. [LDF 2006.11.01.]

⟨ Declare *token_map* 266 ⟩ ≡
  map⟨**unsigned int**, **string**⟩ *token_map*;

This code is used in section 255.

267. **extern** declaration of *token_map* for the header file. [LDF 2006.11.01.]

⟨ **extern** *token_map* declaration 267 ⟩ ≡
  extern map⟨**unsigned int**, **string**⟩ *token_map*;

This code is used in section 259.

268. **Initialize** *keyword_map* **and** *token_map*. [LDF 2006.10.19.]

Log

[LDF 2006.11.03.] Added code for `NULL_TYPE`.

[LDF 2006.12.07.] Added code for `HYPHEN`.

[LDF 2006.12.12.] Added code for `AT_SYMBOL`.

[LDF 2006.12.14.] Added code for `PERCENT`.

⟨ Declare **Scan_Parse** functions 268 ⟩ ≡
  int *initialize_maps*(**void**);

See also sections 291, 295, 296, 298, 299, 300, 301, 303, and 304.

This code is used in sections 255 and 259.

269.

⟨ Define **Scan_Parse** functions 269 ⟩ ≡
  int Scan_Parse::*initialize_maps*(**void**){ **Keyword_Type** ∗*curr_keyword*;

See also sections 270, 271, 272, 273, 274, 275, 276, 277, 278, 279, 280, 281, 283, 284, 285, 286, 287, 288, 289, and 292.

This code is used in section 361.

270. Punctuation. [LDF 2006.10.19.]

⟨ Define **Scan_Parse** functions 269 ⟩ +≡

```
curr_keyword = new Keyword_Type;
curr_keyword→name = "AT_SYMBOL";
curr_keyword→value = AT_SYMBOL;
curr_keyword→value_name = "AT_SYMBOL";
keyword_map["@"] = curr_keyword;
token_map[AT_SYMBOL] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "COMMA";
curr_keyword→value = COMMA;
curr_keyword→value_name = "COMMA";
keyword_map[","] = curr_keyword;
token_map[COMMA] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "PERCENT";
curr_keyword→value = PERCENT;
curr_keyword→value_name = "PERCENT";
keyword_map[","] = curr_keyword;
token_map[PERCENT] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "COLON";
curr_keyword→value = COLON;
curr_keyword→value_name = "COLON";
keyword_map[":"] = curr_keyword;
token_map[COLON] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "PERIOD";
curr_keyword→value = PERIOD;
curr_keyword→value_name = "PERIOD";
keyword_map["."] = curr_keyword;
token_map[PERIOD] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "HYPHEN";
curr_keyword→value = HYPHEN;
curr_keyword→value_name = "HYPHEN";
keyword_map["-"] = curr_keyword;
token_map[HYPHEN] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "SEMI_COLON";
curr_keyword→value = SEMI_COLON;
curr_keyword→value_name = "SEMI_COLON";
keyword_map[";"] = curr_keyword;
token_map[SEMI_COLON] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "OPEN_PARENTHESIS";
curr_keyword→value = OPEN_PARENTHESIS;
curr_keyword→value_name = "OPEN_PARENTHESIS";
keyword_map["("] = curr_keyword;
token_map[OPEN_PARENTHESIS] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "CLOSE_PARENTHESIS";
```

```
curr_keyword→value = CLOSE_PARENTHESIS;
curr_keyword→value_name = "CLOSE_PARENTHESIS";
keyword_map[")"] = curr_keyword;
token_map[CLOSE_PARENTHESIS] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "OPEN_BRACKET";
curr_keyword→value = OPEN_BRACKET;
curr_keyword→value_name = "OPEN_BRACKET";
keyword_map["["] = curr_keyword;
token_map[OPEN_BRACKET] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "CLOSE_BRACKET";
curr_keyword→value = CLOSE_BRACKET;
curr_keyword→value_name = "CLOSE_BRACKET";
keyword_map["]"] = curr_keyword;
token_map[CLOSE_BRACKET] = curr_keyword→value_name;
```

271. Assignment. [LDF 2006.10.31.]

Log

[2006.10.31.] Added this section with code for the following keywords: `ASSIGN`, `PLUS_ASSIGN`, `MINUS_ASSIGN`, `TIMES_ASSIGN`, and `DIVIDE_ASSIGN`.

[LDF 2006.11.14.] Added code for `AND_ASSIGN`, `OR_ASSIGN`, `XOR_ASSIGN`, and `NOT_ASSIGN`.

```
⟨ Define Scan_Parse functions 269 ⟩ +≡
  curr_keyword = new Keyword_Type;
  curr_keyword→name = "ASSIGN";
  curr_keyword→value = ASSIGN;
  curr_keyword→value_name = "ASSIGN";
  keyword_map["="] = curr_keyword;
  token_map[ASSIGN] = curr_keyword→value_name;
  curr_keyword = new Keyword_Type;
  curr_keyword→name = "PLUS_ASSIGN";
  curr_keyword→value = PLUS_ASSIGN;
  curr_keyword→value_name = "PLUS_ASSIGN";
  keyword_map["+="] = curr_keyword;
  token_map[PLUS_ASSIGN] = curr_keyword→value_name;
  curr_keyword = new Keyword_Type;
  curr_keyword→name = "MINUS_ASSIGN";
  curr_keyword→value = MINUS_ASSIGN;
  curr_keyword→value_name = "MINUS_ASSIGN";
  keyword_map["-="] = curr_keyword;
  token_map[MINUS_ASSIGN] = curr_keyword→value_name;
  curr_keyword = new Keyword_Type;
  curr_keyword→name = "TIMES_ASSIGN";
  curr_keyword→value = TIMES_ASSIGN;
  curr_keyword→value_name = "TIMES_ASSIGN";
  keyword_map["*="] = curr_keyword;
  token_map[TIMES_ASSIGN] = curr_keyword→value_name;
  curr_keyword = new Keyword_Type;
  curr_keyword→name = "DIVIDE_ASSIGN";
  curr_keyword→value = DIVIDE_ASSIGN;
  curr_keyword→value_name = "DIVIDE_ASSIGN";
  keyword_map["/="] = curr_keyword;
  token_map[DIVIDE_ASSIGN] = curr_keyword→value_name;
  curr_keyword = new Keyword_Type;
  curr_keyword→name = "AND_ASSIGN";
  curr_keyword→value = AND_ASSIGN;
  curr_keyword→value_name = "AND_ASSIGN";
  keyword_map["&="] = curr_keyword;
  token_map[AND_ASSIGN] = curr_keyword→value_name;
  curr_keyword = new Keyword_Type;
  curr_keyword→name = "OR_ASSIGN";
  curr_keyword→value = OR_ASSIGN;
  curr_keyword→value_name = "OR_ASSIGN";
  keyword_map["|="] = curr_keyword;
  token_map[OR_ASSIGN] = curr_keyword→value_name;
  curr_keyword = new Keyword_Type;
```

```
curr_keyword→name = "XOR_ASSIGN";
curr_keyword→value = XOR_ASSIGN;
curr_keyword→value_name = "XOR_ASSIGN";
keyword_map["^="] = curr_keyword;
token_map[XOR_ASSIGN] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "NOT_ASSIGN";
curr_keyword→value = NOT_ASSIGN;
curr_keyword→value_name = "NOT_ASSIGN";
keyword_map["!="] = curr_keyword;
token_map[NOT_ASSIGN] = curr_keyword→value_name;
```

272. Arithmetical Operations. [LDF 2006.11.14.]

Log

[2006.11.14.] Added this section with code for `PLUS`, `MINUS`, `TIMES`, and `DIVIDE`.

⟨ Define **Scan_Parse** functions 269 ⟩ +≡

```
curr_keyword = new Keyword_Type;
curr_keyword→name = "PLUS";
curr_keyword→value = PLUS;
curr_keyword→value_name = "PLUS";
keyword_map["+"] = curr_keyword;
token_map[PLUS] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "MINUS";
curr_keyword→value = MINUS;
curr_keyword→value_name = "MINUS";
keyword_map["-"] = curr_keyword;
token_map[MINUS] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "TIMES";
curr_keyword→value = TIMES;
curr_keyword→value_name = "TIMES";
keyword_map["*"] = curr_keyword;
token_map[TIMES] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "DIVIDE";
curr_keyword→value = DIVIDE;
curr_keyword→value_name = "DIVIDE";
keyword_map["/"] = curr_keyword;
token_map[DIVIDE] = curr_keyword→value_name;
```

273. Types with values. [LDF 2006.10.19.]

⟨ Define **Scan_Parse** functions 269 ⟩ +≡

```
curr_keyword = new Keyword_Type;
curr_keyword→name = "STRING";
curr_keyword→value = STRING;
curr_keyword→value_name = "STRING";
keyword_map["STRING"] = curr_keyword;
token_map[STRING] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "INTEGER";
curr_keyword→value = INTEGER;
curr_keyword→value_name = "INTEGER";
keyword_map["INTEGER"] = curr_keyword;
token_map[INTEGER] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "FLOAT";
curr_keyword→value = FLOAT;
curr_keyword→value_name = "FLOAT";
keyword_map["FLOAT"] = curr_keyword;
token_map[FLOAT] = curr_keyword→value_name;
```

274. Control. [LDF 2006.10.19.]

⟨ Define **Scan_Parse** functions 269 ⟩ +≡

```
curr_keyword = new Keyword_Type;
curr_keyword→name = "start";
curr_keyword→value = START;
curr_keyword→value_name = "START";
keyword_map["start"] = curr_keyword;
token_map[START] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "end";
curr_keyword→value = END;
curr_keyword→value_name = "END";
keyword_map["end"] = curr_keyword;
token_map[END] = curr_keyword→value_name;
```

275. Queries. [LDF 2006.10.19.]

Log

[2006.11.16.] Added code for `STRING_DECLARATOR`.

⟨ Define **Scan_Parse** functions 269 ⟩ +≡

```
curr_keyword = new Keyword_Type;
curr_keyword→name = "query";
curr_keyword→value = QUERY_DECLARATOR;
curr_keyword→value_name = "QUERY_DECLARATOR";
keyword_map["query"] = curr_keyword;
token_map[QUERY_DECLARATOR] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "local";
curr_keyword→value = LOCAL;
curr_keyword→value_name = "LOCAL";
keyword_map["local"] = curr_keyword;
token_map[LOCAL] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "remote";
curr_keyword→value = REMOTE;
curr_keyword→value_name = "REMOTE";
keyword_map["remote"] = curr_keyword;
token_map[REMOTE] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "database";
curr_keyword→value = DATABASE;
curr_keyword→value_name = "DATABASE";
keyword_map["database"] = curr_keyword;
token_map[DATABASE] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "server";
curr_keyword→value = SERVER;
curr_keyword→value_name = "SERVER";
keyword_map["server"] = curr_keyword;
token_map[SERVER] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "string";
curr_keyword→value = STRING_DECLARATOR;
curr_keyword→value_name = "STRING_DECLARATOR";
keyword_map["string"] = curr_keyword;
token_map[STRING_DECLARATOR] = curr_keyword→value_name;
```

276. Match types. [LDF 2006.12.11.]

Log

[2006.12.11.] Added this section with code for `LIKE` and `FREETEXT`.

[LDF 2006.12.12.] Added code for `CONTAINS`.

⟨ Define **Scan_Parse** functions 269 ⟩ +≡

```
curr_keyword = new Keyword_Type;
curr_keyword→name = "contains";
curr_keyword→value = CONTAINS;
curr_keyword→value_name = "CONTAINS";
keyword_map["contains"] = curr_keyword;
token_map[CONTAINS] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "freetext";
curr_keyword→value = FREETEXT;
curr_keyword→value_name = "FREETEXT";
keyword_map["freetext"] = curr_keyword;
token_map[FREETEXT] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "like";
curr_keyword→value = LIKE;
curr_keyword→value_name = "LIKE";
keyword_map["like"] = curr_keyword;
token_map[LIKE] = curr_keyword→value_name;
```

277. Datasources. [LDF 2006.12.08.]

Log

[2006.11.16.] Added this section with code for `DATASOURCE_DECLARATOR`.

⟨ Define **Scan_Parse** functions 269 ⟩ +≡

```
curr_keyword = new Keyword_Type;
curr_keyword→name = "datasource";
curr_keyword→value = DATASOURCE_DECLARATOR;
curr_keyword→value_name = "DATASOURCE_DECLARATOR";
keyword_map["datasource"] = curr_keyword;
token_map[DATASOURCE_DECLARATOR] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "dbt";
curr_keyword→value = DBT;
curr_keyword→value_name = "DBT";
keyword_map["dbt"] = curr_keyword;
token_map[DBT] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "gbv_gvk";
curr_keyword→value = GBV_GVK;
curr_keyword→value_name = "GBV_GVK";
keyword_map["gbv_gvk"] = curr_keyword;
token_map[GBV_GVK] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "timms";
curr_keyword→value = TIMMS;
curr_keyword→value_name = "TIMMS";
keyword_map["timms"] = curr_keyword;
token_map[TIMMS] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "file";
curr_keyword→value = DATASOURCE_FILE;
curr_keyword→value_name = "DATASOURCE_FILE";
keyword_map["file"] = curr_keyword;
token_map[DATASOURCE_FILE] = curr_keyword→value_name;
```

278. Datetime. [LDF 2006.12.15.]

Log

[LDF 2006.12.15.] Added this section with code for `DATETIME_DECLARATOR`.

⟨ Define **Scan_Parse** functions 269 ⟩ +≡

```
curr_keyword = new Keyword_Type;
curr_keyword→name = "datetime";
curr_keyword→value = DATETIME_DECLARATOR;
curr_keyword→value_name = "DATETIME_DECLARATOR";
keyword_map["datetime"] = curr_keyword;
token_map[DATETIME_DECLARATOR] = curr_keyword→value_name;
```

279. Datetimes. [LDF 2006.12.15.]

Log

[2006.12.15.] Added code for `DAY`, `MONTH`, `YEAR`, `HOUR`, `MINUTE`, and `SECOND`.

[LDF 2006.12.18.] Added code for `YEAR_RANGE_BEGIN` and `YEAR_RANGE_END`.

⟨ Define **Scan_Parse** functions 269 ⟩ +≡

```
curr_keyword = new Keyword_Type;
curr_keyword→name = "year_range_begin";
curr_keyword→value = YEAR_RANGE_BEGIN;
curr_keyword→value_name = "YEAR_RANGE_BEGIN";
keyword_map["year_range_begin"] = curr_keyword;
token_map[YEAR_RANGE_BEGIN] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "year_range_end";
curr_keyword→value = YEAR_RANGE_END;
curr_keyword→value_name = "YEAR_RANGE_END";
keyword_map["year_range_end"] = curr_keyword;
token_map[YEAR_RANGE_END] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "year";
curr_keyword→value = YEAR;
curr_keyword→value_name = "YEAR";
keyword_map["year"] = curr_keyword;
token_map[YEAR] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "month";
curr_keyword→value = MONTH;
curr_keyword→value_name = "MONTH";
keyword_map["month"] = curr_keyword;
token_map[MONTH] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "day";
curr_keyword→value = DAY;
curr_keyword→value_name = "DAY";
keyword_map["day"] = curr_keyword;
token_map[DAY] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "hour";
curr_keyword→value = HOUR;
curr_keyword→value_name = "HOUR";
keyword_map["hour"] = curr_keyword;
token_map[HOUR] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "minute";
curr_keyword→value = MINUTE;
curr_keyword→value_name = "MINUTE";
keyword_map["minute"] = curr_keyword;
token_map[MINUTE] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "second";
```

```
curr_keyword→value = SECOND;
curr_keyword→value_name = "SECOND";
keyword_map["second"] = curr_keyword;
token_map[SECOND] = curr_keyword→value_name;
```

280. Predicates and Control Structures. [LDF 2006.11.14.]

Log

[2006.11.14.] Added this section with code for `IF`, `ELSE`, `ELIF`, `FI`, `FOR`, `DO`, `WHILE`, `AND`, `OR`, `XOR`, `NOT`, `AND_NOT`, `OR_NOT`, and `XOR_NOT`.

⟨ Define **Scan_Parse** functions 269 ⟩ +≡

```
curr_keyword = new Keyword_Type;
curr_keyword→name = "if";
curr_keyword→value = IF;
curr_keyword→value_name = "IF";
keyword_map["if"] = curr_keyword;
token_map[IF] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "else";
curr_keyword→value = ELSE;
curr_keyword→value_name = "ELSE";
keyword_map["else"] = curr_keyword;
token_map[ELSE] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "elif";
curr_keyword→value = ELIF;
curr_keyword→value_name = "ELIF";
keyword_map["elif"] = curr_keyword;
token_map[ELIF] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "fi";
curr_keyword→value = FI;
curr_keyword→value_name = "FI";
keyword_map["fi"] = curr_keyword;
token_map[FI] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "for";
curr_keyword→value = FOR;
curr_keyword→value_name = "FOR";
keyword_map["for"] = curr_keyword;
token_map[FOR] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "do";
curr_keyword→value = DO;
curr_keyword→value_name = "DO";
keyword_map["do"] = curr_keyword;
token_map[DO] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "while";
curr_keyword→value = WHILE;
curr_keyword→value_name = "WHILE";
keyword_map["while"] = curr_keyword;
token_map[WHILE] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "and";
```

```
curr_keyword→value = AND;
curr_keyword→value_name = "AND";
keyword_map["and"] = curr_keyword;
keyword_map["&"] = curr_keyword;
token_map[AND] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "or";
curr_keyword→value = OR;
curr_keyword→value_name = "OR";
keyword_map["or"] = curr_keyword;
keyword_map["|"] = curr_keyword;
token_map[OR] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "xor";
curr_keyword→value = XOR;
curr_keyword→value_name = "XOR";
keyword_map["xor"] = curr_keyword;
keyword_map["^"] = curr_keyword;
token_map[XOR] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "not";
curr_keyword→value = NOT;
curr_keyword→value_name = "NOT";
keyword_map["!"] = curr_keyword;
token_map[NOT] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "AND_NOT";
curr_keyword→value = AND_NOT;
curr_keyword→value_name = "AND_NOT";
keyword_map["&!"] = curr_keyword;
token_map[AND_NOT] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "OR_NOT";
curr_keyword→value = OR_NOT;
curr_keyword→value_name = "OR_NOT";
keyword_map["|!"] = curr_keyword;
token_map[OR_NOT] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "XOR_NOT";
curr_keyword→value = XOR_NOT;
curr_keyword→value_name = "XOR_NOT";
keyword_map["^!"] = curr_keyword;
token_map[XOR_NOT] = curr_keyword→value_name;
```

281. Fields. [LDF 2006.10.19.]

Log

[LDF 2006.12.05.] Added code for CREATOR.

[LDF 2006.12.12.] Added code for MAIN_CANONICAL_TITLE.

[LDF 2006.12.12.] Added code to account for the tokens that refer to additional tables in the OAI database (dc_test).

[LDF 2006.12.12.] Added code to account for the tokens that refer to additional tables in the PICA database (PICA_DB).

⟨ Define **Scan_Parse** functions 269 ⟩ +≡

```
curr_keyword = new Keyword_Type;
curr_keyword→name = "access_number";
curr_keyword→value = ACCESS_NUMBER;
curr_keyword→value_name = "ACCESS_NUMBER";
keyword_map["access_number"] = curr_keyword;
token_map[ACCESS_NUMBER] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "author";
curr_keyword→value = AUTHOR;
curr_keyword→value_name = "AUTHOR";
keyword_map["author"] = curr_keyword;
token_map[AUTHOR] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "bibliographic_type";
curr_keyword→value = BIBLIOGRAPHIC_TYPE;
curr_keyword→value_name = "BIBLIOGRAPHIC_TYPE";
keyword_map["bibliographic_type"] = curr_keyword;
token_map[BIBLIOGRAPHIC_TYPE] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "call_number";
curr_keyword→value = CALL_NUMBER;
curr_keyword→value_name = "CALL_NUMBER";
keyword_map["call_number"] = curr_keyword;
token_map[CALL_NUMBER] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "classification";
curr_keyword→value = CLASSIFICATION;
curr_keyword→value_name = "CLASSIFICATION";
keyword_map["classification"] = curr_keyword;
token_map[CLASSIFICATION] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "company";
curr_keyword→value = COMPANY;
curr_keyword→value_name = "COMPANY";
keyword_map["company"] = curr_keyword;
token_map[COMPANY] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "content_summary";
curr_keyword→value = CONTENT_SUMMARY;
```

```
curr_keyword→value_name = "CONTENT_SUMMARY";
keyword_map["content_summary"] = curr_keyword;
token_map[CONTENT_SUMMARY] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "contributor";
curr_keyword→value = CONTRIBUTOR;
curr_keyword→value_name = "CONTRIBUTOR";
keyword_map["contributor"] = curr_keyword;
token_map[CONTRIBUTOR] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "creator";
curr_keyword→value = CREATOR;
curr_keyword→value_name = "CREATOR";
keyword_map["creator"] = curr_keyword;
token_map[CREATOR] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "database_provider";
curr_keyword→value = DATABASE_PROVIDER;
curr_keyword→value_name = "DATABASE_PROVIDER";
keyword_map["database_provider"] = curr_keyword;
token_map[DATABASE_PROVIDER] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "description";
curr_keyword→value = DESCRIPTION;
curr_keyword→value_name = "DESCRIPTION";
keyword_map["description"] = curr_keyword;
token_map[DESCRIPTION] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "exemplar_production_number";
curr_keyword→value = EXEMPLAR_PRODUCTION_NUMBER;
curr_keyword→value_name = "EXEMPLAR_PRODUCTION_NUMBER";
keyword_map["exemplar_production_number"] = curr_keyword;
token_map[EXEMPLAR_PRODUCTION_NUMBER] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "identifier";
curr_keyword→value = IDENTIFIER;
curr_keyword→value_name = "IDENTIFIER";
keyword_map["identifier"] = curr_keyword;
token_map[IDENTIFIER] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "institution";
curr_keyword→value = INSTITUTION;
curr_keyword→value_name = "INSTITUTION";
keyword_map["institution"] = curr_keyword;
token_map[INSTITUTION] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "language";
curr_keyword→value = LANGUAGE;
curr_keyword→value_name = "LANGUAGE";
keyword_map["language"] = curr_keyword;
token_map[LANGUAGE] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
```

```
curr_keyword→name = "main_canonical_title";
curr_keyword→value = MAIN_CANONICAL_TITLE;
curr_keyword→value_name = "MAIN_CANONICAL_TITLE";
keyword_map["main_canonical_title"] = curr_keyword;
token_map[MAIN_CANONICAL_TITLE] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "permutation_pattern";
curr_keyword→value = PERMUTATION_PATTERN;
curr_keyword→value_name = "PERMUTATION_PATTERN";
keyword_map["permutation_pattern"] = curr_keyword;
token_map[PERMUTATION_PATTERN] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "person";
curr_keyword→value = PERSON;
curr_keyword→value_name = "PERSON";
keyword_map["person"] = curr_keyword;
token_map[PERSON] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "physical_description";
curr_keyword→value = PHYSICAL_DESCRIPTION;
curr_keyword→value_name = "PHYSICAL_DESCRIPTION";
keyword_map["physical_description"] = curr_keyword;
token_map[PHYSICAL_DESCRIPTION] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "publisher";
curr_keyword→value = PUBLISHER;
curr_keyword→value_name = "PUBLISHER";
keyword_map["publisher"] = curr_keyword;
token_map[PUBLISHER] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "record";
curr_keyword→value = RECORD;
curr_keyword→value_name = "RECORD";
keyword_map["record"] = curr_keyword;
token_map[RECORD] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "remote_access";
curr_keyword→value = REMOTE_ACCESS;
curr_keyword→value_name = "REMOTE_ACCESS";
keyword_map["remote_access"] = curr_keyword;
token_map[REMOTE_ACCESS] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "rights";
curr_keyword→value = RIGHTS;
curr_keyword→value_name = "RIGHTS";
keyword_map["rights"] = curr_keyword;
token_map[RIGHTS] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "source";
curr_keyword→value = SOURCE;
curr_keyword→value_name = "SOURCE";
keyword_map["source"] = curr_keyword;
```

```
token_map[SOURCE] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "subject";
curr_keyword→value = SUBJECT;
curr_keyword→value_name = "SUBJECT";
keyword_map["subject"] = curr_keyword;
token_map[SUBJECT] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "superordinate_entities";
curr_keyword→value = SUPERORDINATE_ENTITIES;
curr_keyword→value_name = "SUPERORDINATE_ENTITIES";
keyword_map["superordinate_entities"] = curr_keyword;
token_map[SUPERORDINATE_ENTITIES] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "title";
curr_keyword→value = TITLE;
curr_keyword→value_name = "TITLE";
keyword_map["title"] = curr_keyword;
token_map[TITLE] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "type";
curr_keyword→value = TYPE;
curr_keyword→value_name = "TYPE";
keyword_map["type"] = curr_keyword;
token_map[TYPE] = curr_keyword→value_name;
```

282. Keywords for database table columns. [LDF 2006.12.14.]

Log

[2006.12.14.] Added this section.

283. Generic. [LDF 2006.12.14.]

Log

[2006.12.14.] Added this section.

⟨ Define **Scan_Parse** functions 269 ⟩ +≡

```
curr_keyword = new Keyword_Type;
curr_keyword→name = "id";
curr_keyword→value = ID;
curr_keyword→value_name = "ID";
keyword_map["id"] = curr_keyword;
token_map[ID] = curr_keyword→value_name;
```

284. Names. [2006.12.07.]

Log

[2006.12.07.] Added this section with code for `GIVEN_NAME`, `PREFIX`, and `SURNAME`.

⟨ Define **Scan_Parse** functions 269 ⟩ +≡

```
curr_keyword = new Keyword_Type;
curr_keyword→name = "given_name";
curr_keyword→value = GIVEN_NAME;
curr_keyword→value_name = "GIVEN_NAME";
keyword_map["given_name"] = curr_keyword;
token_map[GIVEN_NAME] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "prefix";
curr_keyword→value = PREFIX;
curr_keyword→value_name = "PREFIX";
keyword_map["prefix"] = curr_keyword;
token_map[PREFIX] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "surname";
curr_keyword→value = SURNAME;
curr_keyword→value_name = "SURNAME";
keyword_map["surname"] = curr_keyword;
token_map[SURNAME] = curr_keyword→value_name;
```

285. Records. [2006.12.07.]

Log

[2006.12.14.] Added this section.

⟨ Define **Scan_Parse** functions 269 ⟩ +≡

```
curr_keyword = new Keyword_Type;
curr_keyword→name = "eln_original_entry";
curr_keyword→value = ELN_ORIGINAL_ENTRY;
curr_keyword→value_name = "ELN_ORIGINAL_ENTRY";
keyword_map["eln_original_entry"] = curr_keyword;
token_map[ELN_ORIGINAL_ENTRY] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "eln_most_recent_change";
curr_keyword→value = ELN_MOST_RECENT_CHANGE;
curr_keyword→value_name = "ELN_MOST_RECENT_CHANGE";
keyword_map["eln_most_recent_change"] = curr_keyword;
token_map[ELN_MOST_RECENT_CHANGE] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "eln_status_change";
curr_keyword→value = ELN_STATUS_CHANGE;
curr_keyword→value_name = "ELN_STATUS_CHANGE";
keyword_map["eln_status_change"] = curr_keyword;
token_map[ELN_STATUS_CHANGE] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "identification_number";
curr_keyword→value = IDENTIFICATION_NUMBER;
curr_keyword→value_name = "IDENTIFICATION_NUMBER";
keyword_map["identification_number"] = curr_keyword;
token_map[IDENTIFICATION_NUMBER] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "date_original_entry";
curr_keyword→value = DATE_ORIGINAL_ENTRY;
curr_keyword→value_name = "DATE_ORIGINAL_ENTRY";
keyword_map["date_original_entry"] = curr_keyword;
token_map[DATE_ORIGINAL_ENTRY] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "date_most_recent_change";
curr_keyword→value = DATE_MOST_RECENT_CHANGE;
curr_keyword→value_name = "DATE_MOST_RECENT_CHANGE";
keyword_map["date_most_recent_change"] = curr_keyword;
token_map[DATE_MOST_RECENT_CHANGE] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "date_status_change";
curr_keyword→value = DATE_STATUS_CHANGE;
curr_keyword→value_name = "DATE_STATUS_CHANGE";
keyword_map["date_status_change"] = curr_keyword;
token_map[DATE_STATUS_CHANGE] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "source_id";
curr_keyword→value = SOURCE_ID;
```

```
curr_keyword→value_name = "SOURCE_ID";
keyword_map["source_id"] = curr_keyword;
token_map[SOURCE_ID] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "year_appearance_begin";
curr_keyword→value = YEAR_APPEARANCE_BEGIN;
curr_keyword→value_name = "YEAR_APPEARANCE_BEGIN";
keyword_map["year_appearance_begin"] = curr_keyword;
token_map[YEAR_APPEARANCE_BEGIN] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "year_appearance_end";
curr_keyword→value = YEAR_APPEARANCE_END;
curr_keyword→value_name = "YEAR_APPEARANCE_END";
keyword_map["year_appearance_end"] = curr_keyword;
token_map[YEAR_APPEARANCE_END] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "year_appearance_rak_wb";
curr_keyword→value = YEAR_APPEARANCE_RAK_WB;
curr_keyword→value_name = "YEAR_APPEARANCE_RAK_WB";
keyword_map["year_appearance_rak_wb"] = curr_keyword;
token_map[YEAR_APPEARANCE_RAK_WB] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "year_appearance_original";
curr_keyword→value = YEAR_APPEARANCE_ORIGINAL;
curr_keyword→value_name = "YEAR_APPEARANCE_ORIGINAL";
keyword_map["year_appearance_original"] = curr_keyword;
token_map[YEAR_APPEARANCE_ORIGINAL] = curr_keyword→value_name;
```

286. Variables. [LDF Undated.]

⟨ Define **Scan_Parse** functions 269 ⟩ +≡

```
curr_keyword = new Keyword_Type;
curr_keyword→name = "VARIABLE";
curr_keyword→value = VARIABLE;
curr_keyword→value_name = "VARIABLE";
keyword_map["VARIABLE"] = curr_keyword;
token_map[VARIABLE] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "VARIABLE_TEXT_SEGMENT";
curr_keyword→value = VARIABLE_TEXT_SEGMENT;
curr_keyword→value_name = "VARIABLE_TEXT_SEGMENT";
keyword_map["VARIABLE_TEXT_SEGMENT"] = curr_keyword;
token_map[VARIABLE_TEXT_SEGMENT] = curr_keyword→value_name;
```

287.

Log

[LDF 2006.11.16.] Added code for `STRING_TYPE`.

[LDF 2006.12.08.] Added code for `DATASOURCE_TYPE`.

[LDF 2006.12.15.] Added code for `DATETIME_TYPE`.

⟨ Define **Scan_Parse** functions 269 ⟩ +≡

```
curr_keyword = new Keyword_Type;
curr_keyword→name = "NULL_TYPE";
curr_keyword→value = NULL_TYPE;
curr_keyword→value_name = "NULL_TYPE";
keyword_map["NULL_TYPE"] = curr_keyword;
token_map[NULL_TYPE] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "DATASOURCE_TYPE";
curr_keyword→value = DATASOURCE_TYPE;
curr_keyword→value_name = "DATASOURCE_TYPE";
keyword_map["DATASOURCE_TYPE"] = curr_keyword;
token_map[DATASOURCE_TYPE] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "DATETIME_TYPE";
curr_keyword→value = DATETIME_TYPE;
curr_keyword→value_name = "DATETIME_TYPE";
keyword_map["DATETIME_TYPE"] = curr_keyword;
token_map[DATETIME_TYPE] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "QUERY_TYPE";
curr_keyword→value = QUERY_TYPE;
curr_keyword→value_name = "QUERY_TYPE";
keyword_map["QUERY_TYPE"] = curr_keyword;
token_map[QUERY_TYPE] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "STRING_TYPE";
curr_keyword→value = STRING_TYPE;
curr_keyword→value_name = "STRING_TYPE";
keyword_map["STRING_TYPE"] = curr_keyword;
token_map[STRING_TYPE] = curr_keyword→value_name;
```

288. Commands. [LDF 2006.11.13.]
[LDF 2006.10.19.]

Log

[LDF 2006.11.13.] Added code for `CLEAR` and `SHOW`.

[LDF 2006.11.13.] Added code for `CLEAR` and `SHOW`.

[LDF 2006.11.13.] Added code for `MESSAGE`, `ERRMESSAGE`, and `PAUSE`.

[LDF 2006.11.16.] Added code for `TEX`, `SQL`, `OAI`, and `PICA`.

[LDF 2006.11.23.] Added code for `OUTPUT`.

```
⟨ Define Scan_Parse functions 269 ⟩ +≡
  curr_keyword = new Keyword_Type;
  curr_keyword→name = "clear";
  curr_keyword→value = CLEAR;
  curr_keyword→value_name = "CLEAR";
  keyword_map["clear"] = curr_keyword;
  token_map[CLEAR] = curr_keyword→value_name;
  curr_keyword = new Keyword_Type;
  curr_keyword→name = "errmessage";
  curr_keyword→value = ERRMESSAGE;
  curr_keyword→value_name = "ERRMESSAGE";
  keyword_map["errmessage"] = curr_keyword;
  token_map[ERRMESSAGE] = curr_keyword→value_name;
  curr_keyword = new Keyword_Type;
  curr_keyword→name = "message";
  curr_keyword→value = MESSAGE;
  curr_keyword→value_name = "MESSAGE";
  keyword_map["message"] = curr_keyword;
  token_map[MESSAGE] = curr_keyword→value_name;
  curr_keyword = new Keyword_Type;
  curr_keyword→name = "pause";
  curr_keyword→value = PAUSE;
  curr_keyword→value_name = "PAUSE";
  keyword_map["pause"] = curr_keyword;
  token_map[PAUSE] = curr_keyword→value_name;
  curr_keyword = new Keyword_Type;
  curr_keyword→name = "show";
  curr_keyword→value = SHOW;
  curr_keyword→value_name = "SHOW";
  keyword_map["show"] = curr_keyword;
  token_map[SHOW] = curr_keyword→value_name;
  curr_keyword = new Keyword_Type;
  curr_keyword→name = "tex";
  curr_keyword→value = TEX;
  curr_keyword→value_name = "TEX";
  keyword_map["tex"] = curr_keyword;
  token_map[TEX] = curr_keyword→value_name;
  curr_keyword = new Keyword_Type;
  curr_keyword→name = "sql";
  curr_keyword→value = SQL;
```

```
curr_keyword→value_name = "SQL";
keyword_map["sql"] = curr_keyword;
token_map[SQL] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "oai";
curr_keyword→value = OAI;
curr_keyword→value_name = "OAI";
keyword_map["oai"] = curr_keyword;
token_map[OAI] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "pica";
curr_keyword→value = PICA;
curr_keyword→value_name = "PICA";
keyword_map["pica"] = curr_keyword;
token_map[PICA] = curr_keyword→value_name;
curr_keyword = new Keyword_Type;
curr_keyword→name = "output";
curr_keyword→value = OUTPUT;
curr_keyword→value_name = "OUTPUT";
keyword_map["output"] = curr_keyword;
token_map[OUTPUT] = curr_keyword→value_name;
```

289. Control. [LDF 2006.10.19.]

```
⟨ Define Scan_Parse functions 269 ⟩ +≡
  curr_keyword = new Keyword_Type;
  curr_keyword→name = "terminate";
  curr_keyword→value = TERMINATE;
  curr_keyword→value_name = "TERMINATE";
  keyword_map["terminate"] = curr_keyword;
  token_map[TERMINATE] = curr_keyword→value_name;
  return 0; }      /* End of Scan_Parse::initialize_maps definition. */
```

290. **Show** *keyword_map*. [LDF 2006.10.19.]

291.

```
⟨ Declare Scan_Parse functions 268 ⟩ +≡
  int show_keyword_map(Scanner_Type *scanner_node);
```

292.

```
⟨ Define Scan_Parse functions 269 ⟩ +≡
  int Scan_Parse::show_keyword_map(Scanner_Type *scanner_node)
  {
    stringstream temp_strm;
    temp_strm ≪ "Showing␣‘keyword_map’:" ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    if (scanner_node) scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
    for (map⟨string, Keyword_Type *⟩::const_iterator iter = keyword_map.begin();
        iter ≠ keyword_map.end(); ++iter) {
      temp_strm ≪ "name:␣␣" ≪ iter→second→name ≪ ",␣value:␣␣" ≪ token_map[iter→second→value] ≪
          "␣(" ≪ iter→second→value ≪ ")␣" ≪ ",␣constant␣name:␣␣" ≪ iter→second→value_name ≪
          endl;
      cerr_mutex.lock();
      cerr ≪ temp_strm.str();
      cerr_mutex.unlock();
      if (scanner_node) scanner_node→log_strm ≪ temp_strm.str();
      temp_strm.str("");
    }     /* for */
    return 0;
  }     /* End of Scan_Parse::show_keyword_map definition. */
```

293. Parser rule functions. [LDF 2006.10.31.]
These functions are used in the parser rules. They are defined in other files. [LDF 2006.10.31.]

Log

[2006.10.31.] Added this section.

294. Functions for variables. [LDF 2006.11.02.]

Log

[2006.11.02.] Added this section.

295. *variable_func.* [LDF 2006.11.02.]

Log

[2006.11.02.] Added this declaration.

⟨ Declare **Scan_Parse** functions 268 ⟩ +≡
void ∗*variable_func*(**void** ∗*v*, **char** ∗*name*);

296. Functions for declarations. [LDF 2006.11.01.]

Log

[2006.11.01.] Added this declaration.

[LDF 2006.11.01.] Added the **char** ∗*name* argument.

[LDF 2006.11.02.] Changed the return value from **int** to **void** ∗.

⟨ Declare **Scan_Parse** functions 268 ⟩ +≡
Id_Node *declare_variable_func*(**void** ∗*v*, **const unsigned short** *type*, **char** ∗*name*);

297. Functions for assignments. [LDF 2006.11.02.]

Log

[LDF 2006.11.02.] Added this section.

298. *query_assignment_func_0.* [LDF 2006.11.02.]

Log

[LDF 2006.11.02.] Added this declaration.

⟨ Declare **Scan_Parse** functions 268 ⟩ +≡
void ∗*query_assignment_func_0*(**void** ∗*v*, **void** ∗*object*, **unsigned int** *assignment_type*, **unsigned int** *arg_0*, **unsigned int** *arg_1*, **void** ∗*value*, **bool** *negate*);

299. *query_assignment_func_1.* [LDF 2006.12.19.]

Log

[LDF 2006.12.19.] Added this declaration.

⟨ Declare **Scan_Parse** functions 268 ⟩ +≡
int *query_assignment_func_1*(**Scanner_Node** *scanner_node*, **Id_Node** &*curr_id_node*, **void** ∗&*field_specifier*, **int** *assignment_operator*, **int** *negation_optional*, **int** *match_term_optional*, **void** ∗&*v*, **int** *type*);

300. *datetime_assignment_func_0.* [LDF 2006.12.15.]

Log

[LDF 2006.12.15.] Added this declaration.

⟨ Declare **Scan_Parse** functions 268 ⟩ +≡
int *datetime_assignment_func_0* (**void** ∗*v*, **Date_Time_Node** &*curr_date_time_node*, **int** *specifier*, **int** *op*, **void** ∗*val*, **int** *type*);

301. *datetime_assignment_func_1.* [LDF 2006.12.18.]

Log

[LDF 2006.12.18.] Added this declaration.

⟨ Declare **Scan_Parse** functions 268 ⟩ +≡
int *datetime_assignment_func_1* (**void** ∗*v*, **Date_Time_Node** &*d*, **int** *op*, **void** ∗&*vec*);

302. Functions for Group Statements. [LDF 2006.10.31.]

Log

[2006.10.31.] Added this section.

303. Start local database query function. [LDF 2006.10.31.]

Log

[2006.10.31.] Added this function declaration.

[LDF 2006.11.01.] Changed the name of this function from **Scan_Parse** :: *start_local_query_func* to **Scan_Parse** :: *start_loca*

⟨ Declare **Scan_Parse** functions 268 ⟩ +≡
int *start_local_database_query_func*(**void** ∗);

304. End query function. [LDF 2006.10.31.]

Log

[2006.10.31.] Added this function declaration.

[LDF 2006.11.01.] Changed the name of this function from **Scan_Parse** :: *end_local_query_func* to **Scan_Parse** :: *end_query_*

⟨ Declare **Scan_Parse** functions 268 ⟩ +≡
  int *end_query_func*(**void** ∗);

305. The scanning function *yylex*. [LDF 2006.10.17.]

Log

[LDF 2006.11.13.] Added code for handling `'+'`.

⟨ Declare *yylex* 305 ⟩ ≡
  int *yylex*(YYSTYPE ∗ *value*, **void** ∗*parameter*);

See also section 394.

This code is used in sections 362 and 676.

306.

⟨ Define *yylex* 306 ⟩ ≡
  int *yylex*(YYSTYPE ∗ *value*, **void** ∗*parameter*){

```
#if 0     /* 1 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
    using namespace Scan_Parse;
    stringstream temp_strm; stack < unsigned short > state_stack;
    unsigned short state = NULL_STATE;
    Scanner_Type *scanner_node = static_cast⟨Scanner_Type *⟩(parameter);
```

See also sections 307, 308, 309, 310, 311, 312, 313, 314, 315, 316, 317, 318, 319, 320, 321, 322, 323, 324, 325, 326, 327, 328, 329, 331, 332, 333, 334, 335, 336, 337, 338, 339, 340, 341, 342, 343, 344, 345, 346, 347, 348, 349, 350, 351, 352, 353, and 354.

This code is used in section 361.

307. "Fake" a token. If *scanner_node→token_stack* isn't empty, extract the token to be returned and its semantic value from the **Token_Type** object at the top of the stack, pop it from the stack, and return immediately, without reading anything from the input stream. This will happen repeatedly, until *scanner_node→token_stack* is empty. [LDF 2006.11.02.]

Log

[2006.11.02.] Added this section.

```
⟨ Define yylex 306 ⟩ +≡
  if (scanner_node→token_stack.size() > 0) {
#ifdef DEBUG_OUTPUT
    temp_strm ≪ "In␣‘yylex’:␣␣‘scanner_node->token_stack.size()␣==␣" ≪
        scanner_node→token_stack.size() ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    Token_Type curr_token = scanner_node→token_stack.top();
#ifdef DEBUG_OUTPUT
    temp_strm ≪ "‘curr_token.type’␣==␣" ≪ token_map[curr_token.type] ≪ "␣(" ≪ curr_token.type ≪
        ")." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    if (curr_token.type ≡ STRING) strcpy(value→string_value, curr_token.value.string_value);
    else if (curr_token.type ≡ INTEGER) value→int_value = curr_token.value.int_value;
    else if (curr_token.type ≡ FLOAT) value→float_value = curr_token.value.float_value;
    else {
      value→pointer_value = curr_token.value.pointer_value;
      curr_token.value.pointer_value = 0;
    }
    scanner_node→token_stack.pop();
    return curr_token.type;
  }     /* if (scanner_node→token_stack.size() > 0) */
  else {
#ifdef DEBUG_OUTPUT
    temp_strm ≪ "In␣‘yylex’:␣␣‘scanner_node->token_stack.size()␣==␣0." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
  }
```

308. Open input file. [LDF 2006.10.17.]

```
⟨ Define yylex 306 ⟩ +≡
#ifdef DEBUG_OUTPUT
  temp_strm ≪ "Entering␣‘yylex’." ≪ endl;
  cerr_mutex.lock( );
  cerr ≪ temp_strm.str( );
  cerr_mutex.unlock( );
  scanner_node→log_strm ≪ temp_strm.str( );
  temp_strm.str("");
#endif
#if 0    /* 1 */
#ifdef DEBUG_OUTPUT
  temp_strm ≪ "‘scanner_node->in_filename’␣==␣" ≪ scanner_node→in_filename ≪ endl;
  cerr_mutex.lock( );
  cerr ≪ temp_strm.str( );
  cerr_mutex.unlock( );
  scanner_node→log_strm ≪ temp_strm.str( );
  temp_strm.str("");
#endif
#endif
```

309. Main loop. [LDF 2006.10.17.]

Log

[LDF 2006.11.01.] Changed **string** *curr_keyword* to *curr_id*.

[LDF 2006.11.13.] Added *next_char*.

```
⟨ Define yylex 306 ⟩ +≡
  char curr_char = 0;
  char next_char = 0;
  string curr_string = "";
  string curr_id = "";
  int curr_value = 0;
  string curr_integer_str = "";
  string curr_float_str = ""; while (curr_char ≠ EOF) { curr_char = scanner_node→in_strm.get();
#ifdef DEBUG_OUTPUT
  temp_strm ≪ curr_char;
  cerr_mutex.lock();
  cerr ≪ temp_strm.str();
  cerr_mutex.unlock();
  scanner_node→log_strm ≪ temp_strm.str();
  temp_strm.str("");
#endif
```

310. Comments. `'#'`. Discard characters until end of line. `#` can occur in strings, however. [LDF 2006.10.17.] ∎

Log

[LDF 2006.10.31.] Changed comment character from `%` to `#`.

```
⟨ Define yylex 306 ⟩ +≡
  if (curr_char ≡ '#' ∧ (state ≡ NULL_STATE ∨ state ≡ COLLECTING_ID ∨ state ≡
      COLLECTING_INTEGER ∨ state ≡ COLLECTING_FLOAT)) {
#ifdef DEBUG_OUTPUT
    temp_strm ≪ endl ≪ "***␣Discarding␣comment.␣␣***" ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    while (¬(curr_char ≡ '\n' ∨ curr_char ≡ EOF)) {
      curr_char = scanner_node→in_strm.get();
      if (curr_char ≡ EOF) goto FINISH;
    }     /* Inner while */
#ifdef DEBUG_OUTPUT
    temp_strm ≪ endl ≪ "***␣Finished␣discarding␣comment.␣␣***" ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
```

```
#endif
  }     /* if (curr_char ≡ '#') (Discarding comment) */
```

311. Double-quote symbol. `'"'`. [LDF 2006.10.17.]

```
⟨ Define yylex 306 ⟩ +≡
  else if (curr_char ≡ '"') {
```

312. *state* ≡ `COLLECTING_STRING` [LDF 2006.10.17.]

```
⟨ Define yylex 306 ⟩ +≡
  if (state ≡ COLLECTING_STRING) {
    state = state_stack.top();
    state_stack.pop();
#ifdef DEBUG_OUTPUT
    temp_strm ≪ endl ≪ "***␣Finished␣collecting␣string." ≪ endl ≪ "'curr_string'␣==␣" ≪
        curr_string.c_str() ≪ endl ≪ "Exiting␣'yylex'␣successfully␣with␣return␣value␣" ≪
        keyword_map["STRING"]→value_name ≪ "␣(" ≪ keyword_map["STRING"]→value ≪ ")" ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    strcpy(value→string_value, curr_string.c_str());
    curr_string = "";
    return STRING;
  }     /* if (state ≡ COLLECTING_STRING) */
```

313. *state* ≡ NULL_STATE. Start collecting string. [LDF 2006.10.18.]

```
⟨ Define yylex 306 ⟩ +≡
  else
  if (state ≡ NULL_STATE) {
#ifdef DEBUG_OUTPUT
    temp_strm ≪ endl ≪ "***␣Starting␣to␣collect␣string.␣␣***" ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    state_stack.push(state);
    state = COLLECTING_STRING;
    curr_string = "";
  }
  else if (state ≡ COLLECTING_ID) {
#ifdef DEBUG_OUTPUT
  temp_strm ≪ endl ≪ "***␣Finished␣collecting␣keyword.␣␣" ≪ "‘curr_id’␣==␣" ≪ curr_id ≪
      endl ≪ "***" ≪ endl;
  cerr_mutex.lock();
  cerr ≪ temp_strm.str();
  cerr_mutex.unlock();
  scanner_node→log_strm ≪ temp_strm.str();
  temp_strm.str("");
#endif
```

314. Look up *curr_id* in *keyword_map* and possibly *id_map*. [LDF 2006.10.19.]

```
⟨ Define yylex 306 ⟩ +≡
  ⟨ Look up curr_id in keyword_map and possibly id_map 357 ⟩
  }    /* else if (state ≡ COLLECTING_ID) */
```

315. *state* ≡ COLLECTING_INTEGER. [LDF 2006.11.02.]

```
⟨ Define yylex 306 ⟩ +≡
  else
    if (state ≡ COLLECTING_INTEGER) {
#ifdef DEBUG_OUTPUT
      temp_strm ≪ endl ≪ "***␣Finished␣collecting␣integer.␣␣" ≪ "‘curr_integer_str’␣==␣" ≪
          curr_integer_str ≪ "␣␣***" ≪ endl;
      cerr_mutex.lock();
      cerr ≪ temp_strm.str();
      cerr_mutex.unlock();
      scanner_node→log_strm ≪ temp_strm.str();
      temp_strm.str("");
#endif
      value→int_value = atoi(curr_integer_str.c_str());
      scanner_node→in_strm.unget();
      return INTEGER;
    }    /* else if (state ≡ COLLECTING_INTEGER) */
```

316. *state* ≡ COLLECTING_FLOAT. [LDF 2006.11.02.]

```
⟨ Define yylex 306 ⟩ +≡
  else
    if (state ≡ COLLECTING_FLOAT) {
#ifdef DEBUG_OUTPUT
      temp_strm ≪ endl ≪ "***␣Finished␣collecting␣float.␣␣" ≪ "‘curr_float_str’␣==␣" ≪
          curr_float_str ≪ "␣␣***" ≪ endl;
      cerr_mutex.lock();
      cerr ≪ temp_strm.str();
      cerr_mutex.unlock();
      scanner_node→log_strm ≪ temp_strm.str();
      temp_strm.str("");
#endif
      value→float_value = atof(curr_float_str.c_str());
      scanner_node→in_strm.unget();
      return FLOAT;
    }     /* else if (state ≡ COLLECTING_FLOAT) */
```

317. Any other state (shouldn't occur.) [LDF 2006.11.02.]

```
⟨ Define yylex 306 ⟩ +≡
  else {
#ifdef DEBUG_OUTPUT
    temp_strm ≪ endl ≪ "***␣Starting␣to␣collect␣string.␣␣***" ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    state_stack.push(state);
    state = COLLECTING_STRING;
    curr_string = "";
  }
  }     /* else if (curr_char ≡ '"') */
```

318. Alphabetical characters and underline character. [LDF 2006.10.18.]

Log

[LDF 2006.12.08.] Now treating underline character like an alphabetical character.

[LDF 2006.12.11.] Added code for common accented characters.

```
⟨ Define yylex 306 ⟩ +≡
  else if (isalpha(curr_char) ∨ curr_char ≡ '_' ∨ curr_char ≡ '' ∨ curr_char ≡ '' ∨ curr_char ≡
      '' ∨ curr_char ≡ '' ∨ curr_char ≡ '
```

319. *state* ≡ NULL_STATE. [LDF 2006.10.18.]

```
⟨ Define yylex 306 ⟩ +≡
  if (state ≡ NULL_STATE) {
#ifdef DEBUG_OUTPUT
    temp_strm ≪ endl ≪ "***␣Read␣an␣alphabetical␣character␣" ≪
        "or␣the␣underline␣character␣in␣'NULL_STATE':" ≪ endl ≪
        "Entering␣state␣'COLLECTING_ID'.␣***" ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    state = COLLECTING_ID;
    curr_id = "";
    curr_id += curr_char;
  }    /* if (state ≡ NULL_STATE) */
```

320. *state* ≡ COLLECTING_ID. [LDF 2006.10.18.]

```
⟨ Define yylex 306 ⟩ +≡
  else
    if (state ≡ COLLECTING_ID) {
      curr_id += curr_char;
    }     /* if (state ≡ COLLECTING_ID) */
    else if (state ≡ COLLECTING_INTEGER) {
#ifdef DEBUG_OUTPUT
      temp_strm ≪ endl ≪ "***␣Finished␣collecting␣integer.␣␣" ≪ "'curr_integer_str'␣==␣" ≪
          curr_integer_str ≪ "␣␣***" ≪ endl;
      cerr_mutex.lock();
      cerr ≪ temp_strm.str();
      cerr_mutex.unlock();
      scanner_node→log_strm ≪ temp_strm.str();
      temp_strm.str("");
#endif
      value→int_value = atoi(curr_integer_str.c_str());
      scanner_node→in_strm.unget();
      return INTEGER;
    }     /* else if (state ≡ COLLECTING_INTEGER) */
    else if (state ≡ COLLECTING_FLOAT) {
#ifdef DEBUG_OUTPUT
      temp_strm ≪ endl ≪ "***␣Finished␣collecting␣float.␣␣" ≪ "'curr_float_str'␣==␣" ≪
          curr_float_str ≪ "␣␣***" ≪ endl;
      cerr_mutex.lock();
      cerr ≪ temp_strm.str();
      cerr_mutex.unlock();
      scanner_node→log_strm ≪ temp_strm.str();
      temp_strm.str("");
#endif
      value→float_value = atof(curr_float_str.c_str());
      scanner_node→in_strm.unget();
      return FLOAT;
    }     /* else if (state ≡ COLLECTING_FLOAT) */
```

321. *state* ≡ COLLECTING_STRING. [LDF 2006.10.18.]

```
⟨ Define yylex 306 ⟩ +≡
  else
    if (state ≡ COLLECTING_STRING) {
      curr_string += curr_char;
    }     /* if (state ≡ COLLECTING_STRING) */
  }     /* else if (isalpha(curr_char) ∨ curr_char ≡ '_') */
```

322. Digits. [LDF 2006.11.02.]

Log

[2006.11.02.] Added this section.

```
⟨ Define yylex 306 ⟩ +≡
  else if (isdigit(curr_char)) {
  if (state ≡ NULL_STATE) {
#ifdef DEBUG_OUTPUT
    temp_strm ≪ endl ≪ "***␣Read␣a␣digit␣in␣'NULL_STATE'.␣␣" ≪
        "Entering␣state␣'COLLECTING_INTEGER'." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    curr_integer_str += curr_char;
    state = COLLECTING_INTEGER;
    continue;
  }     /* if (state ≡ NULL_STATE) */
```

323. *state* ≡ COLLECTING_ID. [LDF 2006.10.18.]

```
⟨ Define yylex 306 ⟩ +≡
  else if (state ≡ COLLECTING_ID) {
#ifdef DEBUG_OUTPUT
  temp_strm ≪ endl ≪ "***␣Finished␣collecting␣keyword.␣␣" ≪ "'curr_id'␣==␣" ≪ curr_id ≪
      endl ≪ "***" ≪ endl;
  cerr_mutex.lock();
  cerr ≪ temp_strm.str();
  cerr_mutex.unlock();
  scanner_node→log_strm ≪ temp_strm.str();
  temp_strm.str("");
#endif
```

324. Look up *curr_id* in *keyword_map* and possibly *id_map*. [LDF 2006.10.19.]

```
⟨ Define yylex 306 ⟩ +≡
  ⟨ Look up curr_id in keyword_map and possibly id_map 357 ⟩
  }    /* else if (state ≡ COLLECTING_ID) */
  else
    if (state ≡ COLLECTING_INTEGER) {
      curr_integer_str += curr_char;
    }
    else if (state ≡ COLLECTING_FLOAT) {
      curr_float_str += curr_char;
    }
    else if (state ≡ COLLECTING_STRING) {
      curr_string += curr_char;
    }
  }    /* else if (isdigit(curr_char)) */
```

325. Escaped characters. '\. [LDF 2006.10.18.]

```
⟨ Define yylex 306 ⟩ +≡
  else if (curr_char ≡ '\\') {
```

326. *state* ≡ COLLECTING_ID. [LDF 2006.10.18.]

```
⟨ Define yylex 306 ⟩ +≡
  if (state ≡ COLLECTING_ID) {
#ifdef DEBUG_OUTPUT
  temp_strm ≪ endl ≪ "***␣Finished␣collecting␣keyword.␣␣" ≪ "‘curr_id’␣==␣" ≪ curr_id ≪
      endl ≪ "***" ≪ endl;
  cerr_mutex.lock();
  cerr ≪ temp_strm.str();
  cerr_mutex.unlock();
  scanner_node→log_strm ≪ temp_strm.str();
  temp_strm.str("");
#endif
```

327. Look up *curr_id* in *keyword_map* and possibly *id_map*. [LDF 2006.10.19.]

```
⟨ Define yylex 306 ⟩ +≡
  ⟨ Look up curr_id in keyword_map and possibly id_map 357 ⟩
  }    /* if (state ≡ COLLECTING_ID) */
  else
    if (state ≡ COLLECTING_INTEGER) {
#ifdef DEBUG_OUTPUT
      temp_strm ≪ endl ≪ "***␣Finished␣collecting␣integer.␣␣" ≪ "‘curr_integer_str’␣==␣" ≪
          curr_integer_str ≪ "␣␣***" ≪ endl;
      cerr_mutex.lock();
      cerr ≪ temp_strm.str();
      cerr_mutex.unlock();
      scanner_node→log_strm ≪ temp_strm.str();
      temp_strm.str("");
#endif
      value→int_value = atoi(curr_integer_str.c_str());
      scanner_node→in_strm.unget();
      return INTEGER;
    }    /* else if (state ≡ COLLECTING_INTEGER) */
    else if (state ≡ COLLECTING_FLOAT) {
#ifdef DEBUG_OUTPUT
      temp_strm ≪ endl ≪ "***␣Finished␣collecting␣float.␣␣" ≪ "‘curr_float_str’␣==␣" ≪
          curr_float_str ≪ "␣␣***" ≪ endl;
      cerr_mutex.lock();
      cerr ≪ temp_strm.str();
      cerr_mutex.unlock();
      scanner_node→log_strm ≪ temp_strm.str();
      temp_strm.str("");
#endif
      value→float_value = atof(curr_float_str.c_str());
      scanner_node→in_strm.unget();
      return FLOAT;
    }    /* else if (state ≡ COLLECTING_FLOAT) */
```

328. *state* ≡ COLLECTING_STRING. [LDF 2006.10.18.]

```
⟨ Define yylex 306 ⟩ +≡
  if (state ≡ COLLECTING_STRING) {
    curr_char = scanner_node→in_strm.get();
    curr_string += curr_char;
    continue;
  }    /* if (state ≡ COLLECTING_STRING) */
```

329.

```
⟨ Define yylex 306 ⟩ +≡
  }    /* else if (curr_char ≡ '\\') */
```

330. Punctuation. [LDF 2006.10.31.]

Log

[LDF 2006.10.31.] Added this section.

331. `'='` (Equals sign). [LDF 2006.10.31.]

Log

[2006.10.31.] Added this section.

```
⟨ Define yylex 306 ⟩ +≡
  else if (curr_char ≡ '=') {
  if (state ≡ NULL_STATE) {
#ifdef DEBUG_OUTPUT
    temp_strm ≪ "In␣‘yylex’:␣␣" ≪ "Got␣‘=’.␣␣Returning␣‘ASSIGN’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    return ASSIGN;
  }
  else if (state ≡ COLLECTING_STRING) {
    curr_string += curr_char;
  }
  else if (state ≡ COLLECTING_ID) {
#ifdef DEBUG_OUTPUT
  temp_strm ≪ endl ≪ "***␣Finished␣collecting␣keyword.␣␣" ≪ "‘curr_id’␣==␣" ≪ curr_id ≪
      endl ≪ "***" ≪ endl;
  cerr_mutex.lock();
  cerr ≪ temp_strm.str();
  cerr_mutex.unlock();
  scanner_node→log_strm ≪ temp_strm.str();
  temp_strm.str("");
#endif
```

332. Look up *curr_id* in *keyword_map* and possibly *id_map*. [LDF 2006.10.19.]

```
⟨ Define yylex 306 ⟩ +≡
  ⟨ Look up curr_id in keyword_map and possibly id_map 357 ⟩
  }    /* else if (state ≡ COLLECTING_ID) */
  else
    if (state ≡ COLLECTING_INTEGER) {
#ifdef DEBUG_OUTPUT
      temp_strm ≪ endl ≪ "***␣Finished␣collecting␣integer.␣␣" ≪ "‘curr_integer_str’␣==␣" ≪
          curr_integer_str ≪ "␣␣***" ≪ endl;
      cerr_mutex.lock();
      cerr ≪ temp_strm.str();
      cerr_mutex.unlock();
      scanner_node→log_strm ≪ temp_strm.str();
      temp_strm.str("");
#endif
      value→int_value = atoi(curr_integer_str.c_str());
      scanner_node→in_strm.unget();
      return INTEGER;
    }    /* else if (state ≡ COLLECTING_INTEGER) */
    else if (state ≡ COLLECTING_FLOAT) {
#ifdef DEBUG_OUTPUT
      temp_strm ≪ endl ≪ "***␣Finished␣collecting␣float.␣␣" ≪ "‘curr_float_str’␣==␣" ≪
          curr_float_str ≪ "␣␣***" ≪ endl;
      cerr_mutex.lock();
      cerr ≪ temp_strm.str();
      cerr_mutex.unlock();
      scanner_node→log_strm ≪ temp_strm.str();
      temp_strm.str("");
#endif
      value→float_value = atof(curr_float_str.c_str());
      scanner_node→in_strm.unget();
      return FLOAT;
    }    /* else if (state ≡ COLLECTING_FLOAT) */
  }    /* else if (curr_char ≡ '=') */
```

333. '+' (Plus sign). [LDF 2006.11.13.]

Log

[LDF 2006.11.13.] Added this section.

```
⟨ Define yylex 306 ⟩ +≡
  else
    if (curr_char ≡ '+') {
      if (state ≡ NULL_STATE) {
#ifdef DEBUG_OUTPUT
        temp_strm ≪ "In␣`yylex':␣␣" ≪ "Got␣`+'." ≪ endl;
        cerr_mutex.lock();
        cerr ≪ temp_strm.str();
        cerr_mutex.unlock();
        scanner_node→log_strm ≪ temp_strm.str();
        temp_strm.str("");
#endif
        next_char = scanner_node→in_strm.peek();
        if (next_char ≡ '=') {
          scanner_node→in_strm.get();
          return PLUS_ASSIGN;
        }
        else return PLUS;
      }    /* if (state ≡ NULL_STATE) */
      goto COMMON_PUNCTUATION;
    }    /* else if (curr_char ≡ '+') */
```

334. `'&'` (Ampersand). [LDF 2006.11.14.]

Log

[LDF 2006.11.14.] Added this section.

```
⟨ Define yylex 306 ⟩ +≡
  else
    if (curr_char ≡ '&') {
      if (state ≡ NULL_STATE) {
#ifdef DEBUG_OUTPUT
        temp_strm ≪ "In␣`yylex':␣␣" ≪ "Got␣`&'." ≪ endl;
        cerr_mutex.lock();
        cerr ≪ temp_strm.str();
        cerr_mutex.unlock();
        scanner_node→log_strm ≪ temp_strm.str();
        temp_strm.str("");
#endif
        next_char = scanner_node→in_strm.peek();
        if (next_char ≡ '=') {
          scanner_node→in_strm.get();
          return AND_ASSIGN;
        }
        else if (next_char ≡ '!') {
          scanner_node→in_strm.get();
          return AND_NOT;
        }
        else return AND;
      }    /* if (state ≡ NULL_STATE) */
      goto COMMON_PUNCTUATION;
    }    /* else if (curr_char ≡ '&') */
```

335. '|' (Vertical line). [LDF 2006.11.14.]

Log

[LDF 2006.11.14.] Added this section.

```
⟨ Define yylex 306 ⟩ +≡
  else
    if (curr_char ≡ '|') {
      if (state ≡ NULL_STATE) {
#ifdef DEBUG_OUTPUT
        temp_strm ≪ "In␣`yylex':␣␣" ≪ "Got␣`|'." ≪ endl;
        cerr_mutex.lock();
        cerr ≪ temp_strm.str();
        cerr_mutex.unlock();
        scanner_node→log_strm ≪ temp_strm.str();
        temp_strm.str("");
#endif
        next_char = scanner_node→in_strm.peek();
        if (next_char ≡ '=') {
          scanner_node→in_strm.get();
          return OR_ASSIGN;
        }
        else if (next_char ≡ '!') {
          scanner_node→in_strm.get();
          return OR_NOT;
        }
        else return OR;
      }    /* if (state ≡ NULL_STATE) */
      goto COMMON_PUNCTUATION;
    }    /* else if (curr_char ≡ '|') */
```

336. '^' (Circumflex accent). [LDF 2006.11.14.]

Log

[LDF 2006.11.14.] Added this section.

```
⟨ Define yylex 306 ⟩ +≡
  else
    if (curr_char ≡ '^') {
      if (state ≡ NULL_STATE) {
#ifdef DEBUG_OUTPUT
        temp_strm ≪ "In␣`yylex':␣␣" ≪ "Got␣`^'." ≪ endl;
        cerr_mutex.lock();
        cerr ≪ temp_strm.str();
        cerr_mutex.unlock();
        scanner_node→log_strm ≪ temp_strm.str();
        temp_strm.str("");
#endif
        next_char = scanner_node→in_strm.peek();
        if (next_char ≡ '=') {
          scanner_node→in_strm.get();
          return XOR_ASSIGN;
        }
        else if (next_char ≡ '!') {
          scanner_node→in_strm.get();
          return XOR_NOT;
        }
        else return XOR;
      }    /* if (state ≡ NULL_STATE) */
      goto COMMON_PUNCTUATION;
    }    /* else if (curr_char ≡ '^') */
```

337. '!' (Exclamation mark). [LDF 2006.11.14.]

Log

[LDF 2006.11.14.] Added this section.

```
⟨ Define yylex 306 ⟩ +≡
  else
    if (curr_char ≡ '!') {
      if (state ≡ NULL_STATE) {
#ifdef DEBUG_OUTPUT
        temp_strm ≪ "In␣‘yylex’:␣␣" ≪ "Got␣‘!’." ≪ endl;
        cerr_mutex.lock();
        cerr ≪ temp_strm.str();
        cerr_mutex.unlock();
        scanner_node→log_strm ≪ temp_strm.str();
        temp_strm.str("");
#endif
        next_char = scanner_node→in_strm.peek();
        if (next_char ≡ '=') {
          scanner_node→in_strm.get();
          return NOT_ASSIGN;
        }
        else return NOT;
      }    /* if (state ≡ NULL_STATE) */
      else goto COMMON_PUNCTUATION;
    }    /* else if (curr_char ≡ '!') */
```

338. ':' (Colon). [LDF 2006.11.14.]

Log

[LDF 2006.11.14.] Added this section.

```
⟨ Define yylex 306 ⟩ +≡
  else
    if (curr_char ≡ ':') {
      if (state ≡ NULL_STATE) {
#ifdef DEBUG_OUTPUT
        temp_strm ≪ "In␣‘yylex’:␣␣" ≪ "Got␣‘:’.␣␣Returning␣‘COLON’." ≪ endl;
        cerr_mutex.lock();
        cerr ≪ temp_strm.str();
        cerr_mutex.unlock();
        scanner_node→log_strm ≪ temp_strm.str();
        temp_strm.str("");
#endif
        return COLON;
      }
      goto COMMON_PUNCTUATION;
    }    /* else if (curr_char ≡ ':') */
```

339. ';' (Semi-colon). [LDF 2006.10.31.]

Log

[2006.10.31.] Added this section.

```
⟨ Define yylex 306 ⟩ +≡
  else
    if (curr_char ≡ ';') {
      if (state ≡ NULL_STATE) {
#ifdef DEBUG_OUTPUT
        temp_strm ≪ "In␣'yylex':␣␣" ≪ "Got␣';'.␣␣Returning␣'SEMI_COLON'." ≪ endl;
        cerr_mutex.lock();
        cerr ≪ temp_strm.str();
        cerr_mutex.unlock();
        scanner_node→log_strm ≪ temp_strm.str();
        temp_strm.str("");
#endif
        return SEMI_COLON;
      }
      goto COMMON_PUNCTUATION;
    }     /* else if (curr_char ≡ ';') */
```

340. ',' (Comma). [LDF 2006.12.06.]

Log

[LDF 2006.12.06.] Added this section.

```
⟨ Define yylex 306 ⟩ +≡
  else
    if (curr_char ≡ ',') {
      if (state ≡ NULL_STATE) {
#ifdef DEBUG_OUTPUT
        temp_strm ≪ "In␣'yylex',␣␣" ≪ "Got␣',.␣␣Returning␣'COMMA'." ≪ endl;
        cerr_mutex.lock();
        cerr ≪ temp_strm.str();
        cerr_mutex.unlock();
        scanner_node→log_strm ≪ temp_strm.str();
        temp_strm.str("");
#endif
        return COMMA;
      }
      goto COMMON_PUNCTUATION;
    }     /* else if (curr_char ≡ ',') */
```

341. '%' (Percent). [LDF 2006.12.14.]

Log

[LDF 2006.12.14.] Added this section.

```
⟨ Define yylex 306 ⟩ +≡
  else
    if (curr_char ≡ '%') {
      if (state ≡ NULL_STATE) {
#ifdef DEBUG_OUTPUT
        temp_strm ≪ "In␣`yylex',␣␣" ≪ "Got␣`%'.␣␣Returning␣`PERCENT'." ≪ endl;
        cerr_mutex.lock();
        cerr ≪ temp_strm.str();
        cerr_mutex.unlock();
        scanner_node→log_strm ≪ temp_strm.str();
        temp_strm.str("");
#endif
        return PERCENT;
      }
      goto COMMON_PUNCTUATION;
    }     /* else if (curr_char ≡ '%') */
```

342. '-' (Hyphen). [LDF 2006.12.07.]

Log

[LDF 2006.12.07.] Added this section.

```
⟨ Define yylex 306 ⟩ +≡
  else
    if (curr_char ≡ '-') {
      if (state ≡ NULL_STATE) {
#ifdef DEBUG_OUTPUT
        temp_strm ≪ "In␣`yylex',␣␣" ≪ "Got␣`,'.␣␣Returning␣`HYPHEN'." ≪ endl;
        cerr_mutex.lock();
        cerr ≪ temp_strm.str();
        cerr_mutex.unlock();
        scanner_node→log_strm ≪ temp_strm.str();
        temp_strm.str("");
#endif
        return HYPHEN;
      }
      goto COMMON_PUNCTUATION;
    }     /* else if (curr_char ≡ '-') */
```

343. '.' (Period). [LDF 2006.11.02.]

Please note: ⟨ Common code for punctuation 355 ⟩ cannot be used for period! It must be handled in a special way, because periods are used to distinguish integers and floats. [LDF 2006.11.14.]

Log

[LDF 2006.11.02.] Added this section.

```
⟨ Define yylex 306 ⟩ +≡
  else if (curr_char ≡ '.') {
  if (state ≡ NULL_STATE) {
#ifdef DEBUG_OUTPUT
    temp_strm ≪ "In␣‘yylex’:␣␣" ≪ "Got␣‘.’.␣␣Returning␣‘PERIOD’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    return PERIOD;
  }
  else if (state ≡ COLLECTING_STRING) {
    curr_string += curr_char;
  }
  else if (state ≡ COLLECTING_ID) {
#ifdef DEBUG_OUTPUT
  temp_strm ≪ endl ≪ "***␣Finished␣collecting␣id.␣␣" ≪ "‘curr_id’␣==␣" ≪ curr_id ≪ endl ≪
      "***" ≪ endl;
  cerr_mutex.lock();
  cerr ≪ temp_strm.str();
  cerr_mutex.unlock();
  scanner_node→log_strm ≪ temp_strm.str();
  temp_strm.str("");
#endif
```

344. Look up *curr_id* in *keyword_map* and possibly *id_map*. [LDF 2006.10.19.]

```
⟨ Define yylex 306 ⟩ +≡
  ⟨ Look up curr_id in keyword_map and possibly id_map 357 ⟩
  }    /* else if (state ≡ COLLECTING_ID) */
  else
    if (state ≡ COLLECTING_INTEGER) {
#ifdef DEBUG_OUTPUT
      temp_strm ≪ "***␣Read␣‘.’␣while␣collecting␣integer.␣␣" ≪
          "Changing␣state␣to␣‘COLLECTING_FLOAT’." ≪ endl;
      cerr_mutex.lock();
      cerr ≪ temp_strm.str();
      cerr_mutex.unlock();
      scanner_node→log_strm ≪ temp_strm.str();
      temp_strm.str("");
#endif
      curr_float_str = curr_integer_str + curr_char;
      curr_integer_str = "";
      state = COLLECTING_FLOAT;
      continue;
    }    /* else if (state ≡ COLLECTING_INTEGER) */
    else if (state ≡ COLLECTING_FLOAT) {
#ifdef DEBUG_OUTPUT
      temp_strm ≪ endl ≪ "***␣Finished␣collecting␣float.␣␣" ≪ "‘curr_float_str’␣==␣" ≪
          curr_float_str ≪ "␣␣***" ≪ endl;
      cerr_mutex.lock();
      cerr ≪ temp_strm.str();
      cerr_mutex.unlock();
      scanner_node→log_strm ≪ temp_strm.str();
      temp_strm.str("");
#endif
      value→float_value = atof(curr_float_str.c_str());
      scanner_node→in_strm.unget();
      return FLOAT;
    }    /* else if (state ≡ COLLECTING_FLOAT) */
  }    /* else if (curr_char ≡ '.') */
```

345. `'@'` (At-symbol). [LDF 2006.12.12.]

Log

[LDF 2006.12.12.] Added this section.

```
⟨ Define yylex 306 ⟩ +≡
  else
    if (curr_char ≡ '@') {
      if (state ≡ NULL_STATE) {
#ifdef DEBUG_OUTPUT
        temp_strm ≪ "In␣‘yylex’@␣␣" ≪ "Got␣‘@’.␣␣Returning␣‘AT_SYMBOL’." ≪ endl;
        cerr_mutex.lock();
        cerr ≪ temp_strm.str();
        cerr_mutex.unlock();
        scanner_node→log_strm ≪ temp_strm.str();
        temp_strm.str("");
#endif
        return AT_SYMBOL;
      }
      goto COMMON_PUNCTUATION;
    }     /* else if (curr_char ≡ '@') */
```

346. `'('` (Open parenthesis). [LDF 2006.11.14.]

Log

[LDF 2006.11.14.] Added this section.

```
⟨ Define yylex 306 ⟩ +≡
  else
    if (curr_char ≡ '(') {
      if (state ≡ NULL_STATE) {
#ifdef DEBUG_OUTPUT
        temp_strm ≪ "In␣‘yylex’:␣␣" ≪ "Got␣‘(’.␣␣Returning␣‘OPEN_PARENTHESIS’." ≪ endl;
        cerr_mutex.lock();
        cerr ≪ temp_strm.str();
        cerr_mutex.unlock();
        scanner_node→log_strm ≪ temp_strm.str();
        temp_strm.str("");
#endif
        return OPEN_PARENTHESIS;
      }
      goto COMMON_PUNCTUATION;
    }     /* else if (curr_char ≡ '(') */
```

347. ')' (Close parenthesis). [LDF 2006.11.14.]

Log

[LDF 2006.11.14.] Added this section.

```
⟨ Define yylex 306 ⟩ +≡
  else
    if (curr_char ≡ ')') {
      if (state ≡ NULL_STATE) {
#ifdef DEBUG_OUTPUT
        temp_strm ≪ "In␣'yylex':␣␣" ≪ "Got␣')'.␣␣Returning␣'CLOSE_PARENTHESIS'." ≪ endl;
        cerr_mutex.lock();
        cerr ≪ temp_strm.str();
        cerr_mutex.unlock();
        scanner_node→log_strm ≪ temp_strm.str();
        temp_strm.str("");
#endif
        return CLOSE_PARENTHESIS;
      }
      goto COMMON_PUNCTUATION;
    }    /* else if (curr_char ≡ ')') */
```

348. '[' (Open bracket). [LDF 2006.11.01.]

Log

[LDF 2006.11.01.] Added this section.

```
⟨ Define yylex 306 ⟩ +≡
  else
    if (curr_char ≡ '[') {
      if (state ≡ NULL_STATE) {
#ifdef DEBUG_OUTPUT
        temp_strm ≪ "In␣'yylex':␣␣" ≪ "Got␣'['.␣␣Returning␣'OPEN_BRACKET'." ≪ endl;
        cerr_mutex.lock();
        cerr ≪ temp_strm.str();
        cerr_mutex.unlock();
        scanner_node→log_strm ≪ temp_strm.str();
        temp_strm.str("");
#endif
        return OPEN_BRACKET;
      }
      goto COMMON_PUNCTUATION;
    }    /* else if (curr_char ≡ '[') */
```

349. `']'` (Close bracket). [LDF 2006.11.01.]

Log

[LDF 2006.11.01.] Added this section.

```
⟨ Define yylex 306 ⟩ +≡
  else
    if (curr_char ≡ ']') {
      if (state ≡ NULL_STATE) {
#ifdef DEBUG_OUTPUT
        temp_strm ≪ "In␣'yylex':␣␣" ≪ "Got␣']'.␣␣Returning␣'CLOSE_BRACKET'." ≪ endl;
        cerr_mutex.lock();
        cerr ≪ temp_strm.str();
        cerr_mutex.unlock();
        scanner_node→log_strm ≪ temp_strm.str();
        temp_strm.str("");
#endif
        return CLOSE_BRACKET;
      }
      goto COMMON_PUNCTUATION;
    }     /* else if (curr_char ≡ ']') */
```

350. Space characters. [LDF 2006.10.18.]

```
⟨ Define yylex 306 ⟩ +≡
  else if (isspace(curr_char)) {
```

351. *state* ≡ `NULL_STATE`. Skip whitespace. [LDF 2006.10.18.]

```
⟨ Define yylex 306 ⟩ +≡
  if (state ≡ NULL_STATE) {
    continue;
  }     /* if (state ≡ NULL_STATE) */
  else if (state ≡ COLLECTING_ID) {
#ifdef DEBUG_OUTPUT
  temp_strm ≪ endl ≪ "***␣Finished␣collecting␣keyword.␣␣" ≪ "'curr_id'␣==␣" ≪ curr_id ≪
      endl ≪ "***" ≪ endl;
  cerr_mutex.lock();
  cerr ≪ temp_strm.str();
  cerr_mutex.unlock();
  scanner_node→log_strm ≪ temp_strm.str();
  temp_strm.str("");
#endif
```

352. Look up *curr_id* in *keyword_map* and possibly *id_map*. [LDF 2006.10.19.]

```
⟨ Define yylex 306 ⟩ +≡
  ⟨ Look up curr_id in keyword_map and possibly id_map 357 ⟩
  }     /* else if (state ≡ COLLECTING_ID) */
```

353. *state* ≡ COLLECTING_STRING. [LDF 2006.10.18.]

```
⟨ Define yylex 306 ⟩ +≡
  else
    if (state ≡ COLLECTING_STRING) {
      curr_string += curr_char;
    }
    else if (state ≡ COLLECTING_INTEGER) {
#ifdef DEBUG_OUTPUT
      temp_strm ≪ endl ≪ "***␣Finished␣collecting␣integer.␣␣" ≪ "'curr_integer_str'␣==␣" ≪
          curr_integer_str ≪ "␣␣***" ≪ endl;
      cerr_mutex.lock();
      cerr ≪ temp_strm.str();
      cerr_mutex.unlock();
      scanner_node→log_strm ≪ temp_strm.str();
      temp_strm.str("");
#endif
      value→int_value = atoi(curr_integer_str.c_str());
      scanner_node→in_strm.unget();
      return INTEGER;
    }     /* else if (state ≡ COLLECTING_INTEGER) */
    else if (state ≡ COLLECTING_FLOAT) {
#ifdef DEBUG_OUTPUT
      temp_strm ≪ endl ≪ "***␣Finished␣collecting␣float.␣␣" ≪ "'curr_float_str'␣==␣" ≪
          curr_float_str ≪ "␣␣***" ≪ endl;
      cerr_mutex.lock();
      cerr ≪ temp_strm.str();
      cerr_mutex.unlock();
      scanner_node→log_strm ≪ temp_strm.str();
      temp_strm.str("");
#endif
      value→float_value = atof(curr_float_str.c_str());
      scanner_node→in_strm.unget();
      return FLOAT;
    }     /* else if (state ≡ COLLECTING_FLOAT) */
  }     /* else if (isspace(curr_char)) */
MAIN_LOOP_END: ; }     /* while (End of main loop) */
FINISH:
#ifdef DEBUG_OUTPUT
  temp_strm ≪ endl ≪ "End␣of␣main␣loop." ≪ endl;
  cerr_mutex.lock();
  cerr ≪ temp_strm.str();
  cerr_mutex.unlock();
  scanner_node→log_strm ≪ temp_strm.str();
  temp_strm.str("");
#endif
```

354. Close input file and exit successfully with return value 0. [LDF 2006.10.17.]

```
⟨ Define yylex 306 ⟩ +≡
#ifdef DEBUG_OUTPUT
  temp_strm ≪ "Exiting␣‘yylex’." ≪ endl;
  cerr_mutex.lock( );
  cerr ≪ temp_strm.str( );
  cerr_mutex.unlock( );
  scanner_node→log_strm ≪ temp_strm.str( );
  temp_strm.str("");
#endif
#undef DEBUG_OUTPUT
  return 0;
COMMON_PUNCTUATION: ⟨ Common code for punctuation 355 ⟩
  }    /* End of yylex definition. */
```

355. Common code for punctuation. [LDF 2006.11.14.]

Log

[2006.11.14.] Added this declaration.

```
⟨ Common code for punctuation 355 ⟩ ≡
  if (state ≡ COLLECTING_STRING) {
    curr_string += curr_char;
    goto MAIN_LOOP_END;
  }
  else if (state ≡ COLLECTING_ID) {
#ifdef DEBUG_OUTPUT
  temp_strm ≪ endl ≪ "***␣Finished␣collecting␣keyword.␣␣" ≪ "‘curr_id’␣==␣" ≪ curr_id ≪
      endl ≪ "***" ≪ endl;
  cerr_mutex.lock( );
  cerr ≪ temp_strm.str( );
  cerr_mutex.unlock( );
  scanner_node→log_strm ≪ temp_strm.str( );
  temp_strm.str("");
#endif
```

See also section 356.

This code is cited in section 343.

This code is used in section 354.

356. Look up *curr_id* in *keyword_map* and possibly *id_map*. [LDF 2006.10.19.]

```
⟨ Common code for punctuation 355 ⟩ +≡
  ⟨ Look up curr_id in keyword_map and possibly id_map 357 ⟩
  }     /* else if (state ≡ COLLECTING_ID) */
  else
    if (state ≡ COLLECTING_INTEGER) {
#ifdef DEBUG_OUTPUT
      temp_strm ≪ endl ≪ "***␣Finished␣collecting␣integer.␣␣" ≪ "‘curr_integer_str’␣==␣" ≪
          curr_integer_str ≪ "␣␣***" ≪ endl;
      cerr_mutex.lock();
      cerr ≪ temp_strm.str();
      cerr_mutex.unlock();
      scanner_node→log_strm ≪ temp_strm.str();
      temp_strm.str("");
#endif
      value→int_value = atoi(curr_integer_str.c_str());
      scanner_node→in_strm.unget();
      return INTEGER;
    }     /* else if (state ≡ COLLECTING_INTEGER) */
    else if (state ≡ COLLECTING_FLOAT) {
#ifdef DEBUG_OUTPUT
      temp_strm ≪ endl ≪ "***␣Finished␣collecting␣float.␣␣" ≪ "‘curr_float_str’␣==␣" ≪
          curr_float_str ≪ "␣␣***" ≪ endl;
      cerr_mutex.lock();
      cerr ≪ temp_strm.str();
      cerr_mutex.unlock();
      scanner_node→log_strm ≪ temp_strm.str();
      temp_strm.str("");
#endif
      value→float_value = atof(curr_float_str.c_str());
      scanner_node→in_strm.unget();
      return FLOAT;
    }     /* else if (state ≡ COLLECTING_FLOAT) */
```

357. Look up *curr_id*. Look up *curr_id* in *keyword_map* and possibly *id_map*. [LDF 2006.11.01.]

A consequence of looking up *curr_id* in *keyword_map* first, and then looking it up in *id_map*, is that it's not possible for variables declared by users to shadow keywords. I could change this, if it were desirable. [LDF 2006.11.01.]

Log

[2006.11.01.] Added this section. It's included in *yylex*.

```
⟨ Look up curr_id in keyword_map and possibly id_map 357 ⟩ ≡
  map⟨string, Keyword_Type *⟩::iterator keyword_iter = keyword_map.find(curr_id); if
      (keyword_iter ≡ keyword_map.end()) {
#ifdef DEBUG_OUTPUT
  temp_strm ≪ endl ≪ "In␣‘yylex’:␣␣" ≪ "‘" ≪ curr_id ≪ "’␣not␣found␣in␣‘keyword_map’." ≪
      endl ≪ "Will␣search␣in␣‘scanner_node->id_map’." ≪ endl;
  cerr_mutex.lock();
  cerr ≪ temp_strm.str();
  cerr_mutex.unlock();
```

```
  scanner_node→log_strm ≪ temp_strm.str();
  temp_strm.str("");
#endif
  map⟨string, Id_Type *⟩::iterator id_iter = scanner_node→id_map.find(curr_id);
```

See also sections 358 and 359.

This code is used in sections 314, 324, 327, 332, 344, 352, and 356.

358. *curr_id* not found in *scanner_node→id_map*. [LDF 2006.11.01.]

```
⟨ Look up curr_id in keyword_map and possibly id_map 357 ⟩ +≡
  if (id_iter ≡ scanner_node→id_map.end()) {
#ifdef DEBUG_OUTPUT
    temp_strm ≪ "In␣‘yylex’:␣␣‘" ≪ curr_id ≪ "’␣not␣found␣in␣" ≪
        "‘scanner_node->id_map’.␣␣Returning␣‘VARIABLE_TEXT_SEGMENT’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str();
#endif
    strcpy(value→string_value, curr_id.c_str());
    curr_id = "";
    scanner_node→in_strm.unget();
    return VARIABLE_TEXT_SEGMENT;
  }    /* if (id_iter ≡ scanner_node→id_map.end()) (curr_id not found in scanner_node→id_map) */
```

359. *curr_id* found in *scanner_node→id_map*. [LDF 2006.11.01.]

```
⟨ Look up curr_id in keyword_map and possibly id_map 357 ⟩ +≡
  else      /* id_iter ≠ scanner_node→id_map.end() */
  {
#ifdef DEBUG_OUTPUT
    temp_strm ≪ "In␣‘yylex’:␣␣‘" ≪ curr_id ≪ "’␣found␣in␣" ≪ "‘scanner_node->id_map’." ≪
        endl ≪ "Pushing␣‘Token_Type’␣object␣onto␣‘scanner_node->token_stack’␣" ≪
        "and␣returning␣‘VARIABLE’␣(" ≪ VARIABLE ≪ ")." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str();
#endif
    Token_Type curr_token;
    curr_token.value.pointer_value = scanner_node→id_map[curr_id];
    curr_token.type = scanner_node→id_map[curr_id]→type;
    scanner_node→token_stack.push(curr_token);
    scanner_node→in_strm.unget();
    curr_id = "";
    value→int_value = 0;
    return VARIABLE;
  }     /* else (id_iter ≠ scanner_node→id_map.end()) */
  }     /* if (keyword_iter ≡ keyword_map.end()) (curr_id not found in keyword_map) */
  else      /* keyword_iter ≠ keyword_map.end() (Keyword found) */
  {
#ifdef DEBUG_OUTPUT
    temp_strm ≪ endl ≪ "Keyword␣‘" ≪ curr_id ≪ "’␣found." ≪ endl ≪
        "Exiting␣function␣successfully␣with␣return␣value␣" ≪ keyword_iter→second→value_name ≪
        "␣(" ≪ keyword_iter→second→value ≪ ")" ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    scanner_node→in_strm.unget();
    return keyword_iter→second→value;
  }     /* else (keyword_iter ≠ keyword_map.end()) (Keyword found) */
```

360. Putting the scanner together.

361. This is what's compiled.

```
⟨ Include files 10 ⟩
⟨ scanner.web 249 ⟩
using namespace std;
⟨ Forward declarations 17 ⟩
⟨ Declare namespace Scan_Parse 255 ⟩
⟨ Define Scan_Parse functions 269 ⟩
⟨ Define yylex 306 ⟩
```

362. This is what's written to `scanner.h`.

⟨ `scanner.hh` 362 ⟩ ≡
```
⟨ Preprocessor macro calls 23 ⟩
using namespace std;
⟨ Forward declarations 17 ⟩
⟨ extern declaration of namespace Scan_Parse 256 ⟩
⟨ Declare yylex 305 ⟩
```

363. Dublin Core Parser (`dbcrprsr.w`). [LDF 2007.02.13.]

Log

[LDF 2007.02.13.] Added this file.

⟨ `dbcrprsr.w` 363 ⟩ ≡
```
static char dbcrprsr_id_string[] = "$Id: dbcrprsr.w,v 1.6 2007/02/13 20:08:02 lfinsto1 Exp $";
```
This code is cited in sections 6 and 8.

This code is used in section 379.

364. Include files. [LDF 2007.02.13.]

Log

[LDF 2007.02.13.] Added this section.

⟨ Include files 10 ⟩ +≡
```
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <ios>
#include <iomanip>
#include <iostream>
#include <iosfwd>
#include <fstream>
#include <sstream>
#include <new>
#include <ctype.h>
#include <string.h>
#include "dbcrprsr.hxx"
#include "dbcrscan.hxx"
```

365. Preprocessor macro definitions. [LDF 2007.02.13.]

Log

[LDF 2007.02.13.] Added this section.

⟨ Preprocessor macro definitions 77 ⟩ +≡
```
#define YYPARSE_PARAM parameter
#define YYLEX_PARAM parameter
```

366. Declare xxerror. [LDF 2007.02.13.]

Log

[LDF 2007.02.13.] Added this section.

⟨ Declare Dublin Core parser functions 366 ⟩ ≡
```
void xxerror(const char *s);
```
This code is used in section 379.

367. Bison options. [LDF 2007.02.13.]

Log

[LDF 2007.02.13.] Added this section.

⟨ Bison options 367 ⟩ ≡
```
%debug
%defines
%locations
%name-prefix="xx"
%output="dbcrprsr.cxx"
%pure_parser
%verbose
```
This code is used in section 379.

368. union declaration for `YYSTYPE`. [LDF 2007.02.13.]

Log

[LDF 2007.02.13.] Added this section.

⟨ **union** declaration for `YYSTYPE` 368 ⟩ ≡
```
%union␣{
    int int_value;
    float float_value;
    char string_value[2048];
    void *pointer_value; }
```
See also section 396.

This code is used in sections 379 and 676.

369. Token and type declarations. [LDF 2007.02.13.]

Log

[LDF 2007.02.13.] Added this section.

370. Record. [LDF 2007.02.13.]

Log

[LDF 2007.02.13.] Added this section.

⟨ Token and type declarations 370 ⟩ ≡

```
%token<int_value>␣DATESTAMP_START_TAG
%token<int_value>␣DATESTAMP_END_TAG
%token<int_value>␣HEADER_START_TAG
%token<int_value>␣HEADER_END_TAG
%token<int_value>␣IDENTIFIER_START_TAG
%token<int_value>␣IDENTIFIER_END_TAG
%token<int_value>␣METADATA_START_TAG
%token<int_value>␣METADATA_END_TAG
%token<int_value>␣OAI_DC_DC_START_TAG
%token<int_value>␣OAI_DC_DC_END_TAG
%token<int_value>␣RECORD_START_TAG
%token<int_value>␣RECORD_END_TAG
```

See also sections 371, 399, 400, 401, 402, 403, 404, 405, 406, 407, 408, 409, 410, 411, 412, 415, 416, 417, and 418.

This code is used in sections 379 and 676.

371. Dublin Core Namespace. [LDF 2007.02.13.]

Log

[LDF 2007.02.13.] Added this section.

⟨ Token and type declarations 370 ⟩ +≡

```
%token<int_value>␣DC_CREATOR_START_TAG
%token<int_value>␣DC_CREATOR_END_TAG
%token<int_value>␣DC_CONTRIBUTOR_START_TAG
%token<int_value>␣DC_CONTRIBUTOR_END_TAG
%token<int_value>␣DC_DESCRIPTION_START_TAG
%token<int_value>␣DC_DESCRIPTION_END_TAG
%token<int_value>␣DC_DATE_START_TAG
%token<int_value>␣DC_DATE_END_TAG
%token<int_value>␣DC_IDENTIFIER_START_TAG
%token<int_value>␣DC_IDENTIFIER_END_TAG
%token<int_value>␣DC_LANGUAGE_START_TAG
%token<int_value>␣DC_LANGUAGE_END_TAG
%token<int_value>␣DC_RIGHTS_START_TAG
%token<int_value>␣DC_RIGHTS_END_TAG
%token<int_value>␣DC_SUBJECT_START_TAG
%token<int_value>␣DC_SUBJECT_END_TAG
%token<int_value>␣DC_TYPE_START_TAG
%token<int_value>␣DC_TYPE_END_TAG
%token<int_value>␣END_OAI
```

372. Dublin Core parser rules. [LDF 2007.02.13.]

Log

[LDF 2007.02.13.] Added this section.

373. ⟨program⟩ **(Start symbol).** [LDF 2007.02.13.]

Log

[LDF 2007.02.13.] Added this rule.

⟨ Dublin Core parser rules 373 ⟩ ≡

```
program:␣statement_list␣END_OAI
{
  cerr ≪ "‘program:␣statement_list␣END_OAI’" ≪ endl;
  return 0;
}
;
```

See also sections 375, 376, and 378.

This code is used in section 379.

374. ⟨statement list⟩. [LDF 2007.02.13.]

Log

[LDF 2007.02.13.] Added this section.

375. ⟨statement list⟩ ⟶ `Empty.` [LDF 2007.02.13.]

Log

[LDF 2007.02.13.] Added this rule.

⟨ Dublin Core parser rules 373 ⟩ +≡

```
statement_list:␣/*␣Empty␣␣*/
{
  cerr ≪ "‘statement_list␣EMPTY’" ≪ endl;
}
;
```

376. ⟨statement list⟩ ⟶ ⟨statement list⟩ ⟨statement⟩. [LDF 2007.02.13.]

Log

[LDF 2007.02.13.] Added this rule.

⟨ Dublin Core parser rules 373 ⟩ +≡

```
statement_list:␣statement_list␣statement
{
  cerr ≪ "‘statement_list:␣statement_list␣statement’" ≪ endl;
}
;
```

377. ⟨statement⟩.

Log

[LDF 2007.02.13.] Added this section.

378. ⟨statement list⟩ ⟶ . . .. ⟨statement list⟩ ⟶ RECORD_START_TAG RECORD_END_TAG. [LDF 2007.02.13.]

Log

[LDF 2007.02.13.] Added this rule.

⟨ Dublin Core parser rules 373 ⟩ +≡

```
statement:␣RECORD_START_TAG␣RECORD_END_TAG
{
  cerr ≪ "‘statement:␣RECORD_START_TAG␣RECORD_END_TAG’" ≪ endl;
}
;
```

379. Putting the Dublin Core parser together. [LDF 2007.02.13.]

Log

[LDF 2007.02.13.] Added this section.

⟨ `dbcrprsr.yxx` 379 ⟩ ≡

```
%{
⟨ Include files 10 ⟩
using namespace std;
⟨ Preprocessor macro definitions 77 ⟩
⟨ Declare Dublin Core parser functions 366 ⟩
⟨ dbcrprsr.w 363 ⟩
%}
⟨ union declaration for YYSTYPE 368 ⟩
⟨ Bison options 367 ⟩
⟨ Token and type declarations 370 ⟩
%%
⟨ Dublin Core parser rules 373 ⟩
```

380. Empty C section. [LDF 2007.02.13.]

Log

[LDF 2007.02.13.] Added this section.

```
/* Empty */
```

381. Dublin Core (XML) Scanner.

⟨ dbcrscan.web 381 ⟩ ≡
```
static char id_string[] = "$Id: dbcrscan.web,v 1.12 2007/02/13 20:36:55 lfinsto1 Exp $";
```
This code is cited in sections 6 and 8.
This code is used in section 390.

382. Include files. [LDF 2007.02.13.]

Log

[LDF 2007.02.13.] Added this section.

⟨ Include files 10 ⟩ +≡
```
#include "nonwin.h"
#include "dbcrprsr.hxx"
```

383. Flex Options. [LDF 2007.02.13.]

Log

[LDF 2007.02.13.] Added this section.

⟨ Flex options 383 ⟩ ≡
```
%option bison-bridge
%option bison-locations
%option debug
%option case-insensitive
%option header-file="dbcrscan.hxx"
%option noyywrap
%option prefix="xx"
%option reentrant
%option stack
```
This code is used in section 390.

384. Start conditions for the Dublin Core scanner. [LDF 2007.02.13.]

Log

[LDF 2007.02.13.] Added this section.

⟨ Start conditions for the Dublin Core scanner 384 ⟩ ≡
```
%s RECORD_SC
```

This code is used in section 390.

385. Dublin Core scanner rules. [LDF 2007.02.13.]

Log

[LDF 2007.02.13.] Added this section.

386. ⟨record⟩ start tag. [LDF 2007.02.13.]

Log

[LDF 2007.02.13.] Added this rule.

```
⟨ Dublin Core scanner rules 386 ⟩ ≡
  "<record>"␣{␣
#if 1     /* 0 */
#define DEBUG_COMPILE 1
#else
#undef DEBUG_COMPILE
#endif
#ifdef DEBUG_COMPILE
  cerr ≪ "In␣`xxlex':␣␣" ≪ yytext ≪ endl ≪ "Returning␣`RECORD_START_TAG'." ≪ endl;
#endif
  yylval→int_value = RECORD_START_TAG;
  return RECORD_START_TAG; }
```

See also sections 387, 388, and 389.

This code is used in section 390.

387. ⟨/record⟩ end tag. [LDF 2007.02.13.]

Log

[LDF 2007.02.13.] Added this rule.

```
⟨ Dublin Core scanner rules 386 ⟩ +≡
  "</record>"␣{␣
#if 1     /* 0 */
#define DEBUG_COMPILE 1
#else
#undef DEBUG_COMPILE
#endif
#ifdef DEBUG_COMPILE
  cerr ≪ "In␣`xxlex':␣␣" ≪ yytext ≪ endl ≪ "Returning␣`RECORD_END_TAG'." ≪ endl;
#endif
  yylval→int_value = RECORD_END_TAG;
  return RECORD_END_TAG; }
```

388. End-of-file (`EOF`). [LDF 2007.02.13.]

Log

[LDF 2007.02.13.] Added this rule.

⟨ Dublin Core scanner rules 386 ⟩ +≡

```
<<EOF>>␣{␣
#if 1     /* 0 */
#define DEBUG_COMPILE 1
#else
#undef DEBUG_COMPILE
#endif
#ifdef DEBUG_COMPILE
  cerr << "In␣`xxlex':␣␣EOF" << endl << "Returning␣`END_OAI'." << endl;
#endif     /* DEBUG_COMPILE */
  yylval→int_value = END_OAI;
  return END_OAI; }
```

389. Whitespace. [LDF 2007.02.13.]

Log

[LDF 2007.02.13.] Added this rule.

⟨ Dublin Core scanner rules 386 ⟩ +≡

```
[[:blank:]\n]*␣{␣
#if 1     /* 0 */
#define DEBUG_COMPILE  1
#else
#undef DEBUG_COMPILE
#endif
#ifdef DEBUG_COMPILE
    /* START HERE!! Change Mutex_Type so that it uses the pthreads type. LDF 2007.02.13. */
  cerr_mutex.lock( );
  cerr ≪ "In␣‘xxlex’:␣␣Whitespace" ≪ endl ≪ "Skipping." ≪ endl;
  cerr_mutex.unlock( );
#endif     /* DEBUG_COMPILE */
  }
```

390. Putting the Dublin Core scanner together. [LDF 2007.02.13.]

Log

[LDF 2007.02.13.] Added this section.

⟨ dbcrscan.lxx 390 ⟩ ≡ /* Definitions */

```
  ⟨ Flex options 383 ⟩
  ⟨ Start conditions for the Dublin Core scanner 384 ⟩
  %{
  ⟨ Include files 10 ⟩
  using namespace std;
  ⟨ dbcrscan.web 381 ⟩
  %}
  %%
  ⟨ Dublin Core scanner rules 386 ⟩
```

391. Empty C section. [LDF 2007.02.13.]

Log

[LDF 2007.02.13.] Added this section.

```
/* Empty */
```

392. Parser (`parser.w`). [LDF 2006.10.20.]

Log

[LDF 2006.10.20.] Added this file.

[LDF 2006.10.31.] Renamed this file. Old name: `parser.web`. New name: `parser.w`.

⟨ `parser.w` 392 ⟩ ≡

```
static char parser_id_string[] = "$Id: parser.w,v 1.7 2007/02/13 19:22:07 lfinsto1 Exp $";
```

This code is cited in sections 6, 7, 8, and 677.

This code is used in section 675.

393. Include files. [LDF 2006.10.20.]

⟨ Include files 10 ⟩ +≡

```
#include "localldf.h"
#ifdef NON_WIN_LDF
#include "nonwin.h"
#else
#include "stdafx.h"
#endif
#include "parser.hxx"
#include "dttmtype.h"
#include "scnrtype.h"
#include "scanner.h"
#include "querytyp.h"
#include "dtsrctyp.h"
#include "idtype.h"
```

394. Declare *yylex*. [LDF 2006.10.20.]

⟨ Declare *yylex* 305 ⟩ +≡

```
int yylex(YYSTYPE *lvalp, void *parameter);
```

395. Declare *yyerror*. [LDF 2006.10.20.]

⟨ Declare *yyerror* 395 ⟩ ≡

```
void yyerror(const char *s);
```

This code is used in section 676.

396. union declaration for `YYSTYPE`.

⟨ **union** declaration for `YYSTYPE` 368 ⟩ +≡

```
%union {
    int int_value;
    float float_value;
    char string_value[2048];
```

void ∗*pointer_value*; }

397. Bison declarations. [LDF 2006.10.20.]

⟨ Bison declarations 397 ⟩ ≡

```
%pure_parser
%debug
```

This code is used in section 676.

398. Token and Type Declarations. [LDF 2006.10.20.]

399. Punctuation. [LDF 2006.10.31.]

Log

[2006.10.31.] Added this section.

[LDF 2006.12.07.] Added token declaration for HYPHEN.

[LDF 2006.12.08.] Added token declaration for UNDERLINE.

[LDF 2006.12.12.] Added token declaration for AT_SYMBOL.

[LDF 2006.12.14.] Added token declaration for PERCENT.

⟨ Token and type declarations 370 ⟩ +≡

```
%token␣<int_value>␣AT_SYMBOL
%token␣<int_value>␣COMMA
%token␣<int_value>␣COLON
%token␣<int_value>␣HYPHEN
%token␣<int_value>␣UNDERLINE
%token␣<int_value>␣PERCENT
%token␣<int_value>␣PERIOD
%token␣<int_value>␣SEMI_COLON
%token␣<int_value>␣OPEN_PARENTHESIS
%token␣<int_value>␣CLOSE_PARENTHESIS
%token␣<int_value>␣OPEN_BRACKET
%token␣<int_value>␣CLOSE_BRACKET
```

400. Assignments. [LDF 2006.10.31.]

Log

[2006.10.31.] Added this section with the declarations of `ASSIGN`, `PLUS_ASSIGN`, `MINUS_ASSIGN`, `TIMES_ASSIGN`, and `DIVIDE_ASSIGN`.

[LDF 2006.11.14.] Added the declarations of `AND_ASSIGN`, `OR_ASSIGN`, `XOR_ASSIGN`, and `NOT_ASSIGN`.

[LDF 2006.12.11.] Added the declarations of `LIKE` and `FREETEXT`.

[LDF 2006.12.12.] Added the declaration of `CONTAINS`.

⟨ Token and type declarations 370 ⟩ +≡

```
%token␣<int_value>␣ASSIGN
%token␣<int_value>␣PLUS_ASSIGN
%token␣<int_value>␣MINUS_ASSIGN
%token␣<int_value>␣TIMES_ASSIGN
%token␣<int_value>␣DIVIDE_ASSIGN
%token␣<int_value>␣AND_ASSIGN
%token␣<int_value>␣OR_ASSIGN
%token␣<int_value>␣XOR_ASSIGN
%token␣<int_value>␣NOT_ASSIGN
%token␣<int_value>␣CONTAINS
%token␣<int_value>␣FREETEXT
%token␣<int_value>␣LIKE
```

401. Arithmetical Operations. [LDF 2006.11.14.]

Log

[2006.11.14.] Added this section with the token declarations of `PLUS`, `MINUS`, `TIMES`, and `DIVIDE`.

⟨ Token and type declarations 370 ⟩ +≡

```
%token␣<int_value>␣PLUS
%token␣<int_value>␣MINUS
%token␣<int_value>␣TIMES
%token␣<int_value>␣DIVIDE
```

402. Types with values. [LDF 2006.10.31.]

Log

[2006.10.31.] Added this section.

⟨ Token and type declarations 370 ⟩ +≡

```
%token␣<string_value>␣STRING
%token␣<int_value>␣␣␣␣INTEGER
%token␣<float_value>␣␣FLOAT
```

403. Control. [LDF 2006.10.20.]

⟨ Token and type declarations 370 ⟩ +≡

```
%token␣<int_value>␣START
%token␣<int_value>␣END
%token␣<int_value>␣TERMINATE
```

404. Declarators. [LDF 2006.12.15.]

Log

[LDF 2006.11.16.] Added token declaration for `STRING_DECLARATOR`.

[LDF 2006.12.08.] Added token declaration for `DATASOURCE_DECLARATOR`.

[LDF 2006.12.15.] Added token declaration for `DATETIME_DECLARATOR`.

⟨ Token and type declarations 370 ⟩ +≡

```
%token␣<int_value>␣DATASOURCE_DECLARATOR
%token␣<int_value>␣DATETIME_DECLARATOR
%token␣<int_value>␣STRING_DECLARATOR
%token␣<int_value>␣QUERY_DECLARATOR
```

405. Queries. [LDF 2006.10.20.]

Log

[LDF 2006.10.31.] Added token declarations for `DATABASE` and `SERVER`.

⟨ Token and type declarations 370 ⟩ +≡

```
%token␣<int_value>␣LOCAL
%token␣<int_value>␣REMOTE
%token␣<int_value>␣DATABASE
%token␣<int_value>␣SERVER
```

406. Datasources. [LDF 2006.12.08.]

Log

[2006.12.08.] Added this section with the token declarations for `DBT`, `GBV_GVK`, `TIMMS`, and `DATASOURCE_FILE`. `LOCAL`, `DATABASE`, and `SERVER` have already been defined, as they are used for queries.

⟨ Token and type declarations 370 ⟩ +≡

```
%token␣<int_value>␣DBT
%token␣<int_value>␣GBV_GVK
%token␣<int_value>␣TIMMS
%token␣<int_value>␣DATASOURCE_FILE
```

407. Datetimes. [LDF 2006.12.15.]

Log

[2006.12.15.] Added this section with the token declarations for `DAY`, `MONTH`, `YEAR`, `HOUR`, `MINUTE`, and `SECOND`.
[LDF 2006.12.18.] Added token declaration for `YEAR_RANGE_BEGIN` and `YEAR_RANGE_END`.

⟨ Token and type declarations 370 ⟩ +≡

```
%token␣<int_value>␣␣␣YEAR_RANGE_BEGIN
%token␣<int_value>␣␣␣YEAR_RANGE_END
%token␣<int_value>␣␣␣YEAR
%token␣<int_value>␣␣␣MONTH
%token␣<int_value>␣␣␣DAY
%token␣<int_value>␣␣␣HOUR
%token␣<int_value>␣␣␣MINUTE
%token␣<int_value>␣␣␣SECOND
```

408. Predicates and Control Structures. [LDF 2006.11.14.]

Log

[2006.11.14.] Added this section with the token declarations for `IF`, `ELSE`, `ELIF`, `FI`, `FOR`, `DO`, `WHILE`, `AND`, `OR`, `XOR`, `NOT`, `AND_NOT`, `OR_NOT`, and `XOR_NOT`.

⟨ Token and type declarations 370 ⟩ +≡

```
%token␣<int_value>␣IF
%token␣<int_value>␣ELSE
%token␣<int_value>␣ELIF
%token␣<int_value>␣FI
%token␣<int_value>␣FOR
%token␣<int_value>␣DO
%token␣<int_value>␣WHILE
%token␣<int_value>␣AND
%token␣<int_value>␣OR
%token␣<int_value>␣XOR
%token␣<int_value>␣NOT
%token␣<int_value>␣AND_NOT
%token␣<int_value>␣OR_NOT
%token␣<int_value>␣XOR_NOT
```

409. Database tables (Field designators). [LDF 2006.10.31.]

Log

[2006.10.31.] Added this section with token declarations for AUTHOR, CONTRIBUTOR, TITLE, and SUBJECT.

[LDF 2006.12.05.] Added the token declaration for CREATOR.

[LDF 2006.12.12.] Added the token declaration for MAIN_CANONICAL_TITLE.

[LDF 2006.12.12.] Added token declarations for additional tables from the OAI database (dc_test).

[LDF 2006.12.12.] Added token declarations for additional tables from the PICA database (PICA_DB).

⟨ Token and type declarations 370 ⟩ +≡

```
%token␣<int_value>␣ACCESS_NUMBER
%token␣<int_value>␣AUTHOR
%token␣<int_value>␣BIBLIOGRAPHIC_TYPE
%token␣<int_value>␣CALL_NUMBER
%token␣<int_value>␣CLASSIFICATION
%token␣<int_value>␣COMPANY
%token␣<int_value>␣CONTENT_SUMMARY
%token␣<int_value>␣CONTRIBUTOR
%token␣<int_value>␣CREATOR
%token␣<int_value>␣DATABASE_PROVIDER
%token␣<int_value>␣DESCRIPTION
%token␣<int_value>␣EXEMPLAR_PRODUCTION_NUMBER
%token␣<int_value>␣IDENTIFIER
%token␣<int_value>␣INSTITUTION
%token␣<int_value>␣LANGUAGE
%token␣<int_value>␣MAIN_CANONICAL_TITLE
%token␣<int_value>␣PERMUTATION_PATTERN
%token␣<int_value>␣PERSON
%token␣<int_value>␣PHYSICAL_DESCRIPTION
%token␣<int_value>␣PUBLISHER
%token␣<int_value>␣RECORD
%token␣<int_value>␣REMOTE_ACCESS
%token␣<int_value>␣RIGHTS
%token␣<int_value>␣SOURCE
%token␣<int_value>␣SUBJECT
%token␣<int_value>␣SUPERORDINATE_ENTITIES
%token␣<int_value>␣TITLE
%token␣<int_value>␣TYPE
```

410. Database table columns (field qualifiers). [LDF 2006.12.13.]

Log

[2006.12.13.] Added this section.

⟨ Token and type declarations 370 ⟩ +≡

411. Generic columns. [LDF 2006.12.13.]

Log

[2006.12.13.] Added this section.

⟨ Token and type declarations 370 ⟩ +≡

```
%token␣<int_value>␣ID
```

412. Names. [LDF 2006.12.07.]

Log

[LDF 2006.12.07.] Added this section with token declarations for `GIVEN_NAME`, `PREFIX`, and `SURNAME`.

[LDF 2006.12.07.] Added token declarations for `AUTHOR_GIVEN_NAME`, `AUTHOR_PREFIX`, `AUTHOR_SURNAME`, `CONTRIBUTOR_GIVEN_NAME`, `CONTRIBUTOR_PREFIX`, and `CONTRIBUTOR_SURNAME`.

⟨ Token and type declarations 370 ⟩ +≡

```
%token␣<int_value>␣GIVEN_NAME
%token␣<int_value>␣PREFIX
%token␣<int_value>␣SURNAME
%token␣<int_value>␣AUTHOR_GIVEN_NAME
%token␣<int_value>␣AUTHOR_PREFIX
%token␣<int_value>␣AUTHOR_SURNAME
%token␣<int_value>␣CONTRIBUTOR_GIVEN_NAME
%token␣<int_value>␣CONTRIBUTOR_PREFIX
%token␣<int_value>␣CONTRIBUTOR_SURNAME
```

413. Columns of individual tables. [LDF 2006.12.14.]

Log

[2006.12.14.] Added this section.

414. Pica. [LDF 2006.12.14.]

Log

[2006.12.14.] Added this section.

415. Records. [LDF 2006.12.14.]
ID in "Generic" section. [LDF 2006.12.14.]

Log

[2006.12.14.] Added this section.

⟨ Token and type declarations 370 ⟩ +≡
```
%token␣<int_value>␣ELN_ORIGINAL_ENTRY
%token␣<int_value>␣ELN_MOST_RECENT_CHANGE
%token␣<int_value>␣ELN_STATUS_CHANGE
%token␣<int_value>␣IDENTIFICATION_NUMBER
%token␣<int_value>␣DATE_ORIGINAL_ENTRY
%token␣<int_value>␣DATE_MOST_RECENT_CHANGE
%token␣<int_value>␣DATE_STATUS_CHANGE
%token␣<int_value>␣SOURCE_ID
%token␣<int_value>␣YEAR_APPEARANCE_BEGIN
%token␣<int_value>␣YEAR_APPEARANCE_END
%token␣<int_value>␣YEAR_APPEARANCE_RAK_WB
%token␣<int_value>␣YEAR_APPEARANCE_ORIGINAL
```

416. Variables. [LDF 2006.11.01.]

Log

[2006.11.01.] Added this section.

⟨ Token and type declarations 370 ⟩ +≡
```
%token␣<int_value>␣VARIABLE
%token␣<string_value>␣VARIABLE_TEXT_SEGMENT
```

417. Data Types. [LDF 2006.11.02.]

Log

[2006.11.02.] Added this section with the token declaration of QUERY_TYPE.

[LDF 2006.11.03.] Added the token declaration of NULL_TYPE.

[LDF 2006.11.16.] Added the token declaration of STRING_TYPE.

[LDF 2006.12.08.] Added the token declaration of DATASOURCE_TYPE.

[LDF 2006.12.15.] Added the token declaration of DATETIME_TYPE.

⟨ Token and type declarations 370 ⟩ +≡
```
%token␣<pointer_value>␣NULL_TYPE
%token␣<pointer_value>␣DATASOURCE_TYPE
%token␣<pointer_value>␣DATETIME_TYPE
%token␣<pointer_value>␣QUERY_TYPE
%token␣<pointer_value>␣STRING_TYPE
```

418. Commands. [LDF 2006.11.13.]

Log

[LDF 2006.11.13.] Added this section with the token declarations of `SHOW` and `CLEAR`.

[LDF 2006.11.13.] Added the token declarations of `MESSAGE`, `ERRMESSAGE`, and `PAUSE`.

[LDF 2006.11.16.] Added the token declarations of `TEX`, `SQL`, `OAI`, and `PICA`.

[LDF 2006.11.23.] Added the token declaration of `OUTPUT`.

⟨ Token and type declarations 370 ⟩ +≡

```
%token␣<int_value>␣CLEAR
%token␣<int_value>␣ERRMESSAGE
%token␣<int_value>␣MESSAGE
%token␣<int_value>␣PAUSE
%token␣<int_value>␣SHOW
%token␣<int_value>␣TEX
%token␣<int_value>␣SQL
%token␣<int_value>␣OAI
%token␣<int_value>␣PICA
%token␣<int_value>␣OUTPUT
```

419. Parser rules. [LDF 2006.10.20.]

420. Program. [LDF 2006.10.31.]

421. ⟨program⟩ −→ ⟨statement list⟩ `TERMINATE.` [LDF 2006.10.31.]

⟨ Parser rules 421 ⟩ ≡

```
program:␣statement_list␣TERMINATE
{
  Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
  temp_strm ≪ endl ≪ "Rule␣‘statement_list:␣TERMINATE’." ≪ endl;
  cerr ≪ temp_strm.str( );
  scanner_node→log_strm ≪ temp_strm.str( );
  temp_strm.str("");
  return 0;
}
;
```

See also sections 423, 424, 427, 428, 429, 436, 437, 438, 439, 442, 443, 444, 445, 447, 449, 451, 453, 457, 459, 460, 461, 463, 464, 465, 466, 468, 469, 471, 472, 474, 475, 477, 478, 482, 483, 485, 486, 487, 488, 490, 491, 493, 494, 495, 496, 497, 498, 499, 500, 502, 503, 505, 506, 507, 508, 510, 511, 512, 513, 514, 515, 517, 519, 520, 521, 522, 523, 524, 525, 526, 527, 528, 529, 530, 531, 532, 533, 534, 535, 536, 537, 538, 539, 540, 541, 542, 543, 544, 545, 546, 548, 549, 552, 554, 555, 556, 559, 560, 561, 562, 563, 564, 565, 566, 567, 568, 569, 570, 572, 573, 574, 575, 576, 578, 579, 580, 581, 582, 583, 584, 586, 587, 588, 590, 591, 592, 593, 594, 595, 596, 597, 602, 603, 604, 605, 606, 607, 608, 609, 610, 614, 615, 616, 617, 618, 620, 621, 623, 624, 626, 627, 629, 630, 631, 632, 633, 634, 638, 639, 641, 643, 645, 648, 649, 650, 652, 654, 656, 660, 661, 662, 664, 666, 668, 670, 671, 672, and 673.

This code is used in section 676.

422. Statement list. [LDF 2006.10.31.]

423. ⟨statement list⟩ ⟶ `EMPTY.` [LDF 2006.10.31.]

⟨ Parser rules 421 ⟩ +≡

```
statement_list:␣/*␣empty␣*/ ;
```

424. ⟨statement list⟩ ⟶ ⟨statement list⟩ ⟨statement⟩**.** [LDF 2006.10.31.]

⟨ Parser rules 421 ⟩ +≡

```
statement_list:␣statement_list␣statement ;
```

425. Statement. [LDF 2006.10.31.]

426. ⟨statement⟩ ⟶ ⟨group statement⟩ `SEMI_COLON.` [LDF 2006.10.31.]

Log

[2006.10.31.] Added this rule.

[LDF 2006.11.13.] Commented-out this rule.

⟨ Garbage 426 ⟩ ≡

```
{
  Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
  temp_strm ≪ endl ≪ "Rule␣‘statement:␣group_statement␣SEMI_COLON’." ≪ endl;
  cerr ≪ temp_strm.str();
  scanner_node→log_strm ≪ temp_strm.str();
  temp_strm.str("");
}
;
```

This code is used in section 677.

427. ⟨statement⟩ ⟶ ⟨declaration⟩ `SEMI_COLON.` [LDF 2006.11.01.]

Log

[2006.11.01.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
statement:␣declaration␣SEMI_COLON
{
  Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
  temp_strm ≪ endl ≪ "Rule␣‘statement:␣declaration␣SEMI_COLON’." ≪ endl;
  cerr ≪ temp_strm.str();
  scanner_node→log_strm ≪ temp_strm.str();
  temp_strm.str("");
}
;
```

428. ⟨statement⟩ ⟶ ⟨assignment⟩ `SEMI_COLON`. [LDF 2006.10.31.]

```
⟨ Parser rules 421 ⟩ +≡
  statement: assignment SEMI_COLON
  {
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘statement: assignment SEMI_COLON’." ≪ endl;
    cerr ≪ temp_strm.str( );
    scanner_node→log_strm ≪ temp_strm.str( );
    temp_strm.str("");
  }
  ;
```

429. ⟨statement⟩ ⟶ ⟨command⟩ `SEMI_COLON`. [LDF 2006.11.13.]

Log

[2006.11.13.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  statement: command SEMI_COLON
  {
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘statement: command SEMI_COLON’." ≪ endl;
    cerr ≪ temp_strm.str( );
    scanner_node→log_strm ≪ temp_strm.str( );
    temp_strm.str("");
  }
  ;
```

430. Group Statement (`grpstmnt.w`). [LDF 2006.10.31.]

Log

[2006.10.31.] Added this section.

[LDF 2006.11.13.] Removed the rules from this file and commented-out the type declaration of *group_statement*.

431.

```
⟨ grpstmnt.w 431 ⟩ ≡
  static char grpstmnt_id_string[ ] = "$Id: grpstmnt.w,v 1.4 2007/02/11 16:31:45 lfinsto1 Exp $";
```

This code is cited in sections 7 and 8.

This code is used in section 675.

432.

⟨ Type declarations for non-terminal symbols 432 ⟩ ≡

See also sections 435, 440, 441, 446, 448, 450, 452, 456, 458, 462, 467, 470, 473, 476, 480, 481, 484, 489, 492, 501, 516, 518, 547, 550, 571, 577, 585, 589, 599, 601, 613, 619, 622, 625, 628, 637, 640, 642, 644, 647, 651, 653, 655, 659, 663, 665, 667, and 669.

This code is used in section 676.

433. Declarations (declrtns.w). [LDF 2006.11.01.]

Log

[LDF 2006.11.01.] Added this file.

434.

⟨ declrtns.w 434 ⟩ ≡

```
static char declrtns_id_string[] = "$Id: declrtns.w,v 1.6 2007/02/13 20:37:24 lfinsto1 Exp $";
```

This code is cited in sections 7 and 8.

This code is used in section 675.

435.

⟨ Type declarations for non-terminal symbols 432 ⟩ +≡

```
%type <int_value> declaration
```

436. ⟨declaration⟩ −→ ⟨query declaration⟩. [LDF 2006.11.01.]

⟨ Parser rules 421 ⟩ +≡

```
declaration: query_declaration
{
  Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
  temp_strm ≪ endl ≪ "Rule ‘declaration: query_declaration’." ≪ endl;
  cerr_mutex.lock();
  cerr ≪ temp_strm.str();
  cerr_mutex.unlock();
  scanner_node→log_strm ≪ temp_strm.str();
  temp_strm.str("");
}
;
```

437. ⟨declaration⟩ —→ ⟨string declaration⟩**.** [LDF 2006.11.16.]

Log

[2006.11.16.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
declaration:␣string_declaration
{
  Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
  temp_strm ≪ endl ≪ "Rule␣‘declaration:␣string_declaration’." ≪ endl;
  cerr_mutex.lock();
  cerr ≪ temp_strm.str();
  cerr_mutex.unlock();
  scanner_node→log_strm ≪ temp_strm.str();
  temp_strm.str("");
}
;
```

438. ⟨declaration⟩ —→ ⟨datasource declaration⟩**.** [LDF 2006.12.08.]

Log

[LDF 2006.12.08.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
declaration:␣datasource_declaration
{
  Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
  temp_strm ≪ endl ≪ "Rule␣‘declaration:␣datasource_declaration’." ≪ endl;
  cerr_mutex.lock();
  cerr ≪ temp_strm.str();
  cerr_mutex.unlock();
  scanner_node→log_strm ≪ temp_strm.str();
  temp_strm.str("");
}
;
```

439. ⟨declaration⟩ ⟶ ⟨datetime declaration⟩. [LDF 2006.12.15.]

Log

[LDF 2006.12.15.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
declaration: datetime_declaration
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘declaration: datetime_declaration’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
  }
  ;
```

440. ⟨variable declaration segment list⟩. [LDF 2006.11.01.]

Log

[2006.11.01.] Added this type declaration.

⟨ Type declarations for non-terminal symbols 432 ⟩ +≡

```
%type <string_value> variable_declaration_segment_list
```

441. ⟨subscript placeholder⟩. [LDF 2006.11.01.]

Log

[2006.11.01.] Added this type declaration.

⟨ Type declarations for non-terminal symbols 432 ⟩ +≡

```
%type <int_value> subscript_placeholder
```

442. ⟨variable declaration segment list⟩ ⟶ `VARIABLE_TEXT_SEGMENT.` [LDF 2006.11.01.]

Log

[2006.11.01.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
variable_declaration_segment_list:␣VARIABLE_TEXT_SEGMENT
{
  Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
  strcpy( $$ , $1 );
  temp_strm ≪ endl ≪ "Rule␣‘variable_declaration_segment_list:␣VARIABLE_TEXT_SEGMENT’." ≪
      endl ≪ "‘$$’␣==␣" ≪ $$ ≪ endl;
  cerr_mutex.lock( );
  cerr ≪ temp_strm.str( );
  cerr_mutex.unlock( );
  scanner_node→log_strm ≪ temp_strm.str( );
  temp_strm.str("");
}
;
```

443. ⟨variable declaration segment list⟩ ⟶ **(etc.).** ⟨variable declaration segment list⟩ ⟶ ⟨variable declaration segment list⟩ `VARIABLE_TEXT_SEGMENT.` [LDF 2006.11.01.]

Log

[2006.11.01.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
variable_declaration_segment_list:␣variable_declaration_segment_list␣ VARIABLE_TEXT_SEGMEN
{
  Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
  strcat( $$ , $2 );
  temp_strm ≪ endl ≪ "Rule␣‘variable_declaration_segment_list:␣" ≪
      "variable_declaration_segment_list␣" ≪ "VARIABLE_TEXT_SEGMENT’." ≪ endl ≪
      "‘$$’␣==␣" ≪ $$ ≪ endl;
  cerr_mutex.lock( );
  cerr ≪ temp_strm.str( );
  cerr_mutex.unlock( );
  scanner_node→log_strm ≪ temp_strm.str( );
  temp_strm.str("");
}
;
```

444. ⟨variable declaration segment list⟩ ⟶ **(etc.).** ⟨variable declaration segment list⟩ ⟶ ⟨variable declaration segment list⟩ ⟨subscript placeholder⟩. [LDF 2006.11.01.]

The "Yen" symbol "¥" (`#A5`) is added to the semantic value of the

⟨variable declaration segment list⟩ as a placeholder. This string will be used as the name of a top-level **Id_Type** object in *scanner_node→id_map*. [LDF 2006.11.01.]

Log

[2006.11.01.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
variable_declaration_segment_list: variable_declaration_segment_list subscript_placeholde
{
  Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
  strcat( $$ , "¥");
  temp_strm ≪ endl ≪ "Rule ‘variable_declaration_segment_list: variable_declarati\
      on_segment_list " ≪ "subscript_placeholder’." ≪ endl ≪ "‘$$’ == " ≪ $$ ≪ endl;
  cerr_mutex.lock( );
  cerr ≪ temp_strm.str( );
  cerr_mutex.unlock( );
  scanner_node→log_strm ≪ temp_strm.str( );
  temp_strm.str("");
}
;
```

445. ⟨subscript placeholder⟩ ⟶ `OPEN_BRACKET CLOSE_BRACKET.` [LDF 2006.11.01.]

Log

[2006.11.01.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
subscript_placeholder: OPEN_BRACKET CLOSE_BRACKET
{
  Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
  temp_strm ≪ endl ≪ "Rule ‘subscript_placeholder: OPEN_BRACKET CLOSE_BRACKET’." ≪ endl;
  cerr_mutex.lock( );
  cerr ≪ temp_strm.str( );
  cerr_mutex.unlock( );
  scanner_node→log_strm ≪ temp_strm.str( );
  temp_strm.str("");
}
;
```

446. ⟨query declaration⟩**.** [LDF 2006.11.01.]

Log

[2006.11.01.] Added this type declaration.

⟨ Type declarations for non-terminal symbols 432 ⟩ +≡

```
%type␣<int_value>␣query_declaration
```

447. ⟨query declaration⟩ ⟶ **(etc.).** ⟨query declaration⟩ ⟶ `QUERY_DECLARATOR` ⟨variable declaration segment list⟩. [LDF 2006.11.01.]

Log

[LDF 2006.11.01.] Added this rule.

[LDF 2006.11.02.] No longer setting `$$` to the return value of **Scan_Parse** :: *declare_variable_func*, because I've changed its return value from **int** to **Id_Node**.

⟨ Parser rules 421 ⟩ +≡

```
query_declaration:␣QUERY_DECLARATOR␣variable_declaration_segment_list
{
  Scan_Parse :: declare_variable_func(parameter, QUERY_TYPE, $2);
  $$ = 0;
}
;
```

448. ⟨datasource declaration⟩**.** [LDF 2006.12.08.]

Log

[LDF 2006.12.08.] Added this type declaration.

⟨ Type declarations for non-terminal symbols 432 ⟩ +≡

```
%type␣<int_value>␣datasource_declaration
```

449. ⟨datasource declaration⟩ ⟶ **(etc.).** ⟨datasource declaration⟩ ⟶ `DATASOURCE_DECLARATOR` ⟨variable declaration segment list⟩. [LDF 2006.12.08.]

Log

[LDF 2006.12.08.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
datasource_declaration:␣DATASOURCE_DECLARATOR␣variable_declaration_segment_list
{
  Scan_Parse :: declare_variable_func(parameter, DATASOURCE_TYPE, $2);
  $$ = 0;
}
;
```

450. ⟨string declaration⟩**.** [LDF 2006.11.01.]

Log

[2006.11.01.] Added this type declaration.

⟨ Type declarations for non-terminal symbols 432 ⟩ +≡

```
%type␣<int_value>␣string_declaration
```

451. ⟨string declaration⟩ −→ **(etc.).** ⟨string declaration⟩ −→ `STRING_DECLARATOR` ⟨variable declaration segment list⟩. [LDF 2006.11.01.]

Log

[LDF 2006.11.01.] Added this rule.

[LDF 2006.11.02.] No longer setting `$$` to the return value of **Scan_Parse** :: *declare_variable_func*, because I've changed its return value from **int** to **Id_Node**.

⟨ Parser rules 421 ⟩ +≡

```
string_declaration:␣STRING_DECLARATOR␣variable_declaration_segment_list
{
  Scan_Parse :: declare_variable_func(parameter, STRING_TYPE, $2);
  $$ = 0;
}
;
```

452. ⟨datetime declaration⟩**.** [LDF 2006.12.15.]

Log

[LDF 2006.12.15.] Added this type declaration.

⟨ Type declarations for non-terminal symbols 432 ⟩ +≡

```
%type␣<int_value>␣datetime_declaration
```

453. ⟨datetime declaration⟩ ⟶ **(etc.).** ⟨datetime declaration⟩ ⟶ `DATETIME_DECLARATOR` ⟨variable declaration segment list⟩. [LDF 2006.12.15.]

Log

[LDF 2006.12.15.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
datetime_declaration: DATETIME_DECLARATOR variable_declaration_segment_list
{
  Scan_Parse::declare_variable_func(parameter, DATETIME_TYPE, $2);
  $$ = 0;
}
;
```

454. Variables (`variabls.w`). [LDF 2006.11.02.]

Log

[LDF 2006.11.02.] Added this file.

455.

⟨ `variabls.w` 455 ⟩ ≡

```
static char variabls_id_string[] = "$Id: variabls.w,v 1.5 2007/02/13 20:42:15 lfinsto1 Exp $";
```

This code is cited in sections 7 and 8.

This code is used in section 675.

456. ⟨variable name⟩**.** [LDF 2006.11.02.]

Log

[LDF 2006.11.02.] Added this type declaration.

⟨ Type declarations for non-terminal symbols 432 ⟩ +≡

```
%type <pointer_value> variable_name
```

457. ⟨variable name⟩ ⟶ ⟨variable segment list⟩. [LDF 2006.11.02.]

```
⟨ Parser rules 421 ⟩ +≡
  variable_name:␣variable_segment_list
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
#ifdef DEBUG_OUTPUT
    temp_strm ≪ endl ≪ "Rule␣‘variable_name:␣variable_segment_list’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
#if 0     /* 1 */
    Token_Type curr_token;
    curr_token.type = yychar;
    curr_token.value = yylval;
#endif
    scanner_node→token_stack.push(Token_Type(yychar, yylval));
    $$ = Scan_Parse::variable_func(parameter, $1);
    yyclearin;
#undef DEBUG_OUTPUT
  }
  ;
```

458. ⟨variable segment list⟩. [LDF 2006.11.02.]

Log

[LDF 2006.11.02.] Added this type declaration.

```
⟨ Type declarations for non-terminal symbols 432 ⟩ +≡
  %type␣<string_value>␣variable_segment_list
```

459. ⟨variable segment list⟩ ⟶ `VARIABLE_TEXT_SEGMENT`. [LDF 2006.11.02.]

Log

[LDF 2006.11.02.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
variable_segment_list: VARIABLE_TEXT_SEGMENT
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    scanner_node→float_vector.clear();
#ifdef DEBUG_OUTPUT
    temp_strm ≪ endl ≪ "Rule ‘variable_segment_list: VARIABLE_TEXT_SEGMENT’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    strcpy( $$ , $1 );
#undef DEBUG_OUTPUT
  }
  ;
```

460. ⟨variable segment list⟩ ⟶ **(etc.).** ⟨variable segment list⟩ ⟶ ⟨variable segment list⟩ `VARIABLE_TEXT_SEGMENT`.
[LDF 2006.11.02.]

Log

[LDF 2006.11.02.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
variable_segment_list: variable_segment_list VARIABLE_TEXT_SEGMENT
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘variable_segment_list: variable_segment_list " ≪
        "VARIABLE_TEXT_SEGMENT’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    strcpy( $$ , $1 );
    strcat( $$ , $2 );
#undef DEBUG_OUTPUT
  }
  ;
```

461. ⟨variable segment list⟩ ⟶ **(etc.).** ⟨variable segment list⟩ ⟶ ⟨variable segment list⟩ ⟨subscript⟩. [LDF 2006.11.03.]

Log

[LDF 2006.11.03.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
variable_segment_list:␣variable_segment_list␣subscript
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    scanner_node→float_vector.push_back( $2 );
#ifdef DEBUG_OUTPUT
    temp_strm ≪ endl ≪ "Rule␣‘variable_segment_list:␣variable_segment_list␣" ≪
        "subscript’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    strcat( $$ , "¥");
#undef DEBUG_OUTPUT
  }
  ;
```

462. ⟨subscript⟩**.** [LDF 2006.11.03.]

Log

[LDF 2006.11.03.] Added this type declaration.

⟨ Type declarations for non-terminal symbols 432 ⟩ +≡

```
%type␣<float_value>␣subscript
```

463. ⟨subscript⟩ ⟶ INTEGER. [LDF 2006.11.03.]

Log

[LDF 2006.11.03.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  subscript:␣INTEGER
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘subscript:␣INTEGER’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = static_cast⟨float⟩($1);
#undef DEBUG_OUTPUT
  }
  ;
```

464. ⟨subscript⟩ ⟶ `FLOAT.` [LDF 2006.11.03.]

Log

[LDF 2006.11.03.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  subscript:␣FLOAT
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘subscript:␣FLOAT’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = $1;
#undef DEBUG_OUTPUT
  }
  ;
```

465. ⟨subscript⟩ —→ OPEN_BRACKET INTEGER CLOSE_BRACKET. [LDF 2006.11.03.]

Log

[LDF 2006.11.03.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
subscript: OPEN_BRACKET INTEGER CLOSE_BRACKET
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘subscript: OPEN_BRACKET INTEGER CLOSE_BRACKET’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = static_cast⟨float⟩( $2 );
#undef DEBUG_OUTPUT
  }
  ;
```

466. ⟨subscript⟩ ⟶ OPEN_BRACKET FLOAT CLOSE_BRACKET. [LDF 2006.11.03.]

Log

[LDF 2006.11.03.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
subscript: OPEN_BRACKET FLOAT CLOSE_BRACKET
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘subscript: OPEN_BRACKET FLOAT CLOSE_BRACKET’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = $2;
#undef DEBUG_OUTPUT
  }
  ;
```

467. ⟨query variable⟩. [LDF 2006.11.02.]

Log

[LDF 2006.11.02.] Added this type declaration.

⟨ Type declarations for non-terminal symbols 432 ⟩ +≡

```
%type <pointer_value> query_variable
```

468. ⟨query variable⟩ —→ `VARIABLE QUERY TYPE`. [LDF 2006.11.02.]

The semantic value of the `QUERY_TYPE` token is the **Id_Type** object associated with the name specified by the semantic value of the `VARIABLE` token, or 0, if there is no **Id_Type** object. [LDF 2006.11.02.]

Log

[LDF 2006.11.02.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  query_variable:␣VARIABLE␣QUERY_TYPE
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘query_variable:␣VARIABLE␣QUERY_TYPE’." ≪ endl;
    if ($2 ≡ 0) {
      temp_strm ≪ "The␣semantic␣value␣of␣‘QUERY_TYPE’␣==␣0.␣␣Not␣showing." ≪ endl;
    }
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
    if ($2 ≠ 0) {
      static_cast⟨Id_Node⟩($2)→show("‘QUERY_TYPE’:");
    }
#endif
    $$ = $2;
#undef DEBUG_OUTPUT
  }
  ;
```

469. ⟨query variable⟩ ⟶ ⟨variable name⟩ `QUERY TYPE`. [LDF 2006.11.02.]

Log

[LDF 2006.11.02.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
query_variable: variable_name QUERY_TYPE
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘query_variable: variable_name QUERY_TYPE’." ≪ endl;
    if ($2 ≡ 0) {
      temp_strm ≪ "The semantic value of ‘QUERY_TYPE’ == 0.  Not showing." ≪ endl;
    }
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#if 0     /* 1 */
    if ($2 ≠ 0) {
      static_cast⟨Id_Node⟩($2)→show("‘QUERY_TYPE’:");
    }
#endif
#endif
    $$ = $2;
#undef DEBUG_OUTPUT
  }
  ;
```

470. ⟨datasource variable⟩. [LDF 2006.12.08.]

Log

[LDF 2006.12.08.] Added this type declaration.

⟨ Type declarations for non-terminal symbols 432 ⟩ +≡

```
%type <pointer_value> datasource_variable
```

471. ⟨datasource variable⟩ —→ `VARIABLE DATASOURCE TYPE.` [LDF 2006.12.08.]

The semantic value of the `DATASOURCE_TYPE` token is the **Id_Type** object associated with the name specified by the semantic value of the `VARIABLE` token, or 0, if there is no **Id_Type** object. [LDF 2006.12.08.]

Log

[LDF 2006.12.08.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  datasource_variable: VARIABLE DATASOURCE_TYPE
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘datasource_variable: VARIABLE DATASOURCE_TYPE’." ≪ endl;
    if ($2 ≡ 0) {
      temp_strm ≪ "The semantic value of ‘DATASOURCE_TYPE’ == 0.  Not showing." ≪ endl;
    }
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
    if ($2 ≠ 0) {
      static_cast⟨Id_Node⟩($2)→show("‘DATASOURCE_TYPE’:");
    }
#endif
    $$ = $2;
#undef DEBUG_OUTPUT
  }
  ;
```

472. ⟨datasource variable⟩ ⟶ ⟨variable name⟩ `DATASOURCE TYPE.` [LDF 2006.12.08.]

Log

[LDF 2006.12.08.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
datasource_variable: variable_name DATASOURCE_TYPE
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘datasource_variable: variable_name DATASOURCE_TYPE’." ≪ endl;
    if ($2 ≡ 0) {
      temp_strm ≪ "The semantic value of ‘DATASOURCE_TYPE’ == 0.  Not showing." ≪ endl;
    }
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
    if ($2 ≠ 0) {
      static_cast⟨Id_Node⟩($2)→show("‘DATASOURCE_TYPE’:");
    }
#endif
    $$ = $2;
#undef DEBUG_OUTPUT
  }
  ;
```

473. ⟨string variable⟩**.** [LDF 2006.11.16.]

Log

[LDF 2006.11.16.] Added this type declaration.

⟨ Type declarations for non-terminal symbols 432 ⟩ +≡

```
%type <pointer_value> string_variable
```

474. ⟨string variable⟩ ⟶ `VARIABLE STRING TYPE`. [LDF 2006.11.16.]

The semantic value of the `STRING_TYPE` token is the **Id_Type** object associated with the name specified by the semantic value of the `VARIABLE` token, or 0, if there is no **Id_Type** object. [LDF 2006.11.16.]

Log

[LDF 2006.11.16.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  string_variable: VARIABLE STRING_TYPE
  {
#if 0     /* 1 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘string_variable: VARIABLE STRING_TYPE’." ≪ endl;
    if ($2 ≡ 0) {
      temp_strm ≪ "The semantic value of ‘STRING_TYPE’ == 0.  Not showing." ≪ endl;
    }
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
    if ($2 ≠ 0) {
      static_cast⟨Id_Node⟩($2)→show("‘STRING_TYPE’:");
    }
#endif
    $$ = $2;
#undef DEBUG_OUTPUT
  }
  ;
```

475. ⟨string variable⟩ ⟶ ⟨variable name⟩ `STRING TYPE.` [LDF 2006.11.16.]

Log

[LDF 2006.11.16.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  string_variable: variable_name STRING_TYPE
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘string_variable: variable_name STRING_TYPE’." ≪ endl;
    if ($2 ≡ 0) {
      temp_strm ≪ "The semantic value of ‘STRING_TYPE’ == 0.  Not showing." ≪ endl;
    }
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
    if ($2 ≠ 0) {
      static_cast⟨Id_Node⟩($2)→show("‘STRING_TYPE’:");
    }
#endif
    $$ = $2;
#undef DEBUG_OUTPUT
  }
  ;
```

476. ⟨datetime variable⟩. [LDF 2006.12.15.]

Log

[LDF 2006.12.15.] Added this type declaration.

```
⟨ Type declarations for non-terminal symbols 432 ⟩ +≡
  %type <pointer_value> datetime_variable
```

477. ⟨datetime variable⟩ −→ `VARIABLE DATETIME TYPE`. [LDF 2006.11.02.]

The semantic value of the `DATETIME_TYPE` token is the **Id_Type** object associated with the name specified by the semantic value of the `VARIABLE` token, or 0, if there is no **Id_Type** object. [LDF 2006.12.15.]

Log

[LDF 2006.12.15.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
  datetime_variable: VARIABLE DATETIME_TYPE
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘datetime_variable: VARIABLE DATETIME_TYPE’." ≪ endl;
#endif
    $$ = $2;
#undef DEBUG_OUTPUT
  }
  ;
```

478. ⟨datetime variable⟩ ⟶ ⟨variable name⟩ `DATETIME TYPE.` [LDF 2006.12.15.]

Log

[LDF 2006.12.15.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  datetime_variable: variable_name DATETIME_TYPE
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘datetime_variable: variable_name DATETIME_TYPE’." ≪ endl;
    if ($2 ≡ 0) {
      temp_strm ≪ "The semantic value of ‘DATETIME_TYPE’ == 0.  Not showing." ≪ endl;
    }
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#if 0     /* 1 */
    if ($2 ≠ 0) {
      static_cast⟨Id_Node⟩($2)→show("‘DATETIME_TYPE’:");
    }
#endif
#endif
    $$ = $2;
#undef DEBUG_OUTPUT
  }
  ;
```

479. Assignment (`assign.w`). [LDF 2006.10.31.]

Log

[2006.10.31.] Added this section.

Renamed this file. Old name: `passign.w`. New name: `assign.w`.

```
⟨ assign.w 479 ⟩ ≡
  static char assign_id_string[] = "$Id: assign.w,v 1.7 2007/02/13 20:34:10 lfinsto1 Exp $";
```

This code is cited in sections 7 and 8.

This code is used in section 675.

480.

⟨ Type declarations for non-terminal symbols 432 ⟩ +≡

```
%type␣<int_value>␣assignment
```

481. ⟨negation optional⟩**.** [LDF 2006.11.14.]

Log

[2006.11.14.] Added this section.

⟨ Type declarations for non-terminal symbols 432 ⟩ +≡

```
%type␣<int_value>␣negation_optional
```

482. ⟨negation optional⟩ ⟶ `EMPTY`**.** [LDF 2006.11.14.]

Log

[2006.11.14.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
negation_optional:␣/*␣Empty␣␣*/
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘negation_optional:␣/*␣Empty␣␣*/’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = 0;
  }
  ;
```

483. ⟨negation optional⟩ ⟶ `NOT`. [LDF 2006.11.14.]

Log

[2006.11.14.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
negation_optional: NOT
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘negation_optional: NOT’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = 1;
  }
  ;
```

484. ⟨match term optional⟩. [LDF 2006.12.11.]

Log

[LDF 2006.12.11.] Added this section.

⟨ Type declarations for non-terminal symbols 432 ⟩ +≡

```
%type <int_value> match_term_optional
```

485. ⟨match term optional⟩ ⟶ `EMPTY.` [LDF 2006.12.11.]

Log

[LDF 2006.12.11.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  match_term_optional:␣/*␣Empty␣␣*/
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘match_term_optional:␣/*␣Empty␣␣*/’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = Query_Type::QUERY_TYPE_NULL_TYPE;
  }
  ;
```

486. ⟨match term optional⟩ ⟶ `CONTAINS`. [LDF 2006.12.12.]

Log

[LDF 2006.12.12.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
match_term_optional: CONTAINS
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘match_term_optional: CONTAINS’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = Query_Type::CONTAINS_VALUE;
  }
  ;
```

487. ⟨match term optional⟩ ⟶ FREETEXT. [LDF 2006.12.11.]

Log

[LDF 2006.12.11.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  match_term_optional: FREETEXT
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘match_term_optional: FREETEXT’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = Query_Type::FREETEXT_VALUE;
  }
  ;
```

488. ⟨match term optional⟩ ⟶ `LIKE`. [LDF 2006.12.11.]

Log

[LDF 2006.12.11.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
match_term_optional: LIKE
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘match_term_optional: LIKE’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = Query_Type::LIKE_VALUE;
  }
  ;
```

489. ⟨assign or plus-assign⟩. [LDF 2006.11.13.]

Log

[2006.11.13.] Added this type declaration.

⟨ Type declarations for non-terminal symbols 432 ⟩ +≡

```
%type <int_value> assign_or_plus_assign
```

490. ⟨assign or plus-assign⟩ ⟶ ASSIGN. [LDF 2006.11.13.]

Log

[2006.11.13.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
assign_or_plus_assign:␣ASSIGN
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘assign_or_plus_assign:␣ASSIGN’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = ASSIGN;
  }
  ;
```

491. ⟨assign or plus-assign⟩ ⟶ `PLUS_ASSIGN`. [LDF 2006.11.13.]

Log

[2006.11.13.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
assign_or_plus_assign: PLUS_ASSIGN
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘assign_or_plus_assign: PLUS_ASSIGN’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = PLUS_ASSIGN;
  }
  ;
```

492. ⟨assignment operator⟩. [LDF 2006.11.14.]

Log

[LDF 2006.11.14.] Added this type declaration.

⟨ Type declarations for non-terminal symbols 432 ⟩ +≡

```
%type <int_value> assignment_operator
```

493. ⟨assignment operator⟩ ⟶ `ASSIGN`. [LDF 2006.11.14.]

Log

[LDF 2006.11.14.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  assignment_operator:␣ASSIGN
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘assignment_operator:␣ASSIGN’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = ASSIGN;
  }
  ;
```

494. ⟨assignment operator⟩ ⟶ `PLUS_ASSIGN`. [LDF 2006.11.14.]

Log

[LDF 2006.11.14.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  assignment_operator:␣PLUS_ASSIGN
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘assignment_operator:␣PLUS_ASSIGN’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = PLUS_ASSIGN;
  }
  ;
```

495. ⟨assignment operator⟩ ⟶ OR_ASSIGN. [LDF 2006.11.14.]

Log

[LDF 2006.11.14.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
assignment_operator: OR_ASSIGN
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘assignment_operator: OR_ASSIGN’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = OR_ASSIGN;
  }
  ;
```

496. ⟨assignment operator⟩ ⟶ `XOR_ASSIGN`. [LDF 2006.11.14.]

Log

[LDF 2006.11.14.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  assignment_operator:␣XOR_ASSIGN
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘assignment_operator:␣XOR_ASSIGN’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = XOR_ASSIGN;
  }
  ;
```

497. ⟨assignment operator⟩ ⟶ NOT_ASSIGN. [LDF 2006.11.14.]

Log

[LDF 2006.11.14.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  assignment_operator: NOT_ASSIGN
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘assignment_operator: NOT_ASSIGN’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = NOT_ASSIGN;
  }
  ;
```

498. ⟨assignment⟩ ⟶ ⟨query assignment⟩. [LDF 2006.11.02.]

```
⟨ Parser rules 421 ⟩ +≡
  assignment: query_assignment
  {
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘assignment: query_assignment’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
  }
  ;
```

499. ⟨assignment⟩ ⟶ ⟨datasource assignment⟩. [LDF 2006.12.08.]

Log

[2006.12.08.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
assignment:␣datasource_assignment
{
  Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
  temp_strm ≪ endl ≪ "Rule␣‘assignment:␣datasource_assignment’." ≪ endl;
  cerr_mutex.lock();
  cerr ≪ temp_strm.str();
  cerr_mutex.unlock();
  scanner_node→log_strm ≪ temp_strm.str();
  temp_strm.str("");
}
;
```

500. ⟨assignment⟩ ⟶ ⟨string assignment⟩. [LDF 2006.11.16.]

Log

[2006.11.16.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
assignment:␣string_assignment
{
  Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
  temp_strm ≪ endl ≪ "Rule␣‘assignment:␣string_assignment’." ≪ endl;
  cerr_mutex.lock();
  cerr ≪ temp_strm.str();
  cerr_mutex.unlock();
  scanner_node→log_strm ≪ temp_strm.str();
  temp_strm.str("");
}
;
```

501. ⟨query assignment⟩.

⟨ Type declarations for non-terminal symbols 432 ⟩ +≡

```
%type␣<pointer_value>␣query_assignment
```

502. ⟨query assignment⟩ ⟶ ⟨query variable⟩ ASSIGN ⟨query expression⟩. [LDF 2006.11.17.]

Log

[2006.11.17.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
query_assignment:␣query_variable␣ASSIGN␣query_expression
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘query_assignment:␣query_variable␣ASSIGN␣query_expression’." ≪
        endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    Id_Node id_node = static_cast⟨Id_Node⟩($1);
    if (¬id_node) $$ = 0;
    else {
      if (id_node→value ≠ 0) delete static_cast⟨Query_Node⟩(id_node→value);
      id_node→value = $3;
      $$ = $3;
    }
#undef DEBUG_OUTPUT
  }
  ;
```

503. ⟨assignment⟩ ⟶ ⟨datetime assignment⟩**.** [LDF 2006.12.15.]

Log

[LDF 2006.12.15.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
assignment: datetime_assignment
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘assignment: datetime_assignment’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
  }
  ;
```

504. Targets. [LDF 2006.11.13.]

Log

[2006.11.13.] Added this section.

505. ⟨query assignment⟩ −→ **(etc.).** ⟨query assignment⟩ −→ ⟨query variable⟩ ⟨assign or plus-assign⟩ `LOCAL DATABASE`. [LDF 2006.11.02.]

Log

[LDF 2006.11.13.] Changed this rule from ⟨query assignment⟩ −→ ⟨query variable⟩ `ASSIGN LOCAL` to ⟨query assignment⟩ −→ ⟨query variable⟩ `ASSIGN LOCAL DATABASE`.

[LDF 2006.11.13.] Changed `ASSIGN` to ⟨assign or plus-assign⟩.

⟨ Parser rules 421 ⟩ +≡

```
query_assignment: query_variable assign_or_plus_assign LOCAL DATABASE
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘query_assignment: query_variable assign_or_plus_assig\
      n LOCAL DATABASE’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = query_assignment_func_0(parameter, $1, $2, LOCAL, DATABASE, 0, 0);
#undef DEBUG_OUTPUT
  }
  ;
```

506. ⟨query assignment⟩ —→ **(etc.).** ⟨query assignment⟩ —→ ⟨query variable⟩ ⟨assign or plus-assign⟩ `LOCAL SERVER`. [LDF 2006.11.13.]

Log

[2006.11.13.] Added this rule.

[LDF 2006.11.13.] Changed `ASSIGN` to ⟨assign or plus-assign⟩.

⟨ Parser rules 421 ⟩ +≡

```
query_assignment:␣query_variable␣assign_or_plus_assign␣LOCAL␣SERVER
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘query_assignment:␣query_variable␣assign_or_plus_assig\
        n␣LOCAL␣SERVER’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = query_assignment_func_0(parameter, $1, $2, LOCAL, SERVER, 0, 0);
#undef DEBUG_OUTPUT
  }
  ;
```

507. ⟨query assignment⟩ —→ **(etc.).** ⟨query assignment⟩ —→ ⟨query variable⟩ ⟨assign or plus-assign⟩ `REMOTE DATABASE`. [LDF 2006.11.13.]

Log

[2006.11.13.] Added this rule.

[LDF 2006.11.13.] Changed `ASSIGN` to ⟨assign or plus-assign⟩.

⟨ Parser rules 421 ⟩ +≡

```
query_assignment:␣query_variable␣assign_or_plus_assign␣REMOTE␣DATABASE
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘query_assignment:␣query_variable␣assign_or_plus_assig\
        n␣REMOTE␣DATABASE’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = query_assignment_func_0(parameter, $1, ASSIGN, REMOTE, DATABASE, 0, 0);
#undef DEBUG_OUTPUT
  }
  ;
```

508. ⟨query assignment⟩ —→ **(etc.).** ⟨query assignment⟩ —→ ⟨query variable⟩ ⟨assign or plus-assign⟩ `REMOTE SERVER`. [LDF 2006.11.13.]

Log

[2006.11.13.] Added this rule.

[LDF 2006.11.13.] Changed `ASSIGN` to ⟨assign or plus-assign⟩.

⟨ Parser rules 421 ⟩ +≡

```
query_assignment:␣query_variable␣assign_or_plus_assign␣REMOTE␣SERVER
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘query_assignment:␣query_variable␣assign_or_plus_assig\
        n␣REMOTE␣SERVER’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = query_assignment_func_0(parameter, $1, $2, REMOTE, SERVER, 0, 0);
#undef DEBUG_OUTPUT
  }
  ;
```

509. Fields. [LDF 2006.11.13.]

Log

[2006.11.13.] Added this section.

510. ⟨query assignment⟩ ⟶ **(etc.).** ⟨query assignment⟩ ⟶ ⟨query variable⟩ `COLON` ⟨field specifier⟩ ⟨assignment operator⟩ ⟨negation optional⟩ ⟨match term optional⟩ ⟨query expression⟩. [LDF 2006.11.15.]

Log

[LDF 2006.11.15.] Added this rule.

[LDF 2006.11.21.] Now setting *curr_id_node→value→id_node* and *curr_id_node→value→name*.

[LDF 2006.12.19.] Removed code from this rule. Now calling **Scan_Parse** :: *query_assignment_func_1* .

⟨ Parser rules 421 ⟩ +≡

```
query_assignment:␣query_variable␣COLON␣field_specifier␣ assignment_operator␣negation_optional␣mat
#if 1    /* 0 */
#define DEBUG_OUTPUT
#else
# # undef DEBUG_OUTPUT
#endif
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
#ifdef DEBUG_OUTPUT
    temp_strm ≪ endl ≪ "Rule␣‘query_assignment:␣query_variable␣COLON␣field_specifier␣" ≪
        "assignment_operator␣negation_optional␣match_term_optional␣" ≪
        "query_expression’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    Id_Node curr_id_node = static_cast⟨Id_Node⟩($1);
    int status = query_assignment_func_1(scanner_node, curr_id_node, $3, $4, $5, $6, $7,
        QUERY_TYPE);
    $$ = static_cast⟨void *⟩(curr_id_node);
```

511. If **Scan_Parse**::*query_assignment_func_1* fails, *curr_id_node* will be 0 anyway, so it's not really necessary to check the value of *status*. It's only done for the sake of debugging output, which is conditionally compiled. [LDF 2006.12.19.]

```
⟨ Parser rules 421 ⟩ +≡
#ifdef DEBUG_OUTPUT
  if (status ≠ 0) {
    temp_strm ≪ "ERROR!␣␣In␣‘yyparse’," ≪ endl ≪
        "rule␣‘query_assignment:␣query_variable␣COLON␣field_specifier␣" ≪
        endl ≪ "assignment_operator␣negation_optional␣match_term_optional␣" ≪
        "query_expression’:" ≪ endl ≪ "‘Scan_Parse::query_assignment_func_1’␣f\
        ailed,␣returning␣" ≪ status ≪ "." ≪ endl ≪ "Setting␣‘query_assignment’␣to␣0." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
    $$ = 0;
  }    /* status ≠ 0 */
#endif
```

512.

```
⟨ Parser rules 421 ⟩ +≡
#ifdef DEBUG_OUTPUT
  temp_strm ≪ endl ≪ "Exiting␣rule␣‘query_assignment:␣query_variable␣COLON␣field_\
      specifier␣" ≪ "assignment_operator␣negation_optional␣match_term_optional␣" ≪
      "query_expression’." ≪ endl;
  cerr_mutex.lock();
  cerr ≪ temp_strm.str();
  cerr_mutex.unlock();
  scanner_node→log_strm ≪ temp_strm.str();
  temp_strm.str("");
#endif
#undef DEBUG_OUTPUT
  } ;
```

513. ⟨query assignment⟩ ⟶ **(etc.).** ⟨query assignment⟩ ⟶ ⟨query variable⟩ `COLON` ⟨field specifier⟩ ⟨assignment operator⟩ ⟨negation optional⟩ ⟨match term optional⟩ ⟨query expression⟩. [LDF 2006.12.19.]

Log

[LDF 2006.12.19.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
query_assignment:␣query_variable␣COLON␣field_specifier␣ assignment_operator␣negation_optional␣mat
#if 1    /* 0 */
#define DEBUG_OUTPUT
#else
# # undef DEBUG_OUTPUT
#endif
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
#ifdef DEBUG_OUTPUT
    temp_strm ≪ endl ≪ "Rule␣‘query_assignment:␣query_variable␣COLON␣field_specifier␣" ≪
        "assignment_operator␣negation_optional␣match_term_optional␣" ≪
        "datetime_expression’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    Id_Node curr_id_node = static_cast⟨Id_Node⟩($1);
    int status = query_assignment_func_1(scanner_node, curr_id_node, $3, $4, $5, $6, $7,
        DATETIME_TYPE);
    $$ = static_cast⟨void *⟩(curr_id_node);
```

514. If **Scan_Parse**::*query_assignment_func_1* fails, *curr_id_node* will be 0 anyway, so it's not really necessary to check the value of *status*. It's only done for the sake of debugging output, which is conditionally compiled. [LDF 2006.12.19.]

⟨ Parser rules 421 ⟩ +≡

```
#ifdef DEBUG_OUTPUT
  if (status ≠ 0) {
    temp_strm ≪ "ERROR!␣␣In␣‘yyparse’," ≪ endl ≪
        "rule␣‘query_assignment:␣query_variable␣COLON␣field_specifier␣" ≪
        endl ≪ "assignment_operator␣negation_optional␣match_term_optional␣" ≪
        "datetime_expression’:" ≪ endl ≪ "‘Scan_Parse::query_assignment_func_1’␣f\
        ailed,␣returning␣" ≪ status ≪ "." ≪ endl ≪ "Setting␣‘query_assignment’␣to␣0." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
    $$ = 0;
  }    /* status ≠ 0 */
#endif
```

515.

```
⟨ Parser rules 421 ⟩ +≡
#ifdef DEBUG_OUTPUT
  temp_strm ≪ endl ≪ "Exiting␣rule␣‘query_assignment:␣query_variable␣COLON␣field_\
      specifier␣" ≪ "assignment_operator␣negation_optional␣match_term_optional␣" ≪
      "datetime_expression’." ≪ endl;
  cerr_mutex.lock( );
  cerr ≪ temp_strm.str( );
  cerr_mutex.unlock( );
  scanner_node→log_strm ≪ temp_strm.str( );
  temp_strm.str("");
#endif
#undef DEBUG_OUTPUT
  } ;
```

516. ⟨field specifier⟩**.** [LDF 2006.12.13.]

Log

[LDF 2006.12.13.] Added this type declaration.

```
⟨ Type declarations for non-terminal symbols 432 ⟩ +≡
  %type␣<pointer_value>␣field_specifier
```

517. ⟨field specifier⟩ —→ ⟨field designator⟩ ⟨field qualifier list⟩**.** [LDF 2006.12.12.]

Log

[LDF 2006.12.12.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  field_specifier:␣field_designator␣field_qualifier_list {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
      Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
      temp_strm ≪ endl ≪ "Rule␣‘field_specifier:␣field_designator␣field_qualifier_list’." ≪
          endl;
      cerr_mutex.lock( );
      cerr ≪ temp_strm.str( );
      cerr_mutex.unlock( );
      scanner_node→log_strm ≪ temp_strm.str( );
      temp_strm.str("");
#endif
      deque < int > *d = ( $2 ≡ 0) ? new deque < int > : static_cast ⟨ deque < int >*> ( $2 );
      d→push_front( $1 );
      $$ = static_cast⟨void *⟩(d); } ;
```

518. ⟨field designator⟩**.** [LDF 2006.11.14.]

Log

[2006.11.14.] Added this type declaration.

⟨ Type declarations for non-terminal symbols 432 ⟩ +≡

```
%type␣<int_value>␣field_designator
```

519. ⟨field designator⟩ −→ `ACCESS_NUMBER`**.** [LDF 2006.12.12.]

Log

[LDF 2006.12.12.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
field_designator:␣ACCESS_NUMBER
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘field_designator:␣ACCESS_NUMBER’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = ACCESS_NUMBER;
  }
  ;
```

520. ⟨field designator⟩ ⟶ AUTHOR. [LDF 2006.11.14.]

Log

[2006.11.14.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  field_designator:␣AUTHOR
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘field_designator:␣AUTHOR’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = AUTHOR;
  }
  ;
```

521. ⟨field designator⟩ —→ BIBLIOGRAPHIC_TYPE. [LDF 2006.12.12.]

Log

[LDF 2006.12.12.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  field_designator:␣BIBLIOGRAPHIC_TYPE
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘field_designator:␣BIBLIOGRAPHIC_TYPE’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = BIBLIOGRAPHIC_TYPE;
  }
  ;
```

522. ⟨field designator⟩ ⟶ CALL_NUMBER. [LDF 2006.12.12.]

Log

[LDF 2006.12.12.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  field_designator:␣CALL_NUMBER
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘field_designator:␣CALL_NUMBER’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = CALL_NUMBER;
  }
  ;
```

523. ⟨field designator⟩ —→ CLASSIFICATION. [LDF 2006.12.12.]

Log

[LDF 2006.12.12.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  field_designator:␣CLASSIFICATION
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘field_designator:␣CLASSIFICATION’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = CLASSIFICATION;
  }
  ;
```

524. ⟨field designator⟩ ⟶ COMPANY. [LDF 2006.12.12.]

Log

[LDF 2006.12.12.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
field_designator:␣COMPANY
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘field_designator:␣COMPANY’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = COMPANY;
  }
  ;
```

525. ⟨field designator⟩ —→ CONTENT_SUMMARY. [LDF 2006.12.12.]

Log

[LDF 2006.12.12.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  field_designator:␣CONTENT_SUMMARY
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘field_designator:␣CONTENT_SUMMARY’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = CONTENT_SUMMARY;
  }
  ;
```

526. ⟨field designator⟩ ⟶ `CONTRIBUTOR`. [LDF 2006.11.14.]

Log

[2006.11.14.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
field_designator:␣CONTRIBUTOR
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘field_designator:␣CONTRIBUTOR’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = CONTRIBUTOR;
  }
  ;
```

527. ⟨field designator⟩ —→ `CREATOR`. [LDF 2006.12.05.]

Log

[LDF 2006.12.05.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  field_designator:␣CREATOR
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘field_designator:␣CREATOR’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = CREATOR;
  }
  ;
```

528. ⟨field designator⟩ ⟶ DATABASE_PROVIDER. [LDF 2006.12.12.]

Log

[LDF 2006.12.12.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
field_designator: DATABASE_PROVIDER
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘field_designator: DATABASE_PROVIDER’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = DATABASE_PROVIDER;
  }
  ;
```

529. ⟨field designator⟩ —→ DESCRIPTION. [LDF 2006.12.12.]

Log

[LDF 2006.12.12.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  field_designator:␣DESCRIPTION
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘field_designator:␣DESCRIPTION’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = DESCRIPTION;
  }
  ;
```

530. ⟨field designator⟩ ⟶ EXEMPLAR_PRODUCTION_NUMBER. [LDF 2006.12.12.]

Log

[LDF 2006.12.12.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
field_designator: EXEMPLAR_PRODUCTION_NUMBER
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘field_designator: EXEMPLAR_PRODUCTION_NUMBER’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = EXEMPLAR_PRODUCTION_NUMBER;
  }
  ;
```

531. ⟨field designator⟩ —→ IDENTIFIER. [LDF 2006.12.12.]

Log

[LDF 2006.12.12.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  field_designator:␣IDENTIFIER
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘field_designator:␣IDENTIFIER’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = IDENTIFIER;
  }
  ;
```

532. ⟨field designator⟩ ⟶ INSTITUTION. [LDF 2006.12.12.]

Log

[LDF 2006.12.12.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  field_designator:␣INSTITUTION
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘field_designator:␣INSTITUTION’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = INSTITUTION;
  }
  ;
```

533. ⟨field designator⟩ —→ `LANGUAGE`. [LDF 2006.12.12.]

Log

[LDF 2006.12.12.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  field_designator:␣LANGUAGE
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘field_designator:␣LANGUAGE’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = LANGUAGE;
  }
  ;
```

534. ⟨field designator⟩ ⟶ MAIN_CANONICAL_TITLE. [LDF 2006.12.12.]

Log

[LDF 2006.12.12.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
field_designator:␣MAIN_CANONICAL_TITLE
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘field_designator:␣MAIN_CANONICAL_TITLE’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = MAIN_CANONICAL_TITLE;
  }
  ;
```

535. ⟨field designator⟩ ⟶ `PERMUTATION_PATTERN`. [LDF 2006.12.12.]

Log

[LDF 2006.12.12.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  field_designator:␣PERMUTATION_PATTERN
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘field_designator:␣PERMUTATION_PATTERN’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = PERMUTATION_PATTERN;
  }
  ;
```

536. ⟨field designator⟩ ⟶ `PERSON`. [LDF 2006.12.12.]

Log

[LDF 2006.12.12.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
field_designator:␣PERSON
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘field_designator:␣PERSON’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = PERSON;
  }
  ;
```

537. ⟨field designator⟩ —→ PHYSICAL_DESCRIPTION. [LDF 2006.12.12.]

Log

[LDF 2006.12.12.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  field_designator:␣PHYSICAL_DESCRIPTION
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘field_designator:␣PHYSICAL_DESCRIPTION’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = PHYSICAL_DESCRIPTION;
  }
  ;
```

538. ⟨field designator⟩ ⟶ PUBLISHER. [LDF 2006.12.12.]

Log

[LDF 2006.12.12.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  field_designator:␣PUBLISHER
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘field_designator:␣PUBLISHER’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = PUBLISHER;
  }
  ;
```

539. ⟨field designator⟩ —→ `RECORD`. [LDF 2006.12.12.]

Log

[LDF 2006.12.12.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  field_designator:␣RECORD
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘field_designator:␣RECORD’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = RECORD;
  }
  ;
```

540. ⟨field designator⟩ ⟶ `REMOTE_ACCESS`. [LDF 2006.12.12.]

Log

[LDF 2006.12.12.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
field_designator: REMOTE_ACCESS
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘field_designator: REMOTE_ACCESS’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = REMOTE_ACCESS;
  }
  ;
```

541. ⟨field designator⟩ —→ `RIGHTS`. [LDF 2006.12.12.]

Log

[LDF 2006.12.12.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  field_designator:␣RIGHTS
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘field_designator:␣RIGHTS’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = RIGHTS;
  }
  ;
```

542. ⟨field designator⟩ ⟶ SOURCE. [LDF 2006.12.12.]

Log

[LDF 2006.12.12.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
field_designator:␣SOURCE
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘field_designator:␣SOURCE’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = SOURCE;
  }
  ;
```

543. ⟨field designator⟩ —→ SUBJECT. [LDF 2006.11.14.]

Log

[2006.11.14.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  field_designator:␣SUBJECT
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘field_designator:␣SUBJECT’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = SUBJECT;
  }
  ;
```

544. ⟨field designator⟩ ⟶ SUPERORDINATE_ENTITIES. [LDF 2006.12.12.]

Log

[LDF 2006.12.12.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
field_designator: SUPERORDINATE_ENTITIES
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘field_designator: SUPERORDINATE_ENTITIES’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = SUPERORDINATE_ENTITIES;
  }
  ;
```

545. ⟨field designator⟩ —→ TITLE. [LDF 2006.11.14.]

Log

[2006.11.14.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  field_designator:␣TITLE
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘field_designator:␣TITLE’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = TITLE;
  }
  ;
```

546. ⟨field designator⟩ ⟶ `TYPE`. [LDF 2006.12.12.]

Log

[LDF 2006.12.12.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
field_designator: TYPE
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘field_designator: TYPE’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = TYPE;
  }
  ;
```

547. ⟨field qualifier⟩. [LDF 2006.12.13.]

Log

[LDF 2006.12.13.] Added this type declaration.

⟨ Type declarations for non-terminal symbols 432 ⟩ +≡

```
%type <pointer_value> field_qualifier_list
```

548. ⟨field qualifier list⟩ —→ `EMPTY`. [LDF 2006.12.13.]

Log

[LDF 2006.12.13.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  field_qualifier_list:␣/*␣Empty␣␣*/ {
#if 1    /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
      Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
      temp_strm ≪ endl ≪ "Rule␣'field_qualifier:␣EMPTY'." ≪ endl;
      cerr_mutex.lock();
      cerr ≪ temp_strm.str();
      cerr_mutex.unlock();
      scanner_node→log_strm ≪ temp_strm.str();
      temp_strm.str("");
#endif
      deque < int > *d = new deque < int > ;
      $$ = static_cast⟨void *⟩(d); } ;
```

549. ⟨field qualifier list⟩ —→ ⟨field qualifier list⟩ `PERIOD` ⟨field qualifier⟩. [LDF 2006.12.13.]

Log

[LDF 2006.12.13.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  field_qualifier_list:␣field_qualifier_list␣PERIOD␣field_qualifier {
#if 1    /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
      Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
      temp_strm ≪ endl ≪ "Rule␣'field_qualifier:␣field_qualifier_list␣PERIOD␣field_qu\
          alifier'." ≪ endl;
      cerr_mutex.lock();
      cerr ≪ temp_strm.str();
      cerr_mutex.unlock();
      scanner_node→log_strm ≪ temp_strm.str();
      temp_strm.str("");
#endif
      deque < int > *d = static_cast < deque < int >*> ( $1 );
      d→push_back( $3 );
      $$ = static_cast⟨void *⟩(d); } ;
```

550. ⟨field qualifier⟩**.** [LDF 2006.12.07.]

Log

[LDF 2006.12.07.] Added this type declaration.

⟨ Type declarations for non-terminal symbols 432 ⟩ +≡

```
%type␣<int_value>␣field_qualifier
```

551. Generic. [LDF 2006.12.13.]

Log

[2006.12.13.] Added this section.

552. ⟨field qualifier⟩ ⟶ `ID`**.** [LDF 2006.12.13.]

Log

[LDF 2006.12.13.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
field_qualifier:␣ID
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘field_qualifier:␣ID’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = ID;
  }
  ;
```

553. Names. [LDF 2006.12.13.]

Log

[2006.12.13.] Added this section.

554. ⟨field qualifier⟩ ⟶ SURNAME. [LDF 2006.12.07.]

Log

[LDF 2006.12.07.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  field_qualifier: SURNAME
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘field_qualifier: SURNAME’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = SURNAME;
  }
  ;
```

555. ⟨field qualifier⟩ —→ GIVEN_NAME. [LDF 2006.12.13.]

Log

[LDF 2006.12.13.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  field_qualifier:␣GIVEN_NAME
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘field_qualifier:␣GIVEN_NAME’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = GIVEN_NAME;
  }
  ;
```

556. ⟨field qualifier⟩ ⟶ `PREFIX`. [LDF 2006.12.13.]

Log

[LDF 2006.12.13.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
field_qualifier:␣PREFIX
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘field_qualifier:␣PREFIX’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = PREFIX;
  }
  ;
```

557. Field qualifiers for database table columns. [LDF 2006.12.14.]

Log

[2006.12.14.] Added this section.

558. Records. [LDF 2006.12.14.]

Log

[2006.12.14.] Added this section.

559. ⟨field qualifier⟩ ⟶ ELN_ORIGINAL_ENTRY. [LDF 2006.12.14.]

Log

[LDF 2006.12.14.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
field_qualifier:␣ELN_ORIGINAL_ENTRY
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘field_qualifier:␣ELN_ORIGINAL_ENTRY’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = ELN_ORIGINAL_ENTRY;
  }
  ;
```

560. ⟨field qualifier⟩ ⟶ `ELN_MOST_RECENT_CHANGE`. [LDF 2006.12.14.]

Log

[LDF 2006.12.14.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  field_qualifier:␣ELN_MOST_RECENT_CHANGE
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘field_qualifier:␣ELN_MOST_RECENT_CHANGE’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = ELN_MOST_RECENT_CHANGE;
  }
  ;
```

561. ⟨field qualifier⟩ —→ ELN_STATUS_CHANGE. [LDF 2006.12.14.]

Log

[LDF 2006.12.14.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  field_qualifier:␣ELN_STATUS_CHANGE
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘field_qualifier:␣ELN_STATUS_CHANGE’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = ELN_STATUS_CHANGE;
  }
  ;
```

562. ⟨field qualifier⟩ —→ IDENTIFICATION_NUMBER. [LDF 2006.12.14.]

Log

[LDF 2006.12.14.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  field_qualifier:␣IDENTIFICATION_NUMBER
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘field_qualifier:␣IDENTIFICATION_NUMBER’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = IDENTIFICATION_NUMBER;
  }
  ;
```

563. ⟨field qualifier⟩ ⟶ DATE_ORIGINAL_ENTRY. [LDF 2006.12.14.]

Log

[LDF 2006.12.14.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  field_qualifier:␣DATE_ORIGINAL_ENTRY
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘field_qualifier:␣DATE_ORIGINAL_ENTRY’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = DATE_ORIGINAL_ENTRY;
  }
  ;
```

564. ⟨field qualifier⟩ ⟶ DATE_MOST_RECENT_CHANGE. [LDF 2006.12.14.]

Log

[LDF 2006.12.14.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
field_qualifier:␣DATE_MOST_RECENT_CHANGE
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘field_qualifier:␣DATE_MOST_RECENT_CHANGE’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = DATE_MOST_RECENT_CHANGE;
  }
  ;
```

565. ⟨field qualifier⟩ ⟶ DATE_STATUS_CHANGE. [LDF 2006.12.14.]

Log

[LDF 2006.12.14.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
field_qualifier:␣DATE_STATUS_CHANGE
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘field_qualifier:␣DATE_STATUS_CHANGE’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = DATE_STATUS_CHANGE;
  }
  ;
```

566. ⟨field qualifier⟩ ⟶ SOURCE_ID. [LDF 2006.12.14.]

Log

[LDF 2006.12.14.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  field_qualifier: SOURCE_ID
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘field_qualifier: SOURCE_ID’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = SOURCE_ID;
  }
  ;
```

567. ⟨field qualifier⟩ —→ YEAR_APPEARANCE_BEGIN. [LDF 2006.12.14.]

Log

[LDF 2006.12.14.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  field_qualifier:␣YEAR_APPEARANCE_BEGIN
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘field_qualifier:␣YEAR_APPEARANCE_BEGIN’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = YEAR_APPEARANCE_BEGIN;
  }
  ;
```

568. ⟨field qualifier⟩ ⟶ `YEAR_APPEARANCE_END`. [LDF 2006.12.14.]

Log

[LDF 2006.12.14.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
field_qualifier:␣YEAR_APPEARANCE_END
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘field_qualifier:␣YEAR_APPEARANCE_END’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = YEAR_APPEARANCE_END;
  }
  ;
```

569. ⟨field qualifier⟩ —→ YEAR_APPEARANCE_RAK_WB. [LDF 2006.12.14.]

Log

[LDF 2006.12.14.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
field_qualifier: YEAR_APPEARANCE_RAK_WB
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘field_qualifier: YEAR_APPEARANCE_RAK_WB’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = YEAR_APPEARANCE_RAK_WB;
  }
  ;
```

570. ⟨field qualifier⟩ ⟶ YEAR_APPEARANCE_ORIGINAL. [LDF 2006.12.14.]

Log

[LDF 2006.12.14.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
field_qualifier: YEAR_APPEARANCE_ORIGINAL
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘field_qualifier: YEAR_APPEARANCE_ORIGINAL’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = YEAR_APPEARANCE_ORIGINAL;
  }
  ;
```

571. ⟨datasource assignment⟩. [LDF 2006.12.08.]

Log

[2006.12.08.] Added this type declaration.

⟨ Type declarations for non-terminal symbols 432 ⟩ +≡

```
%type <pointer_value> datasource_assignment
```

284 ⟨DATASOURCE ASSIGNMENT⟩ ⟶ ⟨DATASOURCE VARIABLE⟩ `ASSIGN` ⟨DATASOURCE EXPRESSION⟩LD

572. ⟨datasource assignment⟩ ⟶ ⟨datasource variable⟩ `ASSIGN` ⟨datasource expression⟩**.** [LDF 2006.12.08.] ∎

Log

[LDF 2006.12.08.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
datasource_assignment:␣datasource_variable␣ASSIGN␣datasource_expression
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘datasource_assignment:␣datasource_variable␣" ≪
        "ASSIGN␣datasource_expression’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    Id_Node id_node = static_cast⟨Id_Node⟩($1);
    if (¬id_node) $$ = 0;
    else {
      if (id_node→value ≠ 0) delete static_cast⟨Datasource_Node⟩(id_node→value);
      id_node→value = $3;
      $$ = $3;
    }
#undef DEBUG_OUTPUT
  }
  ;
```

573. ⟨datasource assignment⟩ −→ ⟨datasource variable⟩ `ASSIGN DBT.` [LDF 2006.12.08.]

Log

[LDF 2006.12.08.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
datasource_assignment: datasource_variable ASSIGN DBT
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘datasource_assignment: datasource_variable ASSIGN DBT’." ≪
        endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    Id_Node id_node = static_cast⟨Id_Node⟩($1);
    if (¬id_node) $$ = 0;
    else {
      if (id_node→value ≡ 0) id_node→value = static_cast⟨void *⟩(new Datasource_Type);
      static_cast⟨Datasource_Node⟩(id_node→value)→type = Datasource_Type::DBT_TYPE;
      $$ = id_node→value;
    }
#undef DEBUG_OUTPUT
  }
  ;
```

574. ⟨datasource assignment⟩ ⟶ ⟨datasource variable⟩ ASSIGN GBV_GVK. [LDF 2006.12.08.]

Log

[LDF 2006.12.08.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
datasource_assignment: datasource_variable ASSIGN GBV_GVK
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘datasource_assignment: datasource_variable ASSIGN GBV\
        _GVK’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    Id_Node id_node = static_cast⟨Id_Node⟩($1);
    if (¬id_node) $$ = 0;
    else {
      if (id_node→value ≡ 0) id_node→value = static_cast⟨void *⟩(new Datasource_Type);
      static_cast⟨Datasource_Node⟩(id_node→value)→type = Datasource_Type::GBV_GVK_TYPE;
      $$ = id_node→value;
    }
#undef DEBUG_OUTPUT
  }
  ;
```

575. ⟨datasource assignment⟩ −→ ⟨datasource variable⟩ `ASSIGN TIMMS.` [LDF 2006.12.08.]

Log

[LDF 2006.12.08.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
datasource_assignment: datasource_variable ASSIGN TIMMS
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘datasource_assignment: datasource_variable ASSIGN TIMMS’." ≪
        endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    Id_Node id_node = static_cast⟨Id_Node⟩($1);
    if (¬id_node) $$ = 0;
    else {
      if (id_node→value ≡ 0) id_node→value = static_cast⟨void *⟩(new Datasource_Type);
      static_cast⟨Datasource_Node⟩(id_node→value)→type = Datasource_Type::TIMMS_TYPE;
      $$ = id_node→value;
    }
#undef DEBUG_OUTPUT
  }
  ;
```

576. ⟨datasource assignment⟩ ⟶ ⟨datasource variable⟩ ASSIGN DATASOURCE_FILE. [LDF 2006.12.08.]

Log

[LDF 2006.12.08.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
datasource_assignment: datasource_variable ASSIGN DATASOURCE_FILE
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘datasource_assignment: datasource_variable ASSIGN DAT\
        ASOURCE_FILE’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    Id_Node id_node = static_cast⟨Id_Node⟩($1);
    if (¬id_node) $$ = 0;
    else {
      if (id_node→value ≡ 0) id_node→value = static_cast⟨void *⟩(new Datasource_Type);
      static_cast⟨Datasource_Node⟩(id_node→value)→type =
          Datasource_Type::DATASOURCE_FILE_TYPE;
      $$ = id_node→value;
    }
#undef DEBUG_OUTPUT
  }
  ;
```

577. ⟨string assignment⟩. [LDF 2006.11.16.]

Log

[2006.11.16.] Added this type declaration.

⟨ Type declarations for non-terminal symbols 432 ⟩ +≡

```
%type <string_value> string_assignment
```

578. ⟨string assignment⟩ ⟶ ⟨string variable⟩ ASSIGN ⟨string expression⟩. [LDF 2006.11.16.]

Log

[2006.11.16.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
string_assignment: string_variable ASSIGN string_expression
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
#ifdef DEBUG_OUTPUT
    temp_strm ≪ endl ≪ "Rule ‘string_assignment:  string_variable " ≪
        "ASSIGN string_expression’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    Id_Node curr_id_node = static_cast⟨Id_Node⟩($1);
    if (curr_id_node ≡ 0) {
      temp_strm ≪ "WARNING!  In ‘yyparse’, rule " ≪
          "‘string_assignment:  string_variable" ≪ endl ≪ "ASSIGN string_expression’:" ≪
          endl ≪ "‘string_variable’ = 0.  Can’t assign." ≪ endl ≪
          "Type <RETURN> to continue: ";
      cerr_mutex.lock();
      cerr ≪ temp_strm.str();
      getchar();
      cerr_mutex.unlock();
      scanner_node→log_strm ≪ temp_strm.str();
      temp_strm.str("");
      strcpy($$, $3);
    }
    else {
      if (curr_id_node→value ≡ 0) curr_id_node→value = new string;
      *static_cast⟨string *⟩(curr_id_node→value) = $3;
      strcpy($$, $3);
    }
#undef DEBUG_OUTPUT
  }
  ;
```

579. ⟨string assignment⟩ ⟶ ⟨string variable⟩ ASSIGN TEX ⟨query expression⟩. [LDF 2006.11.16.]

Log

[2006.11.16.] Added this rule.

[LDF 2006.12.01.] !! BUG FIX: Added code for the case that *curr_id_node→value* ≠ 0.

```
⟨ Parser rules 421 ⟩ +≡
  string_assignment:␣string_variable␣ASSIGN␣TEX␣query_expression{
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
#ifdef DEBUG_OUTPUT
    temp_strm ≪ endl ≪ "Rule␣‘string_assignment:␣string_variable␣ASSIGN␣TEX␣query_e\
      xpression" ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    Id_Node curr_id_node = static_cast⟨Id_Node⟩($1);
    Query_Node q = static_cast⟨Query_Node⟩($4);
    string *curr_string = 0;
    stringstream tex_strm;
    if (curr_id_node ≡ 0 ∨ q ≡ 0) {
      strcpy($$, "");
    }
    else     /* curr_id_node ≠ 0 */
    { curr_id_node→subtype = Id_Type::TEX_STRING_TYPE;
    if (curr_id_node→value ≡ 0) {
      curr_string = new string;
      curr_id_node→value = static_cast⟨void *⟩(curr_string);
    }
    else {
      *static_cast⟨string *⟩(curr_id_node→value) = "";
      curr_string = static_cast⟨string *⟩(curr_id_node→value);
    }
```

580.

```
⟨ Parser rules 421 ⟩ +≡
  stringstream *tex_strm = new stringstream;
  *curr_string = q→generate_tex_string(scanner_node, tex_strm);
  tex_strm→str("");
  strcpy($$, curr_string→c_str()); }     /* else (curr_id_node ≠ 0) */
  } ;
```

581. ⟨string assignment⟩ ⟶ ⟨string variable⟩ `ASSIGN SQL OAI` ⟨query expression⟩. [LDF 2006.12.01.]

Log

[LDF 2006.12.01.] Added this rule.

[LDF 2006.12.06.] Changed this rule from ⟨string assignment⟩ ⟶ ⟨string variable⟩ `ASSIGN SQL` ⟨query expression⟩ to ⟨string assignment⟩ ⟶ ⟨string variable⟩ `ASSIGN SQL OAI` ⟨query expression⟩.

⟨ Parser rules 421 ⟩ +≡

```
string_assignment: string_variable ASSIGN SQL OAI query_expression {
#if 1    /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
#ifdef DEBUG_OUTPUT
    temp_strm ≪ endl ≪ "Rule ‘string_assignment: string_variable ASSIGN " ≪
        "SQL OAI query_expression" ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    stringstream tex_strm;
    stringstream select_strm;
    stringstream from_strm;
    stringstream where_strm_0;
    stringstream where_strm_1;
    Id_Node curr_id_node = static_cast⟨Id_Node⟩($1);
    Query_Node q = static_cast⟨Query_Node⟩($5);
    string *curr_string = 0;
    if (curr_id_node ≡ 0 ∨ q ≡ 0) {
      strcpy($$, "");
    }
    else    /* curr_id_node ≠ 0 */
    { curr_id_node→subtype = Id_Type::SQL_STRING_TYPE;
    if (curr_id_node→value ≡ 0) {
      curr_string = new string;
      curr_id_node→value = static_cast⟨void *⟩(curr_string);
    }
    else {
      *static_cast⟨string *⟩(curr_id_node→value) = "";
      curr_string = static_cast⟨string *⟩(curr_id_node→value);
    }
```

582.

```
⟨ Parser rules 421 ⟩ +≡
  bool first_select = true;
  bool first_from = true;
  bool first_where = true;
  bitset < QUERY_TYPE_BITSET_SIZE > field_flags (0L);
  int r = q→generate_sql_string(scanner_node, OAI, &tex_strm, &select_strm, &from_strm, &where_strm_0,
      &where_strm_1, &first_select, &first_from, &first_where, &field_flags, curr_string);
  tex_strm.str("");
  if (r ≡ 0) strcpy(▣$$▣, curr_string→c_str());
  else strcpy(▣$$▣, "");
  }     /* else (curr_id_node ≠ 0) */
  } ;
```

583. ⟨string assignment⟩ ⟶ ⟨string variable⟩ `ASSIGN SQL PICA` ⟨query expression⟩**.** [LDF 2006.12.01.]

Log

[LDF 2006.12.06.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
string_assignment: string_variable ASSIGN SQL PICA query_expression {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
#ifdef DEBUG_OUTPUT
    temp_strm ≪ endl ≪ "Rule ‘string_assignment: string_variable ASSIGN "
        "SQL PICA query_expression" ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    stringstream tex_strm;
    stringstream select_strm;
    stringstream from_strm;
    stringstream where_strm_0;
    stringstream where_strm_1;
    Id_Node curr_id_node = static_cast⟨Id_Node⟩($1);
    Query_Node q = static_cast⟨Query_Node⟩($5);
    string *curr_string = 0;
    if (curr_id_node ≡ 0 ∨ q ≡ 0) {
      strcpy($$, "");
    }
    else     /* curr_id_node ≠ 0 */
    { curr_id_node→subtype = Id_Type::SQL_STRING_TYPE;
    if (curr_id_node→value ≡ 0) {
      curr_string = new string;
      curr_id_node→value = static_cast⟨void *⟩(curr_string);
    }
    else {
      *static_cast⟨string *⟩(curr_id_node→value) = "";
      curr_string = static_cast⟨string *⟩(curr_id_node→value);
    }
```

584.

```
⟨ Parser rules 421 ⟩ +≡
  bool first_select = true;
  bool first_from = true;
  bool first_where = true;
  bitset < QUERY_TYPE_BITSET_SIZE > field_flags (0L);
  int r = q→generate_sql_string(scanner_node, PICA, &tex_strm, &select_strm, &from_strm, &where_strm_0,
      &where_strm_1, &first_select, &first_from, &first_where, &field_flags, curr_string);
  tex_strm.str("");
  if (r ≡ 0) strcpy( $$ , curr_string→c_str( ));
  else strcpy( $$ , "");
  }    /* else (curr_id_node ≠ 0) */
  } ;
```

585. ⟨datetime assignment⟩. [LDF 2006.12.15.]

Log

[LDF 2006.12.15.] Added this type declaration.

```
⟨ Type declarations for non-terminal symbols 432 ⟩ +≡
  %type␣<pointer_value>␣datetime_assignment
```

586. ⟨datetime assignment⟩ ⟶ ⟨datetime variable⟩ ASSIGN ⟨datetime expression⟩. [LDF 2006.12.15.]

Log

[LDF 2006.12.15.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
datetime_assignment:␣datetime_variable␣ASSIGN␣datetime_expression
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘datetime_assignment:␣datetime_variable␣ASSIGN␣datetim\
        e_expression’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    Id_Node id_node = static_cast⟨Id_Node⟩($1);
    if (¬id_node) $$ = 0;
    else {
      if (id_node→value ≠ 0) delete static_cast⟨Date_Time_Node⟩(id_node→value);
      id_node→value = $3;
      $$ = $3;
    }
#undef DEBUG_OUTPUT
  }
  ;
```

587. ⟨datetime assignment⟩ ⟶ ⟨datetime variable⟩ COLON ⟨datetime specifier⟩ **(etc.).** ⟨datetime assignment⟩ ⟶ ⟨datetime variable⟩ COLON ⟨datetime specifier⟩ ⟨assignment operator⟩ INTEGER. [LDF 2006.12.15.]

Log

[LDF 2006.12.15.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  datetime_assignment:␣datetime_variable␣COLON␣datetime_specifier␣
  assignment_operator␣INTEGER
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘datetime_assignment:␣datetime_variable␣COLON␣" ≪
        "datetime_specifier␣assignment_operator␣INTEGER’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    Id_Node id_node = static_cast⟨Id_Node⟩($1);
    if (¬id_node) {
      temp_strm ≪ "ERROR!␣␣In␣‘yyparse’,␣rule" ≪ endl ≪
          "‘datetime_assignment:␣datetime_variable␣COLON␣" ≪ "datetime_specifier␣\
          assignment_operator␣INTEGER’:" ≪ endl ≪ "‘datetime_variable’␣==␣NULL.␣␣" ≪
          "Setting␣value␣of␣action␣(‘datetime_assignment’)␣" ≪ "to␣0." ≪ endl;
      cerr_mutex.lock();
      cerr ≪ temp_strm.str();
      cerr_mutex.unlock();
      scanner_node→log_strm ≪ temp_strm.str();
      temp_strm.str("");
      $$ = 0;
    }     /* if (¬id_node) */
    else      /* id_node ≠ 0 */
    {
      Date_Time_Node d = static_cast⟨Date_Time_Node⟩(id_node→value);
      int val = $5;
      datetime_assignment_func_0(scanner_node, d, $3, $4, static_cast⟨void *⟩(&val), INTEGER);
      id_node→value = static_cast⟨void *⟩(d);
      $$ = id_node→value;
    }     /* else (id_node ≠ 0) */
#undef DEBUG_OUTPUT
  }
  ;
```

588. ⟨datetime assignment⟩ ⟶ ⟨datetime variable⟩ COLON ⟨datetime specifier⟩ **(etc.).** ⟨datetime assignment⟩ ⟶ ⟨datetime variable⟩ COLON ⟨datetime specifier⟩ ⟨assignment operator⟩ FLOAT. [LDF 2006.12.18.]

Log

[2006.12.18.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
datetime_assignment: datetime_variable COLON datetime_specifier
assignment_operator FLOAT
{
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘datetime_assignment: datetime_variable COLON " ≪
        "datetime_specifier assignment_operator FLOAT’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    Id_Node id_node = static_cast⟨Id_Node⟩($1);
    if (¬id_node) {
      temp_strm ≪ "ERROR!  In ‘yyparse’, rule" ≪ endl ≪
          "‘datetime_assignment: datetime_variable COLON " ≪ "datetime_specifier \
          assignment_operator FLOAT’:" ≪ endl ≪ "‘datetime_variable’ == NULL.  " ≪
          "Setting value of action (‘datetime_assignment’) " ≪ "to 0." ≪ endl;
      cerr_mutex.lock();
      cerr ≪ temp_strm.str();
      cerr_mutex.unlock();
      scanner_node→log_strm ≪ temp_strm.str();
      temp_strm.str("");
      $$ = 0;
    }     /* if (¬id_node) */
    else      /* id_node ≠ 0 */
    {
      Date_Time_Node d = static_cast⟨Date_Time_Node⟩(id_node→value);
      float val = $5;
      datetime_assignment_func_0(scanner_node, d, $3, $4, static_cast⟨void *⟩(&val), FLOAT);
      id_node→value = static_cast⟨void *⟩(d);
      $$ = id_node→value;
    }     /* else (id_node ≠ 0) */
#undef DEBUG_OUTPUT
  }
  ;
```

589. Datetime specifier.

Log

[2006.12.15.] Added this type declaration.

⟨ Type declarations for non-terminal symbols 432 ⟩ +≡

```
%type␣<int_value>␣datetime_specifier
```

590. ⟨datetime specifier⟩ −→ `YEAR_RANGE_BEGIN.` [LDF 2006.12.18.]

Log

[LDF 2006.12.18.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
datetime_specifier:␣YEAR_RANGE_BEGIN
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘datetime_specifier:␣YEAR_RANGE_BEGIN’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = YEAR_RANGE_BEGIN;
  }
  ;
```

591. ⟨datetime specifier⟩ —→ YEAR_RANGE_END. [LDF 2006.12.18.]

Log

[LDF 2006.12.18.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
datetime_specifier:␣YEAR_RANGE_END
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘datetime_specifier:␣YEAR_RANGE_END’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = YEAR_RANGE_END;
  }
  ;
```

592. ⟨datetime specifier⟩ —→ `YEAR`. [LDF 2006.12.15.]

Log

[LDF 2006.12.15.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
datetime_specifier:␣YEAR
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘datetime_specifier:␣YEAR’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = YEAR;
  }
  ;
```

593. ⟨datetime specifier⟩ —→ `MONTH`. [LDF 2006.12.15.]

Log

[LDF 2006.12.15.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  datetime_specifier:␣MONTH
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘datetime_specifier:␣MONTH’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = MONTH;
  }
  ;
```

594. ⟨datetime specifier⟩ —→ `DAY`. [LDF 2006.12.15.]

Log

[LDF 2006.12.15.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
datetime_specifier:␣DAY
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘datetime_specifier:␣DAY’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = DAY;
  }
  ;
```

595. ⟨datetime specifier⟩ ⟶ `HOUR`. [LDF 2006.12.15.]

Log

[LDF 2006.12.15.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  datetime_specifier:␣HOUR
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘datetime_specifier:␣HOUR’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = HOUR;
  }
  ;
```

596. ⟨datetime specifier⟩ —→ `MINUTE`. [LDF 2006.12.15.]

Log

[LDF 2006.12.15.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
datetime_specifier:␣MINUTE
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘datetime_specifier:␣MINUTE’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = MINUTE;
  }
  ;
```

597. ⟨datetime specifier⟩ ⟶ SECOND. [LDF 2006.12.15.]

Log

[LDF 2006.12.15.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
datetime_specifier: SECOND
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘datetime_specifier: SECOND’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = SECOND;
  }
  ;
```

598. Commands (commands.w). [LDF 2006.11.13.]

Log

[LDF 2006.11.13.] Added this file.

⟨ commands.w 598 ⟩ ≡

```
static char commands_id_string[] = "$Id: commands.w, v 1.6 2007/02/13 20:42:\
    40 lfinsto1 Exp $";
```

This code is cited in sections 7 and 8.

This code is used in section 675.

599.

⟨ Type declarations for non-terminal symbols 432 ⟩ +≡

```
%type <int_value> command
```

600. Messages. [LDF 2006.11.15.]

Log

[2006.11.15.] Added this section.

601. ⟨message or errmessage⟩**.** [LDF 2006.11.15.]

Log

[2006.11.15.] Added this type declaration.

⟨ Type declarations for non-terminal symbols 432 ⟩ +≡

```
%type␣<int_value>␣message_or_errmessage
```

602. ⟨message or errmessage⟩ −→ `MESSAGE`**.** [LDF 2006.11.15.]

Log

[LDF 2006.11.15.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
message_or_errmessage:␣MESSAGE
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘message_or_errmessage:␣MESSAGE’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = MESSAGE;
  }
  ;
```

603. ⟨message or errmessage⟩ —→ ERRMESSAGE. [LDF 2006.11.15.]

Log

[LDF 2006.11.15.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  message_or_errmessage: ERRMESSAGE
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘message_or_errmessage: ERRMESSAGE’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = ERRMESSAGE;
  }
  ;
```

604. ⟨command⟩ ⟶ ⟨message or errmessage⟩**.** `STRING`. [LDF 2006.11.13.]

Log

[2006.11.13.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
command: message_or_errmessage STRING
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
#ifdef DEBUG_OUTPUT
    temp_strm ≪ endl ≪ "Rule ‘command: message_or_errmessage STRING’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    if ($1 ≡ ERRMESSAGE) temp_strm ≪ "ERROR!  ";
    temp_strm ≪ $2 ≪ endl;
    if ($1 ≡ ERRMESSAGE) temp_strm ≪ "Type <RETURN> to continue: ";
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
    if ($1 ≡ ERRMESSAGE) getchar();
    cerr_mutex.unlock();
  }
  ;
```

605. ⟨command⟩ ⟶ `PAUSE`. [LDF 2006.11.13.]

Log

[2006.11.13.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
command:␣PAUSE
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
#ifdef DEBUG_OUTPUT
    temp_strm ≪ endl ≪ "Rule␣‘command:␣PAUSE’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    temp_strm ≪ "Enter␣<RETURN>␣to␣continue:␣";
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
    getchar();
    cerr_mutex.unlock();
  }
  ;
```

606. ⟨command⟩ ⟶ SHOW ⟨query variable⟩. [LDF 2006.11.13.]

Log

[2006.11.13.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
command: SHOW query_variable
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
#ifdef DEBUG_OUTPUT
    temp_strm ≪ endl ≪ "Rule ‘command: SHOW query_variable’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    Id_Node curr_id_node = static_cast⟨Id_Node⟩($2);
    if (curr_id_node ≡ 0) {
      temp_strm ≪ "WARNING!  In ‘yyparse’, rule ‘command: SHOW query_variable’:" ≪ endl ≪
          "‘query_variable’ is NULL.  Can’t show.  Continuing.";
      cerr_mutex.lock();
      cerr ≪ temp_strm.str();
      cerr_mutex.unlock();
      scanner_node→log_strm ≪ temp_strm.str();
      temp_strm.str("");
      $$ = 1;
    }    /* if (curr_id_node ≡ 0) */
    else if (curr_id_node→value ≡ 0) {
      temp_strm ≪ "WARNING!  In ‘yyparse’, rule ‘command: SHOW query_variable’:" ≪
          endl ≪ "The ‘value’ element of ‘query_variable’ is NULL.  " ≪
          "Can’t show.  Continuing.";
      cerr_mutex.lock();
      cerr ≪ temp_strm.str();
      cerr_mutex.unlock();
      scanner_node→log_strm ≪ temp_strm.str();
      temp_strm.str("");
      $$ = 1;
    }    /* if (curr_id_node ≡ 0) */
    else if (curr_id_node ∧ curr_id_node→value) {
      Query_Node curr_query_node = static_cast⟨Query_Node⟩(curr_id_node→value);
      cerr_mutex.lock();
      curr_query_node→show("Query_Type:");
      cerr_mutex.unlock();
      $$ = 0;
```

```
    }
#undef DEBUG_OUTPUT
  }
  ;
```

607. ⟨command⟩ ⟶ SHOW ⟨datasource variable⟩. [LDF 2006.12.08.]

Log

[LDF 2006.12.08.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
command: SHOW datasource_variable
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
#ifdef DEBUG_OUTPUT
    temp_strm ≪ endl ≪ "Rule ‘command: SHOW datasource_variable’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    Id_Node curr_id_node = static_cast⟨Id_Node⟩($2);
    if (curr_id_node ≡ 0) {
      temp_strm ≪ "WARNING!  In ‘yyparse’, rule ‘command: SHOW datasource_variable’:" ≪
          endl ≪ "‘datasource_variable’ is NULL.  Can’t show.  Continuing.";
      cerr_mutex.lock();
      cerr ≪ temp_strm.str();
      cerr_mutex.unlock();
      scanner_node→log_strm ≪ temp_strm.str();
      temp_strm.str("");
      $$ = 1;
    }   /* if (curr_id_node ≡ 0) */
    else if (curr_id_node→value ≡ 0) {
      temp_strm ≪ "WARNING!  In ‘yyparse’, rule ‘command: SHOW datasource_variable’:" ≪
          endl ≪ "The ‘value’ element of ‘datasource_variable’ is NULL.  " ≪
          "Can’t show.  Continuing.";
      cerr_mutex.lock();
      cerr ≪ temp_strm.str();
      cerr_mutex.unlock();
      scanner_node→log_strm ≪ temp_strm.str();
      temp_strm.str("");
      $$ = 1;
    }   /* if (curr_id_node ≡ 0) */
    else if (curr_id_node ∧ curr_id_node→value) {
      Datasource_Node curr_datasource_node = static_cast⟨Datasource_Node⟩(curr_id_node→value);
      cerr_mutex.lock();
      curr_datasource_node→show("Datasource_Type:");
      cerr_mutex.unlock();
      $$ = 0;
```

```
    }
#undef DEBUG_OUTPUT
  }
  ;
```

608. ⟨command⟩ ⟶ SHOW ⟨datetime variable⟩. [LDF 2006.12.15.]

Log

[LDF 2006.12.15.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
command: SHOW datetime_variable
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
#ifdef DEBUG_OUTPUT
    temp_strm ≪ endl ≪ "Rule ‘command: SHOW datetime_variable’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    Id_Node curr_id_node = static_cast⟨Id_Node⟩($2);
    if (curr_id_node ≡ 0) {
      temp_strm ≪ "WARNING!  In ‘yyparse’, rule ‘command: SHOW datetime_variable’:" ≪
          endl ≪ "‘datetime_variable’ is NULL.  Can’t show.  Continuing.";
      cerr_mutex.lock();
      cerr ≪ temp_strm.str();
      cerr_mutex.unlock();
      scanner_node→log_strm ≪ temp_strm.str();
      temp_strm.str("");
      $$ = 1;
    }     /* if (curr_id_node ≡ 0) */
    else if (curr_id_node→value ≡ 0) {
      temp_strm ≪ "WARNING!  In ‘yyparse’, rule ‘command: SHOW datetime_variable’:" ≪
          endl ≪ "The ‘value’ element of ‘datetime_variable’ is NULL.  " ≪
          "Can’t show.  Continuing.";
      cerr_mutex.lock();
      cerr ≪ temp_strm.str();
      cerr_mutex.unlock();
      scanner_node→log_strm ≪ temp_strm.str();
      temp_strm.str("");
      $$ = 1;
    }     /* if (curr_id_node ≡ 0) */
    else if (curr_id_node ∧ curr_id_node→value) {
      Date_Time_Node curr_date_time_node = static_cast⟨Date_Time_Node⟩(curr_id_node→value);
      cerr_mutex.lock();
      curr_date_time_node→show("Date_Time_Type:");
      cerr_mutex.unlock();
      $$ = 0;
```

```
    }
#undef DEBUG_OUTPUT
  }
  ;
```

609. ⟨command⟩ —→ SHOW ⟨string expression⟩. [LDF 2006.11.16.]

Log

[LDF 2006.11.16.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
  command:␣SHOW␣string_expression
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
#ifdef DEBUG_OUTPUT
    temp_strm ≪ endl ≪ "Rule␣‘command:␣SHOW␣string_expression’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    temp_strm ≪ "string␣==␣" ≪ $2 ≪ endl;
#undef DEBUG_OUTPUT
  }
  ;
```

610. ⟨command⟩ ⟶ OUTPUT TEX ⟨string expression⟩. [LDF 2006.11.23.]

Log

[LDF 2006.11.23.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
command: OUTPUT TEX string_expression
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
#ifdef DEBUG_OUTPUT
    temp_strm ≪ endl ≪ "Rule ‘command: OUTPUT TEX string_expression’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    stringstream temp_filename;
    tex_mutex.lock();
    temp_filename ≪ tex_filename_str ≪ tex_file_ctr++ ≪ ".tex";
    tex_file_strm.open(temp_filename.str().c_str());
    tex_file_strm ≪ copyright_tex_str ≪ endl;
    time_t tp;
    time(&tp);
    time_mutex.lock();
    tm *local_time = localtime(&tp);
    char *datestamp = asctime(local_time);
    time_mutex.unlock();
    tex_file_strm ≪ "%% This file was generated by ‘Scantest’ on " ≪ datestamp ≪ "\n\n";
    tex_file_strm ≪ "\\input chrtbase.tex\n\n" ≪ $3 ≪ "\n\n\\bye\n";
    tex_file_strm.close();
    tex_mutex.unlock();
#undef DEBUG_OUTPUT
  }
  ;
```

611. Query expressions (queryexp.w). [LDF 2006.11.15.]

Log

[LDF 2006.11.15.] Added this file.

612.

⟨ queryexp.w 612 ⟩ ≡

```
static char queryexp_id_string[] = "$Id: queryexp.w,v 1.5 2007/02/13 20:40:23 lfinsto1 Exp $";
```

This code is cited in sections 7 and 8.

This code is used in section 675.

613. query primary. [LDF 2006.11.15.]

Log

[LDF 2006.11.15.] Added this type declaration.

⟨ Type declarations for non-terminal symbols 432 ⟩ +≡

```
%type <pointer_value> query_primary
```

614. ⟨query primary⟩ ⟶ ⟨query variable⟩. [LDF 2006.11.15.]

Log

[LDF 2006.11.15.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  query_primary:␣query_variable
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘query_primary:␣query_variable’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    Id_Node curr_id_node = static_cast⟨Id_Node⟩($1);
    if (curr_id_node ∧ curr_id_node→value) {
      Query_Node curr_query_node = new Query_Type;
      *curr_query_node = *static_cast⟨Query_Node⟩(curr_id_node→value);
      $$ = static_cast⟨void *⟩(curr_query_node);
    }
    else $$ = 0;
#ifdef DEBUG_OUTPUT
    temp_strm ≪ endl ≪ "Exiting␣rule␣‘query_primary:␣query_variable’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
  }
  ;
```

615. ⟨query primary⟩ −→ (⟨query expression⟩). [LDF 2006.11.15.]

Log

[LDF 2006.11.15.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
query_primary: OPEN_PARENTHESIS query_expression CLOSE_PARENTHESIS
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘query_primary: OPEN_PARENTHESIS query_expression CLOS\
        E_PARENTHESIS’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    Query_Node q = static_cast⟨Query_Node⟩( $2 );
    $$ = $2;
  }
  ;
```

616. ⟨query primary⟩ ⟶ STRING. [LDF 2006.11.15.]

Log

[LDF 2006.11.15.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  query_primary: STRING
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘query_primary: STRING’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    Query_Node curr_query_node = new Query_Type;
    curr_query_node→value_type = Query_Type::QUERY_TYPE_STRING_TYPE;
    curr_query_node→value = static_cast⟨void *⟩(new string);
    *static_cast⟨string *⟩(curr_query_node→value) = $1;
    $$ = static_cast⟨void *⟩(curr_query_node);
  }
  ;
```

617. ⟨query primary⟩ ⟶ INTEGER. [LDF 2006.12.14.]

Log

[LDF 2006.12.14.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  query_primary: INTEGER
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘query_primary: INTEGER’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    Query_Node curr_query_node = new Query_Type;
    curr_query_node→value_type = Query_Type::INT_TYPE;
    curr_query_node→value = static_cast⟨void *⟩(new int);
    *static_cast⟨int *⟩(curr_query_node→value) = $1;
    $$ = static_cast⟨void *⟩(curr_query_node);
  }
  ;
```

618. ⟨query primary⟩ ⟶ `FLOAT`. [LDF 2006.12.14.]

Log

[LDF 2006.12.14.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
query_primary: FLOAT
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘query_primary: FLOAT’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    Query_Node curr_query_node = new Query_Type;
    curr_query_node→value_type = Query_Type::FLOAT_TYPE;
    curr_query_node→value = static_cast⟨void *⟩(new float);
    *static_cast⟨float *⟩(curr_query_node→value) = $1;
    $$ = static_cast⟨void *⟩(curr_query_node);
  }
  ;
```

619. query secondary. [LDF 2006.11.15.]

Log

[LDF 2006.11.15.] Added this type declaration.

⟨ Type declarations for non-terminal symbols 432 ⟩ +≡

```
%type <pointer_value> query_secondary
```

620. ⟨query secondary⟩ ⟶ ⟨query primary⟩. [LDF 2006.11.15.]

Log

[LDF 2006.11.15.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  query_secondary:␣query_primary
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘query_secondary:␣query_primary’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = $1;
  }
  ;
```

621. ⟨query secondary⟩ ⟶ ⟨query secondary⟩ ⟨and or and not⟩ ⟨query primary⟩. [LDF 2006.11.15.]

Log

[LDF 2006.11.15.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
query_secondary: query_secondary and_or_and_not query_primary
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘query_secondary: query_secondary and_or_and_not query\
        _primary’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    Query_Node secondary = static_cast⟨Query_Node⟩( $1 );
    Query_Node primary = static_cast⟨Query_Node⟩( $3 );
    primary→up = secondary;
    primary→query_type = Query_Type :: AND_TYPE;
    primary→negated = ( $2 ≡ AND_NOT) ? true : false;
    while (secondary→and_node ≠ 0) secondary = secondary→and_node;
    secondary→and_node = primary;
    primary→query_ctr = secondary→query_ctr + 1;
    $$ = $1;
  }
  ;
```

622. query tertiary. [LDF 2006.11.15.]

Log

[LDF 2006.11.15.] Added this type declaration.

⟨ Type declarations for non-terminal symbols 432 ⟩ +≡

```
%type <pointer_value> query_tertiary
```

623. ⟨query tertiary⟩ ⟶ ⟨query secondary⟩. [LDF 2006.11.15.]

Log

[LDF 2006.11.15.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  query_tertiary:␣query_secondary
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘query_tertiary:␣query_secondary’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = $1;
  }
  ;
```

624. ⟨query tertiary⟩ ⟶ ⟨query tertiary⟩ ⟨xor or xor not⟩ ⟨query secondary⟩. [LDF 2006.11.15.]

Log

[LDF 2006.11.15.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
query_tertiary:␣query_tertiary␣xor_or_xor_not␣query_secondary
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘query_tertiary:␣query_tertiary␣xor_or_xor_not␣query_s\
        econdary’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    Query_Node tertiary = static_cast⟨Query_Node⟩($1);
    Query_Node secondary = static_cast⟨Query_Node⟩($3);
    secondary→up = tertiary;
    secondary→query_type = Query_Type::XOR_TYPE;
    secondary→negated = ($2 ≡ XOR_NOT) ? true : false;
    while (tertiary→xor_node ≠ 0) tertiary = tertiary→xor_node;
    tertiary→xor_node = secondary;
    secondary→query_ctr = tertiary→query_ctr + 1;
    $$ = $1;
  }
  ;
```

625. query expression. [LDF 2006.11.15.]

Log

[LDF 2006.11.15.] Added this type declaration.

⟨ Type declarations for non-terminal symbols 432 ⟩ +≡

```
%type␣<pointer_value>␣query_expression
```

626. ⟨query expression⟩ ⟶ ⟨query tariary⟩. [LDF 2006.11.15.]

Log

[LDF 2006.11.15.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  query_expression:␣query_tertiary
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘query_expression:␣query_tertiary’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = $1;
  }
  ;
```

627. ⟨query expression⟩ ⟶ ⟨query expression⟩ ⟨or or or not⟩ ⟨query tertiary⟩. [LDF 2006.11.15.]

Log

[LDF 2006.11.15.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
query_expression: query_expression or_or_or_not query_tertiary
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘query_expression: query_expression or_or_or_not query\
        _tertiary’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    Query_Node expression = static_cast⟨Query_Node⟩( $1 );
    Query_Node tertiary = static_cast⟨Query_Node⟩( $3 );
    tertiary→up = expression;
    tertiary→query_type = Query_Type::OR_TYPE;
    while (expression→or_node ≠ 0) expression = expression→or_node;
    tertiary→negated = ( $2 ≡ OR_NOT) ? true : false;
    expression→or_node = tertiary;
    tertiary→query_ctr = expression→query_ctr + 1;
    $$ = $1;
  }
  ;
```

628. Boolean operators. [LDF 2006.11.15.]

Log

[LDF 2006.11.15.] Added this section with the type declarations of *and_or_and_not*, *or_or_or_not*, and *xor_or_xor_not*.

⟨ Type declarations for non-terminal symbols 432 ⟩ +≡

```
%type <int_value> and_or_and_not  %type <int_value> or_or_or_not  %type <int_value> xor_or_xor_no
```

629. ⟨and or and not⟩ ⟶ AND. [LDF 2006.11.15.]

Log

[LDF 2006.11.15.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  and_or_and_not:␣AND
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘and_or_and_not:␣AND’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = AND;
  }
  ;
```

630. ⟨and or and not⟩ ⟶ AND_NOT. [LDF 2006.11.15.]

Log

[LDF 2006.11.15.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  and_or_and_not: AND_NOT
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘and_or_and_not: AND_NOT’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = AND_NOT;
  }
  ;
```

631. ⟨or or or not⟩ ⟶ OR. [LDF 2006.11.15.]

Log

[LDF 2006.11.15.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  or_or_or_not: ␣OR
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘or_or_or_not:␣OR’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = OR;
  }
  ;
```

632. ⟨or or or not⟩ ⟶ OR_NOT. [LDF 2006.11.15.]

Log

[LDF 2006.11.15.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  or_or_or_not: OR_NOT
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘or_or_or_not: OR_NOT’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = OR_NOT;
  }
  ;
```

633. ⟨xor or xor not⟩ ⟶ XOR. [LDF 2006.11.15.]

Log

[LDF 2006.11.15.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  xor_or_xor_not:␣XOR
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘xor_or_xor_not:␣XOR’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = XOR;
  }
  ;
```

634. ⟨xor or xor not⟩ ⟶ `XOR_NOT`. [LDF 2006.11.15.]

Log

[LDF 2006.11.15.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
xor_or_xor_not: XOR_NOT
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘xor_or_xor_not: XOR_NOT’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = XOR_NOT;
  }
  ;
```

635. Datasource expressions (`dtsrcexp.w`). [LDF 2006.12.08.]

Log

[LDF 2006.12.08.] Added this file.

636.

⟨ `dtsrcexp.w` 636 ⟩ ≡

```
static char dtsrcexp_id_string[] = "$Id: dtsrcexp.w,v 1.6 2007/02/13 20:37:48 lfinsto1 Exp $";
```

This code is cited in sections 7 and 8.

This code is used in section 675.

637. datasource primary. [LDF 2006.12.08.]

Log

[LDF 2006.12.08.] Added this type declaration.

⟨ Type declarations for non-terminal symbols 432 ⟩ +≡

```
%type <pointer_value> datasource_primary
```

638. ⟨datasource primary⟩ —→ ⟨datasource variable⟩. [LDF 2006.12.08.]

Log

[LDF 2006.12.08.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
datasource_primary: datasource_variable
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘datasource_primary: datasource_variable’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    Id_Node curr_id_node = static_cast⟨Id_Node⟩($1);
    if (curr_id_node ∧ curr_id_node→value) {
      Datasource_Node curr_datasource_node = new Datasource_Type;
      *curr_datasource_node = *static_cast⟨Datasource_Node⟩(curr_id_node→value);
      $$ = static_cast⟨void *⟩(curr_datasource_node);
    }
    else $$ = 0;
#ifdef DEBUG_OUTPUT
    temp_strm ≪ endl ≪ "Exiting rule ‘datasource_primary: datasource_variable’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
  }
  ;
```

639. ⟨datasource primary⟩ ⟶ (⟨datasource expression⟩). [LDF 2006.12.08.]

Log

[LDF 2006.12.08.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
datasource_primary:␣OPEN_PARENTHESIS␣datasource_expression␣CLOSE_PARENTHESIS
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘datasource_primary:␣OPEN_PARENTHESIS␣datasource_expre\
        ssion␣" ≪ "CLOSE_PARENTHESIS’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    Datasource_Node q = static_cast⟨Datasource_Node⟩( $2 );
    $$ = $2;
  }
  ;
```

640. datasource secondary. [LDF 2006.12.08.]

Log

[LDF 2006.12.08.] Added this type declaration.

⟨ Type declarations for non-terminal symbols 432 ⟩ +≡

```
%type␣<pointer_value>␣datasource_secondary
```

641. ⟨datasource secondary⟩ —→ ⟨datasource primary⟩**.** [LDF 2006.12.08.]

Log

[LDF 2006.12.08.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
datasource_secondary:␣datasource_primary
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘datasource_secondary:␣datasource_primary’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = $1;
  }
  ;
```

642. datasource tertiary. [LDF 2006.12.08.]

Log

[LDF 2006.12.08.] Added this type declaration.

⟨ Type declarations for non-terminal symbols 432 ⟩ +≡

```
%type␣<pointer_value>␣datasource_tertiary
```

643. ⟨datasource tertiary⟩ ⟶ ⟨datasource secondary⟩**.** [LDF 2006.12.08.]

Log

[LDF 2006.12.08.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
datasource_tertiary: datasource_secondary
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘datasource_tertiary: datasource_secondary’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = $1;
  }
  ;
```

644. datasource expression. [LDF 2006.12.08.]

Log

[LDF 2006.12.08.] Added this type declaration.

⟨ Type declarations for non-terminal symbols 432 ⟩ +≡

```
%type <pointer_value> datasource_expression
```

645. ⟨datasource expression⟩ ⟶ ⟨datasource tertiary⟩. [LDF 2006.12.08.]

Log

[LDF 2006.12.08.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
datasource_expression: datasource_tertiary
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘datasource_expression: datasource_tertiary’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = $1;
  }
  ;
```

646. String expressions (`strings.w`). [LDF 2006.11.16.]

Log

[LDF 2006.11.16.] Added this file.

⟨ `strings.w` 646 ⟩ ≡

```
  static char strings_id_string[] = "$Id: strings.w,v 1.5 2007/02/13 20:41:57 lfinsto1 Exp $";
```

This code is used in section 675.

647. ⟨string primary⟩. [LDF 2006.11.16.]

Log

[2006.11.16.] Added this type declaration.

⟨ Type declarations for non-terminal symbols 432 ⟩ +≡

```
%type <string_value> string_primary
```

648. ⟨string primary⟩ ⟶ ⟨string variable⟩. [LDF 2006.11.16.]

Log

[LDF 2006.11.16.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  string_primary:␣string_variable
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘string_primary:␣string_variable’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    Id_Node curr_id_node = static_cast⟨Id_Node⟩($1);
    if (curr_id_node ≡ 0 ∨ curr_id_node→value ≡ 0) strcpy($$, "");
    else {
      strcpy($$, static_cast⟨string *⟩(curr_id_node→value)→c_str());
    }
  }
  ;
```

649. ⟨string primary⟩: STRING. [LDF 2006.11.16.]

Log

[LDF 2006.11.16.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  string_primary:␣STRING
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘string_primary:␣STRING’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    strcpy($$, $1);
  }
  ;
```

650. ⟨string primary⟩ ⟶ (⟨string expression⟩). [LDF 2006.11.16.]

Log

[LDF 2006.11.16.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
string_primary:␣OPEN_PARENTHESIS␣string_expression␣CLOSE_PARENTHESIS
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘string_primary:␣OPEN_PARENTHESIS␣string_expression␣CL\
        OSE_PARENTHESIS’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    strcpy( $$ , $2 );
  }
  ;
```

651. string secondary. [LDF 2006.11.16.]

Log

[LDF 2006.11.16.] Added this type declaration.

⟨ Type declarations for non-terminal symbols 432 ⟩ +≡

```
%type␣<string_value>␣string_secondary
```

652. ⟨string secondary⟩ ⟶ ⟨string primary⟩**.** [LDF 2006.11.16.]

Log

[LDF 2006.11.16.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
string_secondary:␣string_primary
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘string_secondary:␣string_primary’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    strcpy($$, $1);
  }
  ;
```

653. string tertiary. [LDF 2006.11.16.]

Log

[LDF 2006.11.16.] Added this type declaration.

⟨ Type declarations for non-terminal symbols 432 ⟩ +≡

```
%type␣<string_value>␣string_tertiary
```

654. ⟨string tertiary⟩ ⟶ ⟨string secondary⟩. [LDF 2006.11.16.]

Log

[LDF 2006.11.16.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
string_tertiary:␣string_secondary
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘string_tertiary:␣string_secondary’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    strcpy( $$ , $1 );
  }
  ;
```

655. string expression. [LDF 2006.11.16.]

Log

[LDF 2006.11.16.] Added this type declaration.

⟨ Type declarations for non-terminal symbols 432 ⟩ +≡

```
%type␣<string_value>␣string_expression
```

656. ⟨string expression⟩ ⟶ ⟨string tertiary⟩. [LDF 2006.11.16.]

Log

[LDF 2006.11.16.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
string_expression:␣string_tertiary
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘string_expression:␣string_tertiary’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    strcpy( $$ , $1 );
  }
  ;
```

657. Datetime expressions (dttmexp.w). [LDF 2006.12.15.]

Log

[LDF 2006.12.15.] Added this file.

658.

⟨ dttmexp.w 658 ⟩ ≡

```
static char dttmexp_id_string[] = "$Id:␣dttmexp.w,v␣1.5␣2007/02/13␣20:38:33␣lfinsto1␣Exp␣$";
```

This code is cited in sections 7 and 8.

This code is used in section 675.

659. datetime primary. [LDF 2006.12.15.]

Log

[LDF 2006.12.15.] Added this type declaration.

⟨ Type declarations for non-terminal symbols 432 ⟩ +≡

```
%type␣<pointer_value>␣datetime_primary
```

660. ⟨datetime primary⟩ ⟶ ⟨datetime variable⟩. [LDF 2006.12.15.]

Log

[LDF 2006.12.15.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  datetime_primary: datetime_variable
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘datetime_primary: datetime_variable’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    Id_Node curr_id_node = static_cast⟨Id_Node⟩($1);
    if (curr_id_node ∧ curr_id_node→value) {
      Date_Time_Node curr_datetime_node = new Date_Time_Type;
      *curr_datetime_node = *static_cast⟨Date_Time_Node⟩(curr_id_node→value);
      $$ = static_cast⟨void *⟩(curr_datetime_node);
    }
    else $$ = 0;
#ifdef DEBUG_OUTPUT
    temp_strm ≪ endl ≪ "Exiting rule ‘datetime_primary: datetime_variable’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
  }
  ;
```

661. ⟨datetime primary⟩ ⟶ (⟨datetime expression⟩). [LDF 2006.12.15.]

Log

[LDF 2006.12.15.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  datetime_primary:␣OPEN_PARENTHESIS␣datetime_expression␣CLOSE_PARENTHESIS
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘datetime_primary:␣OPEN_PARENTHESIS␣" ≪
        "datetime_expression␣CLOSE_PARENTHESIS’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    Date_Time_Node q = static_cast⟨Date_Time_Node⟩( $2 );
    $$ = $2;
  }
  ;
```

662. ⟨datetime primary⟩ ⟶ ⟨datetime element list⟩. [LDF 2006.12.18.]

Log

[LDF 2006.12.18.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
datetime_primary:␣datetime_element_list
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘datetime_primary:␣datetime_element_list." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    Date_Time_Node d = 0;
    datetime_assignment_func_1 (scanner_node, d, ASSIGN, $1);
    $$ = static_cast⟨void *⟩(d);
  }
  ;
```

663. datetime secondary. [LDF 2006.12.15.]

Log

[LDF 2006.12.15.] Added this type declaration.

⟨ Type declarations for non-terminal symbols 432 ⟩ +≡

```
%type␣<pointer_value>␣datetime_secondary
```

664. ⟨datetime secondary⟩ ⟶ ⟨datetime primary⟩. [LDF 2006.12.15.]

Log

[LDF 2006.12.15.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
datetime_secondary: datetime_primary
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘datetime_secondary: datetime_primary’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = $1;
  }
  ;
```

665. datetime tertiary. [LDF 2006.12.15.]

Log

[LDF 2006.12.15.] Added this type declaration.

⟨ Type declarations for non-terminal symbols 432 ⟩ +≡

```
%type <pointer_value> datetime_tertiary
```

666. ⟨datetime tertiary⟩ —→ ⟨datetime secondary⟩**.** [LDF 2006.12.15.]

Log

[LDF 2006.12.15.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
datetime_tertiary:␣datetime_secondary
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘datetime_tertiary:␣datetime_secondary’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = $1;
  }
  ;
```

667. datetime expression. [LDF 2006.12.15.]

Log

[LDF 2006.12.15.] Added this type declaration.

⟨ Type declarations for non-terminal symbols 432 ⟩ +≡

```
%type␣<pointer_value>␣datetime_expression
```

668. ⟨datetime expression⟩ ⟶ ⟨datetime tertiary⟩. [LDF 2006.12.15.]

Log

[LDF 2006.12.15.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
datetime_expression: datetime_tertiary
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘datetime_expression: datetime_tertiary’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    $$ = $1;
  }
  ;
```

669. Datetime element list. [LDF 2006.12.18.]

Log

[LDF 2006.12.18.] Added this type declaration.

⟨ Type declarations for non-terminal symbols 432 ⟩ +≡

```
%type <pointer_value> datetime_element_list
```

670. ⟨datetime element list⟩ —→ INTEGER COLON INTEGER. [LDF 2006.12.18.]

Log

[LDF 2006.12.18.] Added this rule.

```
⟨ Parser rules 421 ⟩ +≡
  datetime_element_list:␣INTEGER␣COLON
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘datetime_element_list:␣INTEGER␣COLON␣INTEGER’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    vector⟨pair⟨int, void *⟩⟩ *v = new vector⟨pair⟨int, void *⟩⟩;
    int *i = new int( $1 );
    v→push_back(make_pair(INTEGER, static_cast⟨void *⟩(i)));
    $$ = static_cast⟨void *⟩(v);
  }
  ;
```

671. ⟨datetime element list⟩ ⟶ `FLOAT COLON.` [LDF 2006.12.18.]

Log

[LDF 2006.12.18.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
datetime_element_list: FLOAT COLON
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘datetime_element_list: FLOAT COLON’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    vector⟨pair⟨int, void *⟩⟩ *v = new vector⟨pair⟨int, void *⟩⟩;
    float *f = new float( $1 );
    v→push_back(make_pair(FLOAT, static_cast⟨void *⟩(f)));
    $$ = static_cast⟨void *⟩(v);
  }
  ;
```

672. ⟨datetime element list⟩ ⟶ ⟨datetime element list⟩ COLON INTEGER. [LDF 2006.12.18.]

Log

[LDF 2006.12.18.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
datetime_element_list:␣datetime_element_list␣INTEGER␣COLON
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule␣‘datetime_element_list:␣datetime_element_list␣" ≪
        "INTEGER␣COLON’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    vector⟨pair⟨int, void *⟩⟩ *v = static_cast⟨vector⟨pair⟨int, void *⟩⟩ *⟩($1);
    int *i = new int($2);
    v→push_back(make_pair(INTEGER, static_cast⟨void *⟩(i)));
    $$ = static_cast⟨void *⟩(v);
  }
  ;
```

673. ⟨datetime element list⟩ −→ ⟨datetime element list⟩ `FLOAT COLON`. [LDF 2006.12.18.]

Log

[LDF 2006.12.18.] Added this rule.

⟨ Parser rules 421 ⟩ +≡

```
datetime_element_list: datetime_element_list FLOAT COLON
  {
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(parameter);
    temp_strm ≪ endl ≪ "Rule ‘datetime_element_list: datetime_element_list " ≪
        "FLOAT COLON’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    vector⟨pair⟨int, void *⟩⟩ *v = static_cast⟨vector⟨pair⟨int, void *⟩⟩ *⟩($1);
    float *f = new float($2);
    v→push_back(make_pair(FLOAT, static_cast⟨void *⟩(f)));
    $$ = static_cast⟨void *⟩(v);
  }
  ;
```

674. Putting the parser together.

675. Filename sections. These sections contain the CVS ID strings for the individual parser files. [LDF 2006.10.31.] ∎

Log

[2006.10.31.] Added this section.

⟨ Filename sections 675 ⟩ ≡

```
⟨ parser.w 392 ⟩
⟨ declrtns.w 434 ⟩
⟨ grpstmnt.w 431 ⟩
⟨ variabls.w 455 ⟩
⟨ assign.w 479 ⟩
⟨ queryexp.w 612 ⟩
⟨ dtsrcexp.w 636 ⟩
⟨ commands.w 598 ⟩
⟨ strings.w 646 ⟩
⟨ dttmexp.w 658 ⟩
```

This code is used in sections 676 and 677.

676. This is what's written to `parser.yyy`. [LDF 2006.10.20.]

⟨ `parser.yyy` 676 ⟩ ≡

```
%{
⟨ Include files 10 ⟩
⟨ Filename sections 675 ⟩
⟨ Declare yylex 305 ⟩
⟨ Declare yyerror 395 ⟩
#define YYPARSE_PARAM parameter
#define YYLEX_PARAM parameter
  stringstream temp_strm;
%}
⟨ union declaration for YYSTYPE 368 ⟩
⟨ Bison declarations 397 ⟩
⟨ Token and type declarations 370 ⟩
⟨ Type declarations for non-terminal symbols 432 ⟩
%%
⟨ Parser rules 421 ⟩
```

677. This is what *isn't* compiled. The file `parser.c` isn't compiled, but including ⟨ `parser.w` 392 ⟩ here prevents CWEAVE from issuing a warning. [LDF 2006.10.24.]

```
⟨ Filename sections 675 ⟩
#if 0    /* 1 */
⟨ Garbage 426 ⟩
#endif
```

678. Parser functions (`prsrfncs.web`). [LDF 2006.10.31.]

Log

[LDF 2006.10.31.] Created this file.

⟨ `prsrfncs.web` 678 ⟩ ≡

```
static char id_string[] = "$Id: prsrfncs.web,v 1.6 2007/02/13 20:39:45 lfinsto1 Exp $";
```

This code is used in section 728.

679. Include files.

⟨ Include files 10 ⟩ +≡

```
#include "localldf.h"
#ifdef NON_WIN_LDF
#include "nonwin.h"
#else
#include "stdafx.h"
#endif
#include "parser.hxx"
#include "dttmtype.h"
#include "idtype.h"
#include "scnrtype.h"
#include "scanner.h"
#include "querytyp.h"
#include "dtsrctyp.h"
```

680. Preprocessor macro calls.

⟨ Preprocessor macro calls 23 ⟩ +≡

```
#ifdef WIN_LDF
#pragma once
#endif
```

681. Parser function definitions. [LDF 2006.10.31.]

682. Functions for variables. [LDF 2006.11.02.]

Log

[2006.11.02.] Added this section.

683. *variable_func.* [LDF 2006.11.02.]

Log

[2006.11.02.] Added this function.

```
⟨ Define parser functions 683 ⟩ ≡
  void *Scan_Parse::variable_func(void *v, char *name){
#if 0     /* 1 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
      stringstream temp_strm;
      Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(v);
#ifdef DEBUG_OUTPUT
      temp_strm ≪ "Entering␣`Scan_Parse::variable_func'." ≪ endl ≪ "`name'␣==␣" ≪ name ≪
          endl;
      cerr_mutex.lock();
      cerr ≪ temp_strm.str();
      cerr_mutex.unlock();
      if (scanner_node ≠ 0) scanner_node→log_strm ≪ temp_strm.str();
      temp_strm.str("");
#endif
```

See also sections 684, 685, 686, 687, 688, 689, 691, 692, 693, 695, 696, 697, 698, 699, 701, 702, 703, 704, 705, 706, 707, 708, 709, 710, 711, 712, 713, 714, 715, 716, 717, 718, 719, 720, 721, 722, 723, 724, 725, and 726.

This code is used in section 728.

684. Error handling: *scanner_node* ≡ 0. This shouldn't ever happen. If it does, we can't continue. [LDF 2006.11.01.]

```
⟨ Define parser functions 683 ⟩ +≡
  if (scanner_node ≡ 0) {
    temp_strm ≪ "ERROR!␣␣In␣`Scan_Parse::variable_func':" ≪
        "`scanner_node'␣==␣0.␣␣Can't␣continue." ≪ endl ≪
        "Exiting␣function␣unsuccessfully␣with␣return␣value␣0." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    temp_strm.str("");
    return 0;
  }     /* if (scanner_node ≡ 0) */
  map⟨string, Id_Node⟩::iterator iter = scanner_node→id_map.find(name);
```

685. Error handling: *name* not found in *scanner_node→id_map*. [LDF 2006.11.03.]

```
⟨ Define parser functions 683 ⟩ +≡
  if (iter ≡ scanner_node→id_map.end()) {
    temp_strm ≪ "ERROR!␣␣In␣‘Scan_Parse::variable_func’:" ≪ endl ≪
        "‘" ≪ name ≪ "’␣not␣found␣in␣‘scanner_node->id_map’." ≪ endl ≪
        "Exiting␣function␣unsuccessfully␣with␣return␣value␣0." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    if (scanner_node ≠ 0) scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
    scanner_node→float_vector.clear();
    return 0;
  }     /* if (iter ≡ scanner_node→id_map.end()) */
```

686. *name* found in *scanner_node→id_map*. [LDF 2006.11.03.]

```
⟨ Define parser functions 683 ⟩ +≡
  else      /* iter ≠ scanner_node→id_map.end() */
  { Id_Node curr_id_node = 0;
#ifdef DEBUG_OUTPUT
  temp_strm ≪ "In␣‘Scan_Parse::variable_func’:" ≪ endl ≪ "‘" ≪ name ≪
      "’␣found␣in␣‘scanner_node->id_map’." ≪ endl;
  cerr_mutex.lock();
  cerr ≪ temp_strm.str();
  cerr_mutex.unlock();
  if (scanner_node ≠ 0) scanner_node→log_strm ≪ temp_strm.str();
  temp_strm.str("");
#endif
```

687. *name* doesn't refer to an array. [LDF 2006.11.03.]

```
⟨ Define parser functions 683 ⟩ +≡
  if (strchr(name, '¥') ≡ 0) {
    curr_id_node = iter→second;
  }     /* if (strchr(name, '¥') ≡ 0) */
```

688. *name* refers to an array. [LDF 2006.11.03.]

```
⟨ Define parser functions 683 ⟩ +≡
  else      /* (strchr(name, '¥') ≠ 0) */
  {
#ifdef DEBUG_OUTPUT
    temp_strm ≪ "‘name’␣(‘" ≪ name ≪ "’)␣contains␣" ≪ scanner_node→float_vector.size() ≪
        "␣subscript␣placeholder";
    if (scanner_node→float_vector.size() > 1) temp_strm ≪ "s";
    temp_strm ≪ "." ≪ endl;
#endif
    int i = 0;
    for (vector⟨float⟩::const_iterator subscript_iter = scanner_node→float_vector.begin();
        subscript_iter ≠ scanner_node→float_vector.end(); ++subscript_iter) {
#ifdef DEBUG_OUTPUT
      temp_strm ≪ "Subscript␣" ≪ i++ ≪ "␣==␣" ≪ *subscript_iter ≪ endl;
#endif
    }     /* for */
#ifdef DEBUG_OUTPUT
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    curr_id_node = scanner_node→lookup(name, true, iter→second→type);
  }     /* else (strchr(name, '¥') ≠ 0) */
```

689. Push a **Token_Type** object onto *scanner_node→token_stack*. [LDF 2006.11.03.]

```
⟨ Define parser functions 683 ⟩ +≡
  YYSTYPE curr_value;
  curr_value.pointer_value = static_cast⟨void *⟩(curr_id_node);
  scanner_node→token_stack.push(Token_Type(curr_id_node→type, curr_value));
#ifdef DEBUG_OUTPUT
  temp_strm ≪ "Exiting␣'Scan_Parse::variable_func'␣successfully␣" ≪
      "with␣return␣value␣'curr_id_node'␣(cast␣to␣'void*')." ≪ endl;
  cerr_mutex.lock( );
  cerr ≪ temp_strm.str( );
  cerr_mutex.unlock( );
  scanner_node→log_strm ≪ temp_strm.str( );
  temp_strm.str("");
#endif
  scanner_node→float_vector.clear( );
  return static_cast⟨void *⟩(curr_id_node); }      /* else (iter ≠ scanner_node→id_map.end( )) */
#undef DEBUG_OUTPUT
  }      /* End of Scan_Parse::variable_func definition. */
```

690. Functions for declarations. [LDF 2006.11.01.]

Log

[LDF 2006.11.01.] Added this section.

691. Declare variable function. [LDF 2006.11.01.]

Log

[2006.11.01.] Added this function.

[LDF 2006.11.01.] Added the **char** $*name$ argument.

[LDF 2006.11.02.] Changed the return value to **Id_Node**. Now returning *curr_id_node* if successful, or 0 if not.

⟨ Define parser functions 683 ⟩ +≡

```
  Id_Node Scan_Parse::declare_variable_func(void *v, const unsigned short type, char *name){
#if 0     /* 1 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
      stringstream temp_strm;
      Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(v);
#ifdef DEBUG_OUTPUT
      temp_strm ≪ "Entering ‘Scan_Parse::declare_variable_func’." ≪ endl ≪ "‘type’ == ‘" ≪
          token_map[type] ≪ "’" ≪ endl ≪ "‘name’ == " ≪ name ≪ endl;
      cerr_mutex.lock();
      cerr ≪ temp_strm.str();
      cerr_mutex.unlock();
      if (scanner_node ≠ 0) scanner_node→log_strm ≪ temp_strm.str();
      temp_strm.str("");
#endif
```

692. Error handling: *scanner_node* ≡ 0. This shouldn't ever happen. If it does, we can't continue. [LDF 2006.11.01.]

⟨ Define parser functions 683 ⟩ +≡

```
  if (scanner_node ≡ 0) {
    temp_strm ≪ "ERROR!  In ‘Scan_Parse::declare_variable_func’:" ≪
        "‘scanner_node’ == 0.  Can’t continue." ≪ endl ≪
        "Exiting function unsuccessfully with return value 0." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    temp_strm.str("");
    return 0;
  }     /* if (scanner_node ≡ 0) */
```

693.

Log

[LDF 2006.11.02.] Now setting *curr_id_node→scanner_node* = *scanner_node*.

⟨ Define parser functions 683 ⟩ +≡

```
  Id_Node curr_id_node = new Id_Type;
  curr_id_node→name = name;
  curr_id_node→type = type;
  curr_id_node→scanner_node = scanner_node;
  scanner_node→id_map[curr_id_node→name] = curr_id_node;
#ifdef DEBUG_OUTPUT
  temp_strm ≪ "‘scanner_node->id_map[curr_id_node->name]->name’␣==␣" ≪
      scanner_node→id_map[curr_id_node→name]→name ≪ endl ≪
      "‘scanner_node->id_map[curr_id_node->name]->type’␣==␣‘" ≪
      token_map[scanner_node→id_map[curr_id_node→name]→type] ≪ "’" ≪ endl;
  cerr_mutex.lock();
  cerr ≪ temp_strm.str();
  cerr_mutex.unlock();
  scanner_node→log_strm ≪ temp_strm.str();
  temp_strm.str("");
#endif
#ifdef DEBUG_OUTPUT
  temp_strm ≪ endl ≪ "Exiting␣‘Scan_Parse::declare_variable_func’." ≪ endl;
  cerr_mutex.lock();
  cerr ≪ temp_strm.str();
  cerr_mutex.unlock();
  scanner_node→log_strm ≪ temp_strm.str();
  temp_strm.str("");
#endif
  return curr_id_node;
#undef DEBUG_OUTPUT
  }    /* End of Scan_Parse::declare_variable_func definition. */
```

694. Functions for assignments. [LDF 2006.11.02.]

Log

[LDF 2006.11.02.] Added this section.

695. *query_assignment_func_0.* [LDF 2006.11.02.]

Log

[LDF 2006.11.02.] Added this function.

[LDF 2006.11.13.] Added the arguments **unsigned int** *arg_0*, **unsigned int** *arg_1*, and **void** ∗*value*.

```
⟨ Define parser functions 683 ⟩ +≡
  void ∗Scan_Parse::query_assignment_func_0(void ∗v, void ∗object, unsigned int
        assignment_type, unsigned int arg_0, unsigned int arg_1, void ∗value, bool negate){
#if 1     /∗ 0 ∗/
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
    stringstream temp_strm;
    Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(v);
#ifdef DEBUG_OUTPUT
    temp_strm ≪ "Entering␣‘Scan_Parse::query_assignment_func_0’." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    if (scanner_node ≠ 0) scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
```

696. Error handling: *scanner_node* ≡ 0. This shouldn't ever happen. If it does, we can't continue. [LDF 2006.11.01.]

```
⟨ Define parser functions 683 ⟩ +≡
  if (scanner_node ≡ 0) {
    temp_strm ≪ "ERROR!␣␣In␣‘Scan_Parse::query_assignment_func_0’:" ≪
        "‘scanner_node’␣==␣0.␣␣Can’t␣continue." ≪ endl ≪
        "Exiting␣function␣unsuccessfully␣with␣return␣value␣0." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    temp_strm.str("");
    return 0;
  }     /∗ if (scanner_node ≡ 0) ∗/
```

697.

```
⟨ Define parser functions 683 ⟩ +≡
  if (object ≡ 0) {
    temp_strm ≪ "ERROR!␣␣In␣'Scan_Parse::query_assignment_func_0':" ≪
        endl ≪ "'object'␣==␣0.␣␣Can't␣perform␣assignment." ≪ endl ≪
        "Exiting␣function␣unsuccessfully␣with␣return␣value␣0." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
    return 0;
  }     /* if (object ≡ 0) */
```

698.

```
⟨ Define parser functions 683 ⟩ +≡
  Id_Node curr_id_node = static_cast⟨Id_Node⟩(object);
  Query_Node curr_query_node = 0;
  if (curr_id_node→value ≡ 0) {
    curr_query_node = new Query_Type;
    curr_query_node→query_type = Query_Type::TOP_TYPE;
    curr_query_node→id_node = curr_id_node;
    curr_query_node→name = curr_id_node→name;
    curr_query_node→scanner_node = scanner_node;
    curr_id_node→value = static_cast⟨void *⟩(curr_query_node);
  }     /* if (curr_id_node→value ≡ 0) */
  else {
    curr_query_node = static_cast⟨Query_Node⟩(curr_id_node→value);
  }
#if 0     /* 1 */
#ifdef DEBUG_OUTPUT
  temp_strm ≪ "arg_0␣==␣" ≪ token_map[arg_0] ≪ endl ≪ "arg_1␣==␣" ≪ token_map[arg_1] ≪ endl;
  cerr_mutex.lock();
  cerr ≪ temp_strm.str();
  cerr_mutex.unlock();
  scanner_node→log_strm ≪ temp_strm.str();
  temp_strm.str("");
#endif
#endif
```

699. Targets. [LDF 2006.11.13.]

Log

[2006.11.13.] Added this section.

```
⟨ Define parser functions 683 ⟩ +≡
  if (arg_0 ≡ LOCAL) {
    if (arg_1 ≡ DATABASE ∧ find(curr_query_node→target_types.begin(), curr_query_node→target_types.end(),
          Query_Type::LOCAL_DATABASE_TARGET) ≡ curr_query_node→target_types.end())
      curr_query_node→target_types.push_back(Query_Type::LOCAL_DATABASE_TARGET);
    else if (arg_1 ≡ SERVER∧find(curr_query_node→target_types.begin(), curr_query_node→target_types.end(),
          Query_Type::LOCAL_SERVER_TARGET) ≡ curr_query_node→target_types.end())
      curr_query_node→target_types.push_back(Query_Type::LOCAL_SERVER_TARGET);
  }    /* if (arg_0 ≡ LOCAL) */
  else if (arg_0 ≡ REMOTE) {
    if (arg_1 ≡ DATABASE ∧ find(curr_query_node→target_types.begin(), curr_query_node→target_types.end(),
          Query_Type::REMOTE_DATABASE_TARGET) ≡ curr_query_node→target_types.end())
      curr_query_node→target_types.push_back(Query_Type::REMOTE_DATABASE_TARGET);
    else if (arg_1 ≡ SERVER∧find(curr_query_node→target_types.begin(), curr_query_node→target_types.end(),
          Query_Type::REMOTE_SERVER_TARGET) ≡ curr_query_node→target_types.end())
      curr_query_node→target_types.push_back(Query_Type::REMOTE_SERVER_TARGET);
  }    /* else if (arg_0 ≡ REMOTE) */
```

700. Fields. [LDF 2006.11.13.]

Log

[2006.11.13.] Added this section.

701. Fields. [LDF 2006.11.14.]

Log

[LDF 2006.11.14.] Added this section.

[LDF 2006.12.05.] Added code for CREATOR.

[LDF 2006.12.12.] Added code for MAIN_CANONICAL_TITLE.

[LDF 2006.12.12.] Added code to account for tokens that refer to additional tables from the OAI database (dc_test).

[LDF 2006.12.12.] Added code to account for the tokens that refer to additional tables in the PICA database (PICA_DB).

```
⟨ Define parser functions 683 ⟩ +≡
  if (arg_0 ≡ ACCESS_NUMBER ∨ arg_0 ≡ AUTHOR ∨ arg_0 ≡ BIBLIOGRAPHIC_TYPE ∨ arg_0 ≡
      CALL_NUMBER ∨ arg_0 ≡ CLASSIFICATION ∨ arg_0 ≡ COMPANY ∨ arg_0 ≡ CONTENT_SUMMARY ∨ arg_0 ≡
      CONTRIBUTOR ∨ arg_0 ≡ CREATOR ∨ arg_0 ≡ DATABASE_PROVIDER ∨ arg_0 ≡ DESCRIPTION ∨ arg_0 ≡
      EXEMPLAR_PRODUCTION_NUMBER ∨ arg_0 ≡ IDENTIFIER ∨ arg_0 ≡ INSTITUTION ∨ arg_0 ≡
      LANGUAGE ∨ arg_0 ≡ MAIN_CANONICAL_TITLE ∨ arg_0 ≡ PERMUTATION_PATTERN ∨ arg_0 ≡
      PERSON ∨ arg_0 ≡ PHYSICAL_DESCRIPTION ∨ arg_0 ≡ PUBLISHER ∨ arg_0 ≡ RECORD ∨ arg_0 ≡
      REMOTE_ACCESS ∨ arg_0 ≡ RIGHTS ∨ arg_0 ≡ SOURCE ∨ arg_0 ≡ SUBJECT ∨ arg_0 ≡
      SUPERORDINATE_ENTITIES ∨ arg_0 ≡ TITLE ∨ arg_0 ≡ TYPE) { unsigned int curr_field_type;
  if (arg_0 ≡ ACCESS_NUMBER) curr_field_type = Query_Type::ACCESS_NUMBER_FIELD;
  else if (arg_0 ≡ AUTHOR) curr_field_type = Query_Type::AUTHOR_FIELD;
  else if (arg_0 ≡ BIBLIOGRAPHIC_TYPE) curr_field_type = Query_Type::BIBLIOGRAPHIC_TYPE_FIELD;
  else if (arg_0 ≡ CALL_NUMBER) curr_field_type = Query_Type::CALL_NUMBER_FIELD;
  else if (arg_0 ≡ CLASSIFICATION) curr_field_type = Query_Type::CLASSIFICATION_FIELD;
  else if (arg_0 ≡ COMPANY) curr_field_type = Query_Type::COMPANY_FIELD;
  else if (arg_0 ≡ CONTENT_SUMMARY) curr_field_type = Query_Type::CONTENT_SUMMARY_FIELD;
  else if (arg_0 ≡ CONTRIBUTOR) curr_field_type = Query_Type::CONTRIBUTOR_FIELD;
  else if (arg_0 ≡ CREATOR) curr_field_type = Query_Type::CREATOR_FIELD;
  else if (arg_0 ≡ DATABASE_PROVIDER) curr_field_type = Query_Type::DATABASE_PROVIDER_FIELD;
  else if (arg_0 ≡ DESCRIPTION) curr_field_type = Query_Type::DESCRIPTION_FIELD;
  else if (arg_0 ≡ EXEMPLAR_PRODUCTION_NUMBER)
    curr_field_type = Query_Type::EXEMPLAR_PRODUCTION_NUMBER_FIELD;
  else if (arg_0 ≡ IDENTIFIER) curr_field_type = Query_Type::IDENTIFIER_FIELD;
  else if (arg_0 ≡ INSTITUTION) curr_field_type = Query_Type::INSTITUTION_FIELD;
  else if (arg_0 ≡ LANGUAGE) curr_field_type = Query_Type::LANGUAGE_FIELD;
  else if (arg_0 ≡ MAIN_CANONICAL_TITLE)
    curr_field_type = Query_Type::MAIN_CANONICAL_TITLE_FIELD;
  else if (arg_0 ≡ PERMUTATION_PATTERN)
    curr_field_type = Query_Type::PERMUTATION_PATTERN_FIELD;
  else if (arg_0 ≡ PERSON) curr_field_type = Query_Type::PERSON_FIELD;
  else if (arg_0 ≡ PHYSICAL_DESCRIPTION)
    curr_field_type = Query_Type::PHYSICAL_DESCRIPTION_FIELD;
  else if (arg_0 ≡ PUBLISHER) curr_field_type = Query_Type::PUBLISHER_FIELD;
  else if (arg_0 ≡ RECORD) curr_field_type = Query_Type::RECORD_FIELD;
  else if (arg_0 ≡ REMOTE_ACCESS) curr_field_type = Query_Type::REMOTE_ACCESS_FIELD;
  else if (arg_0 ≡ RIGHTS) curr_field_type = Query_Type::RIGHTS_FIELD;
  else if (arg_0 ≡ SOURCE) curr_field_type = Query_Type::SOURCE_FIELD;
  else if (arg_0 ≡ SUBJECT) curr_field_type = Query_Type::SUBJECT_FIELD;
```

```
else if (arg_0 ≡ SUPERORDINATE_ENTITIES)
  curr_field_type = Query_Type::SUPERORDINATE_ENTITIES_FIELD;
else if (arg_0 ≡ TITLE) curr_field_type = Query_Type::TITLE_FIELD;
else if (arg_0 ≡ TYPE) curr_field_type = Query_Type::TYPE_FIELD;
while (curr_query_node→query_type ≠ Query_Type::TOP_TYPE)
  curr_query_node = curr_query_node→up;
if (curr_query_node→field_type ≡ Query_Type::QUERY_TYPE_NULL_TYPE ∧ curr_query_node→value ≡ 0) {
  curr_query_node→field_type = curr_field_type;
  string *curr_string = new string;
  *curr_string = static_cast⟨char *⟩(value);
  curr_query_node→value = static_cast⟨void *⟩(curr_string);
  curr_query_node→value_type = Query_Type::QUERY_TYPE_STRING_TYPE;
  curr_query_node→negated = negate;
}
```

702.

Log

[2006.11.14.] Added this section.

```
⟨ Define parser functions 683 ⟩ +≡
  else {
    if (assignment_type ≡ ASSIGN ∨ assignment_type ≡ PLUS_ASSIGN) {
      while (curr_query_node→and_node ≠ 0) curr_query_node = curr_query_node→and_node;
      curr_query_node→and_node = new Query_Type;
      curr_query_node→and_node→query_ctr = curr_query_node→query_ctr + 1;
      curr_query_node→and_node→id_node = curr_id_node;
      curr_query_node→and_node→name = curr_id_node→name;
    }
    else if (assignment_type ≡ OR_ASSIGN) {
      while (curr_query_node→or_node ≠ 0) curr_query_node = curr_query_node→or_node;
      curr_query_node→or_node = new Query_Type;
      curr_query_node→or_node→query_ctr = curr_query_node→query_ctr + 1;
      curr_query_node→or_node→id_node = curr_id_node;
      curr_query_node→or_node→name = curr_id_node→name;
    }
    else if (assignment_type ≡ XOR_ASSIGN) {
      while (curr_query_node→xor_node ≠ 0) curr_query_node = curr_query_node→xor_node;
      curr_query_node→xor_node = new Query_Type;
      curr_query_node→xor_node→query_ctr = curr_query_node→query_ctr + 1;
      curr_query_node→xor_node→id_node = curr_id_node;
      curr_query_node→xor_node→name = curr_id_node→name;
    }
    if (curr_query_node→query_type ≡ Query_Type::TOP_TYPE) {
      if (assignment_type ≡ ASSIGN ∨ assignment_type ≡ PLUS_ASSIGN) {
        curr_query_node→and_node→up = curr_query_node;
      }
      else if (assignment_type ≡ OR_ASSIGN) {
        curr_query_node→or_node→up = curr_query_node;
      }
      else if (assignment_type ≡ XOR_ASSIGN) {
        curr_query_node→xor_node→up = curr_query_node;
      }
    }    /* if */
    else {
      if (assignment_type ≡ ASSIGN ∨ assignment_type ≡ PLUS_ASSIGN) {
        curr_query_node→and_node→up = curr_query_node→up;
      }
      else if (assignment_type ≡ OR_ASSIGN) {
        curr_query_node→or_node→up = curr_query_node→up;
      }
      else if (assignment_type ≡ XOR_ASSIGN) {
        curr_query_node→xor_node→up = curr_query_node→up;
      }
    }    /* else */
    if (assignment_type ≡ ASSIGN ∨ assignment_type ≡ PLUS_ASSIGN) {
```

```
    curr_query_node = curr_query_node→and_node;
    curr_query_node→query_type = Query_Type::AND_TYPE;
    curr_query_node→field_type = curr_field_type;
  }
  else if (assignment_type ≡ OR_ASSIGN) {
    curr_query_node = curr_query_node→or_node;
    curr_query_node→query_type = Query_Type::OR_TYPE;
    curr_query_node→field_type = curr_field_type;
  }
  else if (assignment_type ≡ XOR_ASSIGN) {
    curr_query_node = curr_query_node→xor_node;
    curr_query_node→query_type = Query_Type::XOR_TYPE;
    curr_query_node→field_type = curr_field_type;
  }
  string *curr_string = new string;
  *curr_string = static_cast⟨char *⟩(value);
  curr_query_node→value = static_cast⟨void *⟩(curr_string);
  curr_query_node→value_type = Query_Type::QUERY_TYPE_STRING_TYPE;
  curr_query_node→negated = negate;
}    /* else */
}    /* if */
#ifdef DEBUG_OUTPUT
  temp_strm ≪ "Exiting␣‘Scan_Parse::query_assignment_func_0’␣successfully␣" ≪ endl ≪
      "with␣return␣value␣‘curr_query_node’,␣cast␣to␣‘void*’." ≪ endl;
  cerr_mutex.lock();
  cerr ≪ temp_strm.str();
  cerr_mutex.unlock();
  if (scanner_node ≠ 0) scanner_node→log_strm ≪ temp_strm.str();
  temp_strm.str("");
#endif
  return static_cast⟨void *⟩(curr_query_node); }
    /* End of Scan_Parse::query_assignment_func_0 definition. */
```

703. *query_assignment_func_1.* [LDF 2006.12.19.]

Log

[LDF 2006.12.19.] Added this function.

```
⟨ Define parser functions 683 ⟩ +≡
  int Scan_Parse::query_assignment_func_1(Scanner_Node scanner_node, Id_Node &curr_id_node, void
        *&field_specifier, int assignment_operator, int negation_optional, int match_term_optional, void
        *&v, int type){ stringstream temp_strm;
#if 1    /* 0 */
#define DEBUG_OUTPUT
#else
# # undef DEBUG_OUTPUT
#endif
#ifdef DEBUG_OUTPUT
    temp_strm ≪ endl ≪ "Entering␣'Scan_Parse::query_assignment_func_1'." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    Query_Node curr_query = 0;
    Query_Node traverse_query = 0;
    Query_Node temp_query = 0;
    if (assignment_operator ≡ ASSIGN ∨ assignment_operator ≡ PLUS_ASSIGN ∨ assignment_operator ≡
        AND_ASSIGN) {
      if (curr_id_node ∧ curr_id_node→value) {
        curr_query = static_cast⟨Query_Node⟩(curr_id_node→value);
        while (curr_query→and_node ≠ 0) curr_query = curr_query→and_node;
        if (type ≡ QUERY_TYPE) curr_query→and_node = static_cast⟨Query_Node⟩(v);
        else if (type ≡ DATETIME_TYPE) {
          temp_query = new Query_Type;
          temp_query→value_type = Query_Type::DATE_TIME_TYPE;
          temp_query→value = v;
          curr_query→and_node = temp_query;
        }
        curr_query→and_node→query_ctr = curr_query→query_ctr + 1;
        traverse_query = curr_query→or_node;
        while (traverse_query→or_node) traverse_query = traverse_query→or_node;
        if (traverse_query) curr_query→and_node→query_ctr += traverse_query→query_ctr;
        traverse_query = curr_query→xor_node;
        while (traverse_query→xor_node) traverse_query = traverse_query→xor_node;
        if (traverse_query) curr_query→and_node→query_ctr += traverse_query→query_ctr;
        curr_query→and_node→query_type = Query_Type::AND_TYPE;
        curr_query→and_node→up = curr_query;
        curr_query = curr_query→and_node;
        curr_query→set_field_specifier(field_specifier, true, scanner_node);
        curr_query→negated = (negation_optional);
      }    /* if */
      else if (curr_id_node) {
```

```
    if (type ≡ QUERY_TYPE) curr_id_node→value = v;
    else if (type ≡ DATETIME_TYPE) {
      temp_query = new Query_Type;
      temp_query→value_type = Query_Type::DATE_TIME_TYPE;
      temp_query→value = v;
      curr_id_node→value = static_cast⟨void *⟩(temp_query);
    }
    static_cast⟨Query_Node⟩(curr_id_node→value)→id_node = curr_id_node;
    static_cast⟨Query_Node⟩(curr_id_node→value)→name = curr_id_node→name;
    static_cast⟨Query_Node⟩(curr_id_node→value)→query_type = Query_Type::TOP_TYPE;
    static_cast⟨Query_Node⟩(curr_id_node→value)→query_ctr = 0;
    static_cast⟨Query_Node⟩(curr_id_node→value)→set_field_specifier(field_specifier, true,
        scanner_node);
    static_cast⟨Query_Node⟩(curr_id_node→value)→negated = (negation_optional);
    curr_query = static_cast⟨Query_Node⟩(curr_id_node→value);
  }    /* else */
  else {
    if (type ≡ QUERY_TYPE) {
      delete static_cast⟨Query_Node⟩(v);
    }
    else if (type ≡ DATETIME_TYPE) {
      delete static_cast⟨Date_Time_Node⟩(v);
    }
    v = 0;
    curr_query = 0;
  }
}    /* if (assignment_operator ≡ ASSIGN ∨ assignment_operator ≡
      PLUS_ASSIGN ∨ assignment_operator ≡ AND_ASSIGN) */
else if (assignment_operator ≡ OR_ASSIGN) {
  if (curr_id_node ∧ curr_id_node→value) {
    curr_query = static_cast⟨Query_Node⟩(curr_id_node→value);
    while (curr_query→or_node ≠ 0) curr_query = curr_query→or_node;
    if (type ≡ QUERY_TYPE) curr_query→or_node = static_cast⟨Query_Node⟩(v);
    else if (type ≡ DATETIME_TYPE) {
      temp_query = new Query_Type;
      temp_query→value_type = Query_Type::DATE_TIME_TYPE;
      temp_query→value = v;
      curr_query→or_node = temp_query;
    }
    curr_query→or_node→query_type = Query_Type::OR_TYPE;
    curr_query→or_node→query_ctr = curr_query→query_ctr + 1;
    traverse_query = curr_query→and_node;
    while (traverse_query→and_node) traverse_query = traverse_query→and_node;
    if (traverse_query) curr_query→or_node→query_ctr += traverse_query→query_ctr;
    traverse_query = curr_query→xor_node;
    while (traverse_query→xor_node) traverse_query = traverse_query→xor_node;
    if (traverse_query) curr_query→or_node→query_ctr += traverse_query→query_ctr;
    curr_query→or_node→up = curr_query;
    curr_query = curr_query→or_node;
    curr_query→set_field_specifier(field_specifier, true, scanner_node);
    curr_query→negated = (negation_optional);
  }    /* if */
```

```
    else if (curr_id_node) {
      if (type ≡ QUERY_TYPE) curr_id_node→value = v;
      else if (type ≡ DATETIME_TYPE) {
        temp_query = new Query_Type;
        temp_query→value_type = Query_Type::DATE_TIME_TYPE;
        temp_query→value = v;
        curr_id_node→value = static_cast⟨void *⟩(temp_query);
      }
      static_cast⟨Query_Node⟩(curr_id_node→value)→id_node = curr_id_node;
      static_cast⟨Query_Node⟩(curr_id_node→value)→name = curr_id_node→name;
      static_cast⟨Query_Node⟩(curr_id_node→value)→query_type = Query_Type::TOP_TYPE;
      static_cast⟨Query_Node⟩(curr_id_node→value)→set_field_specifier(field_specifier, true,
          scanner_node);
      static_cast⟨Query_Node⟩(curr_id_node→value)→query_ctr = 0;
      static_cast⟨Query_Node⟩(curr_id_node→value)→negated = (negation_optional);
      curr_query = static_cast⟨Query_Node⟩(curr_id_node→value);
    }     /* else */
    else {
      if (type ≡ QUERY_TYPE) {
        delete static_cast⟨Query_Node⟩(v);
      }
      else if (type ≡ DATETIME_TYPE) {
        delete static_cast⟨Date_Time_Node⟩(v);
      }
      v = 0;
      curr_query = 0;
      return 1;
    }
  }     /* if (assignment_operator ≡ OR_ASSIGN) */
  else if (assignment_operator ≡ XOR_ASSIGN) {
    if (curr_id_node ∧ curr_id_node→value) {
      curr_query = static_cast⟨Query_Node⟩(curr_id_node→value);
      while (curr_query→xor_node ≠ 0) curr_query = curr_query→xor_node;
      if (type ≡ QUERY_TYPE) curr_query→xor_node = static_cast⟨Query_Node⟩(v);
      else if (type ≡ DATETIME_TYPE) {
        temp_query = new Query_Type;
        temp_query→value_type = Query_Type::DATE_TIME_TYPE;
        temp_query→value = v;
        curr_query→xor_node = temp_query;
      }
      curr_query→xor_node→query_ctr = curr_query→query_ctr + 1;
      traverse_query = curr_query→and_node;
      while (traverse_query→and_node) traverse_query = traverse_query→and_node;
      if (traverse_query) curr_query→xor_node→query_ctr += traverse_query→query_ctr;
      traverse_query = curr_query→or_node;
      while (traverse_query→or_node) traverse_query = traverse_query→or_node;
      if (traverse_query) curr_query→xor_node→query_ctr += traverse_query→query_ctr;
      curr_query→xor_node→query_type = Query_Type::XOR_TYPE;
      curr_query→xor_node→up = curr_query;
      curr_query = curr_query→xor_node;
      curr_query→set_field_specifier(field_specifier, true, scanner_node);
      curr_query→negated = (negation_optional);
```

```
    }    /* if */
    else if (curr_id_node) {
      if (type ≡ QUERY_TYPE) curr_id_node→value = v;
      else if (type ≡ DATETIME_TYPE) {
        temp_query = new Query_Type;
        temp_query→value_type = Query_Type::DATE_TIME_TYPE;
        temp_query→value = v;
        curr_id_node→value = static_cast⟨void *⟩(temp_query);
      }
      static_cast⟨Query_Node⟩(curr_id_node→value)→id_node = curr_id_node;
      static_cast⟨Query_Node⟩(curr_id_node→value)→name = curr_id_node→name;
      static_cast⟨Query_Node⟩(curr_id_node→value)→query_type = Query_Type::TOP_TYPE;
      static_cast⟨Query_Node⟩(curr_id_node→value)→query_ctr = 0;
      static_cast⟨Query_Node⟩(curr_id_node→value)→set_field_specifier(field_specifier, true,
          scanner_node);
      static_cast⟨Query_Node⟩(curr_id_node→value)→negated = (negation_optional);
      curr_query = static_cast⟨Query_Node⟩(curr_id_node→value);
    }    /* else */
    else {
      if (type ≡ QUERY_TYPE) {
        delete static_cast⟨Query_Node⟩(v);
      }
      else if (type ≡ DATETIME_TYPE) {
        delete static_cast⟨Date_Time_Node⟩(v);
      }
      v = 0;
      curr_query = 0;
      return 1;
    }
  }    /* if (assignment_operator ≡ XOR_ASSIGN) */
```

704.

```
⟨ Define parser functions 683 ⟩ +≡
  else {
    curr_query = 0;
    return 1;
  }
```

705. Set *match_value*. [LDF 2006.12.12.]

Log

[2006.12.12.] Added this section.

```
⟨ Define parser functions 683 ⟩ +≡
  if (curr_query) {
    curr_query→match_value = match_term_optional;
  }    /* if (curr_query) */
```

706.

```
⟨ Define parser functions 683 ⟩ +≡
#ifdef DEBUG_OUTPUT
  temp_strm ≪ endl ≪ "Exiting␣‘Scan_Parse::query_assignment_func_1’␣successfully␣" ≪
      "with␣return␣value␣0." ≪ endl;
  cerr_mutex.lock( );
  cerr ≪ temp_strm.str( );
  cerr_mutex.unlock( );
  scanner_node→log_strm ≪ temp_strm.str( );
  temp_strm.str("");
#endif
  return 0;
#undef DEBUG_OUTPUT
  }    /* End of Scan_Parse::query_assignment_func_1 definition. */
```

707. *datetime_assignment_func_0.* [LDF 2006.12.15.]

Log

[LDF 2006.12.15.] Added this function.

To Do

[LDF 2006.12.18.] Add range checking and code for other assignment operators.

```
⟨ Define parser functions 683 ⟩ +≡
  int Scan_Parse::datetime_assignment_func_0(void *v, Date_Time_Node &curr_date_time_node, int
        specifier, int op, void *val, int type){
#if 1    /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
      stringstream temp_strm;
      Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(v);
#ifdef DEBUG_OUTPUT
      temp_strm ≪ "Entering␣‘Scan_Parse::datetime_assignment_func_0’." ≪ endl;
      cerr_mutex.lock( );
      cerr ≪ temp_strm.str( );
      cerr_mutex.unlock( );
      if (scanner_node ≠ 0) scanner_node→log_strm ≪ temp_strm.str( );
      temp_strm.str("");
#endif
#ifdef DEBUG_OUTPUT
      temp_strm ≪ "‘specifier’␣==␣" ≪ token_map[specifier] ≪ endl ≪ "‘op’␣==␣" ≪
          token_map[op] ≪ endl ≪ "‘type’␣==␣" ≪ token_map[type] ≪ endl;
      cerr_mutex.lock( );
      cerr ≪ temp_strm.str( );
      cerr_mutex.unlock( );
      scanner_node→log_strm ≪ temp_strm.str( );
      temp_strm.str("");
#endif
```

708. Error handling: $val \equiv 0$. [LDF 2006.12.18.]

```
⟨ Define parser functions 683 ⟩ +≡
  if (val ≡ 0) {
    temp_strm ≪ "ERROR!␣␣In␣'Scan_Parse::datetime_assignment_func_0':" ≪
        endl ≪ "'val'␣==␣0'.␣␣Can't␣assign." ≪ endl ≪
        "Exiting␣function␣unsuccessfully␣with␣return␣value␣1." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
    return 1;
  }     /* if (val ≡ 0) */
```

709.

```
⟨ Define parser functions 683 ⟩ +≡
  if (curr_date_time_node ≡ 0) {
    curr_date_time_node = new Date_Time_Type;
  }     /* if (curr_date_time_node ≡ 0) */
```

710.

```
⟨ Define parser functions 683 ⟩ +≡
  if (op ≡ ASSIGN) {
    if (specifier ≡ YEAR_RANGE_BEGIN) {
      if (curr_date_time_node→year_range_begin ≡ 0) curr_date_time_node→year_range_begin = new short;
      *curr_date_time_node→year_range_begin = *static_cast⟨short *⟩(val);
    }     /* if (specifier ≡ YEAR_RANGE_BEGIN) */
    if (specifier ≡ YEAR_RANGE_END) {
      if (curr_date_time_node→year_range_end ≡ 0) curr_date_time_node→year_range_end = new short;
      *curr_date_time_node→year_range_end = *static_cast⟨short *⟩(val);
    }     /* if (specifier ≡ YEAR_RANGE_END) */
    if (specifier ≡ YEAR) {
      if (curr_date_time_node→year ≡ 0) curr_date_time_node→year = new short;
      *curr_date_time_node→year = *static_cast⟨short *⟩(val);
    }     /* if (specifier ≡ YEAR) */
    else if (specifier ≡ MONTH) {
      if (curr_date_time_node→month ≡ 0) curr_date_time_node→month = new unsigned short;
      *curr_date_time_node→month = *static_cast⟨unsigned short *⟩(val);
    }     /* else if (specifier ≡ MONTH) */
    else if (specifier ≡ DAY) {
      if (curr_date_time_node→day ≡ 0) curr_date_time_node→day = new unsigned short;
      *curr_date_time_node→day = *static_cast⟨unsigned short *⟩(val);
    }     /* else if (specifier ≡ DAY) */
    else if (specifier ≡ HOUR) {
      if (curr_date_time_node→hour ≡ 0) curr_date_time_node→hour = new unsigned short;
      *curr_date_time_node→hour = *static_cast⟨unsigned short *⟩(val);
    }     /* else if (specifier ≡ HOUR) */
    else if (specifier ≡ MINUTE) {
      if (curr_date_time_node→minute ≡ 0) curr_date_time_node→minute = new unsigned short;
      *curr_date_time_node→minute = *static_cast⟨unsigned short *⟩(val);
    }     /* else if (specifier ≡ MINUTE) */
    else if (specifier ≡ SECOND) {
      if (curr_date_time_node→second ≡ 0) curr_date_time_node→second = new float;
      if (type ≡ FLOAT) *curr_date_time_node→second = *static_cast⟨float *⟩(val);
      else if (type ≡ INTEGER)
        *curr_date_time_node→second = static_cast⟨float⟩(*static_cast⟨int *⟩(val));
    }     /* else if (specifier ≡ SECOND) */
  }     /* if (op ≡ ASSIGN) */
```

711.

```
⟨ Define parser functions 683 ⟩ +≡
  else
    if (op ≡ PLUS_ASSIGN) {
      if (specifier ≡ YEAR_RANGE_BEGIN) {
        if (curr_date_time_node→year_range_begin ≡ 0)
          curr_date_time_node→year_range_begin = new short(0);
        *curr_date_time_node→year_range_begin += *static_cast⟨short *⟩(val);
      }     /* if (specifier ≡ YEAR_RANGE_BEGIN) */
      if (specifier ≡ YEAR_RANGE_END) {
        if (curr_date_time_node→year_range_end ≡ 0)
          curr_date_time_node→year_range_end = new short(0);
        *curr_date_time_node→year_range_end += *static_cast⟨short *⟩(val);
      }     /* if (specifier ≡ YEAR_RANGE_END) */
      if (specifier ≡ YEAR) {
        if (curr_date_time_node→year ≡ 0) curr_date_time_node→year = new short(0);
        *curr_date_time_node→year += *static_cast⟨short *⟩(val);
      }     /* if (specifier ≡ YEAR) */
      else if (specifier ≡ MONTH) {
        if (curr_date_time_node→month ≡ 0) curr_date_time_node→month = new unsigned short(0);
        *curr_date_time_node→month += *static_cast⟨unsigned short *⟩(val);
      }     /* else if (specifier ≡ MONTH) */
      else if (specifier ≡ DAY) {
        if (curr_date_time_node→day ≡ 0) curr_date_time_node→day = new unsigned short(0);
        *curr_date_time_node→day += *static_cast⟨unsigned short *⟩(val);
      }     /* else if (specifier ≡ DAY) */
      else if (specifier ≡ HOUR) {
        if (curr_date_time_node→hour ≡ 0) curr_date_time_node→hour = new unsigned short(0);
        *curr_date_time_node→hour += *static_cast⟨unsigned short *⟩(val);
      }     /* else if (specifier ≡ HOUR) */
      else if (specifier ≡ MINUTE) {
        if (curr_date_time_node→minute ≡ 0) curr_date_time_node→minute = new unsigned short(0);
        *curr_date_time_node→minute += *static_cast⟨unsigned short *⟩(val);
      }     /* else if (specifier ≡ MINUTE) */
      else if (specifier ≡ SECOND) {
        if (curr_date_time_node→second ≡ 0) curr_date_time_node→second = new float(0);
        if (type ≡ FLOAT) *curr_date_time_node→second += *static_cast⟨float *⟩(val);
        else if (type ≡ INTEGER)
          *curr_date_time_node→second += static_cast⟨float⟩(*static_cast⟨int *⟩(val));
      }     /* else if (specifier ≡ SECOND) */
    }     /* else if (op ≡ PLUS_ASSIGN) */
```

712.

```
⟨ Define parser functions 683 ⟩ +≡
  else
    if (op ≡ MINUS_ASSIGN) { }     /* else if (op ≡ MINUS_ASSIGN) */
```

713.

```
⟨ Define parser functions 683 ⟩ +≡
  else
    if (op ≡ TIMES_ASSIGN) { }     /* else if (op ≡ TIMES_ASSIGN) */
```

714.

```
⟨ Define parser functions 683 ⟩ +≡
  else
    if (op ≡ DIVIDE_ASSIGN) {}      /* else if (op ≡ DIVIDE_ASSIGN) */
```

715. Error handling: *op* has invalid value. [LDF 2006.12.18.]

```
⟨ Define parser functions 683 ⟩ +≡
  else {
    temp_strm ≪ "ERROR!␣␣In␣'Scan_Parse::datetime_assignment_func_0':" ≪ endl ≪
        "'op'␣has␣invalid␣value:␣␣" ≪ token_map[op] ≪ "␣(" ≪ op ≪ ")" ≪ endl ≪
        "Exiting␣function␣unsuccessfully␣with␣return␣value␣1." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
    return 1;
  }     /* else */
#ifdef DEBUG_OUTPUT
  temp_strm ≪ "Exiting␣'Scan_Parse::datetime_assignment_func_0'␣" ≪
      "successfully␣with␣return␣value␣0." ≪ endl;
  cerr_mutex.lock();
  cerr ≪ temp_strm.str();
  cerr_mutex.unlock();
  if (scanner_node ≠ 0) scanner_node→log_strm ≪ temp_strm.str();
  temp_strm.str("");
  getchar();
#endif
  return 0; }      /* End of Scan_Parse::datetime_assignment_func_0 definition. */
```

716. *datetime_assignment_func_1.* [LDF 2006.12.18.]

Log

[LDF 2006.12.18.] Added this function.

To Do

[LDF 2006.12.18.] Add range checking and perhaps code for handling different assignment operators.

```
⟨ Define parser functions 683 ⟩ +≡
  int Scan_Parse::datetime_assignment_func_1(void *v, Date_Time_Node &d, int op, void *&w){
#if 1     /* 0 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
      stringstream temp_strm;
      Scanner_Node scanner_node = static_cast⟨Scanner_Node⟩(v);
#ifdef DEBUG_OUTPUT
      temp_strm << "Entering␣‘Scan_Parse::datetime_assignment_func_1’." << endl;
      cerr_mutex.lock();
      cerr << temp_strm.str();
      cerr_mutex.unlock();
      if (scanner_node ≠ 0) scanner_node→log_strm << temp_strm.str();
      temp_strm.str("");
#endif
```

717.

```
⟨ Define parser functions 683 ⟩ +≡
  vector⟨pair⟨int, void *⟩⟩ *vec = static_cast⟨vector⟨pair⟨int, void *⟩⟩ *⟩(w);
  if (vec ≡ 0) {
    temp_strm << "ERROR!␣␣In␣‘Scan_Parse::datetime_assignment_func_1’:" <<
        endl << "‘datetime_element_list’␣==␣NULL.␣␣" <<
        "Exiting␣function␣unsuccessfully␣with␣return␣value␣1." << endl;
    cerr_mutex.lock();
    cerr << temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm << temp_strm.str();
    temp_strm.str("");
    return 1;
  }     /* if (vec ≡ 0) */
```

718.

```
⟨ Define parser functions 683 ⟩ +≡
  if (vec→size() ≡ 0) {
    temp_strm ≪ "ERROR!␣␣In␣‘Scan_Parse::datetime_assignment_func_1’:" ≪ endl ≪
        "‘vec’␣is␣empty.␣␣" ≪ "Exiting␣function␣unsuccessfully␣with␣return␣value␣1." ≪
        endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
    delete vec;
    vec = 0;
    return 1;
  }     /* if (vec→size() ≡ 0) */
```

719.

```
⟨ Define parser functions 683 ⟩ +≡
  if (vec→size() > 0 ∧ vec→at(0).first ≠ INTEGER     /* year */
  ∨ vec→size() > 1 ∧ vec→at(1).first ≠ INTEGER     /* month */
  ∨ vec→size() > 2 ∧ vec→at(2).first ≠ INTEGER     /* day */
  ∨ vec→size() > 3 ∧ vec→at(3).first ≠ INTEGER     /* hour */
  ∨ vec→size() > 4 ∧ vec→at(4).first ≠ INTEGER     /* minute */
  ) {
    temp_strm ≪ "ERROR!␣␣In␣‘Scan_Parse::datetime_assignment_func_1’:" ≪
        endl ≪ "Invalid␣value␣in␣‘vec’." ≪ endl ≪
        "Exiting␣function␣unsuccessfully␣with␣return␣value␣1." ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
    for (vector⟨pair⟨int, void *⟩⟩::iterator iter = vec→begin(); iter ≠ vec→end(); ++iter) {
      if (iter→first ≡ INTEGER) {
        delete static_cast⟨int *⟩(iter→second);
      }
      else if (iter→first ≡ FLOAT) {
        delete static_cast⟨float *⟩(iter→second);
      }
      iter→second = 0;
    }     /* for */
    vec→clear();
    delete vec;
    vec = 0;
    return 1;
  }     /* if */
```

720. Year. [LDF 2006.12.18.]

```
⟨ Define parser functions 683 ⟩ +≡
  if (d ≡ 0) d = new Date_Time_Type;
  d→year = static_cast⟨short *⟩(vec→at(0).second);
  vec→at(0).second = 0;
```

721. Month. [LDF 2006.12.18.]

```
⟨ Define parser functions 683 ⟩ +≡
  if (vec→size() > 1) {
    d→month = static_cast⟨unsigned short *⟩(vec→at(1).second);
    vec→at(1).second = 0;
  }
```

722. Day. [LDF 2006.12.18.]

```
⟨ Define parser functions 683 ⟩ +≡
  if (vec→size() > 2) {
    d→day = static_cast⟨unsigned short *⟩(vec→at(2).second);
    vec→at(2).second = 0;
  }
```

723. Hour. [LDF 2006.12.18.]

```
⟨ Define parser functions 683 ⟩ +≡
  if (vec→size() > 3) {
    d→hour = static_cast⟨unsigned short *⟩(vec→at(3).second);
    vec→at(3).second = 0;
  }
```

724. Minute. [LDF 2006.12.18.]

```
⟨ Define parser functions 683 ⟩ +≡
  if (vec→size() > 4) {
    d→minute = static_cast⟨unsigned short *⟩(vec→at(4).second);
    vec→at(4).second = 0;
  }
```

725. Second. [LDF 2006.12.18.]

```
⟨ Define parser functions 683 ⟩ +≡
  if (vec→size() > 5) {
    if (vec→at(5).first ≡ FLOAT) d→second = static_cast⟨float *⟩(vec→at(5).second);
    else {
      d→second = new float;
      *d→second = static_cast⟨float⟩(*static_cast⟨int *⟩(vec→at(5).second));
      delete static_cast⟨int *⟩(vec→at(5).second);
    }
    vec→at(5).second = 0;
  }
```

726.

```
⟨ Define parser functions 683 ⟩ +≡
#ifdef DEBUG_OUTPUT
  temp_strm ≪ "Exiting␣‘Scan_Parse::datetime_assignment_func_1’␣" ≪
      "successfully␣with␣return␣value␣0." ≪ endl;
  cerr_mutex.lock( );
  cerr ≪ temp_strm.str( );
  cerr_mutex.unlock( );
  if (scanner_node ≠ 0) scanner_node→log_strm ≪ temp_strm.str( );
  temp_strm.str("");
#endif
  return 0; }      /* End of Scan_Parse::datetime_assignment_func_1 definition. */
```

727. Putting Parser Functions together. [LDF 2006.10.31.]

728. This is what's compiled.

⟨ Include files 10 ⟩
⟨ prsrfncs.web 678 ⟩

```
using namespace std;
using namespace Scan_Parse;
```

⟨ Define parser functions 683 ⟩

729. Scan Test (scantest.web). [LDF 2006.10.17.]
This file is used with Microsoft Visual Studio. It's not used when using The GNU Compiler Collection (GCC). [LDF 2006.10.24.]
Test application for the scanner *yylex* for ZTest. [LDF 2006.10.17.]

Log

[LDF 2006.10.17.] Created this file.

⟨ scantest.web 729 ⟩ ≡

```
static char id_string[] = "$Id: scantest.web,v 1.5 2007/02/13 20:41:23 lfinsto1 Exp $";
```

This code is cited in sections 6 and 8.
This code is used in section 733.

730. Include files. [LDF 2006.10.17.]

⟨ Include files 10 ⟩ +≡

```
#include "stdafx.h"
#ifdef _DEBUG
#define new DEBUG_NEW
#endif
```

731. Global variable declarations. [LDF 2006.10.19.]

Log

[LDF 2006.10.19.] Added this section.

⟨ Global variables 731 ⟩ ≡

```
ofstream log_strm;
CMutex log_strm_mutex;
CMutex cerr_mutex;
CMutex cout_mutex;
ifstream in_strm;
```

See also section 736.
This code is used in sections 733 and 750.

732. Define _tmain. [LDF 2006.10.17.]

Log

[LDF 2006.10.17.] Added this function.

⟨ Define _tmain 732 ⟩ ≡

```
CWinApp theApp;
```

```
  using namespace std;
  int _tmain(int argc, TCHAR * argv[], TCHAR * envp[])
  {
    int nRetCode = 0;      /* MFC initialisieren und drucken. Bei Fehlschlag Fehlermeldung aufrufen. */
    if (¬AfxWinInit(::GetModuleHandle(NULL), NULL, ::GetCommandLine(), 0)) {
        /* TODO: Passen Sie den Fehlercode an Ihre Anforderungen an */
      _tprintf(_T("Schwerwiegender␣Fehler:␣MFC-Initialisierung␣fehlgeschlagen\n"));
      nRetCode = 1;
    }
    else {
#define DEBUG_OUPUT
      using namespace Scan_Parse;
      int status;
      log_strm_mutex.lock();
      log_strm.open("log.txt");
      log_strm ≪ "%%␣log.txt\n\n" ≪ copyright_tex_str ≪ endl;
      log_strm_mutex.unlock();
      status = initialize_keyword_map();
      status = show_keyword_map();
      YYSTYPE * value = new YYSTYPE;
      YYLTYPE * location = 0;
      Scanner_Type *scanner_node = new Scanner_Type;
      strcpy(scanner_node→in_filename, "commands.txt");
      in_strm.open(scanner_node→in_filename);
      status = 0;
      while (status ≠ TERMINATE) status = yylex(value, location, static_cast⟨void *⟩(scanner_node));
#ifdef DEBUG_OUTPUT
      temp_strm ≪ "In␣‘t_main’:␣␣Finished␣scanning." ≪ endl;
      cerr_mutex.lock();
      cerr ≪ temp_strm.str();
      cerr_mutex.unlock();
      log_strm_mutex.lock();
      log_strm ≪ temp_strm.str();
      log_strm_mutex.unlock();
      temp_strm.str("");
#endif
      in_strm.close();
      log_strm_mutex.lock();
      log_strm.close();
      log_strm_mutex.unlock();
      delete scanner_node;
      scanner_node = 0;
      char c;
      cerr_mutex.lock();
      cerr ≪ "‘yylex’␣returned␣" ≪ status ≪ endl ≪ "Enter␣a␣character␣to␣exit:␣";
      cerr_mutex.unlock();
      cin ≫ c;
      return 0;
#undef DEBUG_OUPUT
    }
```

```
    return nRetCode;
  }     /* End of _tmain definition. */
```

This code is used in section 733.

733. Putting Scan Test together. [LDF 2006.10.17.]

```
⟨ Include files 10 ⟩
⟨ scantest.web 729 ⟩
using namespace std;
⟨ Global variables 731 ⟩
⟨ Define _tmain 732 ⟩
```

734. Main when using GCC (main.web). [LDF 2006.10.20.]

Log

[LDF 2006.10.20.] Created this file.

```
⟨ main.web 734 ⟩ ≡
  static char id_string[] = "$Id: main.web,v 1.12 2007/02/13 20:39:20 lfinsto1 Exp $";
```

This code is cited in sections 6 and 8.

This code is used in section 750.

735. Include files.

```
⟨ Include files 10 ⟩ +≡
#include "localldf.h"
#include "nonwin.h"
#include "parser.hxx"
#include "dttmtype.h"
#include "scanner.h"
#include "dtsrctyp.h"
#include "querytyp.h"
#include "idtype.h"
#include "scnrtype.h"
#include "dbcrprsr.hxx"
#include "dbcrscan.hxx"
```

736. Global variables. [LDF 2006.10.20.]

Log

[2006.10.20.] Added this section.

[LDF 2006.11.21.] Added **unsigned short** *tex_file_ctr*, **string** *tex_filename_str*, **ofstream** *tex_file_strm*, and **Mutex_Type** *tex_mutex*.

[LDF 2006.11.30.] Added **string** *copyright_tex_str*.

[LDF 2006.11.30.] Added **Mutex_Type** *time_mutex*.

```
⟨ Global variables 731 ⟩ +≡
  Mutex_Type cerr_mutex;
  Mutex_Type cout_mutex;
  Mutex_Type time_mutex;
```

```
ofstream tex_file_strm;
Mutex_Type tex_mutex;
unsigned short tex_file_ctr;
string tex_filename_str;
string copyright_tex_str;
```

737. Scanning and parsing input. [LDF Undated.]

738. *yyparse* declaration. [LDF Undated.]

```
⟨ Declare scanning and parsing functions 738 ⟩ ≡
  int yyparse(void *);
```

See also sections 739, 740, 742, and 743.

This code is used in section 750.

739. *yywrap*.

```
⟨ Declare scanning and parsing functions 738 ⟩ +≡
#if 0
  int yywrap(void);
#endif
```

740. *yyerror*. [LDF 2006.10.20.]

```
⟨ Declare scanning and parsing functions 738 ⟩ +≡
  void yyerror(const char *s);
```

741.

```
⟨ Define scanning and parsing functions 741 ⟩ ≡
  void yyerror(const char *s)
  {
    return;
  }
```

See also section 744.

This code is used in section 750.

742. *xxparse* declaration. [LDF 2007.02.13.]

```
⟨ Declare scanning and parsing functions 738 ⟩ +≡
  int xxparse(void *);
```

743. *xxerror*. [LDF 2007.02.13.]

```
⟨ Declare scanning and parsing functions 738 ⟩ +≡
  void xxerror(const char *s);
```

744.

```
⟨ Define scanning and parsing functions 741 ⟩ +≡
  void xxerror(const char *s)
  {
    return;
  }
```

745. Main itself. [LDF 2006.10.20.]

Log

[LDF 2006.10.20.] Added this function.

[LDF 2006.11.02.] No longer closing *scanner_node→in_strm* and *scanner_node→log_strm*. This is now done in the **Scanner_Node** destructor.

[LDF 2006.11.02.] Now calling *scanner_node→initialize_id_map*.

[LDF 2006.11.21.] Now initializing the global variable **unsigned short** *tex_file_ctr* to 0.

```
⟨ Define main 745 ⟩ ≡
  int main(int argc, char *argv[]){ FILE *fp = fopen("oai.xml", "r");
      yyscan_t scanner;
      xxlex_init(&scanner);
      xxset_in(fp, scanner);
      YYSTYPE * i = new YYSTYPE;
      xxparse(static_cast⟨void *⟩(scanner));
      xxlex_destroy(scanner);
      return 0;
#if 0     /* 1 */
      unsigned long long temp_val = 4096LL;
      bitset < 64 > b;
      b.flip( );
      cerr << "'b' == " << b << endl << "'temp_val' == " << temp_val << "b & temp_val == " <<
          (b & temp_val) << endl;
      getchar( );
      cerr << "'sizeof(unsigned long long)' == " << sizeof(unsigned long
          long) << endl << "'ULONG_LONG_MAX' == " << ULONG_LONG_MAX << endl;
      getchar( );
      for (int i = 27; i < 36; ++i) cerr << (long long) pow((double) 2, i) << "\n";
      getchar( );
#endif
#if 0     /* 1 */
#define DEBUG_OUTPUT
#else
#undef DEBUG_OUTPUT
#endif
      copyright_tex_str = "%% *(1) Copyright and License.\n\n";
      copyright_tex_str += "%% This file is part of the IWF Metadata Harvester, ";
      copyright_tex_str += "a package for metadata harvesting.\n";
      copyright_tex_str += "%% Copyright (C) 2006, 2007 IWF Wissen und Medien ";
      copyright_tex_str += "gGmbH\n\n";
      copyright_tex_str += "%% The author is Laurence D. Finston.\n\n";
```

```
copyright_tex_str += "%% The IWF Metadata Harvester is free software; ";
copyright_tex_str += "you can redistribute it and/or modify\n";
copyright_tex_str += "%% it under the terms of the GNU General Public License ";
copyright_tex_str += "as published by\n";
copyright_tex_str += "%% the Free Software Foundation; either version 2 of the ";
copyright_tex_str += "License, or\n";
copyright_tex_str += "%% (at your option) any later version.\n\n";
copyright_tex_str += "%% The IWF Metadata Harvester is distributed in ";
copyright_tex_str += "the hope that it will be useful,\n";
copyright_tex_str += "%% but WITHOUT ANY WARRANTY; without even the implied ";
copyright_tex_str += "warranty of\n";
copyright_tex_str += "%% MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  ";
copyright_tex_str += "See the\n";
copyright_tex_str += "%% GNU General Public License for more details.\n\n";
copyright_tex_str += "%% You should have received a copy of the GNU General ";
copyright_tex_str += "Public License\n";
copyright_tex_str += "%% along with the IWF Metadata Harvester; if not, ";
copyright_tex_str += "write to the Free Software\n";
copyright_tex_str += "%% Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA  ";
copyright_tex_str += "02110-1301  USA\n\n";
copyright_tex_str += "%% The IWF Metadata Harvester is available for downloading \
    from the\n";
copyright_tex_str += "%% following FTP server:\n";
copyright_tex_str += "%% ftp://ftp.gwdg.de/pub/gnu2/iwfmdh/\n\n";
copyright_tex_str += "%% Please send bug reports to lfinsto1@gwdg.de\n\n";
copyright_tex_str += "%% The author can be contacted at:\n\n";
copyright_tex_str += "%% Laurence D. Finston\n";
copyright_tex_str += "%% Kreuzbergring 41\n";
copyright_tex_str += "%% D-37075 Goettingen\n";
copyright_tex_str += "%% Germany\n\n";
copyright_tex_str += "%% lfinsto1@gwdg.de\n";
copyright_tex_str += "%% s246794@stud.uni-goettingen.de\n";
copyright_tex_str += "\n\n";
using namespace Scan_Parse;
stringstream temp_strm;
int status;
status = initialize_maps();
status = Query_Type::initialize_type_maps();
if ((status = Query_Type::initialize_flags()) != 0) {
  cerr << "ERROR! In 'main':" << endl << "'Query_Type::initialize_flags' returned \
      unsuccessfully, " << "with return value " << status << endl <<
      "Exiting 'main' unsuccessfully with return value 1." << endl;
  return 1;
}
status = Datasource_Type::initialize_type_maps();
tex_file_ctr = 0;
tex_filename_str = "scttex_";
Scanner_Type *scanner_node = new Scanner_Type;
status = Id_Type::initialize_subtype_map(scanner_node);
```

See also sections 746, 747, and 748.

This code is used in section 750.

746. Process command line options. [LDF 2006.11.03.]
Options:
`b` — Enable GNU Bison's tracing facilities.

Log

[2006.11.03.] Added this section.

```
⟨ Define main 745 ⟩ +≡
  for (int curr_opt = 0; curr_opt ≥ 0; ) {
    curr_opt = getopt(argc, argv, "b");
#ifdef DEBUG_OUTPUT
    temp_strm ≪ "‘curr_opt’␣␣==␣" ≪ curr_opt ≪ endl;
    cerr_mutex.lock();
    cerr ≪ temp_strm.str();
    cerr_mutex.unlock();
    scanner_node→log_strm ≪ temp_strm.str();
    temp_strm.str("");
#endif
    switch (curr_opt) {
    case 'b': yydebug = 1;
      break;
    default: break;
    }     /* switch */
  }     /* for */
```

747. Process filename argument. [LDF 2006.11.03.]

Log

[2006.11.03.] Added this section.

```
⟨ Define main 745 ⟩ +≡
#if 0    /* 1 */
#ifdef DEBUG_OUTPUT
  temp_strm ≪ "`argc' == " ≪ argc ≪ ", `optind' == " ≪ optind ≪ endl;
  if (argv[optind] ≡ 0) temp_strm ≪ "No filename argument.";
  else temp_strm ≪ "Filename argument == `" ≪ argv[optind] ≪ "'";
  cerr_mutex.lock();
  cerr ≪ temp_strm.str();
  cerr_mutex.unlock();
  scanner_node→log_strm ≪ temp_strm.str();
  temp_strm.str("");
  getchar();
#endif
#endif
  if (argc > optind) {
    strcpy(scanner_node→in_filename, argv[optind]);
  }
  else strcpy(scanner_node→in_filename, "commands.txt");
  scanner_node→in_strm.open(scanner_node→in_filename);
  strcpy(scanner_node→log_filename, "log_1.txt");
  scanner_node→log_strm.open(scanner_node→log_filename);
  scanner_node→log_strm ≪ "%% log_1.txt" ≪ endl ≪ endl ≪ copyright_tex_str ≪ endl;
```

748.

```
⟨ Define main 745 ⟩ +≡
  scanner_node→initialize_id_map();
#ifdef DEBUG_OUTPUT
  status = show_keyword_map(scanner_node);
#endif
  status = yyparse(scanner_node);
  delete scanner_node;
  scanner_node = 0;
  return 0;
#undef DEBUG_OUTPUT
  }    /* End of main definition. */
```

749. Putting Main together.

750. This is what's compiled.

⟨Include files 10⟩
⟨`main.web` 734⟩

using namespace std;

⟨Global variables 731⟩
⟨Declare scanning and parsing functions 738⟩
⟨Define *main* 745⟩
⟨Define scanning and parsing functions 741⟩

751. GNU General Public License. [LDF 2006.10.23.]

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright © 1989, 1991 Free Software Foundation, Inc.
51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software–to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Library General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE

TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

> a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.
>
> b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.
>
> c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the

free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

> ⟨one line to give the program's name and a brief idea of what it does.⟩
> Copyright (C) ⟨year⟩ ⟨name of author⟩
>
> This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.
>
> This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.
>
> You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

> Gnomovision version 69, Copyright © year name of author
> Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type 'show w'.
> This is free software, and you are welcome to redistribute it under certain conditions; type 'show c' for details.

The hypothetical commands 'show w' and 'show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than 'show w' and 'show c'; they could even be mouse-clicks or menu items–whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program 'Gnomovision' (which makes passes at compilers) written by James Hacker.

⟨signature of Ty Coon⟩, 1 April 1989 Ty Coon, President of Vice

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Library General Public License instead of this License.

⟨ GNU General Public License 751 ⟩ ≡ /* This section contains no C++ code. */

This code is cited in section 2.

This code is used in section 753.

752. GNU Free Documentation License. [LDF 2006.10.23.]

GNU Free Documentation License
Version 1.2, November 2002

Copyright © 2000,2001,2002 Free Software Foundation, Inc.
51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

0. PREAMBLE

The purpose of this License is to make a manual, textbook, or other functional and useful document "free" in the sense of freedom: to assure everyone the effective freedom to copy and redistribute it, with or without modifying it, either commercially or noncommercially. Secondarily, this License preserves for the author and publisher a way to get credit for their work, while not being considered responsible for modifications made by others.

This License is a kind of "copyleft", which means that derivative works of the document must themselves be free in the same sense. It complements the GNU General Public License, which is a copyleft license designed for free software.

We have designed this License in order to use it for manuals for free software, because free software needs free documentation: a free program should come with manuals providing the same freedoms that the software does. But this License is not limited to software manuals; it can be used for any textual work, regardless of subject matter or whether it is published as a printed book. We recommend this License principally for works whose purpose is instruction or reference.

1. APPLICABILITY AND DEFINITIONS

This License applies to any manual or other work, in any medium, that contains a notice placed by the copyright holder saying it can be distributed under the terms of this License. Such a notice grants a world-wide, royalty-free license, unlimited in duration, to use that work under the conditions stated herein. The "Document", below, refers to any such manual or work. Any member of the public is a licensee, and is addressed as "you". You accept the license if you copy, modify or distribute the work in a way requiring permission under copyright law.

A "Modified Version" of the Document means any work containing the Document or a portion of it, either copied verbatim, or with modifications and/or translated into another language.

A "Secondary Section" is a named appendix or a front-matter section of the Document that deals exclusively with the relationship of the publishers or authors of the Document to the Document's overall subject (or to related matters) and contains nothing that could fall directly within that overall subject. (Thus, if the Document is in part a textbook of mathematics, a Secondary Section may not explain any mathematics.) The relationship could be a matter of historical connection with the subject or with related matters, or of legal, commercial, philosophical, ethical or political position regarding them.

The "Invariant Sections" are certain Secondary Sections whose titles are designated, as being those of Invariant Sections, in the notice that says that the Document is released under this License. If a section does not fit the above definition of Secondary then it is not allowed to be designated as Invariant. The Document may contain zero Invariant Sections. If the Document does not identify any Invariant Sections then there are none.

The "Cover Texts" are certain short passages of text that are listed, as Front-Cover Texts or Back-Cover Texts, in the notice that says that the Document is released under this License. A Front-Cover Text may be at most 5 words, and a Back-Cover Text may be at most 25 words.

A "Transparent" copy of the Document means a machine-readable copy, represented in a format whose specification is available to the general public, that is suitable for revising the document straightforwardly with generic text editors or (for images composed of pixels) generic paint programs or (for drawings) some widely available drawing editor, and that is suitable for input to text formatters or for automatic translation to a variety of formats suitable for input to text formatters. A copy made in an otherwise Transparent file format whose markup, or absence of markup, has been arranged to thwart or discourage subsequent

modification by readers is not Transparent. An image format is not Transparent if used for any substantial amount of text. A copy that is not "Transparent" is called "Opaque".

Examples of suitable formats for Transparent copies include plain ASCII without markup, Texinfo input format, LaTeX input format, SGML or XML using a publicly available DTD, and standard-conforming simple HTML, PostScript or PDF designed for human modification. Examples of transparent image formats include PNG, XCF and JPG. Opaque formats include proprietary formats that can be read and edited only by proprietary word processors, SGML or XML for which the DTD and/or processing tools are not generally available, and the machine-generated HTML, PostScript or PDF produced by some word processors for output purposes only.

The "Title Page" means, for a printed book, the title page itself, plus such following pages as are needed to hold, legibly, the material this License requires to appear in the title page. For works in formats which do not have any title page as such, "Title Page" means the text near the most prominent appearance of the work's title, preceding the beginning of the body of the text.

A section "Entitled XYZ" means a named subunit of the Document whose title either is precisely XYZ or contains XYZ in parentheses following text that translates XYZ in another language. (Here XYZ stands for a specific section name mentioned below, such as "Acknowledgements", "Dedications", "Endorsements", or "History".) To "Preserve the Title" of such a section when you modify the Document means that it remains a section "Entitled XYZ" according to this definition.

The Document may include Warranty Disclaimers next to the notice which states that this License applies to the Document. These Warranty Disclaimers are considered to be included by reference in this License, but only as regards disclaiming warranties: any other implication that these Warranty Disclaimers may have is void and has no effect on the meaning of this License.

2. VERBATIM COPYING

You may copy and distribute the Document in any medium, either commercially or noncommercially, provided that this License, the copyright notices, and the license notice saying this License applies to the Document are reproduced in all copies, and that you add no other conditions whatsoever to those of this License. You may not use technical measures to obstruct or control the reading or further copying of the copies you make or distribute. However, you may accept compensation in exchange for copies. If you distribute a large enough number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and you may publicly display copies.

3. COPYING IN QUANTITY

If you publish printed copies (or copies in media that commonly have printed covers) of the Document, numbering more than 100, and the Document's license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible. You may add other material on the covers in addition. Copying with changes limited to the covers, as long as they preserve the title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit legibly, you should put the first ones listed (as many as fit reasonably) on the actual cover, and continue the rest onto adjacent pages.

If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along with each Opaque copy, or state in or with each Opaque copy a computer-network location from which the general network-using public has access to download using public-standard network protocols a complete Transparent copy of the Document, free of added material. If

you use the latter option, you must take reasonably prudent steps, when you begin distribution of Opaque copies in quantity, to ensure that this Transparent copy will remain thus accessible at the stated location until at least one year after the last time you distribute an Opaque copy (directly or through your agents or retailers) of that edition to the public.

It is requested, but not required, that you contact the authors of the Document well before redistributing any large number of copies, to give them a chance to provide you with an updated version of the Document.

4. MODIFICATIONS

You may copy and distribute a Modified Version of the Document under the conditions of sections 2 and 3 above, provided that you release the Modified Version under precisely this License, with the Modified Version filling the role of the Document, thus licensing distribution and modification of the Modified Version to whoever possesses a copy of it. In addition, you must do these things in the Modified Version:

A. Use in the Title Page (and on the covers, if any) a title distinct from that of the Document, and from those of previous versions (which should, if there were any, be listed in the History section of the Document). You may use the same title as a previous version if the original publisher of that version gives permission. B. List on the Title Page, as authors, one or more persons or entities responsible for authorship of the modifications in the Modified Version, together with at least five of the principal authors of the Document (all of its principal authors, if it has fewer than five), unless they release you from this requirement. C. State on the Title page the name of the publisher of the Modified Version, as the publisher. D. Preserve all the copyright notices of the Document. E. Add an appropriate copyright notice for your modifications adjacent to the other copyright notices. F. Include, immediately after the copyright notices, a license notice giving the public permission to use the Modified Version under the terms of this License, in the form shown in the Addendum below. G. Preserve in that license notice the full lists of Invariant Sections and required Cover Texts given in the Document's license notice. H. Include an unaltered copy of this License. I. Preserve the section Entitled "History", Preserve its Title, and add to it an item stating at least the title, year, new authors, and publisher of the Modified Version as given on the Title Page. If there is no section Entitled "History" in the Document, create one stating the title, year, authors, and publisher of the Document as given on its Title Page, then add an item describing the Modified Version as stated in the previous sentence. J. Preserve the network location, if any, given in the Document for public access to a Transparent copy of the Document, and likewise the network locations given in the Document for previous versions it was based on. These may be placed in the "History" section. You may omit a network location for a work that was published at least four years before the Document itself, or if the original publisher of the version it refers to gives permission. K. For any section Entitled "Acknowledgements" or "Dedications", Preserve the Title of the section, and preserve in the section all the substance and tone of each of the contributor acknowledgements and/or dedications given therein. L. Preserve all the Invariant Sections of the Document, unaltered in their text and in their titles. Section numbers or the equivalent are not considered part of the section titles. M. Delete any section Entitled "Endorsements". Such a section may not be included in the Modified Version. N. Do not retitle any existing section to be Entitled "Endorsements" or to conflict in title with any Invariant Section. O. Preserve any Warranty Disclaimers.

If the Modified Version includes new front-matter sections or appendices that qualify as Secondary Sections and contain no material copied from the Document, you may at your option designate some or all of these sections as invariant. To do this, add their titles to the list of Invariant Sections in the Modified Version's license notice. These titles must be distinct from any other section titles.

You may add a section Entitled "Endorsements", provided it contains nothing but endorsements of your Modified Version by various parties–for example, statements of peer review or that the text has been approved by an organization as the authoritative definition of a standard.

You may add a passage of up to five words as a Front-Cover Text, and a passage of up to 25 words as a Back-Cover Text, to the end of the list of Cover Texts in the Modified Version. Only one passage of Front-Cover Text and one of Back-Cover Text may be added by (or through arrangements made by) any

one entity. If the Document already includes a cover text for the same cover, previously added by you or by arrangement made by the same entity you are acting on behalf of, you may not add another; but you may replace the old one, on explicit permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License give permission to use their names for publicity for or to assert or imply endorsement of any Modified Version.

5. COMBINING DOCUMENTS

You may combine the Document with other documents released under this License, under the terms defined in section 4 above for modified versions, provided that you include in the combination all of the Invariant Sections of all of the original documents, unmodified, and list them all as Invariant Sections of your combined work in its license notice, and that you preserve all their Warranty Disclaimers.

The combined work need only contain one copy of this License, and multiple identical Invariant Sections may be replaced with a single copy. If there are multiple Invariant Sections with the same name but different contents, make the title of each such section unique by adding at the end of it, in parentheses, the name of the original author or publisher of that section if known, or else a unique number. Make the same adjustment to the section titles in the list of Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections Entitled "History" in the various original documents, forming one section Entitled "History"; likewise combine any sections Entitled "Acknowledgements", and any sections Entitled "Dedications". You must delete all sections Entitled "Endorsements".

6. COLLECTIONS OF DOCUMENTS

You may make a collection consisting of the Document and other documents released under this License, and replace the individual copies of this License in the various documents with a single copy that is included in the collection, provided that you follow the rules of this License for verbatim copying of each of the documents in all other respects.

You may extract a single document from such a collection, and distribute it individually under this License, provided you insert a copy of this License into the extracted document, and follow this License in all other respects regarding verbatim copying of that document.

7. AGGREGATION WITH INDEPENDENT WORKS

A compilation of the Document or its derivatives with other separate and independent documents or works, in or on a volume of a storage or distribution medium, is called an "aggregate" if the copyright resulting from the compilation is not used to limit the legal rights of the compilation's users beyond what the individual works permit. When the Document is included in an aggregate, this License does not apply to the other works in the aggregate which are not themselves derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these copies of the Document, then if the Document is less than one half of the entire aggregate, the Document's Cover Texts may be placed on covers that bracket the Document within the aggregate, or the electronic equivalent of covers if the Document is in electronic form. Otherwise they must appear on printed covers that bracket the whole aggregate.

8. TRANSLATION

Translation is considered a kind of modification, so you may distribute translations of the Document under the terms of section 4. Replacing Invariant Sections with translations requires special permission from their copyright holders, but you may include translations of some or all Invariant Sections in addition to the original versions of these Invariant Sections. You may include a translation of this License, and all the license notices in the Document, and any Warranty Disclaimers, provided that you also include the original English

version of this License and the original versions of those notices and disclaimers. In case of a disagreement between the translation and the original version of this License or a notice or disclaimer, the original version will prevail.

If a section in the Document is Entitled "Acknowledgements", "Dedications", or "History", the requirement (section 4) to Preserve its Title (section 1) will typically require changing the actual title.

9. TERMINATION

You may not copy, modify, sublicense, or distribute the Document except as expressly provided for under this License. Any other attempt to copy, modify, sublicense or distribute the Document is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

10. FUTURE REVISIONS OF THIS LICENSE

The Free Software Foundation may publish new, revised versions of the GNU Free Documentation License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns. See `http://www.gnu.org/copyleft/`.

Each version of the License is given a distinguishing version number. If the Document specifies that a particular numbered version of this License "or any later version" applies to it, you have the option of following the terms and conditions either of that specified version or of any later version that has been published (not as a draft) by the Free Software Foundation. If the Document does not specify a version number of this License, you may choose any version ever published (not as a draft) by the Free Software Foundation.

ADDENDUM: How to use this License for your documents

To use this License in a document you have written, include a copy of the License in the document and put the following copyright and license notices just after the title page:

> Copyright © YEAR YOUR NAME. Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.2 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".

If you have Invariant Sections, Front-Cover Texts and Back-Cover Texts, replace the "with...Texts." line with this:

> with the Invariant Sections being LIST THEIR TITLES, with the Front-Cover Texts being LIST, and with the Back-Cover Texts being LIST.

If you have Invariant Sections without Cover Texts, or some other combination of the three, merge those two alternatives to suit the situation.

If your document contains nontrivial examples of program code, we recommend releasing these examples in parallel under your choice of free software license, such as the GNU General Public License, to permit their use in free software.

⟨ GNU Free Documentation License 752 ⟩ ≡ `/* This section contains no C++ code. */`

This code is cited in section 2.

This code is used in section 753.

753. Include sections without C++ code. These sections contain no code, or only commented-out code. However, they must be included somewhere, or CWEAVE will issue warnings. [LDF 2006.09.27.]

⟨GNU General Public License 751⟩
⟨GNU Free Documentation License 752⟩

754. Index.

_AFX_NO_AFXCMN_SUPPORT: 24.
_ATL_CSTRING_EXPLICIT_CONSTRUCTORS: 24.
_DEBUG: 730.
_T: 732.
_tmain: 6, 8, 732.
_tprintf: 732.
aand_node: 88, 89.
ACCESS_NUMBER: 106, 281, 519, 701.
ACCESS_NUMBER_FIELD: 62, 68, 92, 100, 106, 117, 701.
ACCESS_NUMBER_FLAG: 79, 80, 103.
AfxWinInit: 732.
AND: 280, 334, 408, 629.
AND_ASSIGN: 271, 334, 400, 703.
and_node: 53, 87, 92, 97, 108, 112, 119, 130, 152, 621, 702, 703.
AND_NOT: 280, 334, 408, 621, 630.
and_or_and_not: 628.
AND_TYPE: 59, 60, 100, 130, 621, 702, 703.
arg_0: 55, 226, 298, 695, 698, 699, 701.
arg_1: 55, 226, 298, 695, 698, 699.
argc: 732, 745, 746, 747.
argv: 732, 745, 746, 747.
asctime: 610.
ASSIGN: 271, 331, 400, 490, 493, 507, 662, 702, 703, 710.
assign.w: 5, 8.
assign_id_string: 479.
assignment_operator: 55, 226, 299, 703.
assignment_type: 55, 226, 298, 695, 702.
at: 719, 720, 721, 722, 723, 724, 725.
AT_SYMBOL: 268, 270, 345, 399.
atof: 316, 320, 327, 332, 344, 353, 356.
atoi: 315, 320, 327, 332, 353, 356.
AUTHOR: 106, 281, 409, 520, 701.
AUTHOR_FIELD: 61, 62, 68, 92, 100, 106, 117, 701.
AUTHOR_FLAG: 79, 80, 103, 132, 133, 134.
AUTHOR_GIVEN_NAME: 412.
AUTHOR_GIVEN_NAME_FIELD: 61, 64, 70, 92, 100, 106, 133.
AUTHOR_GIVEN_NAME_FLAG: 79, 80, 103, 133.
AUTHOR_PREFIX: 412.
AUTHOR_PREFIX_FIELD: 61, 64, 70, 92, 100, 106, 134.
AUTHOR_PREFIX_FLAG: 79, 80, 103, 134.
AUTHOR_SURNAME: 412.
AUTHOR_SURNAME_FIELD: 61, 64, 70, 92, 100, 106, 132.
AUTHOR_SURNAME_FLAG: 79, 80, 103, 132.
begin: 97, 112, 117, 152, 233, 292, 688, 699, 719.
BIBLIOGRAPHIC_TYPE: 106, 281, 521, 701.
BIBLIOGRAPHIC_TYPE_FIELD: 62, 68, 92, 100, 106, 117, 701.
BIBLIOGRAPHIC_TYPE_FLAG: 79, 80, 103.
bitset: 78, 79, 80, 114, 127, 582, 584, 745.
BUG FIX: 33, 90, 579.
c: 732.
c_str: 312, 315, 316, 320, 327, 332, 344, 353, 356, 358, 580, 582, 584, 610, 648.
CALL_NUMBER: 106, 281, 522, 701.
CALL_NUMBER_FIELD: 62, 68, 92, 100, 106, 117, 701.
CALL_NUMBER_FLAG: 79, 80, 103.
cerr: 41, 43, 45, 91, 93, 96, 97, 104, 111, 113, 118, 119, 127, 128, 130, 131, 156, 172, 176, 177, 180, 184, 203, 206, 209, 233, 235, 237, 238, 240, 241, 242, 243, 244, 245, 292, 307, 308, 309, 310, 312, 313, 315, 316, 317, 319, 320, 322, 323, 326, 327, 331, 332, 333, 334, 335, 336, 337, 338, 339, 340, 341, 342, 343, 344, 345, 346, 347, 348, 349, 351, 353, 354, 355, 356, 357, 358, 359, 373, 375, 376, 378, 386, 387, 388, 389, 421, 426, 427, 428, 429, 436, 437, 438, 439, 442, 443, 444, 445, 457, 459, 460, 461, 463, 464, 465, 466, 468, 469, 471, 472, 474, 475, 478, 482, 483, 485, 486, 487, 488, 490, 491, 493, 494, 495, 496, 497, 498, 499, 500, 502, 503, 505, 506, 507, 508, 510, 511, 512, 513, 514, 515, 517, 519, 520, 521, 522, 523, 524, 525, 526, 527, 528, 529, 530, 531, 532, 533, 534, 535, 536, 537, 538, 539, 540, 541, 542, 543, 544, 545, 546, 548, 549, 552, 554, 555, 556, 559, 560, 561, 562, 563, 564, 565, 566, 567, 568, 569, 570, 572, 573, 574, 575, 576, 578, 579, 581, 583, 586, 587, 588, 590, 591, 592, 593, 594, 595, 596, 597, 602, 603, 604, 605, 606, 607, 608, 609, 610, 614, 615, 616, 617, 618, 620, 621, 623, 624, 626, 627, 629, 630, 631, 632, 633, 634, 638, 639, 641, 643, 645, 648, 649, 650, 652, 654, 656, 660, 661, 662, 664, 666, 668, 670, 671, 672, 673, 683, 684, 685, 686, 688, 689, 691, 692, 693, 695, 696, 697,

698, 702, 703, 706, 707, 708, 715, 716, 717, 718, 719, 726, 732, 745, 746, 747.
cerr_mutex: 18, 25, 41, 43, 91, 93, 96, 97, 111, 113, 118, 119, 127, 128, 130, 156, 176, 177, 180, 184, 203, 206, 209, 233, 235, 237, 238, 240, 241, 242, 243, 244, 245, 292, 307, 308, 309, 310, 312, 313, 315, 316, 317, 319, 320, 322, 323, 326, 327, 331, 332, 333, 334, 335, 336, 337, 338, 339, 340, 341, 342, 343, 344, 345, 346, 347, 348, 349, 351, 353, 354, 355, 356, 357, 358, 359, 389, 436, 437, 438, 439, 442, 443, 444, 445, 457, 459, 460, 461, 463, 464, 465, 466, 468, 469, 471, 472, 474, 475, 478, 482, 483, 485, 486, 487, 488, 490, 491, 493, 494, 495, 496, 497, 498, 499, 500, 502, 503, 505, 506, 507, 508, 510, 511, 512, 513, 514, 515, 517, 519, 520, 521, 522, 523, 524, 525, 526, 527, 528, 529, 530, 531, 532, 533, 534, 535, 536, 537, 538, 539, 540, 541, 542, 543, 544, 545, 546, 548, 549, 552, 554, 555, 556, 559, 560, 561, 562, 563, 564, 565, 566, 567, 568, 569, 570, 572, 573, 574, 575, 576, 578, 579, 581, 583, 586, 587, 588, 590, 591, 592, 593, 594, 595, 596, 597, 602, 603, 604, 605, 606, 607, 608, 609, 610, 614, 615, 616, 617, 618, 620, 621, 623, 624, 626, 627, 629, 630, 631, 632, 633, 634, 638, 639, 641, 643, 645, 648, 649, 650, 652, 654, 656, 660, 661, 662, 664, 666, 668, 670, 671, 672, 673, 683, 684, 685, 686, 688, 689, 691, 692, 693, 695, 696, 697, 698, 702, 703, 706, 707, 708, 715, 716, 717, 718, 719, 726, 731, 732, 736, 746, 747.
cin: 732.
CLASSIFICATION: 106, 281, 523, 701.
CLASSIFICATION_FIELD: 62, 68, 92, 100, 106, 117, 701.
CLASSIFICATION_FLAG: 79, 80, 103.
CLEAR: 288, 418.
clear: 97, 233, 459, 685, 689, 719.
close: 233, 610, 732.
CLOSE_BRACKET: 270, 349.
CLOSE_PARENTHESIS: 270, 347.
close_parenthesis_str: 130, 153.
CMutex: 25, 731.
COLLECTING_ARGUMENT: 255.
COLLECTING_FLOAT: 255, 258, 310, 316, 320, 324, 327, 332, 344, 353, 356.
COLLECTING_ID: 255, 258, 310, 313, 314, 319, 320, 323, 324, 326, 327, 331, 332, 343, 344, 351, 352, 355, 356.
COLLECTING_INTEGER: 255, 258, 310, 315, 320, 322, 324, 327, 332, 344, 353, 356.
COLLECTING_KEYWORD: 255.
COLLECTING_STRING: 255, 258, 312, 313, 317, 321, 324, 328, 331, 343, 353, 355.
COLON: 270, 338.
column: 106, 107.
COMMA: 270, 340.
commands.w: 5, 8.
commands_id_string: 598.
COMMON_PUNCTUATION: 333, 334, 335, 336, 337, 338, 339, 340, 341, 342, 345, 346, 347, 348, 349, 354.
COMPANY: 106, 281, 524, 701.
COMPANY_FIELD: 62, 68, 92, 100, 106, 117, 701.
COMPANY_FLAG: 79, 80, 103.
compare: 245.
const_iterator: 97, 292, 688.
CONTAINS: 276, 400.
CONTAINS_VALUE: 82, 83, 100, 128, 486.
CONTENT_SUMMARY: 106, 281, 525, 701.
CONTENT_SUMMARY_FIELD: 62, 68, 92, 100, 106, 117, 701.
CONTENT_SUMMARY_FLAG: 79, 80, 103.
CONTRIBUTOR: 106, 281, 409, 526, 701.
CONTRIBUTOR_FIELD: 61, 62, 68, 92, 100, 106, 117, 138, 701.
CONTRIBUTOR_FLAG: 79, 80, 103, 135, 136, 137, 138.
CONTRIBUTOR_GIVEN_NAME: 108, 412.
CONTRIBUTOR_GIVEN_NAME_FIELD: 61, 65, 71, 92, 100, 106, 108, 136.
CONTRIBUTOR_GIVEN_NAME_FLAG: 79, 80, 103, 136.
CONTRIBUTOR_PREFIX: 108, 412.
CONTRIBUTOR_PREFIX_FIELD: 61, 65, 71, 92, 100, 106, 108, 137.
CONTRIBUTOR_PREFIX_FLAG: 79, 80, 103, 137.
CONTRIBUTOR_SURNAME: 108, 412.
CONTRIBUTOR_SURNAME_FIELD: 61, 65, 71, 92, 100, 106, 108, 135.
CONTRIBUTOR_SURNAME_FLAG: 79, 80, 103, 135.
copyright_tex_str: 18, 610, 732, 736, 745, 747.
cout_mutex: 18, 25, 731, 736.
create: 236, 237, 240, 243, 244, 245.
CREATOR: 106, 281, 409, 527, 701.
CREATOR_FIELD: 61, 62, 68, 92, 100, 106, 117, 139, 701.
CREATOR_FLAG: 79, 80, 103, 139.
curr_char: 309, 310, 311, 317, 318, 319, 320, 321, 322, 324, 325, 328, 329, 331, 332, 333, 334, 335, 336, 337, 338, 339, 340, 341, 342, 343, 344, 345, 346, 347, 348, 349, 350, 353, 355.
curr_datasource_node: 607, 638.
curr_date_time_node: 32, 33, 55, 226, 300, 608, 707, 709, 710, 711.
curr_datetime_node: 660.

curr_field_type: 701, 702.
curr_float_str: 309, 316, 320, 324, 327, 332, 344, 353, 356.
curr_id: 309, 313, 314, 319, 320, 323, 324, 326, 327, 331, 332, 343, 344, 351, 352, 355, 356, 357, 358, 359.
curr_id_node: 55, 226, 237, 238, 240, 242, 244, 245, 299, 510, 511, 513, 514, 578, 579, 580, 581, 582, 583, 584, 606, 607, 608, 614, 638, 648, 660, 686, 687, 688, 689, 691, 693, 698, 702, 703.
curr_integer_str: 309, 315, 320, 322, 324, 327, 332, 344, 353, 356.
curr_keyword: 269, 270, 271, 272, 273, 274, 275, 276, 277, 278, 279, 280, 281, 283, 284, 285, 286, 287, 288, 289, 309.
curr_name: 241, 244, 245.
curr_name_strm: 241.
curr_opt: 746.
curr_query: 223, 234, 703, 704, 705.
curr_query_node: 606, 614, 616, 617, 618, 698, 699, 701, 702.
curr_string: 309, 312, 313, 317, 321, 324, 328, 331, 343, 353, 355, 579, 580, 581, 582, 583, 584, 701, 702.
curr_token: 307, 359, 457.
curr_value: 309, 689.
CWinApp: 732.
d: 32, 33, 40, 41, 42, 43, 55, 149, 179, 180, 226, 301, 587, 588, 662, 716.
`DATABASE`: 275, 405, 406, 505, 507, 699.
`DATABASE_PROVIDER`: 106, 281, 528, 701.
`DATABASE_PROVIDER_FIELD`: 62, 68, 92, 100, 106, 117, 701.
`DATABASE_PROVIDER_FLAG`: 79, 80, 103.
database_type: 114, 127, 130, 132, 133, 134, 135, 136, 137, 138, 139, 140, 142, 144, 145, 146, 147, 148, 149, 151, 152.
`DATASOURCE_DECLARATOR`: 277, 404.
`DATASOURCE_FILE`: 277, 406.
`DATASOURCE_FILE_TYPE`: 165, 166, 181, 182, 576.
Datasource_Node: 162, 163, 179, 180, 572, 573, 574, 575, 576, 607, 638, 639.
datasource_type: 168, 173, 174.
Datasource_Type: 6, 8, 162, 163, 166, 167, 171, 172, 174, 175, 176, 178, 179, 180, 182, 184, 573, 574, 575, 576, 638, 745.
`DATASOURCE_TYPE`: 287, 417, 449, 471.
datasource_type_map: 163, 167, 182, 184.
`DATASOURCE_TYPE_NULL_TYPE`: 165, 166, 182.
`DATE_MOST_RECENT_CHANGE`: 107, 285, 564.
`DATE_ORIGINAL_ENTRY`: 107, 285, 563.
`DATE_STATUS_CHANGE`: 107, 285, 565.
date_strm: 127, 149.
Date_Time_Node: 32, 33, 40, 41, 55, 92, 97, 112, 117, 149, 226, 252, 300, 301, 586, 587, 588, 608, 660, 661, 662, 703, 707, 716.
Date_Time_Type: 6, 8, 32, 33, 36, 37, 38, 39, 40, 41, 42, 43, 45, 97, 252, 660, 709, 720.
`DATE_TIME_TYPE`: 73, 74, 97, 100, 112, 703.
datestamp: 610.
datetime_assignment_func_0: 32, 33, 55, 226, 300, 587, 588, 707, 715.
datetime_assignment_func_1: 32, 33, 55, 226, 301, 662, 716, 726.
`DATETIME_DECLARATOR`: 278, 404.
`DATETIME_TYPE`: 287, 417, 453, 477, 513, 703.
day: 33, 37, 39, 41, 43, 45, 149, 710, 711, 719, 722.
`DAY`: 279, 407, 594, 710, 711.
`dbcrprsr.w`: 5, 8, 363.
dbcrprsr_id_string: 363.
`dbcrscan.web`: 5, 8, 381.
`DBT`: 277, 406.
`DBT_TYPE`: 165, 166, 181, 182, 573.
`DEBUG_COMPILE`: 386, 387, 388, 389.
`DEBUG_NEW`: 730.
`DEBUG_OUPUT`: 732.
`DEBUG_OUTPUT`: 41, 43, 91, 93, 96, 97, 106, 108, 111, 113, 127, 156, 176, 177, 180, 203, 206, 209, 233, 235, 237, 240, 241, 242, 243, 244, 245, 306, 307, 308, 309, 310, 312, 313, 315, 316, 317, 319, 320, 322, 323, 326, 327, 331, 332, 333, 334, 335, 336, 337, 338, 339, 340, 341, 342, 343, 344, 345, 346, 347, 348, 349, 351, 353, 354, 355, 356, 357, 358, 359, 439, 457, 459, 460, 461, 463, 464, 465, 466, 468, 469, 471, 472, 474, 475, 477, 478, 482, 483, 485, 486, 487, 488, 490, 491, 493, 494, 495, 496, 497, 502, 503, 505, 506, 507, 508, 510, 511, 512, 513, 514, 515, 517, 519, 520, 521, 522, 523, 524, 525, 526, 527, 528, 529, 530, 531, 532, 533, 534, 535, 536, 537, 538, 539, 540, 541, 542, 543, 544, 545, 546, 548, 549, 552, 554, 555, 556, 559, 560, 561, 562, 563, 564, 565, 566, 567, 568, 569, 570, 572, 573, 574, 575, 576, 578, 579, 581, 583, 586, 587, 588, 590, 591, 592, 593, 594, 595, 596, 597, 602, 603, 604, 605, 606, 607, 608, 609, 610, 614, 615, 616, 617, 618, 620, 621, 623, 624, 626, 627, 629, 630, 631, 632, 633, 634, 638, 639, 641, 643, 645, 648, 649, 650, 652, 654, 656, 660, 661, 662, 664, 666, 668, 670, 671, 672, 673, 683, 686, 688, 689, 691, 693, 695, 698, 702, 703, 706, 707, 715, 716, 726, 732, 745, 746, 747, 748.
declare_variable_func: 55, 226, 296, 447, 449, 451, 453, 691, 693.
`declrtns.w`: 5, 8.

declrtns_id_string: 434.
deque: 106, 517, 548, 549.
DESCRIPTION: 106, 281, 529, 701.
DESCRIPTION_FIELD: 62, 68, 92, 100, 106, 117, 701.
DESCRIPTION_FLAG: 79, 80, 103.
DIVIDE: 272, 401.
DIVIDE_ASSIGN: 271, 400, 714.
DO: 280, 408.
dtsrcexp.w: 5.
dtsrcexp.web: 8.
dtsrcexp_id_string: 636.
dtsrctyp.web: 5, 8, 159.
DTSRCTYP_KNOWN: 187.
dttmexp.w: 5, 8.
dttmexp_id_string: 658.
dttmtype.web.web: 5, 8.
dttmtype.web: 29.
ELIF: 280, 408.
ELN_MOST_RECENT_CHANGE: 107, 285, 560.
ELN_ORIGINAL_ENTRY: 107, 285, 559.
ELN_STATUS_CHANGE: 107, 285, 561.
ELSE: 280, 408.
end: 97, 112, 117, 152, 233, 237, 239, 292, 357, 358, 359, 685, 686, 688, 689, 699, 719.
END: 274.
end_local_query_func: 55, 226, 304.
END_OAI: 388.
end_query_func: 55, 226, 304.
endl: 41, 43, 45, 91, 93, 96, 97, 104, 111, 112, 113, 117, 119, 127, 128, 130, 131, 132, 133, 134, 135, 136, 137, 138, 139, 140, 142, 144, 145, 146, 147, 148, 149, 151, 152, 154, 155, 156, 172, 176, 177, 180, 184, 203, 206, 209, 233, 235, 237, 238, 240, 241, 242, 243, 244, 245, 292, 307, 308, 310, 312, 313, 315, 316, 317, 319, 320, 322, 323, 326, 327, 331, 332, 333, 334, 335, 336, 337, 338, 339, 340, 341, 342, 343, 344, 345, 346, 347, 348, 349, 351, 353, 354, 355, 356, 357, 358, 359, 373, 375, 376, 378, 386, 387, 388, 389, 421, 426, 427, 428, 429, 436, 437, 438, 439, 442, 443, 444, 445, 457, 459, 460, 461, 463, 464, 465, 466, 468, 469, 471, 472, 474, 475, 477, 478, 482, 483, 485, 486, 487, 488, 490, 491, 493, 494, 495, 496, 497, 498, 499, 500, 502, 503, 505, 506, 507, 508, 510, 511, 512, 513, 514, 515, 517, 519, 520, 521, 522, 523, 524, 525, 526, 527, 528, 529, 530, 531, 532, 533, 534, 535, 536, 537, 538, 539, 540, 541, 542, 543, 544, 545, 546, 548, 549, 552, 554, 555, 556, 559, 560, 561, 562, 563, 564, 565, 566, 567, 568, 569, 570, 572, 573, 574, 575, 576, 578, 579, 581, 583, 586, 587, 588, 590, 591, 592, 593, 594, 595, 596, 597, 602, 603, 604, 605, 606, 607, 608, 609, 610, 614, 615, 616, 617, 618, 620, 621, 623, 624, 626, 627, 629, 630, 631, 632, 633, 634, 638, 639, 641, 643, 645, 648, 649, 650, 652, 654, 656, 660, 661, 662, 664, 666, 668, 670, 671, 672, 673, 683, 684, 685, 686, 688, 689, 691, 692, 693, 695, 696, 697, 698, 702, 703, 706, 707, 708, 715, 716, 717, 718, 719, 726, 732, 745, 746, 747.
envp: 732.
EOF: 309, 310.
ERRMESSAGE: 288, 418, 603, 604.
EXEMPLAR_PRODUCTION_NUMBER: 106, 281, 530, 701.
EXEMPLAR_PRODUCTION_NUMBER_FIELD: 62, 68, 92, 100, 106, 117, 701.
EXEMPLAR_PRODUCTION_NUMBER_FLAG: 79, 80, 103.
expression: 627.
f: 671, 673.
false: 87, 88, 105, 132, 133, 134, 135, 136, 137, 138, 139, 140, 142, 144, 145, 146, 147, 148, 149, 151, 152, 236, 240, 243, 245, 621, 624, 627.
ffield: 88.
ffield_type: 88, 89.
FI: 280, 408.
field_flags: 114, 127, 132, 133, 134, 135, 136, 137, 138, 139, 140, 142, 144, 145, 146, 147, 148, 149, 151, 152, 582, 584.
field_specifier: 55, 106, 107, 226, 299, 703.
field_type: 53, 57, 61, 87, 90, 92, 97, 106, 107, 108, 112, 117, 131, 132, 133, 134, 135, 136, 137, 138, 139, 140, 141, 142, 144, 145, 146, 147, 148, 149, 150, 152, 701, 702.
field_type_map: 53, 81, 99, 100, 112, 117, 131.
find: 237, 357, 684, 699.
FINISH: 310, 353.
first: 719, 725.
first_from: 114, 127, 132, 133, 134, 135, 136, 137, 138, 139, 140, 142, 144, 145, 146, 147, 148, 149, 151, 152, 582, 584.
first_select: 114, 127, 132, 133, 134, 135, 136, 137, 138, 139, 140, 142, 144, 145, 146, 147, 148, 149, 151, 152, 582, 584.
first_where: 114, 127, 132, 133, 134, 135, 136, 137, 138, 139, 140, 142, 144, 145, 146, 147, 148, 149, 151, 152, 582, 584.
fixed: 149.
flip: 745.
FLOAT: 273, 307, 316, 320, 327, 332, 344, 353, 356, 588, 671, 673, 710, 711, 719, 725.
FLOAT_TYPE: 73, 74, 97, 100, 112, 618.
float_value: 307, 316, 320, 327, 332, 344, 353, 356, 368, 396.

float_vector: 223, 241, 459, 461, 685, 688, 689.
fopen: 745.
FOR: 280, 408.
fp: 745.
FREETEXT: 276, 400.
FREETEXT_VALUE: 82, 83, 100, 128, 487.
from_strm: 114, 127, 132, 133, 134, 135, 136, 137, 138, 139, 140, 142, 144, 145, 146, 147, 148, 149, 151, 152, 154, 581, 582, 583, 584.
GBV_GVK: 277, 406.
GBV_GVK_TYPE: 165, 166, 181, 182, 574.
GCC. See "GNU Compiler Collection": 6.
generate_sql_string: 6, 8, 114, 127, 152, 156, 582, 584.
generate_tex_string: 110, 111, 112, 113, 580.
get: 309, 310, 328, 333, 334, 335, 336, 337.
getchar: 104, 127, 578, 604, 605, 715, 745, 747.
GetCommandLine: 732.
GetModuleHandle: 732.
getopt: 9, 746.
GIVEN_NAME: 106, 284, 412, 555.
GNU Compiler Collection: 6.
group_statement: 430.
grpstmnt.w: 5, 8.
grpstmnt_id_string: 431.
hour: 33, 37, 39, 41, 43, 45, 149, 710, 711, 719, 723.
HOUR: 279, 407, 595, 710, 711.
HYPHEN: 268, 270, 342, 399.
i: 112, 117, 152, 241, 670, 672, 688, 745.
ID: 107, 283, 415, 552.
id_iter: 357, 358, 359.
id_map: 223, 233, 237, 239, 240, 314, 324, 327, 332, 344, 352, 356, 357, 358, 359, 444, 684, 685, 686, 689, 693.
id_node: 53, 87, 502, 510, 572, 573, 574, 575, 576, 586, 587, 588, 698, 702, 703.
Id_Node: 52, 53, 55, 162, 191, 192, 216, 226, 236, 237, 252, 296, 299, 447, 451, 468, 469, 471, 472, 474, 475, 478, 502, 510, 513, 572, 573, 574, 575, 576, 578, 579, 581, 583, 586, 587, 588, 606, 607, 608, 614, 638, 648, 660, 684, 686, 691, 693, 698, 703.
id_string: 9, 22, 29, 49, 124, 159, 188, 213, 249, 381, 678, 729, 734.
Id_Type: 6, 8, 52, 162, 191, 192, 193, 194, 195, 199, 200, 202, 203, 206, 209, 216, 223, 233, 240, 244, 245, 252, 357, 444, 468, 471, 474, 477, 579, 581, 583, 693, 745.
IDENTIFICATION_NUMBER: 107, 285, 562.
IDENTIFIER: 106, 281, 531, 701.
IDENTIFIER_FIELD: 62, 68, 92, 100, 106, 117, 701.
IDENTIFIER_FLAG: 79, 80, 103.
idtype.web.web: 5, 8.
idtype.web: 188.
IF: 280, 408.
ifstream: 25, 223, 731.
in_filename: 223, 308, 732, 747.
in_strm: 25, 223, 233, 309, 310, 315, 316, 320, 327, 328, 332, 333, 334, 335, 336, 337, 344, 353, 356, 358, 359, 731, 732, 745, 747.
initialize_flags: 101, 102, 104, 745.
initialize_id_map: 234, 235, 745, 748.
initialize_keyword_map: 732.
initialize_maps: 268, 269, 289, 745.
initialize_subtype_map: 195, 205, 206, 745.
initialize_type_maps: 99, 100, 181, 182, 745.
inner_mutex: 12, 14, 16.
INSTITUTION: 106, 281, 532, 701.
INSTITUTION_FIELD: 62, 68, 92, 100, 106, 117, 701.
INSTITUTION_FLAG: 79, 80, 103.
INT_TYPE: 73, 74, 97, 100, 112, 617.
int_value: 220, 307, 315, 320, 327, 332, 353, 356, 359, 368, 386, 387, 388, 396.
INTEGER: 273, 307, 315, 320, 327, 332, 353, 356, 587, 670, 672, 710, 711, 719.
is_open: 118, 119, 184, 233, 235.
isalpha: 318, 321.
isdigit: 322, 324.
isspace: 350, 353.
iter: 97, 112, 117, 152, 233, 237, 239, 292, 684, 685, 686, 687, 688, 689, 719.
iterator: 112, 117, 152, 233, 237, 357, 684, 719.
j: 241.
keyword_iter: 357, 359.
keyword_map: 263, 264, 270, 271, 272, 273, 274, 275, 276, 277, 278, 279, 280, 281, 283, 284, 285, 286, 287, 288, 289, 292, 312, 314, 324, 327, 332, 344, 352, 356, 357, 359.
Keyword_Type: 259, 261, 263, 264, 269, 270, 271, 272, 273, 274, 275, 276, 277, 278, 279, 280, 281, 283, 284, 285, 286, 287, 288, 289, 292, 357.
LANGUAGE: 106, 281, 533, 701.
LANGUAGE_FIELD: 62, 68, 92, 100, 106, 117, 701.
LANGUAGE_FLAG: 79, 80, 103.
left: 192, 200, 203, 242, 244, 245.
level_ctr: 115.
LIKE: 276, 400.
LIKE_VALUE: 82, 83, 100, 128, 488.
LOCAL: 275, 406, 505, 506, 699.
LOCAL_DATABASE_TARGET: 75, 76, 100, 699.
LOCAL_SERVER_TARGET: 75, 76, 100, 699.
local_time: 610.
localtime: 610.

location: 732.
lock: 13, 14, 41, 43, 91, 93, 96, 97, 111, 113, 118, 119, 127, 128, 130, 156, 176, 177, 180, 184, 203, 206, 209, 233, 235, 237, 238, 240, 241, 242, 243, 244, 245, 292, 307, 308, 309, 310, 312, 313, 315, 316, 317, 319, 320, 322, 323, 326, 327, 331, 332, 333, 334, 335, 336, 337, 338, 339, 340, 341, 342, 343, 344, 345, 346, 347, 348, 349, 351, 353, 354, 355, 356, 357, 358, 359, 389, 436, 437, 438, 439, 442, 443, 444, 445, 457, 459, 460, 461, 463, 464, 465, 466, 468, 469, 471, 472, 474, 475, 478, 482, 483, 485, 486, 487, 488, 490, 491, 493, 494, 495, 496, 497, 498, 499, 500, 502, 503, 505, 506, 507, 508, 510, 511, 512, 513, 514, 515, 517, 519, 520, 521, 522, 523, 524, 525, 526, 527, 528, 529, 530, 531, 532, 533, 534, 535, 536, 537, 538, 539, 540, 541, 542, 543, 544, 545, 546, 548, 549, 552, 554, 555, 556, 559, 560, 561, 562, 563, 564, 565, 566, 567, 568, 569, 570, 572, 573, 574, 575, 576, 578, 579, 581, 583, 586, 587, 588, 590, 591, 592, 593, 594, 595, 596, 597, 602, 603, 604, 605, 606, 607, 608, 609, 610, 614, 615, 616, 617, 618, 620, 621, 623, 624, 626, 627, 629, 630, 631, 632, 633, 634, 638, 639, 641, 643, 645, 648, 649, 650, 652, 654, 656, 660, 661, 662, 664, 666, 668, 670, 671, 672, 673, 683, 684, 685, 686, 688, 689, 691, 692, 693, 695, 696, 697, 698, 702, 703, 706, 707, 708, 715, 716, 717, 718, 719, 726, 732, 746, 747.
log_filename: 223, 747.
log_strm: 25, 90, 96, 97, 111, 113, 118, 119, 127, 128, 130, 156, 180, 184, 203, 206, 209, 223, 233, 235, 237, 238, 240, 241, 242, 243, 244, 245, 292, 307, 308, 309, 310, 312, 313, 315, 316, 317, 319, 320, 322, 323, 326, 327, 331, 332, 333, 334, 335, 336, 337, 338, 339, 340, 341, 342, 343, 344, 345, 346, 347, 348, 349, 351, 353, 354, 355, 356, 357, 358, 359, 421, 426, 427, 428, 429, 436, 437, 438, 439, 442, 443, 444, 445, 457, 459, 460, 461, 463, 464, 465, 466, 468, 469, 471, 472, 474, 475, 478, 482, 483, 485, 486, 487, 488, 490, 491, 493, 494, 495, 496, 497, 498, 499, 500, 502, 503, 505, 506, 507, 508, 510, 511, 512, 513, 514, 515, 517, 519, 520, 521, 522, 523, 524, 525, 526, 527, 528, 529, 530, 531, 532, 533, 534, 535, 536, 537, 538, 539, 540, 541, 542, 543, 544, 545, 546, 548, 549, 552, 554, 555, 556, 559, 560, 561, 562, 563, 564, 565, 566, 567, 568, 569, 570, 572, 573, 574, 575, 576, 578, 579, 581, 583, 586, 587, 588, 590, 591, 592, 593, 594, 595, 596, 597, 602, 603, 604, 605, 606, 607, 608, 609, 610, 614, 615, 616, 617, 618, 620, 621, 623, 624, 626, 627, 629, 630, 631, 632, 633, 634, 638, 639, 641, 643, 645, 648, 649, 650, 652, 654, 656, 660, 661, 662, 664, 666, 668, 670, 671, 672, 673, 683, 685, 686, 688, 689, 691, 693, 695, 697, 698, 702, 703, 706, 707, 708, 715, 716, 717, 718, 719, 726, 731, 732, 745, 746, 747.
log_strm_mutex: 25, 731, 732.
lookup: 236, 237, 245, 688.
lvalp: 394.
main: 6, 8, 195, 224, 745, 748.
`main.web`: 5, 8, 734.
`MAIN_CANONICAL_TITLE`: 106, 281, 409, 534, 701.
`MAIN_CANONICAL_TITLE_FIELD`: 61, 62, 68, 92, 99, 100, 105, 106, 117, 141, 142, 701.
`MAIN_CANONICAL_TITLE_FLAG`: 79, 80, 103, 114, 126, 142.
`MAIN_LOOP_END`: 353, 355.
make_pair: 670, 671, 672, 673.
map: 53, 81, 163, 167, 192, 195, 223, 233, 237, 263, 264, 266, 267, 292, 357, 684.
match_str: 128, 132, 133, 134, 135, 136, 137, 138, 139, 140, 142, 144, 145, 146, 147, 148, 149, 151, 152.
match_term_optional: 55, 226, 299, 703, 705.
match_value: 53, 82, 87, 89, 98, 117, 128, 705.
match_value_map: 53, 81, 99, 100, 117.
match_values: 53.
`MESSAGE`: 288, 418, 602.
Microsoft Visual Studio: 6.
`MINUS`: 272, 401.
`MINUS_ASSIGN`: 271, 400, 712.
`MINUTE`: 279, 407, 596, 710, 711.
minute: 33, 37, 39, 41, 43, 45, 149, 710, 711, 719, 724.
month: 33, 37, 39, 41, 43, 45, 149, 710, 711, 719, 721.
`MONTH`: 279, 407, 593, 710, 711.
mutex. See CMutex: 3.
Mutex_Type: 12, 14, 16, 18, 389, 736.
name: 53, 55, 97, 112, 117, 163, 192, 200, 203, 209, 226, 236, 237, 240, 241, 242, 244, 245, 261, 270, 271, 272, 273, 274, 275, 276, 277, 278, 279, 280, 281, 283, 284, 285, 286, 287, 288, 289, 292, 295, 296, 510, 683, 684, 685, 686, 687, 688, 691, 693, 698, 702, 703.
negate: 55, 226, 298, 695, 701, 702.
negated: 53, 87, 97, 112, 130, 621, 624, 627, 701, 702, 703.
negation_optional: 55, 226, 299, 703.
next: 53.
next_char: 309, 333, 334, 335, 336, 337.
nnegated: 88, 89.
`NON_WIN_LDF`: 30, 50, 125, 160, 189, 214, 250, 393, 679.

nonwin.web: 5, 8, 9.
NOT: 280, 337, 408.
NOT_ASSIGN: 271, 337, 400, 497.
nRetCode: 732.
NULL_BITSET: 78, 80, 132, 133, 134, 135, 136, 137, 138, 139, 140, 142, 144, 145, 146, 147, 148, 149, 151, 152.
NULL_STATE: 255, 258, 306, 310, 313, 319, 322, 331, 333, 334, 335, 336, 337, 338, 339, 340, 341, 342, 343, 345, 346, 347, 348, 349, 351.
NULL_TYPE: 236, 268, 287, 417.
OAI: 130, 138, 139, 140, 152, 288, 418, 582.
object: 55, 226, 298, 695, 697, 698.
ofstream: 18, 25, 223, 731, 736.
once: 23, 31, 51, 161, 190, 215, 251, 680.
oor_node: 88, 89.
op: 32, 33, 55, 226, 300, 301, 707, 710, 711, 712, 713, 714, 715, 716.
open: 610, 732, 747.
OPEN_BRACKET: 270, 348.
OPEN_PARENTHESIS: 270, 346.
open_parenthesis_str: 130, 132, 133, 134, 135, 136, 137, 138, 139, 140, 142, 144, 145, 146, 147, 148, 149, 151, 152.
optind: 747.
OR: 280, 335, 408, 631.
OR_ASSIGN: 271, 335, 400, 495, 702, 703.
or_node: 53, 87, 92, 97, 108, 112, 119, 130, 152, 627, 702, 703.
OR_NOT: 280, 335, 408, 627, 632.
or_or_or_not: 628.
OR_TYPE: 59, 60, 100, 130, 627, 702, 703.
ostream: 33, 42, 43.
OUTPUT: 288, 418.
pair: 670, 671, 672, 673, 717, 719.
parameter: 305, 306, 365, 394, 421, 426, 427, 428, 429, 436, 437, 438, 439, 442, 443, 444, 445, 447, 449, 451, 453, 457, 459, 460, 461, 463, 464, 465, 466, 468, 469, 471, 472, 474, 475, 477, 478, 482, 483, 485, 486, 487, 488, 490, 491, 493, 494, 495, 496, 497, 498, 499, 500, 502, 503, 505, 506, 507, 508, 510, 513, 517, 519, 520, 521, 522, 523, 524, 525, 526, 527, 528, 529, 530, 531, 532, 533, 534, 535, 536, 537, 538, 539, 540, 541, 542, 543, 544, 545, 546, 548, 549, 552, 554, 555, 556, 559, 560, 561, 562, 563, 564, 565, 566, 567, 568, 569, 570, 572, 573, 574, 575, 576, 578, 579, 581, 583, 586, 587, 588, 590, 591, 592, 593, 594, 595, 596, 597, 602, 603, 604, 605, 606, 607, 608, 609, 610, 614, 615, 616, 617, 618, 620, 621, 623, 624, 626, 627, 629, 630, 631, 632, 633, 634, 638, 639, 641, 643, 645, 648, 649, 650, 652, 654, 656, 660, 661, 662, 664, 666, 668, 670, 671, 672, 673, 676.
parser.w: 5, 8, 392.
parser_id_string: 392.
PAUSE: 288, 418.
peek: 333, 334, 335, 336, 337.
PERCENT: 268, 270, 341, 399.
PERIOD: 270, 343.
PERMUTATION_PATTERN: 106, 281, 535, 701.
PERMUTATION_PATTERN_FIELD: 62, 68, 92, 100, 106, 117, 701.
PERMUTATION_PATTERN_FLAG: 79, 80, 103.
PERSON: 106, 281, 536, 701.
PERSON_FIELD: 62, 68, 92, 100, 106, 117, 701.
PERSON_FLAG: 79, 80, 103.
PHYSICAL_DESCRIPTION: 106, 281, 537, 701.
PHYSICAL_DESCRIPTION_FIELD: 62, 68, 92, 100, 106, 117, 701.
PHYSICAL_DESCRIPTION_FLAG: 79, 80, 103.
PICA: 132, 133, 134, 135, 136, 137, 142, 144, 145, 146, 147, 148, 149, 151, 288, 418, 584.
PLUS: 272, 333, 401.
PLUS_ASSIGN: 271, 333, 400, 491, 494, 702, 703, 711.
pointer_value: 307, 359, 368, 396, 689.
pop: 307, 312.
pow: 745.
PQF_STRING_TYPE: 193, 194, 206.
PREFIX: 106, 284, 412, 556.
primary: 621.
prsrfncs.web: 678.
pthread_mutex_init: 12.
pthread_mutex_lock: 14.
pthread_mutex_t: 12.
pthread_mutex_unlock: 16.
PUBLISHER: 106, 281, 538, 701.
PUBLISHER_FIELD: 62, 68, 92, 100, 106, 117, 701.
PUBLISHER_FLAG: 79, 80, 103.
push: 313, 317, 359, 457, 689.
push_back: 97, 461, 549, 670, 671, 672, 673, 699.
push_front: 517.
q: 95, 96, 98, 579, 581, 583, 615, 639, 661.
qquery_type: 88, 89.
qtgensql.web: 5, 8, 124.
query_assignment_func_0: 55, 226, 298, 505, 506, 507, 508, 695, 702.
query_assignment_func_1: 55, 226, 299, 510, 511, 513, 514, 703, 706.
query_ctr: 53, 54, 87, 96, 111, 112, 127, 131, 152, 153, 154, 155, 621, 624, 627, 702, 703.
QUERY_DECLARATOR: 275.
query_node: 229.

Query_Node: 17, 52, 53, 88, 89, 92, 95, 96, 203, 216, 223, 229, 252, 502, 579, 581, 583, 606, 614, 615, 616, 617, 618, 621, 624, 627, 698, 703.
Query_Nodes: 115.
QUERY_TYPE: 203, 287, 417, 447, 468, 510, 703.
query_type: 53, 57, 59, 87, 97, 112, 117, 127, 130, 621, 624, 627, 698, 701, 702, 703.
Query_Type: 6, 8, 17, 32, 33, 52, 53, 58, 60, 68, 70, 71, 72, 74, 76, 80, 81, 83, 86, 87, 89, 90, 91, 94, 95, 96, 97, 98, 100, 102, 104, 106, 108, 111, 113, 115, 116, 120, 127, 156, 216, 252, 485, 486, 487, 488, 614, 616, 617, 618, 621, 624, 627, 698, 699, 701, 702, 703, 745.
QUERY_TYPE_BITSET_SIZE: 77, 78, 79, 80, 104, 114, 127, 582, 584.
query_type_map: 53, 81, 100, 112, 117, 127.
QUERY_TYPE_NULL_TYPE: 57, 58, 87, 89, 97, 100, 108, 128, 485, 701.
query_type_str: 129, 130, 132, 133, 134, 135, 136, 137, 138, 139, 140, 142, 144, 145, 146, 147, 148, 149, 151, 152.
QUERY_TYPE_STRING_TYPE: 73, 74, 97, 100, 112, 117, 152, 616, 701, 702.
queryexp.w: 5, 8.
queryexp_id_string: 612.
querytyp.web: 5, 8, 49.
QUERYTYP_KNOWN: 123.
r: 582, 584.
RECORD: 107, 281, 539, 701.
RECORD_DATE_MOST_RECENT_CHANGE_FIELD: 66, 72, 92, 100, 107, 117.
RECORD_DATE_MOST_RECENT_CHANGE_FLAG: 79, 80, 103.
RECORD_DATE_ORIGINAL_ENTRY_FIELD: 66, 72, 92, 100, 107, 117.
RECORD_DATE_ORIGINAL_ENTRY_FLAG: 79, 80, 103.
RECORD_DATE_STATUS_CHANGE_FIELD: 66, 72, 92, 100, 107, 117, 149.
RECORD_DATE_STATUS_CHANGE_FLAG: 79, 80, 103, 149.
RECORD_ELN_MOST_RECENT_CHANGE_FIELD: 66, 72, 92, 107, 117, 146.
RECORD_ELN_MOST_RECENT_CHANGE_FLAG: 79, 80, 103, 146.
RECORD_ELN_ORIGINAL_ENTRY_FIELD: 66, 72, 92, 107, 117, 145.
RECORD_ELN_ORIGINAL_ENTRY_FLAG: 79, 80, 103, 145.
RECORD_ELN_STATUS_CHANGE_FIELD: 66, 72, 92, 100, 107, 117, 147.
RECORD_ELN_STATUS_CHANGE_FLAG: 79, 80, 103, 147.
RECORD_END_TAG: 387.
RECORD_FIELD: 62, 68, 92, 100, 107, 117, 701.
RECORD_FLAG: 79, 80, 103, 144, 145, 146, 147, 148, 149.
RECORD_ID_FIELD: 66, 72, 92, 107, 117, 144.
RECORD_ID_FLAG: 79, 80, 103, 144.
RECORD_IDENTIFICATION_NUMBER_FIELD: 66, 72, 92, 100, 107, 117, 148.
RECORD_IDENTIFICATION_NUMBER_FLAG: 79, 80, 103, 148.
RECORD_SOURCE_ID_FIELD: 66, 72, 92, 107, 117.
RECORD_SOURCE_ID_FLAG: 79, 80, 103.
RECORD_START_TAG: 386.
RECORD_YEAR_APPEARANCE_BEGIN_FIELD: 66, 72, 92, 107, 117.
RECORD_YEAR_APPEARANCE_BEGIN_FLAG: 79, 80, 103.
RECORD_YEAR_APPEARANCE_END_FIELD: 66, 72, 92, 107, 117.
RECORD_YEAR_APPEARANCE_END_FLAG: 79, 80, 103.
RECORD_YEAR_APPEARANCE_ORIGINAL_FIELD: 66, 72, 92, 107, 117.
RECORD_YEAR_APPEARANCE_ORIGINAL_FLAG: 79, 80, 103.
RECORD_YEAR_APPEARANCE_RAK_WB_FIELD: 66, 72, 92, 107, 117.
RECORD_YEAR_APPEARANCE_RAK_WB_FLAG: 79, 80, 103.
REMOTE: 275, 507, 508, 699.
REMOTE_ACCESS: 108, 281, 540, 701.
REMOTE_ACCESS_FIELD: 62, 68, 92, 100, 108, 117, 701.
REMOTE_ACCESS_FLAG: 79, 80, 103.
REMOTE_DATABASE_TARGET: 75, 76, 100, 699.
REMOTE_SERVER_TARGET: 75, 76, 100, 699.
return_str: 114, 127, 130, 152, 156.
right: 149, 192, 200, 203, 245.
RIGHTS: 108, 281, 541, 701.
RIGHTS_FIELD: 62, 68, 92, 100, 108, 117, 701.
RIGHTS_FLAG: 79, 80, 103.
s: 44, 45, 115, 116, 183, 184, 205, 206, 209, 366, 395, 740, 741, 743, 744.
Scan_Parse: 32, 33, 55, 122, 158, 186, 203, 209, 226, 238, 248, 255, 256, 259, 269, 289, 292, 303, 304, 306, 447, 449, 451, 453, 457, 510, 511, 514, 683, 689, 691, 693, 695, 702, 703, 706, 707, 715, 716, 726, 728, 732, 745.
scanner: 745.
scanner.web: 5, 8, 249.
Scanner_Node: 17, 52, 54, 55, 88, 89, 105, 106, 110, 111, 114, 115, 116, 127, 162, 163, 173, 174, 183, 184, 191, 192, 198, 205, 206, 216, 223, 226,

252, 299, 421, 426, 427, 428, 429, 436, 437, 438, 439, 442, 443, 444, 445, 457, 459, 460, 461, 463, 464, 465, 466, 468, 469, 471, 472, 474, 475, 477, 478, 482, 483, 485, 486, 487, 488, 490, 491, 493, 494, 495, 496, 497, 498, 499, 500, 502, 503, 505, 506, 507, 508, 510, 513, 517, 519, 520, 521, 522, 523, 524, 525, 526, 527, 528, 529, 530, 531, 532, 533, 534, 535, 536, 537, 538, 539, 540, 541, 542, 543, 544, 545, 546, 548, 549, 552, 554, 555, 556, 559, 560, 561, 562, 563, 564, 565, 566, 567, 568, 569, 570, 572, 573, 574, 575, 576, 578, 579, 581, 583, 586, 587, 588, 590, 591, 592, 593, 594, 595, 596, 597, 602, 603, 604, 605, 606, 607, 608, 609, 610, 614, 615, 616, 617, 618, 620, 621, 623, 624, 626, 627, 629, 630, 631, 632, 633, 634, 638, 639, 641, 643, 645, 648, 649, 650, 652, 654, 656, 660, 661, 662, 664, 666, 668, 670, 671, 672, 673, 683, 691, 695, 703, 707, 716, 745.

scanner_node: 54, 55, 87, 90, 94, 96, 97, 108, 110, 111, 112, 113, 114, 115, 116, 118, 119, 127, 128, 130, 152, 156, 163, 178, 180, 184, 192, 198, 200, 203, 209, 226, 291, 292, 299, 306, 307, 308, 309, 310, 312, 313, 315, 316, 317, 319, 320, 322, 323, 326, 327, 328, 331, 332, 333, 334, 335, 336, 337, 338, 339, 340, 341, 342, 343, 344, 345, 346, 347, 348, 349, 351, 353, 354, 355, 356, 357, 358, 359, 421, 426, 427, 428, 429, 436, 437, 438, 439, 442, 443, 444, 445, 457, 459, 460, 461, 463, 464, 465, 466, 468, 469, 471, 472, 474, 475, 477, 478, 482, 483, 485, 486, 487, 488, 490, 491, 493, 494, 495, 496, 497, 498, 499, 500, 502, 503, 505, 506, 507, 508, 510, 511, 512, 513, 514, 515, 517, 519, 520, 521, 522, 523, 524, 525, 526, 527, 528, 529, 530, 531, 532, 533, 534, 535, 536, 537, 538, 539, 540, 541, 542, 543, 544, 545, 546, 548, 549, 552, 554, 555, 556, 559, 560, 561, 562, 563, 564, 565, 566, 567, 568, 569, 570, 572, 573, 574, 575, 576, 578, 579, 580, 581, 582, 583, 584, 586, 587, 588, 590, 591, 592, 593, 594, 595, 596, 597, 602, 603, 604, 605, 606, 607, 608, 609, 610, 614, 615, 616, 617, 618, 620, 621, 623, 624, 626, 627, 629, 630, 631, 632, 633, 634, 638, 639, 641, 643, 645, 648, 649, 650, 652, 654, 656, 660, 661, 662, 664, 666, 668, 670, 671, 672, 673, 683, 684, 685, 686, 688, 689, 691, 692, 693, 695, 696, 697, 698, 702, 703, 706, 707, 708, 715, 716, 717, 718, 719, 726, 732, 745, 746, 747, 748.

Scanner_Type: 6, 8, 17, 52, 162, 191, 192, 216, 223, 230, 231, 232, 233, 235, 237, 245, 252, 291, 292, 306, 732, 745.

`scantest.web`: 5, 8, 729.

`scnrtype.web`: 5, 8, 213.

`SCNRTYPE_KNOWN`: 248.

`SECOND`: 279, 407, 597, 710, 711.

second: 33, 37, 39, 41, 43, 45, 149, 233, 237, 292, 359, 687, 688, 710, 711, 719, 720, 721, 722, 723, 724, 725.

secondary: 621, 624.

select_strm: 114, 127, 131, 132, 133, 134, 135, 136, 137, 138, 139, 140, 142, 144, 145, 146, 147, 148, 149, 151, 152, 154, 581, 582, 583, 584.

`SEMI_COLON`: 270, 339.

`SERVER`: 275, 405, 406, 506, 508, 699.

set: 88, 89, 173, 174.

set_field_specifier: 105, 106, 108, 703.

set_field_type: 105.

setfill: 149.

setprecision: 149.

setw: 149.

shift_value: 102, 103, 104.

shorts: 61, 75, 82, 90, 99, 105, 114, 117, 126, 193, 194.

show: 44, 45, 115, 116, 119, 120, 183, 184, 208, 209, 468, 469, 471, 472, 474, 475, 478, 606, 607, 608.

`SHOW`: 288, 418.

show_keyword_map: 291, 292, 732, 748.

size: 106, 107, 112, 152, 307, 688, 718, 719, 721, 722, 723, 724, 725.

`SOURCE`: 108, 281, 542, 701.

`SOURCE_FIELD`: 62, 68, 92, 100, 108, 117, 701.

`SOURCE_FLAG`: 79, 80, 103.

`SOURCE_ID`: 107, 285, 566.

specifier: 32, 33, 55, 226, 300, 707, 710, 711.

`SQL`: 288, 418.

`SQL_STRING_TYPE`: 193, 194, 206, 581, 583.

sql_strm: 114, 127, 152, 154, 155, 156.

sscanner_node: 88, 89, 105, 106, 115, 116, 119, 173, 174, 183, 184.

stack: 223, 306.

`START`: 274.

start_local_database_query_func: 55, 226, 303.

start_local_query_func: 55, 226, 303.

state: 306, 310, 312, 313, 314, 315, 316, 317, 319, 320, 321, 322, 323, 324, 326, 327, 328, 331, 332, 333, 334, 335, 336, 337, 338, 339, 340, 341, 342, 343, 344, 345, 346, 347, 348, 349, 351, 352, 353, 355, 356.

state_stack: 306, 312, 313, 317.

status: 510, 511, 513, 514, 732, 745, 748.

std: 20, 21, 47, 48, 122, 123, 158, 186, 187, 211, 212, 247, 248, 361, 362, 379, 390, 728, 732, 733, 750.

`stdafx.web`: 5, 8, 22.

str: 41, 43, 45, 91, 93, 96, 97, 111, 113, 118, 119, 127, 128, 130, 149, 154, 155, 156, 176, 177, 180, 184, 203, 206, 209, 233, 235, 237, 238, 240, 241, 242, 243, 244, 245, 292, 307, 308, 309, 310, 312, 313, 315, 316, 317, 319, 320, 322, 323, 326, 327, 331, 332, 333, 334, 335, 336, 337, 338, 339, 340, 341, 342, 343, 344, 345, 346, 347, 348, 349, 351, 353, 354, 355, 356, 357, 358, 359, 421, 426, 427, 428, 429, 436, 437, 438, 439, 442, 443, 444, 445, 457, 459, 460, 461, 463, 464, 465, 466, 468, 469, 471, 472, 474, 475, 478, 482, 483, 485, 486, 487, 488, 490, 491, 493, 494, 495, 496, 497, 498, 499, 500, 502, 503, 505, 506, 507, 508, 510, 511, 512, 513, 514, 515, 517, 519, 520, 521, 522, 523, 524, 525, 526, 527, 528, 529, 530, 531, 532, 533, 534, 535, 536, 537, 538, 539, 540, 541, 542, 543, 544, 545, 546, 548, 549, 552, 554, 555, 556, 559, 560, 561, 562, 563, 564, 565, 566, 567, 568, 569, 570, 572, 573, 574, 575, 576, 578, 579, 580, 581, 582, 583, 584, 586, 587, 588, 590, 591, 592, 593, 594, 595, 596, 597, 602, 603, 604, 605, 606, 607, 608, 609, 610, 614, 615, 616, 617, 618, 620, 621, 623, 624, 626, 627, 629, 630, 631, 632, 633, 634, 638, 639, 641, 643, 645, 648, 649, 650, 652, 654, 656, 660, 661, 662, 664, 666, 668, 670, 671, 672, 673, 683, 684, 685, 686, 688, 689, 691, 692, 693, 695, 696, 697, 698, 702, 703, 706, 707, 708, 715, 716, 717, 718, 719, 726, 732, 746, 747.
strcat: 443, 444, 460, 461.
strchar: 240, 241, 245.
strchr: 240, 687, 688.
strcpy: 307, 312, 358, 442, 459, 460, 578, 579, 580, 581, 582, 583, 584, 648, 649, 650, 652, 654, 656, 732, 747.
STRING: 273, 307, 312.
string: 18, 44, 45, 53, 81, 90, 92, 97, 110, 111, 112, 114, 115, 116, 117, 127, 128, 129, 130, 132, 133, 134, 135, 136, 137, 138, 139, 140, 142, 148, 151, 152, 163, 167, 183, 184, 192, 193, 195, 208, 209, 223, 233, 237, 241, 261, 263, 264, 266, 267, 292, 309, 357, 578, 579, 581, 583, 616, 648, 684, 701, 702, 736.
STRING_DECLARATOR: 275, 404.
STRING_TYPE: 287, 417, 451, 474.
string_value: 307, 312, 358, 368, 396.
strings: 192.
strings_id_string: 646.
stringstream: 41, 43, 45, 91, 96, 106, 110, 111, 114, 116, 127, 176, 180, 184, 203, 206, 209, 233, 235, 237, 241, 292, 306, 579, 580, 581, 583, 610, 676, 683, 691, 695, 703, 707, 716, 745.
strlen: 241.
SUBJECT: 108, 281, 409, 543, 701.
SUBJECT_FIELD: 61, 62, 68, 92, 100, 108, 117, 150, 152, 701.
SUBJECT_FLAG: 79, 80, 103, 151, 152.
subscript_iter: 688.
subtype: 192, 200, 209, 579, 581, 583.
subtype_map: 192, 195, 206, 209.
SUPERORDINATE_ENTITIES: 108, 281, 544, 701.
SUPERORDINATE_ENTITIES_FIELD: 62, 68, 92, 100, 108, 117, 701.
SUPERORDINATE_ENTITIES_FLAG: 79, 80, 103.
SURNAME: 106, 284, 412, 554.
table: 106, 107, 108.
target_type: 57, 89, 117.
target_type_map: 53, 81, 99, 100, 112, 117, 152.
target_types: 53, 75, 97, 112, 117, 152, 699.
TCHAR: 732.
temp_filename: 610.
temp_query: 703.
temp_strm: 41, 43, 45, 91, 93, 96, 97, 106, 111, 113, 116, 117, 118, 119, 127, 128, 130, 152, 155, 156, 176, 177, 180, 184, 203, 206, 209, 233, 235, 237, 238, 240, 241, 242, 243, 244, 245, 292, 306, 307, 308, 309, 310, 312, 313, 315, 316, 317, 319, 320, 322, 323, 326, 327, 331, 332, 333, 334, 335, 336, 337, 338, 339, 340, 341, 342, 343, 344, 345, 346, 347, 348, 349, 351, 353, 354, 355, 356, 357, 358, 359, 421, 426, 427, 428, 429, 436, 437, 438, 439, 442, 443, 444, 445, 457, 459, 460, 461, 463, 464, 465, 466, 468, 469, 471, 472, 474, 475, 477, 478, 482, 483, 485, 486, 487, 488, 490, 491, 493, 494, 495, 496, 497, 498, 499, 500, 502, 503, 505, 506, 507, 508, 510, 511, 512, 513, 514, 515, 517, 519, 520, 521, 522, 523, 524, 525, 526, 527, 528, 529, 530, 531, 532, 533, 534, 535, 536, 537, 538, 539, 540, 541, 542, 543, 544, 545, 546, 548, 549, 552, 554, 555, 556, 559, 560, 561, 562, 563, 564, 565, 566, 567, 568, 569, 570, 572, 573, 574, 575, 576, 578, 579, 581, 583, 586, 587, 588, 590, 591, 592, 593, 594, 595, 596, 597, 602, 603, 604, 605, 606, 607, 608, 609, 610, 614, 615, 616, 617, 618, 620, 621, 623, 624, 626, 627, 629, 630, 631, 632, 633, 634, 638, 639, 641, 643, 645, 648, 649, 650, 652, 654, 656, 660, 661, 662, 664, 666, 668, 670, 671, 672, 673, 676, 683, 684, 685, 686, 688, 689, 691, 692, 693, 695, 696, 697, 698, 702, 703, 706, 707, 708, 715, 716, 717, 718, 719, 726, 732, 745, 746, 747.
temp_val: 745.
TERMINATE: 289, 732.
tertiary: 624, 627.
TEX: 288, 418.

tex_file_ctr: 18, 610, 736, 745.
tex_file_strm: 18, 610, 736.
tex_filename_str: 18, 610, 736, 745.
tex_mutex: 18, 610, 736.
TEX_STRING_TYPE: 193, 194, 206, 579.
tex_strm: 110, 111, 112, 113, 579, 580, 581, 582, 583, 584.
theApp: 732.
this: 41, 96, 97, 98, 180, 234.
time: 610.
time_mutex: 18, 610, 736.
TIMES: 272, 401.
TIMES_ASSIGN: 271, 400, 713.
TIMMS: 277, 406.
TIMMS_TYPE: 165, 166, 181, 182, 575.
TITLE: 108, 281, 409, 545, 701.
TITLE_FIELD: 61, 62, 68, 92, 100, 108, 117, 139, 140, 701.
TITLE_FLAG: 79, 80, 103, 140.
tm: 610.
TO DO: 90, 92, 707, 716.
token_map: 127, 203, 209, 238, 266, 267, 270, 271, 272, 273, 274, 275, 276, 277, 278, 279, 280, 281, 283, 284, 285, 286, 287, 288, 289, 292, 307, 691, 693, 698, 707, 715.
token_stack: 223, 307, 359, 457, 689.
Token_Type: 217, 219, 220, 221, 222, 223, 307, 359, 457, 689.
top: 307, 312.
TOP_TYPE: 59, 60, 100, 168, 698, 701, 702, 703.
tp: 610.
traverse: 105, 106, 108.
traverse_query: 703.
true: 108, 240, 244, 245, 582, 584, 621, 624, 627, 688, 703.
ttarget: 88.
ttarget_type: 88.
ttype: 221, 222.
type: 32, 33, 55, 163, 180, 184, 192, 200, 203, 209, 217, 220, 222, 226, 236, 237, 238, 240, 244, 245, 296, 299, 300, 307, 359, 457, 573, 574, 575, 576, 688, 689, 691, 693, 703, 707, 710, 711.
TYPE: 108, 281, 546, 701.
TYPE_FIELD: 62, 68, 92, 100, 108, 117, 701.
TYPE_FLAG: 79, 80, 103.
ULONG_LONG_MAX: 745.
UNDERLINE: 399.
unget: 315, 316, 320, 327, 332, 344, 353, 356, 358, 359.
unlock: 15, 16, 41, 43, 91, 93, 96, 97, 111, 113, 118, 119, 127, 128, 130, 156, 176, 177, 180, 184, 203, 206, 209, 233, 235, 237, 238, 240, 241, 242, 243, 244, 245, 292, 307, 308, 309, 310, 312, 313, 315, 316, 317, 319, 320, 322, 323, 326, 327, 331, 332, 333, 334, 335, 336, 337, 338, 339, 340, 341, 342, 343, 344, 345, 346, 347, 348, 349, 351, 353, 354, 355, 356, 357, 358, 359, 389, 436, 437, 438, 439, 442, 443, 444, 445, 457, 459, 460, 461, 463, 464, 465, 466, 468, 469, 471, 472, 474, 475, 478, 482, 483, 485, 486, 487, 488, 490, 491, 493, 494, 495, 496, 497, 498, 499, 500, 502, 503, 505, 506, 507, 508, 510, 511, 512, 513, 514, 515, 517, 519, 520, 521, 522, 523, 524, 525, 526, 527, 528, 529, 530, 531, 532, 533, 534, 535, 536, 537, 538, 539, 540, 541, 542, 543, 544, 545, 546, 548, 549, 552, 554, 555, 556, 559, 560, 561, 562, 563, 564, 565, 566, 567, 568, 569, 570, 572, 573, 574, 575, 576, 578, 579, 581, 583, 586, 587, 588, 590, 591, 592, 593, 594, 595, 596, 597, 602, 603, 604, 605, 606, 607, 608, 609, 610, 614, 615, 616, 617, 618, 620, 621, 623, 624, 626, 627, 629, 630, 631, 632, 633, 634, 638, 639, 641, 643, 645, 648, 649, 650, 652, 654, 656, 660, 661, 662, 664, 666, 668, 670, 671, 672, 673, 683, 684, 685, 686, 688, 689, 691, 692, 693, 695, 696, 697, 698, 702, 703, 706, 707, 708, 715, 716, 717, 718, 719, 726, 732, 746, 747.
up: 53, 87, 92, 97, 112, 117, 152, 192, 200, 244, 245, 621, 624, 627, 701, 702, 703.
uup: 88, 89.
v: 32, 33, 55, 105, 106, 226, 295, 296, 298, 299, 300, 301, 670, 671, 672, 673, 683, 691, 695, 703, 707, 716.
val: 32, 33, 55, 226, 300, 587, 588, 707, 708, 710, 711.
value: 53, 55, 87, 92, 97, 112, 117, 132, 133, 134, 135, 136, 137, 138, 139, 140, 142, 144, 145, 146, 147, 148, 149, 151, 152, 163, 192, 200, 203, 209, 217, 220, 222, 226, 261, 270, 271, 272, 273, 274, 275, 276, 277, 278, 279, 280, 281, 283, 284, 285, 286, 287, 288, 289, 292, 298, 305, 306, 307, 312, 315, 316, 320, 327, 332, 344, 353, 356, 358, 359, 457, 502, 510, 572, 573, 574, 575, 576, 578, 579, 581, 583, 586, 587, 588, 606, 607, 608, 614, 616, 617, 618, 638, 648, 660, 695, 698, 701, 702, 703, 732.
value_name: 261, 270, 271, 272, 273, 274, 275, 276, 277, 278, 279, 280, 281, 283, 284, 285, 286, 287, 288, 289, 292, 312, 359.
value_type: 53, 57, 73, 87, 97, 112, 117, 152, 616, 617, 618, 701, 702, 703.
value_type_map: 53, 81, 100, 112, 117, 152.
values: 90.
VARIABLE: 286, 359, 468, 471, 474, 477.
variable_func: 55, 226, 295, 457, 683, 689.

VARIABLE_TEXT_SEGMENT: 286, 358.
variabls.w : 5, 8.
variabls_id_string: 455.
VC_EXTRALEAN: 24.
vec: 32, 33, 55, 226, 301, 717, 718, 719, 720, 721, 722, 723, 724, 725.
vector: 53, 97, 112, 117, 152, 223, 670, 671, 672, 673, 688, 717, 719.
vvalue: 88, 89, 221, 222.
vvalue_type: 88, 89.
w: 716.
where_strm_0: 114, 127, 132, 133, 134, 135, 136, 137, 138, 139, 140, 142, 144, 145, 146, 147, 148, 149, 151, 152, 153, 154, 581, 582, 583, 584.
where_strm_1: 114, 127, 132, 133, 134, 135, 136, 137, 138, 139, 140, 142, 151, 152, 154, 581, 582, 583, 584.
WHILE: 280, 408.
WIN_LDF: 23, 31, 51, 161, 190, 215, 251, 680.
XOR: 280, 336, 408, 633.
XOR_ASSIGN: 271, 336, 400, 496, 702, 703.
xor_node: 53, 87, 92, 97, 108, 112, 119, 130, 152, 624, 702, 703.
XOR_NOT: 280, 336, 408, 624, 634.
xor_or_xor_not: 628.
XOR_TYPE: 59, 60, 100, 130, 624, 702, 703.
xxerror: 366, 743, 744.
xxlex_destroy: 745.
xxlex_init: 745.
xxor_node: 88, 89.
xxparse: 742, 745.
xxset_in: 745.
year: 33, 37, 39, 41, 43, 45, 149, 710, 711, 719, 720.
YEAR: 279, 407, 592, 710, 711.
YEAR_APPEARANCE_BEGIN: 107, 285, 567.
YEAR_APPEARANCE_END: 107, 285, 568.
YEAR_APPEARANCE_ORIGINAL: 107, 285, 570.
YEAR_APPEARANCE_RAK_WB: 107, 285, 569.
YEAR_RANGE_BEGIN: 279, 407, 590, 710, 711.
year_range_begin: 33, 37, 39, 41, 43, 45, 710, 711.
year_range_end: 33, 37, 39, 41, 43, 45, 710, 711.
YEAR_RANGE_END: 279, 407, 591, 710, 711.
yychar: 457.
yyclearin: 457.
yydebug: 18, 746.
yyerror: 395, 740, 741.
yylex: 6, 8, 223, 224, 305, 306, 354, 357, 394, 729, 732.
YYLEX_PARAM: 365, 676.
YYLTYPE: 732.
yylval: 386, 387, 388, 457.
yyparse: 33, 55, 164, 223, 224, 738, 748.
YYPARSE_PARAM: 365, 676.
yyscan_t: 745.
YYSTYPE: 217, 221, 222, 224, 305, 306, 368, 394, 396, 689, 732, 745.
yytext: 386, 387.
yywrap: 739.

⟨ Bison declarations 397 ⟩ Used in section 676.
⟨ Bison options 367 ⟩ Used in section 379.
⟨ Common code for punctuation 355, 356 ⟩ Cited in section 343. Used in section 354.
⟨ Declare Dublin Core parser functions 366 ⟩ Used in section 379.
⟨ Declare namespace **Scan_Parse** 255 ⟩ Used in section 361.
⟨ Declare non-member functions for **Date_Time_Type** 42 ⟩ Used in sections 47 and 48.
⟨ Declare scanning and parsing functions 738, 739, 740, 742, 743 ⟩ Used in section 750.
⟨ Declare **Datasource_Type** functions 171, 173, 175, 179, 181, 183 ⟩ Used in section 163.
⟨ Declare **Date_Time_Type** functions 36, 38, 40, 44 ⟩ Used in section 33.
⟨ Declare **Id_Type** functions 199, 202, 205, 208 ⟩ Used in section 192.
⟨ Declare **Mutex_Type** functions 13, 15 ⟩ Used in section 12.
⟨ Declare **Query_Type** functions 86, 88, 90, 95, 99, 101, 105, 110, 114, 115 ⟩ Used in section 54.
⟨ Declare **Scan_Parse** functions 268, 291, 295, 296, 298, 299, 300, 301, 303, 304 ⟩ Used in sections 255 and 259.
⟨ Declare **Scanner_Type** functions 230, 232, 234, 236 ⟩ Used in section 223.
⟨ Declare **Token_Type** functions 219, 221 ⟩ Used in section 217.
⟨ Declare **class Datasource_Type** 163 ⟩ Used in sections 186 and 187.
⟨ Declare **class Date_Time_Type** 33 ⟩ Used in sections 47 and 48.
⟨ Declare **class Query_Type** 53, 54 ⟩ Used in sections 122 and 123.
⟨ Declare **class Scanner_Type** 223 ⟩ Used in sections 247 and 248.
⟨ Declare *keyword_map* 263 ⟩ Used in section 255.
⟨ Declare **static Datasource_Type** constants 165, 168 ⟩ Used in section 163.
⟨ Declare **static Id_Type** constants 193 ⟩ Used in section 192.
⟨ Declare **static Id_Type** variables 195 ⟩ Used in section 211.
⟨ Declare **static Query_Type** constants 57, 59, 62, 64, 65, 66, 73, 75, 82 ⟩ Used in section 54.
⟨ Declare **static Query_Type** variables 78, 79 ⟩ Used in section 54.
⟨ Declare **struct Id_Type** 192 ⟩ Used in sections 211 and 212.
⟨ Declare **struct Keyword_Type** 261 ⟩ Used in section 255.
⟨ Declare **struct Token_Type** 217 ⟩ Used in sections 247 and 248.
⟨ Declare *token_map* 266 ⟩ Used in section 255.
⟨ Declare *yyerror* 395 ⟩ Used in section 676.
⟨ Declare *yylex* 305, 394 ⟩ Used in sections 362 and 676.
⟨ Define non-member functions for **Date_Time_Type** 43 ⟩ Used in section 47.
⟨ Define parser functions 683, 684, 685, 686, 687, 688, 689, 691, 692, 693, 695, 696, 697, 698, 699, 701, 702, 703, 704, 705, 706, 707, 708, 709, 710, 711, 712, 713, 714, 715, 716, 717, 718, 719, 720, 721, 722, 723, 724, 725, 726 ⟩ Used in section 728.
⟨ Define scanning and parsing functions 741, 744 ⟩ Used in section 750.
⟨ Define **Datasource_Type** functions 172, 174, 176, 177, 178, 180, 182, 184 ⟩ Used in section 186.
⟨ Define **Date_Time_Type** functions 37, 39, 41, 45 ⟩ Used in section 47.
⟨ Define **Id_Type** functions 200, 203, 206, 209 ⟩ Used in section 211.
⟨ Define **Mutex_Type** functions 14, 16 ⟩ Used in section 21.
⟨ Define **Query_Type** functions 87, 89, 91, 92, 93, 94, 96, 97, 98, 100, 102, 103, 104, 106, 107, 108, 111, 112, 113, 116, 117, 118, 119, 120, 127, 128, 129, 130, 131, 132, 133, 134, 135, 136, 137, 138, 139, 140, 141, 142, 144, 145, 146, 147, 148, 149, 150, 151, 152, 153, 154, 155, 156 ⟩ Used in sections 122 and 158.
⟨ Define **Scan_Parse** functions 269, 270, 271, 272, 273, 274, 275, 276, 277, 278, 279, 280, 281, 283, 284, 285, 286, 287, 288, 289, 292 ⟩ Used in section 361.
⟨ Define **Scanner_Type** functions 231, 233, 235, 237, 238, 239, 240, 241, 242, 243, 244, 245 ⟩ Used in section 247.
⟨ Define **Token_Type** functions 220, 222 ⟩ Used in section 247.
⟨ Define *_tmain* 732 ⟩ Used in section 733.
⟨ Define *main* 745, 746, 747, 748 ⟩ Used in section 750.
⟨ Define *yylex* 306, 307, 308, 309, 310, 311, 312, 313, 314, 315, 316, 317, 318, 319, 320, 321, 322, 323, 324, 325, 326, 327, 328, 329, 331, 332, 333, 334, 335, 336, 337, 338, 339, 340, 341, 342, 343, 344, 345, 346, 347, 348, 349, 350, 351, 352, 353, 354 ⟩ Used in section 361.

⟨ Dublin Core parser rules 373, 375, 376, 378 ⟩ Used in section 379.
⟨ Dublin Core scanner rules 386, 387, 388, 389 ⟩ Used in section 390.
⟨ Filename sections 675 ⟩ Used in sections 676 and 677.
⟨ Flex options 383 ⟩ Used in section 390.
⟨ Forward declarations 17, 32, 52, 162, 191, 216, 252 ⟩ Used in sections 20, 47, 48, 122, 123, 186, 187, 211, 212, 247, 248, 361, and 362.
⟨ GNU Free Documentation License 752 ⟩ Cited in section 2. Used in section 753.
⟨ GNU General Public License 751 ⟩ Cited in section 2. Used in section 753.
⟨ Garbage 426 ⟩ Used in section 677.
⟨ Global variables 731, 736 ⟩ Used in sections 733 and 750.
⟨ Include files 10, 24, 30, 50, 125, 160, 189, 214, 250, 364, 382, 393, 679, 730, 735 ⟩ Used in sections 20, 21, 28, 47, 122, 158, 186, 211, 247, 361, 379, 390, 676, 728, 733, and 750.
⟨ Initialize **static Datasource_Type** constants 166 ⟩ Used in section 186.
⟨ Initialize **static Datasource_Type** variables 167 ⟩ Used in section 186.
⟨ Initialize **static Id_Type** constants 194 ⟩ Used in section 211.
⟨ Initialize **static Query_Type** constants 58, 60, 67, 68, 70, 71, 72, 74, 76, 83 ⟩ Used in section 122.
⟨ Initialize **static Query_Type** variables 80, 81 ⟩ Used in section 122.
⟨ Look up *curr_id* in *keyword_map* and possibly *id_map* 357, 358, 359 ⟩ Used in sections 314, 324, 327, 332, 344, 352, and 356.
⟨ Parser rules 421, 423, 424, 427, 428, 429, 436, 437, 438, 439, 442, 443, 444, 445, 447, 449, 451, 453, 457, 459, 460, 461, 463, 464, 465, 466, 468, 469, 471, 472, 474, 475, 477, 478, 482, 483, 485, 486, 487, 488, 490, 491, 493, 494, 495, 496, 497, 498, 499, 500, 502, 503, 505, 506, 507, 508, 510, 511, 512, 513, 514, 515, 517, 519, 520, 521, 522, 523, 524, 525, 526, 527, 528, 529, 530, 531, 532, 533, 534, 535, 536, 537, 538, 539, 540, 541, 542, 543, 544, 545, 546, 548, 549, 552, 554, 555, 556, 559, 560, 561, 562, 563, 564, 565, 566, 567, 568, 569, 570, 572, 573, 574, 575, 576, 578, 579, 580, 581, 582, 583, 584, 586, 587, 588, 590, 591, 592, 593, 594, 595, 596, 597, 602, 603, 604, 605, 606, 607, 608, 609, 610, 614, 615, 616, 617, 618, 620, 621, 623, 624, 626, 627, 629, 630, 631, 632, 633, 634, 638, 639, 641, 643, 645, 648, 649, 650, 652, 654, 656, 660, 661, 662, 664, 666, 668, 670, 671, 672, 673 ⟩ Used in section 676.
⟨ Preprocessor macro calls 23, 31, 51, 161, 190, 215, 251, 680 ⟩ Used in sections 28, 48, 123, 187, 212, 248, and 362.
⟨ Preprocessor macro definitions 77, 365 ⟩ Used in sections 122, 123, and 379.
⟨ Start conditions for the Dublin Core scanner 384 ⟩ Used in section 390.
⟨ Token and type declarations 370, 371, 399, 400, 401, 402, 403, 404, 405, 406, 407, 408, 409, 410, 411, 412, 415, 416, 417, 418 ⟩ Used in sections 379 and 676.
⟨ Type declarations for non-terminal symbols 432, 435, 440, 441, 446, 448, 450, 452, 456, 458, 462, 467, 470, 473, 476, 480, 481, 484, 489, 492, 501, 516, 518, 547, 550, 571, 577, 585, 589, 599, 601, 613, 619, 622, 625, 628, 637, 640, 642, 644, 647, 651, 653, 655, 659, 663, 665, 667, 669 ⟩ Used in section 676.
⟨ `assign.w` 479 ⟩ Cited in sections 7 and 8. Used in section 675.
⟨ `commands.w` 598 ⟩ Cited in sections 7 and 8. Used in section 675.
⟨ `dbcrprsr.w` 363 ⟩ Cited in sections 6 and 8. Used in section 379.
⟨ `dbcrscan.web` 381 ⟩ Cited in sections 6 and 8. Used in section 390.
⟨ `declrtns.w` 434 ⟩ Cited in sections 7 and 8. Used in section 675.
⟨ `dtsrcexp.w` 636 ⟩ Cited in sections 7 and 8. Used in section 675.
⟨ `dtsrctyp.web` 159 ⟩ Cited in sections 6 and 8. Used in section 186.
⟨ `dttmexp.w` 658 ⟩ Cited in sections 7 and 8. Used in section 675.
⟨ `dttmtype.web` 29 ⟩ Cited in sections 6 and 8. Used in section 47.
⟨ `grpstmnt.w` 431 ⟩ Cited in sections 7 and 8. Used in section 675.
⟨ `idtype.web` 188 ⟩ Cited in sections 6 and 8. Used in section 211.
⟨ `main.web` 734 ⟩ Cited in sections 6 and 8. Used in section 750.
⟨ `nonwin.web` 9 ⟩ Cited in sections 6 and 8. Used in section 21.
⟨ `parser.w` 392 ⟩ Cited in sections 6, 7, 8, and 677. Used in section 675.
⟨ `prsrfncs.web` 678 ⟩ Used in section 728.
⟨ `qtgensql.web` 124 ⟩ Cited in sections 6 and 8. Used in section 158.
⟨ `queryexp.w` 612 ⟩ Cited in sections 7 and 8. Used in section 675.

⟨ querytyp.web 49 ⟩ Cited in sections 6 and 8. Used in section 122.
⟨ scanner.web 249 ⟩ Cited in sections 6 and 8. Used in section 361.
⟨ scantest.web 729 ⟩ Cited in sections 6 and 8. Used in section 733.
⟨ scnrtype.web 213 ⟩ Cited in sections 6 and 8. Used in section 247.
⟨ stdafx.web 22 ⟩ Cited in sections 6 and 8. Used in section 27.
⟨ strings.w 646 ⟩ Used in section 675.
⟨ variabls.w 455 ⟩ Cited in sections 7 and 8. Used in section 675.
⟨ dbcrprsr.yxx 379 ⟩
⟨ dbcrscan.lxx 390 ⟩
⟨ dtsrctyp.hh 187 ⟩
⟨ dttmtype.hh 48 ⟩
⟨ idtype.hh 212 ⟩
⟨ nonwin.hh 20 ⟩
⟨ parser.yyy 676 ⟩
⟨ querytyp.hh 123 ⟩
⟨ scanner.hh 362 ⟩
⟨ scnrtype.hh 248 ⟩
⟨ stdafx.hh 28 ⟩
⟨ **Mutex_Type** declaration 12 ⟩ Used in sections 20 and 21.
⟨ **extern** declaration of namespace **Scan_Parse** 256, 258, 259 ⟩ Used in section 362.
⟨ **extern** declarations for global variables 18, 25 ⟩ Used in sections 20 and 28.
⟨ **extern** *keyword_map* declaration 264 ⟩ Used in section 259.
⟨ **extern** *token_map* declaration 267 ⟩ Used in section 259.
⟨ **friend** declarations for **Scanner_Type** 224, 226 ⟩ Used in section 223.
⟨ **friend** declarations for **class Datasource_Type** 164 ⟩ Used in section 163.
⟨ **friend** declarations for **class Query_Type** 55 ⟩ Used in section 53.
⟨ **union** declaration for YYSTYPE 368, 396 ⟩ Used in sections 379 and 676.

LDF Metadata Exchange Utilities
by Laurence D. Finston

February 2007

	Section	Page
Introduction	1	1
Copyright and licenses	2	1
Formatting commands	3	2
File Lists	4	2
Source Files	5	2
Logical and Hierarchical Order	6	2
Parser files	7	3
Alphabetical Order	8	3
Non-Windows Code (`nonwin.web`)	9	4
Include files	10	4
Type declarations	11	4
Mutex_Type	12	4
Lock	13	5
Unlock	15	5
Forward declarations	17	6
extern declarations for global variables	18	6
Putting Non-Win together	19	6
stdafx (`stdafx.web`)	22	8
Preprocessor macro calls	23	8
Include files in `stdafx.h`	24	8
extern declarations for global variables	25	9
Putting `stdafx.web` together	26	9
Date_Time_Type (`dttmtype.web`)	29	10
Include files	30	10
Preprocessor macro calls	31	10
class Date_Time_Type declaration	33	11
Date_Time_Type functions	34	11
Constructors and setting functions	35	11
Default constructor	36	12
Destructor	38	12
Assignment	40	13
Output operator	42	16
Show	44	18
Putting **Date_Time_Type** together	46	19

Query_Type (querytyp.web) ... 49 21
Include files ... 50 21
Preprocessor macro calls ... 51 21
Forward declarations ... 52 21
class Query_Type declaration ... 53 22
friend declarations for **class Query_Type** ... 55 23
Declare **static Query_Type** constants and variables ... 56 23
Flags ... 77 29
Initialize **static Query_Type** variables ... 81 32
Query_Type functions ... 84 32
Constructor and setting functions ... 85 32
Default constructor ... 86 33
Set ... 88 33
Destructor ... 90 34
Assignment ... 95 36
Initialize type maps ... 99 40
Initialize flags ... 101 42
Set field specifier ... 105 45
Functions for generating strings ... 109 48
Generate TEX string ... 110 48
Generate SQL string ... 114 52
Show ... 115 52
Putting **Query_Type** together ... 121 56
Query_Type::*generate_sql_string* **definition** (qtgensql.web) ... 124 58
Include files ... 125 58
Generate SQL string ... 126 58
Putting **Query_Type**::*generate_sql_string* together ... 157 80
datasource_type (dtsrctyp.web) ... 159 81
Include files ... 160 81
Preprocessor macro calls ... 161 81
Forward declarations ... 162 81
class datasource_type declaration ... 163 82
friend declarations for **class datasource_type** ... 164 82
Declare **static datasource_type** constants ... 165 82
Initialize **static Datasource_Type** variables ... 167 83
datasource_type functions ... 169 83
Constructor and setting functions ... 170 83
Default constructor ... 171 83
Set ... 173 84
Destructor ... 175 84
Assignment ... 179 85
Initialize type maps ... 181 86
Show ... 183 87
Putting **datasource_type** together ... 185 87
id_type (idtype.web) ... 188 88
Include files ... 189 88
Preprocessor macro calls ... 190 88
struct id_type declaration ... 192 89
static Id_Type constants ... 193 89
id_type functions ... 196 90
Constructors and setting functions ... 197 90
Default constructor ... 198 90

Destructor ... 201 91
Initialize *subtype_map* ... 204 92
Show ... 207 93
Putting **id_type** together ... 210 94

Scanner_Type (`scnrtype.web`) ... 213 95
Include files ... 214 95
Preprocessor macro calls ... 215 95
Forward declarations ... 216 95
struct Token_Type declaration ... 217 96
Token_Type functions ... 218 96
Default Constructor ... 219 96
Non-Default Constructor ... 221 97
class Scanner_Type declaration ... 223 98
friend declarations for **Scanner_Type** ... 224 98
friend declarations for parser rule functions ... 225 98
friend declarations for functions for group statements ... 226 99
Scanner_Type functions ... 227 99
Constructors and setting functions ... 228 99
Default constructor ... 229 100
Destructor ... 232 100
Initialize *id_map* ... 234 101
Lookup ... 236 102
Putting **Scanner_Type** together ... 246 109

Scanning (`scanner.web`) ... 249 110
Include files ... 250 110
Preprocessor macro calls ... 251 110
Forward declarations ... 252 110
Type declarations for the scanner ... 253 111
Declare namespace **Scan_Parse** ... 254 111
extern declaration of namespace **Scan_Parse** ... 256 111
Keywords ... 260 112
Declare **struct Keyword_Type** ... 261 112
Keyword map ... 262 112
Declare *keyword_map* ... 263 112
Token map ... 265 113
Declare *token_map* ... 266 113
Initialize *keyword_map* and *token_map* ... 268 113
Show *keyword_map* ... 290 135
Parser rule functions ... 293 136
Functions for variables ... 294 136
variable_func ... 295 137
Functions for declarations ... 296 137
Functions for assignments ... 297 137
query_assignment_func_0 ... 298 137
query_assignment_func_1 ... 299 137
datetime_assignment_func_0 ... 300 138
datetime_assignment_func_1 ... 301 138
Functions for Group Statements ... 302 138
Start local database query function ... 303 138
End query function ... 304 139
The scanning function *yylex* ... 305 139
Comments ... 310 142

Double-quote symbol ... 311 143
Alphabetical characters and underline character ... 318 145
Digits ... 322 148
Escaped characters ... 325 149
Punctuation ... 330 150
Space characters ... 350 164
Common code for punctuation ... 355 166
Look up *curr_id* ... 357 167
Putting the scanner together ... 360 169
Dublin Core Parser (`dbcrprsr.w`) ... 363 170
Include files ... 364 170
Preprocessor macro definitions ... 365 170
Declare **xxerror** ... 366 170
Bison options ... 367 171
union declaration for `YYSTYPE` ... 368 171
Token and type declarations ... 369 171
Record ... 370 171
Dublin Core Namespace ... 371 172
Dublin Core parser rules ... 372 172
⟨program⟩ (Start symbol) ... 373 173
⟨statement list⟩ ... 374 173
⟨statement list⟩ ⟶ `Empty` ... 375 173
⟨statement list⟩ ⟶ ⟨statement list⟩ ⟨statement⟩ ... 376 174
⟨statement⟩ ... 377 174
⟨statement list⟩ ⟶ 378 174
Dublin Core (XML) Scanner ... 381 176
Include files ... 382 176
Flex Options ... 383 176
Start conditions for the Dublin Core scanner ... 384 176
Dublin Core scanner rules ... 385 177
Putting the Dublin Core scanner together ... 390 179
Parser (`parser.w`) ... 392 180
Include files ... 393 180
Declare *yylex* ... 394 180
Declare *yyerror* ... 395 180
union declaration for `YYSTYPE` ... 396 180
Bison declarations ... 397 181
Token and Type Declarations ... 398 181
Punctuation ... 399 181
Assignments ... 400 182
Arithmetical Operations ... 401 182
Control ... 403 183
Declarators ... 404 183
Queries ... 405 183
Predicates and Control Structures ... 408 184
Columns of individual tables ... 413 186
Pica ... 414 186
Records ... 415 187
Parser rules ... 419 188
Program ... 420 188
⟨program⟩ ⟶ ⟨statement list⟩ `TERMINATE` ... 421 188
Statement list ... 422 188

⟨statement list⟩ ⟶ EMPTY . . . 423 189
⟨statement list⟩ ⟶ ⟨statement list⟩ ⟨statement⟩ . . . 424 189
Statement . . . 425 189
⟨statement⟩ ⟶ ⟨group statement⟩ SEMI_COLON . . . 426 189
⟨statement⟩ ⟶ ⟨declaration⟩ SEMI_COLON . . . 427 189
⟨statement⟩ ⟶ ⟨assignment⟩ SEMI_COLON . . . 428 190
⟨statement⟩ ⟶ ⟨command⟩ SEMI_COLON . . . 429 190
Group Statement (grpstmnt.w) . . . 430 190
Declarations (declrtns.w) . . . 433 191
⟨declaration⟩ ⟶ ⟨query declaration⟩ . . . 436 191
⟨declaration⟩ ⟶ ⟨string declaration⟩ . . . 437 192
⟨declaration⟩ ⟶ ⟨datasource declaration⟩ . . . 438 192
⟨declaration⟩ ⟶ ⟨datetime declaration⟩ . . . 439 193
⟨variable declaration segment list⟩ . . . 440 193
⟨subscript placeholder⟩ . . . 441 193
⟨variable declaration segment list⟩ ⟶ VARIABLE_TEXT_SEGMENT . . . 442 194
⟨variable declaration segment list⟩ ⟶ (etc.) . . . 443 194
⟨variable declaration segment list⟩ ⟶ (etc.) . . . 444 195
⟨subscript placeholder⟩ ⟶ OPEN_BRACKET CLOSE_BRACKET . . . 445 195
⟨query declaration⟩ . . . 446 196
⟨query declaration⟩ ⟶ (etc.) . . . 447 196
⟨datasource declaration⟩ . . . 448 196
⟨datasource declaration⟩ ⟶ (etc.) . . . 449 196
⟨string declaration⟩ . . . 450 197
⟨string declaration⟩ ⟶ (etc.) . . . 451 197
⟨datetime declaration⟩ . . . 452 197
⟨datetime declaration⟩ ⟶ (etc.) . . . 453 198
Variables (variabls.w) . . . 454 198
⟨variable name⟩ . . . 456 198
⟨variable name⟩ ⟶ ⟨variable segment list⟩ . . . 457 199
⟨variable segment list⟩ . . . 458 199
⟨variable segment list⟩ ⟶ VARIABLE_TEXT_SEGMENT . . . 459 200
⟨variable segment list⟩ ⟶ (etc.) . . . 460 201
⟨variable segment list⟩ ⟶ (etc.) . . . 461 202
⟨subscript⟩ . . . 462 202
⟨subscript⟩ ⟶ INTEGER . . . 463 203
⟨subscript⟩ ⟶ FLOAT . . . 464 204
⟨subscript⟩ ⟶ OPEN_BRACKET INTEGER CLOSE_BRACKET . . . 465 205
⟨subscript⟩ ⟶ OPEN_BRACKET FLOAT CLOSE_BRACKET . . . 466 206
⟨query variable⟩ . . . 467 206
⟨query variable⟩ ⟶ VARIABLE QUERY TYPE . . . 468 207
⟨query variable⟩ ⟶ ⟨variable name⟩ QUERY TYPE . . . 469 208
⟨datasource variable⟩ . . . 470 208
⟨datasource variable⟩ ⟶ VARIABLE DATASOURCE TYPE . . . 471 209
⟨datasource variable⟩ ⟶ ⟨variable name⟩ DATASOURCE TYPE . . . 472 210
⟨string variable⟩ . . . 473 210
⟨string variable⟩ ⟶ VARIABLE STRING TYPE . . . 474 211
⟨string variable⟩ ⟶ ⟨variable name⟩ STRING TYPE . . . 475 212
⟨datetime variable⟩ . . . 476 212
⟨datetime variable⟩ ⟶ VARIABLE DATETIME TYPE . . . 477 213
⟨datetime variable⟩ ⟶ ⟨variable name⟩ DATETIME TYPE . . . 478 214
Assignment (assign.w) . . . 479 214

⟨negation optional⟩ ... 481 215
⟨negation optional⟩ ⟶ EMPTY ... 482 215
⟨negation optional⟩ ⟶ NOT ... 483 216
⟨match term optional⟩ ... 484 216
⟨match term optional⟩ ⟶ EMPTY ... 485 217
⟨match term optional⟩ ⟶ CONTAINS ... 486 218
⟨match term optional⟩ ⟶ FREETEXT ... 487 219
⟨match term optional⟩ ⟶ LIKE ... 488 220
⟨assign or plus-assign⟩ ... 489 220
⟨assign or plus-assign⟩ ⟶ ASSIGN ... 490 221
⟨assign or plus-assign⟩ ⟶ PLUS_ASSIGN ... 491 222
⟨assignment operator⟩ ... 492 222
⟨assignment operator⟩ ⟶ ASSIGN ... 493 223
⟨assignment operator⟩ ⟶ PLUS_ASSIGN ... 494 224
⟨assignment operator⟩ ⟶ OR_ASSIGN ... 495 225
⟨assignment operator⟩ ⟶ XOR_ASSIGN ... 496 226
⟨assignment operator⟩ ⟶ NOT_ASSIGN ... 497 227
⟨assignment⟩ ⟶ ⟨query assignment⟩ ... 498 227
⟨assignment⟩ ⟶ ⟨datasource assignment⟩ ... 499 228
⟨assignment⟩ ⟶ ⟨string assignment⟩ ... 500 228
⟨query assignment⟩ ... 501 228
⟨query assignment⟩ ⟶ ⟨query variable⟩ ASSIGN ⟨query expression⟩ ... 502 229
⟨assignment⟩ ⟶ ⟨datetime assignment⟩ ... 503 230
Targets ... 504 230
⟨query assignment⟩ ⟶ (etc.) ... 505 231
⟨query assignment⟩ ⟶ (etc.) ... 506 232
⟨query assignment⟩ ⟶ (etc.) ... 507 233
⟨query assignment⟩ ⟶ (etc.) ... 508 234
Fields ... 509 234
⟨query assignment⟩ ⟶ (etc.) ... 510 235
⟨query assignment⟩ ⟶ (etc.) ... 513 237
⟨field specifier⟩ ... 516 238
⟨field specifier⟩ ⟶ ⟨field designator⟩ ⟨field qualifier list⟩ ... 517 238
⟨field designator⟩ ... 518 239
⟨field designator⟩ ⟶ ACCESS_NUMBER ... 519 239
⟨field designator⟩ ⟶ AUTHOR ... 520 240
⟨field designator⟩ ⟶ BIBLIOGRAPHIC_TYPE ... 521 241
⟨field designator⟩ ⟶ CALL_NUMBER ... 522 242
⟨field designator⟩ ⟶ CLASSIFICATION ... 523 243
⟨field designator⟩ ⟶ COMPANY ... 524 244
⟨field designator⟩ ⟶ CONTENT_SUMMARY ... 525 245
⟨field designator⟩ ⟶ CONTRIBUTOR ... 526 246
⟨field designator⟩ ⟶ CREATOR ... 527 247
⟨field designator⟩ ⟶ DATABASE_PROVIDER ... 528 248
⟨field designator⟩ ⟶ DESCRIPTION ... 529 249
⟨field designator⟩ ⟶ EXEMPLAR_PRODUCTION_NUMBER ... 530 250
⟨field designator⟩ ⟶ IDENTIFIER ... 531 251
⟨field designator⟩ ⟶ INSTITUTION ... 532 252
⟨field designator⟩ ⟶ LANGUAGE ... 533 253
⟨field designator⟩ ⟶ MAIN_CANONICAL_TITLE ... 534 254
⟨field designator⟩ ⟶ PERMUTATION_PATTERN ... 535 255
⟨field designator⟩ ⟶ PERSON ... 536 256

⟨field designator⟩ ⟶ PHYSICAL_DESCRIPTION ... 537 257
⟨field designator⟩ ⟶ PUBLISHER ... 538 258
⟨field designator⟩ ⟶ RECORD ... 539 259
⟨field designator⟩ ⟶ REMOTE_ACCESS ... 540 260
⟨field designator⟩ ⟶ RIGHTS ... 541 261
⟨field designator⟩ ⟶ SOURCE ... 542 262
⟨field designator⟩ ⟶ SUBJECT ... 543 263
⟨field designator⟩ ⟶ SUPERORDINATE_ENTITIES ... 544 264
⟨field designator⟩ ⟶ TITLE ... 545 265
⟨field designator⟩ ⟶ TYPE ... 546 266
⟨field qualifier⟩ ... 547 266
⟨field qualifier list⟩ ⟶ EMPTY ... 548 267
⟨field qualifier list⟩ ⟶ ⟨field qualifier list⟩ PERIOD ⟨field qualifier⟩ ... 549 267
⟨field qualifier⟩ ... 550 268
Generic ... 551 268
⟨field qualifier⟩ ⟶ ID ... 552 268
Names ... 553 268
⟨field qualifier⟩ ⟶ SURNAME ... 554 269
⟨field qualifier⟩ ⟶ GIVEN_NAME ... 555 270
⟨field qualifier⟩ ⟶ PREFIX ... 556 271
Field qualifiers for database table columns ... 557 271
Records ... 558 271
⟨field qualifier⟩ ⟶ ELN_ORIGINAL_ENTRY ... 559 272
⟨field qualifier⟩ ⟶ ELN_MOST_RECENT_CHANGE ... 560 273
⟨field qualifier⟩ ⟶ ELN_STATUS_CHANGE ... 561 274
⟨field qualifier⟩ ⟶ IDENTIFICATION_NUMBER ... 562 275
⟨field qualifier⟩ ⟶ DATE_ORIGINAL_ENTRY ... 563 276
⟨field qualifier⟩ ⟶ DATE_MOST_RECENT_CHANGE ... 564 277
⟨field qualifier⟩ ⟶ DATE_STATUS_CHANGE ... 565 278
⟨field qualifier⟩ ⟶ SOURCE_ID ... 566 279
⟨field qualifier⟩ ⟶ YEAR_APPEARANCE_BEGIN ... 567 280
⟨field qualifier⟩ ⟶ YEAR_APPEARANCE_END ... 568 281
⟨field qualifier⟩ ⟶ YEAR_APPEARANCE_RAK_WB ... 569 282
⟨field qualifier⟩ ⟶ YEAR_APPEARANCE_ORIGINAL ... 570 283
⟨datasource assignment⟩ ... 571 283
⟨datasource assignment⟩ ⟶ ⟨datasource variable⟩ ASSIGN ⟨datasource expression⟩ 572 284
⟨datasource assignment⟩ ⟶ ⟨datasource variable⟩ ASSIGN DBT ... 573 285
⟨datasource assignment⟩ ⟶ ⟨datasource variable⟩ ASSIGN GBV_GVK ... 574 286
⟨datasource assignment⟩ ⟶ ⟨datasource variable⟩ ASSIGN TIMMS ... 575 287
⟨datasource assignment⟩ ⟶ ⟨datasource variable⟩ ASSIGN DATASOURCE_FILE ... 576 288
⟨string assignment⟩ ... 577 288
⟨string assignment⟩ ⟶ ⟨string variable⟩ ASSIGN ⟨string expression⟩ ... 578 289
⟨string assignment⟩ ⟶ ⟨string variable⟩ ASSIGN TEX ⟨query expression⟩ ... 579 290
⟨string assignment⟩ ⟶ ⟨string variable⟩ ASSIGN SQL OAI ⟨query expression⟩ ... 581 291
⟨string assignment⟩ ⟶ ⟨string variable⟩ ASSIGN SQL PICA ⟨query expression⟩ ... 583 293
⟨datetime assignment⟩ ... 585 294
⟨datetime assignment⟩ ⟶ ⟨datetime variable⟩ ASSIGN ⟨datetime expression⟩ ... 586 295
⟨datetime assignment⟩ ⟶ ⟨datetime variable⟩ COLON ⟨datetime specifier⟩ (etc.) . 587 296
⟨datetime assignment⟩ ⟶ ⟨datetime variable⟩ COLON ⟨datetime specifier⟩ (etc.) . 588 297
Datetime specifier ... 589 298
⟨datetime specifier⟩ ⟶ YEAR_RANGE_BEGIN ... 590 298
⟨datetime specifier⟩ ⟶ YEAR_RANGE_END ... 591 299

⟨datetime specifier⟩ ⟶ YEAR ... 592 300
⟨datetime specifier⟩ ⟶ MONTH ... 593 301
⟨datetime specifier⟩ ⟶ DAY ... 594 302
⟨datetime specifier⟩ ⟶ HOUR ... 595 303
⟨datetime specifier⟩ ⟶ MINUTE ... 596 304
⟨datetime specifier⟩ ⟶ SECOND ... 597 305
Commands (commands.w) ... 598 305
Messages ... 600 305
⟨message or errmessage⟩ ... 601 306
⟨message or errmessage⟩ ⟶ MESSAGE ... 602 306
⟨message or errmessage⟩ ⟶ ERRMESSAGE ... 603 307
⟨command⟩ ⟶ ⟨message or errmessage⟩ ... 604 308
⟨command⟩ ⟶ PAUSE ... 605 309
⟨command⟩ ⟶ SHOW ⟨query variable⟩ ... 606 310
⟨command⟩ ⟶ SHOW ⟨datasource variable⟩ ... 607 312
⟨command⟩ ⟶ SHOW ⟨datetime variable⟩ ... 608 314
⟨command⟩ ⟶ SHOW ⟨string expression⟩ ... 609 315
⟨command⟩ ⟶ OUTPUT TEX ⟨string expression⟩ ... 610 316
Query expressions (queryexp.w) ... 611 316
query primary ... 613 317
⟨query primary⟩ ⟶ ⟨query variable⟩ ... 614 318
⟨query primary⟩ ⟶ (⟨query expression⟩) ... 615 319
⟨query primary⟩ ⟶ STRING ... 616 320
⟨query primary⟩ ⟶ INTEGER ... 617 321
⟨query primary⟩ ⟶ FLOAT ... 618 322
query secondary ... 619 322
⟨query secondary⟩ ⟶ ⟨query primary⟩ ... 620 323
⟨query secondary⟩ ⟶ ⟨query secondary⟩ ⟨and or and not⟩ ⟨query primary⟩ ... 621 324
query tertiary ... 622 324
⟨query tertiary⟩ ⟶ ⟨query secondary⟩ ... 623 325
⟨query tertiary⟩ ⟶ ⟨query tertiary⟩ ⟨xor or xor not⟩ ⟨query secondary⟩ ... 624 326
query expression ... 625 326
⟨query expression⟩ ⟶ ⟨query tertiary⟩ ... 626 327
⟨query expression⟩ ⟶ ⟨query expression⟩ ⟨or or or not⟩ ⟨query tertiary⟩ ... 627 328
Boolean operators ... 628 328
⟨and or and not⟩ ⟶ AND ... 629 329
⟨and or and not⟩ ⟶ AND_NOT ... 630 330
⟨or or or not⟩ ⟶ OR ... 631 331
⟨or or or not⟩ ⟶ OR_NOT ... 632 332
⟨xor or xor not⟩ ⟶ XOR ... 633 333
⟨xor or xor not⟩ ⟶ XOR_NOT ... 634 334
Datasource expressions (dtsrcexp.w) ... 635 334
datasource primary ... 637 334
⟨datasource primary⟩ ⟶ ⟨datasource variable⟩ ... 638 335
⟨datasource primary⟩ ⟶ (⟨datasource expression⟩) ... 639 336
datasource secondary ... 640 336
⟨datasource secondary⟩ ⟶ ⟨datasource primary⟩ ... 641 337
datasource tertiary ... 642 337
⟨datasource tertiary⟩ ⟶ ⟨datasource secondary⟩ ... 643 338
datasource expression ... 644 338
⟨datasource expression⟩ ⟶ ⟨datasource tertiary⟩ ... 645 339
String expressions (strings.w) ... 646 339

⟨string primary⟩ ... 647 339
⟨string primary⟩ ⟶ ⟨string variable⟩ ... 648 340
⟨string primary⟩: STRING ... 649 341
⟨string primary⟩ ⟶ (⟨string expression⟩) ... 650 342
string secondary ... 651 342
⟨string secondary⟩ ⟶ ⟨string primary⟩ ... 652 343
string tertiary ... 653 343
⟨string tertiary⟩ ⟶ ⟨string secondary⟩ ... 654 344
string expression ... 655 344
⟨string expression⟩ ⟶ ⟨string tertiary⟩ ... 656 345
Datetime expressions (dttmexp.w) ... 657 345
datetime primary ... 659 345
⟨datetime primary⟩ ⟶ ⟨datetime variable⟩ ... 660 346
⟨datetime primary⟩ ⟶ (⟨datetime expression⟩) ... 661 347
⟨datetime primary⟩ ⟶ ⟨datetime element list⟩ ... 662 348
datetime secondary ... 663 348
⟨datetime secondary⟩ ⟶ ⟨datetime primary⟩ ... 664 349
datetime tertiary ... 665 349
⟨datetime tertiary⟩ ⟶ ⟨datetime secondary⟩ ... 666 350
datetime expression ... 667 350
⟨datetime expression⟩ ⟶ ⟨datetime tertiary⟩ ... 668 351
Datetime element list ... 669 351
⟨datetime element list⟩ ⟶ INTEGER COLON INTEGER ... 670 352
⟨datetime element list⟩ ⟶ FLOAT COLON ... 671 353
⟨datetime element list⟩ ⟶ ⟨datetime element list⟩ COLON INTEGER ... 672 354
⟨datetime element list⟩ ⟶ ⟨datetime element list⟩ FLOAT COLON ... 673 355
Putting the parser together ... 674 355
Parser functions (prsrfncs.web) ... 678 357
Include files ... 679 357
Preprocessor macro calls ... 680 357
Parser function definitions ... 681 357
Functions for variables ... 682 357
variable_func ... 683 358
Functions for declarations ... 690 361
Declare variable function ... 691 362
Functions for assignments ... 694 363
query_assignment_func_0 ... 695 364
query_assignment_func_1 ... 703 371
datetime_assignment_func_0 ... 707 375
datetime_assignment_func_1 ... 716 380
Putting Parser Functions together ... 727 383
Scan Test (scantest.web) ... 729 384
Include files ... 730 384
Global variable declarations ... 731 384
Define **_tmain** ... 732 384
Putting Scan Test together ... 733 386
Main when using GCC (main.web) ... 734 386
Include files ... 735 386
Global variables ... 736 386
Scanning and parsing input ... 737 387
Main itself ... 745 388
Putting Main together ... 749 391

GNU General Public License 751 392
GNU Free Documentation License 752 396
Index 754 402