

Package ‘muscle’

November 21, 2025

Type Package
Title Multiple Sequence Alignment with MUSCLE
Version 3.53.0
Date 2012-10-05
Author Algorithm by Robert C. Edgar. R port by Alex T. Kalinka.
Maintainer Alex T. Kalinka <alex.t.kalinka@gmail.com>
Description MUSCLE performs multiple sequence alignments of nucleotide or amino acid sequences.
biocViews MultipleSequenceAlignment, Alignment, Sequencing, Genetics, SequenceMatching, DataImport
Depends Biostrings
License Unlimited
URL <http://www.drive5.com/muscle/>
LazyLoad yes
LazyData yes
NeedsCompilation yes
git_url <https://git.bioconductor.org/packages/muscle>
git_branch devel
git_last_commit e0bf042
git_last_commit_date 2025-10-29
Repository Bioconductor 3.23
Date/Publication 2025-11-20

Contents

muscle-package	2
muscle	2
umax	4
Index	5

muscle-package	<i>Multiple Sequence Alignment</i>
----------------	------------------------------------

Description

MUSCLE performs multiple sequence alignments of nucleotide and amino acid sequences.

Details

Details about the algorithm can be found on the MUSCLE website:

<http://www.drive5.com/muscle/>

Author(s)

Algorithm: Robert C. Edgar

R port: Alex T. Kalinka <alex.t.kalinka@gmail.com>

References

Edgar, R.C. (2004) MUSCLE: multiple sequence alignment with high accuracy and high throughput. *Nucleic Acids Res* **32**, 1792-1797.

See Also

[muscle](#), [umax](#)

Examples

```
## Align sequences in an XStringSet object.  
## Not run:  
aln <- muscle(stringset = umax)  
  
## End(Not run)
```

muscle	<i>Multiple Sequence Alignment</i>
--------	------------------------------------

Description

MUSCLE performs multiple sequence alignments of nucleotide or amino acid sequences.

Usage

```
muscle(stringset, quiet = FALSE, ...)
```

Arguments

stringset	An object of class <code>XStringSet</code> : <code>DNAStringSet</code> , <code>RNAStringSet</code> , or <code>AAStringSet</code> .
quiet	Logical, whether to prevent printing of the progress of the algorithm to the screen. Defaults to FALSE.
...	Arguments (options and flags) for the MUSCLE algorithm (see Details).

Details

Arguments for the MUSCLE algorithm are either options or flags. Options take a variety of values, but flags are always logicals (TRUE or FALSE). All options and flags are explained in detail on the MUSCLE website: http://www.drive5.com/muscle/muscle_userguide3.8.html

Value

Output is an object of class `MultipleAlignment`: `DNAMultipleAlignment`, `RNAMultipleAlignment`, or `AAMultipleAlignment`.

Note

For further details see the MUSCLE website: <http://www.drive5.com/muscle/>

Author(s)

Algorithm by Robert C. Edgar. Ported into R by Alex T. Kalinka <alex.t.kalinka@gmail.com>

References

Edgar, R.C. (2004) MUSCLE: multiple sequence alignment with high accuracy and high throughput. *Nucleic Acids Res* **32**, 1792-1797.

See Also

[umax](#)

Examples

```
## Align sequences in an XStringSet object.
aln <- muscle(stringset = umax)

## Switch on the diags flag.
aln <- muscle(stringset = umax, diags = TRUE)
```

umax

Unaligned MAX sequences

Description

Unaligned DNA sequences of the MAX gene for 31 mammalian species.

Usage

umax

Format

An object of class [DNASTringSet](#).

Value

An object of class [DNASTringSet](#).

Source

<http://www.ensembl.org/index.html>

References

Wagner, AJ et al. (1992) Expression, regulation, and chromosomal localization of the Max gene. *Proc Natl Acad Sci USA* **89**: 3111-3115.

Index

* **datasets**

umax, [4](#)

AAMultipleAlignment, [3](#)

AAStringSet, [3](#)

DNAMultipleAlignment, [3](#)

DNAStrngSet, [3](#), [4](#)

MultipleAlignment, [3](#)

muscle, [2](#), [2](#)

muscle-package, [2](#)

RNAMultipleAlignment, [3](#)

RNAStrngSet, [3](#)

umax, [2](#), [3](#), [4](#)

XStringSet, [3](#)