

Package ‘openPrimeR’

November 20, 2025

Title Multiplex PCR Primer Design and Analysis

Version 1.33.0

Description An implementation of methods for designing, evaluating, and comparing primer sets for multiplex PCR. Primers are designed by solving a set cover problem such that the number of covered template sequences is maximized with the smallest possible set of primers. To guarantee that high-quality primers are generated, only primers fulfilling constraints on their physicochemical properties are selected. A Shiny app providing a user interface for the functionalities of this package is provided by the 'openPrimeRui' package.

Depends R (>= 4.0.0)

License GPL-2

Encoding UTF-8

RoxygenNote 7.3.2

Imports Biostrings (>= 2.38.4), palign, XML (>= 3.98-1.4), scales (>= 0.4.0), reshape2 (>= 1.4.1), seqinr (>= 3.3-3), IRanges (>= 2.4.8), GenomicRanges (>= 1.22.4), ggplot2 (>= 2.1.0), plyr (>= 1.8.4), dplyr (>= 0.5.0), stringdist (>= 0.9.4.1), stringr (>= 1.0.0), RColorBrewer (>= 1.1-2), DECIPHER (>= 1.16.1), lpSolveAPI (>= 5.5.2.0-17), digest (>= 0.6.9), Hmisc (>= 3.17-4), ape (>= 3.5), BiocGenerics (>= 0.16.1), S4Vectors (>= 0.8.11), foreach (>= 1.4.3), magrittr (>= 1.5), unqiqt (>= 1.0), openxlsx (>= 4.0.17), grid (>= 3.1.0), grDevices (>= 3.1.0), stats (>= 3.1.0), utils (>= 3.1.0), methods (>= 3.1.0)

Suggests testthat (>= 1.0.2), knitr (>= 1.13), rmarkdown (>= 1.0), devtools (>= 1.12.0), doParallel (>= 1.0.10), pandoc (>= 0.6.0), learnr (>= 0.9)

SystemRequirements MAFFT (>= 7.305), OligoArrayAux (>= 3.8), ViennaRNA (>= 2.4.1), MELTING (>= 5.1.1), Pandoc (>= 1.12.3)

biocViews Software, Technology, Coverage, MultipleComparison

VignetteBuilder knitr

Collate 'AnalysisStats.R' 'Comparison.R' 'Data.R' 'templates.R'
 'primers.R' 'IO.R' 'IO_view.R' 'Input.R' 'Ippolito.R'
 'Output.R' 'Plots.R' 'PrimerDesign.R' 'PrimerEvaluation.R'
 'RefCoverage.R' 'Scoring.R' 'SettingsDoc.R' 'TemplatesDoc.R'
 'Tiller.R' 'ambiguity.R' 'check_stop_codons.R'
 'con_annealing_temperature.R' 'con_dimerization.R'
 'con_gc_clamp.R' 'con_gc_ratio.R' 'con_melting_temperature.R'
 'con_primer_coverage.R' 'con_primer_efficiency.R'
 'con_primer_secondary_structures.R' 'con_repeats.R'
 'con_runs.R' 'con_template_secondary_structures.R'
 'constraints.R' 'constraints_eval.R' 'errors.R' 'filters.R'
 'helper_functions.R' 'initialize_primers.R'
 'initialize_primers_tree.R' 'openPrimeR.R' 'optimization_ILP.R'
 'optimization_algo.R' 'optimization_global.R'
 'optimization_greedy.R' 'plots_comparison.R' 'settings.R'
 'plots_constraints.R' 'plots_coverage.R' 'plots_filtering.R'
 'primer_significance.R' 'startApp.R' 'zzz.R'

git_url <https://git.bioconductor.org/packages/openPrimeR>

git_branch devel

git_last_commit 9ac7cf4

git_last_commit_date 2025-10-29

Repository Bioconductor 3.23

Date/Publication 2025-11-19

Author Matthias Döring [aut, cre],
 Nico Pfeifer [aut]

Maintainer Matthias Döring <matthias-doering@gmx.de>

Contents

openPrimeR-package	10
AbstractConstraintSettings-class	11
add.coverage.constraints	11
add.dimerization.constraints	12
add.uniform.leaders.to.seqs	12
adjust.ORF.start	13
align.seqs	13
align.structures	14
AnalysisStats	14
ancestor_of	17
annealing.temp.rule.of.thumb	17
annotate.binding.events	18
apply.constraint	18
apply.constraint.list	19
assign_binding_regions.character	20
assign_binding_regions.numeric	21

augment.primer.cvg	22
batchify	22
batchify.simple	23
batchify.temp	23
build.gain.df	24
build.ILP.df	24
build.tool.overview	25
build_leader_df	26
call.melt	26
call.melt.single	27
cascaded.filter	28
cascaded.filter.quick	29
cbind.Primers	30
cbind.Templates	31
cbind2,Primers,ANY-method	31
cbind2,Templates,ANY-method	32
check.3prime.hexamers	34
check.3prime.mismatches	34
check.init.primer.length	35
check.init.primer.length.single	36
check.mutations	36
check.template.constraints	37
check.tool.function	38
check.tool.installation	38
check_constraints_comparison	39
check_constraint_settings_validity	40
check_correspondence	40
check_cvg_constraints	41
check_interval	42
check_limits	42
check_limit_value	43
check_names	43
check_report_deps	44
check_restriction_sites_single	44
check_setting	45
check_settings_validity	46
combine.binding.events	46
combine.strings	47
comp	47
compare.constraints	48
comparison.cvg	48
comparison.stats.raw	49
complement.sequence	49
compute.all.cross.dimers	50
compute.all.cross.dimers.frontend	51
compute.all.cross.dimers.unfiltered	52
compute.all.primer.subsets.ILP	53
compute.all.self.dimers	53

compute.all.self.dimers.frontend	54
compute.basic.details	55
compute.constraints	56
compute.covered.Ta	57
compute.dimer.matrix	58
compute.efficiency	59
compute.empiric.melting.temp	60
compute.gc.ratio	60
compute.melting.temps	61
compute.melting.temps.thermo	61
compute.mismatch.table	62
compute.primer.efficiencies	63
compute.secondary.structures	64
compute.sodium.equivalent.conc	65
compute.structure.vienna	66
compute.Ta	66
compute.template.secondary.structures	67
compute.Tm.baldino	68
compute.Tm.sets	69
compute.unique.covered.idx	71
compute_annealing_temp	71
condition	72
consecutive.GC.count	73
constraints.to.df	73
constraints.xml.format	74
constraints_to_unit	74
convert.from.iupac	75
convert.PCR.units	75
convert.temperature	76
convert.to.iupac	76
con_select	77
copy.melt.config	77
covered.primers.to.ID.string	78
covered.seqs.to.ID.string	78
covered.seqs.to.idx	79
create.constraint.table	79
create.constraint.XML	80
create.cvg.text	81
create.G.matrix	81
create.initial.primer.set	82
create.k.mers	83
create.kmer	83
create.options.table	84
create.other.table	84
create.PCR.table	85
create.primer.ranges	85
create.primers.naive	86
create.primers.tree	87

create.Tm.brackets	88
create.uniform.leaders	89
create_fulfilled_counts	89
create_report,list,list-method	90
create_report,Primers,Templates-method	91
Data	92
design_primers.single	93
detect.gap.columns	95
dimerization.table	96
dir.copy	96
disambiguate.primers	97
estimate.cvg	97
estimate.cvg.dir	98
eval.comparison.primers	98
eval.constraints	99
evaluate.basic.cvg	100
evaluate.constrained.cvg	101
evaluate.cvg	101
evaluate.diff.primers.cvg	102
evaluate.fw.rev.combinations	103
evaluate.GC.clamp	103
evaluate.primers.cvg	104
evaluate.template.constraints	104
exclude.cols	105
filter.by.constraints	106
filter.comparison.primers	106
filter.primers.candidates	107
filter.primers.set.opti	108
filterLimits	109
filters	109
filter_primers.by.Tm.delta	110
fix_constraint_boundaries	110
format.constraints	111
format.seq.ali	111
format.seqs.tex	112
get.3prime.mismatch.pos	112
get.analysis.mode	113
get.consensus.seq	113
get.constraint.value.idx	114
get.constraint.values	114
get.coverage.matrix	115
get.covered.templates	115
get.cross.dimers	116
get.cvg.constraint.settings	116
get.cvg.gain	117
get.delta.G	118
get.dimer.data	119
get.duplex.energies	119

get.eval.cols	120
get.extension	121
get.ILP.vars	121
get.init.file.name	122
get.leader.exon.regions	123
get.leader.exon.regions.single	123
get.matches	124
get.melting.temp.diff	124
get.merge.idx	125
get.missing.df	125
get.ORFs	126
get.other.constraint.settings	126
get.PCR.settings	127
get.plot.height	128
get.primer.binding.idx	128
get.primer.identifier.string	129
get.redundant.cols	130
get.relative.binding.pos	130
get.run.names	131
get.self.dimers	131
get.sets.from.decisions	132
get.static.tool.info	132
get.tree.seqs	133
get.unlist.idx	133
get_constraint_deviation_data	134
get_covered.vanilla	134
get_cvg_stats,list-method	135
get_cvg_stats,Primers-method	136
get_max_set_coverage	137
get_plot_primer_data	137
get_primer_cvg_mm_plot_df	138
get_report_fname	139
get_template_cvg_data	139
hclust.tree	140
highlight.mismatch	140
html.format.structure	141
I.cvg	141
ILPConstrained	142
initialize.primer.set	142
Input	143
insert_str	149
interleave	149
J.cvg	150
joule.to.cal	150
listToXml	151
merge.ambig.primers	151
merge.binding.information	152
merge.primer.entries	153

merge.primer.entries.single	153
merge.select	154
merge.template.decisions	154
mismatch.info	155
mismatch.mutation.check	155
mismatch.string.to.list	156
modify.col.rep	156
my.disambiguate	157
my.error	157
my.read.fasta	158
my.warning	158
my_ggsave	159
my_rbind	159
nbr.of.repeats	160
nbr.of.runs	160
opti	161
optiLimits	161
optimize.ILP	162
optimize.primer.cvg	163
optimize.template.binding.regions.dir	164
optimize.template.binding.regions.single	165
Output	166
pair_primers	168
parse.constraints	169
parse.header	169
parse.IMGt.gene.groups	170
parse.oligo.results	170
plot.all.cvg.info	171
plot.all.filtering.stats	172
plot.Delta.DeltaG	173
plot.dimer.dist	173
plot.excluded.hist	174
plot.filtering.runtime	174
plot.filtering.stats	175
plot.filtering.stats.cvg	175
Plots	176
plot_constraint,list-method	182
plot_constraint,Primers-method	182
plot_constraint.histogram	183
plot_constraint.histogram.nbr.mismatches	184
plot_constraint.histogram.primer efficiencies	184
plot_constraint_deviation,list-method	185
plot_constraint_deviation,Primers-method	185
plot_constraint_fulfillment,list-method	186
plot_constraint_fulfillment,Primers-method	187
plot_cvg_constraints,list-method	187
plot_cvg_constraints,Primers-method	188
plot_primer.comparison.box	189

plot_primer.comparison.mismatches	190
plot_primer_binding_regions,list,list-method	190
plot_primer_binding_regions,Primers,Templates-method	191
plot_primer_cvg,list,list-method	192
plot_primer_cvg,Primers,Templates-method	193
plot_primer_cvg_mismatches	193
plot_primer_cvg_unstratified	194
plot_template_cvg,list,list-method	195
plot_template_cvg,Primers,Templates-method	195
plot_template_cvg_comparison_mismatch	196
plot_template_cvg_comparison_unstratified	196
plot_template_cvg_mismatches	197
plot_template_cvg_unstratified	197
plot_template_structure	198
pos.to.range	198
predict_coverage	199
prefilter.primer.candidates	200
prepare.constraint.plot	200
prepare.dimer.seqs	201
prepare_mm_plot	201
prepare_template_cvg_mm_data	202
primer.binding.regions.data	202
primer.coverage.for.groups	203
primer.set.parameter.stats	204
PrimerDesign	204
PrimerEval	208
rbind.primer.data	212
rbind.Primers	213
rbind.Templates	213
read.leaders	214
read.secondary.structure.raw	214
read.sequences	215
read_primers.internal	215
read_primers_csv	216
read_primers_multiple	216
read_templates_csv	217
read_templates_fasta	218
read_templates_multiple	219
read_templates_single	220
relax.constraints	221
relax.opti.constraints	222
remove.redundant.cols	223
remove.seqs.by.keyword	223
rename.constraint.options	224
render_report	224
reorder.primer.table	225
restriction_ali	225
restriction_hits	226

restriction_match	226
retrieve.leader.region	227
rev.comp.sequence	227
rev.sequence	228
runTutorial	228
sanitize_path	229
score.conservation	230
Scoring	230
select.allowed.binding.events	232
select.best.ILP	233
select.best.opti.result	233
select.best.primer.idx	234
select.best.primer.set	235
select.binding.events	235
select.constraints	236
select.min.cross.idx	236
select.primer.region.by.conservation	237
select.primers.by.cvg	238
select_best_binding	239
selenium.installed	240
set.new.constraint.value	240
set.new.limits	241
Settings	241
shannon.entropy	251
solve.ILP	251
split_str_by_index	252
stats_plot_data	253
store.filtering.sets	253
string.list.format	254
string.list.format.total	254
string.to.IQR	255
subset.ILP	255
TemplatesFunctions	256
ungap_sequence	258
unify.leaders	259
update.binding.ranges.by.conservation	259
update.binding.regions	260
update.constraint.values	261
update.cvg.data	261
update.individual.binding.region	262
update.opti.results	263
update_primer_binding_regions	263
update_primer_cvg	264
validate_primers	264
validate_templates	265
view.cvg.primers	265
view.dimer.df	266
view.input.primers	266

view.primers	267
view.primers.report	267
visualize.all.results	268
visualize.filtering.results	269
were.constraints.relaxed	270
write.out.primer.info	270
xmlToChar	271

Index	272
--------------	------------

openPrimeR-package	<i>Multiplex PCR Primer Design and Analysis.</i>
--------------------	--

Description

With openPrimeR you can evaluate existing primers or design novel primers for multiplex polymerase chain reaction that are optimized with respect to the coverage of template sequences and the physicochemical properties of the primers.

Details

For designing primers, you just need the function `design_primers` from **openPrimeR**. As a minimal input, this function requires:

A set of template sequences You can load a `Templates` object with `read_templates`.

Settings for primer design You can load a `DesignSettings` object from a (supplied) XML file with `read_settings`. The settings can be easily customized using the setters `constraints`, `constraintLimits`, `cvg_constraints`, `conOptions`, and `PCR`.

For evaluating existing primers you can load a FASTA or CSV file containing the primers and templates of of interest using `read_primers` and `read_templates`, respectively. After evaluating the properties of the primers using `check_constraints`, you can interpret the results with several functions. For example, you can analyze the coverage of the template sequences using `get_cvg_stats`, determine the deviation from the target constraints using `plot_constraint_deviation`, or create a comprehensive report on the analyzed primers using `create_report`. In order to compare several primer sets with each other, you can create a table of the properties of the primer sets using `get_comparison_table` or create a full report, again using `create_report`.

Package options

openPrimeR uses the following options:

`openPrimeR.constraint_order` The identifiers of constraints in the order they are applied during the filtering procedure. This order is maintained when loading a `DesignSettings` object.

`openPrimeR.relax_order` The identifiers of constraints in the order in which they shall be relaxed during the relaxation procedure when designing primers.

`openPrimeR.plot_abbrev` The maximal number of allowed characters for tick labels in plots.

`openPrimeR.plot_colors` A named vector providing the identifiers of `RColorBrewer` palettes. Each vector entry provides the plotting colors for a specific type of stratification (i.e. by run, constraint, or primer). The palettes should provide at least eight colors.

Author(s)

Maintainer: Matthias Döring <matthias-doering@gmx.de>

Authors:

- Nico Pfeifer <pfeifer@informatik.uni-tuebingen.de>

AbstractConstraintSettings-class

AbstractClass for Constraint Settings.

Description

The ConstraintSettings class encapsulates the constraints on the physicochemical properties of primers.

Value

An AbstractConstraintSettings object.

Slots

status Named boolean vector indicating which of the possible constraints are active (TRUE) and which are not (FALSE).

settings Named list containing the settings of the active constraints

add.coverage.constraints

Addition of Coverage Constraints.

Description

Adds coverage constraints to ILP instance.

Usage

```
add.coverage.constraints(lprec, covered.templates, template.coverage)
```

Arguments

lprec An ILP instance.

covered.templates

Indices of covered template sequences.

template.coverage

List containing the indices of covering primers for each template.

Value

lprec with coverage constraints.

```
add.dimerization.constraints
```

Addition of Dimerization Constraints

Description

Updates ILP formulation with dimerization constraints.

Usage

```
add.dimerization.constraints(lprec, D.idx, indices)
```

Arguments

lprec	An ILP instance.
D.idx	Data frame giving the indices of dimerizing primer pairs.
indices	Row indices for setting the dimerization constraints in lprec.

Value

lprec with added dimerization constraints.

```
add.uniform.leaders.to.seqs
```

Add Uniform Binding Regions.

Description

Augments a template data frame with uniform binding regions.

Usage

```
add.uniform.leaders.to.seqs(lex.seq, leaders)
```

Arguments

lex.seq	Template data frame
leaders	Data frame with uniform binding regions.

Value

Template data frame with updated binding regions.

adjust. ORF.start	<i>Adjust ORF position</i>
-------------------	----------------------------

Description

Adjusts the reading frame according to the position at which we consider a subsequence.

Usage

```
adjust. ORF.start(ORFs, seq.start)
```

Arguments

ORFs	the reading frames (0,1,2).
seq.start	the position where a sequence is extracted .

Value

The adjusted reading frames for the given start positions.

align.seqs	<i>Multiple Sequence Alignment</i>
------------	------------------------------------

Description

Computes a multiple sequence alignment using MAFFT.

Usage

```
align.seqs(seqs, names)
```

Arguments

seqs	The sequences to be aligned.
names	The identifiers of the sequences.

Value

An alignment object as created from seqinr's read.alignment method.

References

Katoh, Misawa, Kuma, Miyata 2002 (Nucleic Acids Res. 30:3059-3066) MAFFT: a novel method for rapid multiple sequence alignment based on fast Fourier transform.

<code>align.structures</code>	<i>Formatting of Dimerization Structures.</i>
-------------------------------	---

Description

Formats the given dimerization structures nicely.

Usage

```
align.structures(structs)
```

Arguments

<code>s1</code>	structs A character vector, where a block of 4 elements contains: sequence 1 (with removed overlaps), part of sequence 1 overlapping with sequence 2, part of sequence 2 overlapping with sequence 1, and sequence 2 (with removed overlaps).
-----------------	---

Value

A list of two elements given the conformation of the first and the second sequence, respectively.

<code>AnalysisStats</code>	<i>Primer Analysis Statistics.</i>
----------------------------	------------------------------------

Description

`get_cvg_ratio` Determines the ratio of template sequences that are covered by the evaluated input primers. The ratio is in the interval [0,1] where 0 indicates 0% coverage (no templates covered) and 1 indicates 100% coverage (all templates covered).

`get_cvg_stats` Retrieve statistics on covered templates, either for a single or multiple primer sets.

`get_cvg_stats_primer` Creates a table summarizing the coverage events of individual primers.

`get_comparison_table` Creates an overview of the properties of multiple primer sets by providing the inter-quartile range of primer properties in bracket notation.

Usage

```
get_cvg_ratio(
  primer.df,
  template.df,
  allowed.mismatches = NULL,
  cvg.definition = c("constrained", "basic"),
  mode.directionality = NULL,
  as.char = FALSE
)
```

```

get_comparison_table(templates, primers, sample.name = NULL)

get_cvg_stats_primer(
  primer.df,
  template.df,
  cvg.definition = c("constrained", "basic")
)

get_cvg_stats(
  primers,
  templates,
  for.viewing = FALSE,
  total.percentages = FALSE,
  allowed.mismatches = Inf,
  cvg.definition = c("constrained", "basic")
)

```

Arguments

<code>primer.df</code>	A Primers object containing the primers.
<code>template.df</code>	A Templates object containing the template sequences corresponding to <code>primer.df</code> .
<code>allowed.mismatches</code>	The number of allowed mismatches for determining the coverage of the templates. By default, all annotated coverage events are considered.
<code>cvg.definition</code>	If <code>cvg.definition</code> is set to "constrained", the statistics for the expected coverage (after applying the coverage constraints) are retrieved. If <code>cvg.definition</code> is set to "basic", the coverage is determined solely by string matching (i.e. without applying the coverage constraints). By default, <code>cvg.definition</code> is set to "constrained".
<code>mode.directionality</code>	If <code>mode.directionality</code> is provided, the coverage of templates is computed for a specific direction of primers. Either "fw" (forward coverage only), "rev" (reverse coverage only), or "both" for both directions. By default, <code>mode.directionality</code> is NULL such that the directionality of the primers is determined automatically.
<code>as.char</code>	Whether the coverage ratio should be outputted as a percentage-formatted character vector. By default, <code>as.char</code> is set to FALSE such that a numeric is returned.
<code>templates</code>	If <code>primers</code> is an object of class <code>Primers</code> , please provide an object of class <code>Templates</code> containing the template sequences targeted by <code>primers</code> . If <code>primers</code> is a list, <code>templates</code> should be a list of <code>Template</code> objects.
<code>primers</code>	To retrieve statistics for a single primer set, please provide an object of class <code>Primers</code> containing a set of evaluated primers. To retrieve statistics for multiple primer sets, please provide a list with evaluated <code>Primers</code> objects.
<code>sample.name</code>	Either a single identifier or a character vector of identifiers for every <code>Templates</code> object in <code>templates</code> . By default, <code>sample.name</code> is NULL such that the Run annotations in the provided <code>Templates</code> objects are used.

`for.viewing` Whether the table should be formatted to be human-readable. By default, `for.viewing` is FALSE.

`total.percentages` Whether group coverage percentages should be computed in relation to the total number of template sequences or in relation to the number of templates belonging to a specific group. By default, `total.percentages` is FALSE such that the percentages are group-specific.

Details

The manner in which `get_cvg_ratio` determines the coverage ratio depends on the directionality of the input primers. If either only forward or reverse primers are inputted, the individual coverage of each primer is used to determine the overall coverage. If, however, forward and reverse primers are inputted at the same time, the coverage is defined by the intersection of binding events from both, forward and reverse primers.

For `get_cvg_stats_primer`, the cells corresponding to columns with numeric identifiers indicate the percentage of coverage events occurring with a certain number of mismatches. For example column 3 provides the number of coverage events where there are exactly three mismatches between primers and templates. The column `Group_Coverage` provides a listing of the percentage of covered templates per group.

Value

By default, `get_cvg_ratio` returns a numeric providing the expected primer coverage ratio. If `as.char` is TRUE, the output is provided as a percentage-formatted character vector. The attributes `no_covered`, `no_templates`, and `covered_templates` provide the number of covered templates, the total number of templates, and the IDs of covered templates, respectively.

`get_comparison_table` returns a data frame summarizing the properties of the provided primer data sets.

`get_cvg_stats_primer` returns a list with the following entries. `cvg_per_nbr_mismatches` contains a data frame listing the number of binding events broken down according to the number of expected mismatches between primers and templates. `cvg_per_group` contains a data frame listing the coverage of individual primers per group of templates.

`get_cvg_stats` returns a data frame whose entries provide the coverage of templates per group of templates.

Examples

```
data(Ippolito)
# Determine the overall coverage
cvg.ratio <- get_cvg_ratio(primer.df, template.df)
# Determine the identity coverage ratio
cvg.ratio.0 <- get_cvg_ratio(primer.df, template.df, allowed.mismatches = 0)

# Summarize the properties of multiple primer sets
data(Comparison)
tab <- get_comparison_table(template.data[1:3], primer.data[1:3], "IGH")

data(Ippolito)
```



```
# Determine coverage stats per primer
primer.cvg.stats <- get_cvg_stats_primer(primer.df, template.df)

# Coverage statistics for a single primer set
data(Ippolito)
cvg.stats <- get_cvg_stats(primer.df, template.df)
# Coverage statistics for multiple primer sets
data(Comparison)
cvg.stats.comp <- get_cvg_stats(primer.data[1:2], template.data[1:2])
```

ancestor_of	<i>Tree Ancestry</i>
-------------	----------------------

Description

Checks whether `ancestor.node` is an ancestor to the nodes specified in `test.node`.

Usage

```
ancestor_of(tree, ancestor.node, test.node)
```

Arguments

<code>tree</code>	The phylogenetic tree to be tested.
<code>ancestor.node</code>	A node to be checked for being an ancestor to <code>test.node</code> .
<code>test.node</code>	Possible descendants of <code>ancestor.node</code> .

Value

TRUE, if `ancestor.node` is an ancestor to any node in `test.node`.

annealing.temp.rule.of.thumb	<i>Rule of thumb for annealing temperature</i>
------------------------------	--

Description

Computes the annealing temperature using a rule of thumb

Usage

```
annealing.temp.rule.of.thumb(melting.temp)
```

Arguments

<code>melting.temp</code>	Melting temperatures of primers
---------------------------	---------------------------------

Value

The annealing temperature corresponding to the input melting temperature.

```
annotate.binding.events
```

Annotation of Primer Binding Events.

Description

Annotates whether primer binding events are in the allowed binding region or not.

Usage

```
annotate.binding.events(  
  fw.binding,  
  allowed.range,  
  nbr.primers,  
  allowed.region.definition = c("within", "any")  
)
```

Arguments

fw.binding	IRanges with coverage information.
allowed.range	IRanges of the allowed binding ranges in the templates.
nbr.primers	Number of primers to consider.
allowed.region.definition	Definition of the allowed binding region

Value

IRanges with annotations of (preliminary) specificity and allowed binding. The field `all_binding` contains all binding regions, `on_target` contains all events in the target region, and `off_target` contains all off-target binding events.

```
apply.constraint
```

Application of Constraints

Description

Checks whether the input values are within the specified limits.

Usage

```

apply.constraint(
  gc.ratio.fw,
  gc.ratio.rev,
  min.GC,
  max.GC,
  fw.idx,
  rev.idx,
  mode.directionality = c("fw", "rev", "both")
)

```

Arguments

gc.ratio.fw	Forward values.
gc.ratio.rev	Reverse values.
min.GC	Minimal allowed value.
max.GC	Maximal allowed value.
fw.idx	Indices of forward values to consider.
rev.idx	Indices of reverse values to consider.
mode.directionality	Direction of primers

Value

Data frame with TRUE for values fulfilling the constraints, FALSE otherwise. Also returns FALSE if a data point is not available.

apply.constraint.list *Apply Constraints to a List.*

Description

Checks whether the input values are within the specified limits.

Usage

```

apply.constraint.list(
  gc.ratio.fw,
  gc.ratio.rev,
  min.GC,
  max.GC,
  fw.idx,
  rev.idx,
  mode.directionality = c("fw", "rev", "both")
)

```

Arguments

gc.ratio.fw	Forward values (comma-separated strings).
gc.ratio.rev	Reverse values (comma-separated strings).
min.GC	Minimal allowed value.
max.GC	Maximal allowed value.
fw.idx	Indices of forward values to consider.
rev.idx	Indices of reverse values to consider.
mode.directionality	Direction of primers

Details

Applies a constraint to every element in a vector of comma separated strings. Applied when filtering covered seqs according to primer efficiency.

Value

Data frame with TRUE for values fulfilling the constraints, FALSE otherwise.

assign_binding_regions.character

Character Assignment of Binding Regions

Description

Generic method for assigning the binding region using individual binding regions.

Usage

```
## S3 method for class 'character'
assign_binding_regions(
  template.df,
  fw,
  rev,
  optimize.region = FALSE,
  primer.length = 20,
  gap.char = "-"
)
```

Arguments

template.df	Template data frame.
fw	FASTA file specifying the forward binding regions.
rev	FASTA file specifying the reverse binding regions.
optimize.region	Should the primer binding region be optimized using secondary structure prediction?
primer.length	Probe length for optimizing template secondary structure.
gap.char	The gap character for aligned sequences.

Value

Template data frame with assigned binding regions.

assign_binding_regions.numeric
Numeric Assignment of Binding Regions.

Description

Numeric S3 generic case for assigning binding regions.

Usage

```
## S3 method for class 'numeric'
assign_binding_regions(
  template.df,
  fw,
  rev,
  optimize.region = FALSE,
  primer.length = 20,
  gap.char = "-"
)
```

Arguments

template.df	Template data frame.
fw	Binding region data forward primers.
rev	Binding region data for reverse primers.
optimize.region	Should the primer binding region be optimized using secondary structure prediction?
primer.length	Probe length for optimizing template secondary structure.

Value

The template data frame with assigned binding regions.

augment.primers.cvg	<i>Augmentation of Primer Coverage.</i>
---------------------	---

Description

Computes the coverage for the primers in `primer.df` that is still missing such that the relaxation procedure can adjust appropriate constraints.

Usage

```
augment.primers.cvg(
  primer.df,
  template.df,
  settings,
  partial = FALSE,
  constraint = NULL
)
```

Arguments

<code>primer.df</code>	A Primers object for which the primer coverage shall be augmented.
<code>template.df</code>	A Templates object.
<code>settings</code>	A DesignSettings object giving the parameters for coverage computations.
<code>partial</code>	Whether all missing primer coverage values should be computed. If <code>partial</code> is <code>TRUE</code> , only the coverage values of the primers that were excluded due to the specified constraint are computed.
<code>constraint</code>	A character vector specifying the exclusion reason for which the partial augmentation should take place.

Value

A Primers object with augmented coverage entries.

batchify	<i>Creates multiple Batches for Parallelization.</i>
----------	--

Description

Creates multiple Batches for Parallelization.

Usage

```
batchify(tasks, annealing.temps = NULL)
```

Arguments

tasks An integer vector with indices representing individual computations.
 annealing.temps Temperatures according to which to batchify.

Value

A list of lists containing indices corresponding to tasks, each list gives a batch.

batchify.simple	<i>Simple Batchification</i>
-----------------	------------------------------

Description

Simple Batchification

Usage

```
batchify.simple(tasks)
```

Arguments

tasks The tasks to assign to individual batches.

Value

A list of lists containing indices corresponding to tasks, each list gives a batch.

batchify.temp	<i>Batchification by Temperature.</i>
---------------	---------------------------------------

Description

Batchification by Temperature.

Usage

```
batchify.temp(tasks, annealing.temp)
```

Arguments

tasks The tasks to assign to individual batches.
 annealing.temp The annealing temperatures according to which batches are to be created.

Value

A list of lists containing indices corresponding to tasks, each list gives a batch.

build.gain.df	<i>Gain of Coverage by Excluded Primers.</i>
---------------	--

Description

Computes a data frame on the excluded sequences per constraint.

Usage

```
build.gain.df(candidate.df, constraint.settings, constraint.limits, relax.df)
```

Arguments

candidate.df	An object of class Primers containing excluded primers that are considered for addition to filtered.df.
constraint.settings	A list with the current constraint settings.
constraint.limits	The current constraint limits.
relax.df	Data frame with count of relaxations per constraint.

Value

A data frame with exclusion data.

build.ILP.df	<i>Construction of ILP Results.</i>
--------------	-------------------------------------

Description

Constructs a data frame summarizing the properties of an ILP solution.

Usage

```
build.ILP.df(
  ILP,
  vars,
  primer.df,
  template.df,
  i,
  target.temp,
  time = NA,
  deltaG_Cutoff = NA,
  deltaG_Limit = NA
)
```


Arguments

ILP	A solved ILP instance.
vars	The ILP decision variables.
primer.df	The primer data frame corresponding to the ILP.
template.df	The template data frame.
i	Index for the ILP.
target.temp	Target melting temperature in Celsius.
time	Runtime of the ILP.
deltaG_Cutoff	Free energy cutoff used for the dimerization constraint.
deltaG_Limit	The free energy boundary for dimerization.

Value

Data frame summarizing the ILP solution.

build.tool.overview	<i>Creation of an Overview of Third-Party Tools.</i>
---------------------	--

Description

Creates a table of required third-party tools and their installation status.

Usage

```
build.tool.overview(AVAILABLE.TOOLS, for.shiny = FALSE)
```

Arguments

AVAILABLE.TOOLS	A vector whose names give the required tools and whose entries give their installation status as logicals.
If	for.shiny is TRUE, provide the URLs for the tool using HTML.

Value

A data frame with information on third-party tools.

build_leader_df	<i>Building of Leader Data Frame.</i>
-----------------	---------------------------------------

Description

Constructs the leader data frame.

Usage

```
build_leader_df(  
  direction = c("fw", "rev"),  
  leader,  
  start,  
  end,  
  ali.start,  
  ali.end  
)
```

Arguments

direction	The primer direction for which we are annotating binding regions.
leader	The binding region sequence.
start	The start positions of the binding region.
end	The end positions of the binding region.
ali.start	The start positions of the binding region in the aligned input.
ali.end	The end positions of the binding region in the aligned input.

Value

A data frame with binding region information.

call.melt	<i>Thermodynamic melting temperature computations.</i>
-----------	--

Description

Computes the melting temperature for the input primers.

Usage

```
call.melt(  
  primers,  
  complements,  
  primer_conc,  
  na_salt_conc,  
  mg_salt_conc,  
  k_salt_conc,  
  tris_salt_conc  
)
```

Arguments

primers	Character vector of primer strings.
complements	Character vector with complement sequences corresponding to primers.
primer_conc	Primer concentration.
na_salt_conc	Sodium ion concentration.
mg_salt_conc	Magensium ion concentration.
k_salt_conc	Potassium ion concentration.
tris_salt_conc	Tris buffer concentration.

Value

Melting temperature data frame.

References

Le Novère N. (2001). MELTING, computing the melting temperature of nucleic acid duplex. *Bioinformatics*, 17: 1226-1227. Dumousseau M., Rodriguez N., Juty N., Le Novère N. (2012) MELTING, a flexible platform to predict the melting temperatures of nucleic acids. *BMC Bioinformatics*, 13: 101.

call.melt.single	<i>Thermodynamic melting temperature computations.</i>
------------------	--

Description

Computes the melting temperature for the input primers.

Usage

```
call.melt.single(  
  primers,  
  complements,  
  out.file,  
  primer_conc,  
  na_salt_conc,  
  mg_salt_conc,  
  k_salt_conc,  
  tris_salt_conc,  
  ID  
)
```

Arguments

primers	List of primer strings.
complements	List with corresponding complements.
out.file	Path to the file where MELTING will write the results.
primer_conc	Primer concentration.
na_salt_conc	Sodium ion concentration.
mg_salt_conc	Magensium ion concentration.
k_salt_conc	Potassium ion concentration.
tris_salt_conc	Tris buffer concentration.
ID	identifiers of the input primers

Value

Melting temperature data frame.

cascaded.filter	<i>Filtering for the Optimization</i>
-----------------	---------------------------------------

Description

Filter primers according to constraints and relax constraints if necessary.

Usage

```
cascaded.filter(  
  primer.df,  
  template.df,  
  settings,  
  mode.directionality = c("fw", "rev", "both"),  
  required.cvg = 1,
```

```

    target.temps = NULL,
    updateProgress = NULL,
    results.loc = NULL
  )

```

Arguments

<code>primer.df</code>	Primer data frame.
<code>template.df</code>	Template data frame.
<code>settings</code>	Settings object.
<code>mode.directionality</code>	Primer direction.
<code>required.cvg</code>	Required ratio of covered templates. If <code>required.cvg</code> is set to 0, the constraints are not relaxed.
<code>target.temps</code>	Target melting temperature of the primers in Celsius. This argument is only required if we try to match the melting temperatures of another primer set, e.g. when first optimizing forward and then optimizing reverse primers.
<code>updateProgress</code>	Progress callback function for shiny.
<code>results.loc</code>	Directory where the filtering results should be stored.

Details

Constraints are relaxed if the `required.cvg` could not be reached with the input constraints.

Value

The filtered primer data frame with respect to `required.cvg`.

`cascaded.filter.quick` *Cascaded Filter*

Description

Filter primers in a cascaded fashion.

Usage

```

cascaded.filter.quick(
  primer.df,
  template.df,
  settings,
  to.compute.constraints,
  mode.directionality = c("fw", "rev", "both"),
  active.constraints = NULL,
  no.structures = FALSE,
  updateProgress = NULL
)

```

Arguments

<code>primer.df</code>	Primer data frame.
<code>template.df</code>	Template data frame.
<code>settings</code>	Settings object.
<code>to.compute.constraints</code>	Names of constraints that still have to be computed.
<code>mode.directionality</code>	Primer direction.
<code>active.constraints</code>	The constraints that are to be used for filtering. If <code>active.constraints</code> is NULL, all filtering constraints are used.
<code>no.structures</code>	Whether dimerization structures shall be computed.
<code>updateProgress</code>	Progress callback function for shiny.

Details

At each constraint evaluation all primers that do not fulfill the current constraint are removed. Constraints that are specified in `to.compute.constraints` are computed on the fly.

Value

The filtered primer data frame.

<code>cbind.Primers</code>	<i>cbind for Primers class.</i>
----------------------------	---------------------------------

Description

Ensures that the cbind result has the appropriate class.

Usage

```
## S3 method for class 'Primers'
cbind(...)
```

Arguments

<code>...</code>	Parameters for cbind function.
------------------	--------------------------------

Value

Column binded Primers data frame.

Examples

```
data(Ippolito)
primer.df <- cbind(primer.df, primer.df)
```

cbind.Templates	<i>cbind for Template class.</i>
-----------------	----------------------------------

Description

Ensures that the cbind result has the appropriate class.

Usage

```
## S3 method for class 'Templates'
cbind(...)
```

Arguments

... Parameters for cbind function.

Value

Column binded Templates data frame.

Examples

```
data(Ippolito)
template.df <- cbind(template.df, seq_len(nrow(template.df)))
```

cbind2,Primers,ANY-method	<i>S4 cbind for Primers.</i>
---------------------------	------------------------------

Description

S4 cbind function for Primers.

S4 rbind function for Primers.

Slices a Primers data frame.

Stores data in a column of a Primers data frame.

Usage

```
## S4 method for signature 'Primers,ANY'
cbind2(x, y, ...)
```

```
## S4 method for signature 'Primers,ANY'
rbind2(x, y, ...)
```

```
## S4 method for signature 'Primers,ANY'
```

```
x[i, j, ..., drop = TRUE]

## S4 replacement method for signature 'Primers'
x$name <- value
```

Arguments

x	The Primers data frame.
y	Another data frame.
...	Other arguments to the slice operator.
i	The row index.
j	The column index.
drop	Simplify data frame?
name	The name of the column.
value	The values of the column.

Value

Cbinded primer data frame.
 Rbinded primer data frame.
 Subset of primer data frame.
 Primer data frame with replaced column.

Examples

```
data(Ippolito)
primer.df <- cbind2(primer.df, seq_len(nrow(primer.df)))
data(Ippolito)
primer.df <- primer.df[1:2,]
data(Ippolito)
primer.df$Forward[1] <- "ctagcgggaccg"
```

cbind2, Templates, ANY-method

S4 cbind for Templates.

Description

S4 cbind function for Templates data frame.
 S4 rbind function for templates.
 Slicing of Templates data frame object.
 Set a column in a Templates data frame.

Usage

```
## S4 method for signature 'Templates,ANY'
cbind2(x, y, ...)

## S4 method for signature 'Templates,ANY'
rbind2(x, y, ...)

## S4 method for signature 'Templates,ANY'
x[i, j, ..., drop = TRUE]

## S4 replacement method for signature 'Templates'
x$name <- value
```

Arguments

x	The Template data frame.
y	Another data frame.
...	Other arguments to the slice operator.
i	The row index.
j	The column index.
drop	Simplify data frame?
name	The name of the column.
value	The values of the column.

Value

Cbinded template data frame.

Rbinded template data frame.

Subsetted template data frame.

Templates with replaced column.

Examples

```
data(Ippolito)
template.df <- cbind2(template.df, seq_len(nrow(template.df)))
data(Ippolito)
template.df <- rbind2(template.df, template.df)
data(Ippolito)
template.df <- template.df[1:2,]
data(Ippolito)
template.df$ID[1] <- "newID"
```

`check.3prime.hexamers` *3' Hexamer Check.*

Description

Check whether the 3' hexamer of a primer is fully complementary to the corresponding region in the template.

Usage

```
check.3prime.hexamers(  
  template.df,  
  primer.df,  
  mode.directionality = c("fw", "rev", "both")  
)
```

Arguments

<code>template.df</code>	Template data frame.
<code>primer.df</code>	Primer data frame.
<code>mode.directionality</code>	Primer directionality.

Value

Returns TRUE if the 3' hexamer of a primer is fully complementary to the corresponding template region and FALSE otherwise.

`check.3prime.mismatches`
3' Mismatch Check.

Description

Check for mismatches at primer 3' ends.

Usage

```
check.3prime.mismatches(  
  template.df,  
  primer.df,  
  mode.directionality = c("fw", "rev", "both")  
)
```

Arguments

template.df	Template data frame.
primer.df	Primer data frame.
mode.directionality	Primer directionality.

Value

Returns the distance of mismatches from the 3' terminal end of primers.

check.init.primer.length
<i>Primer Length Check.</i>

Description

Checks whether it is possible to construct primers of the desired length.

Usage

```
check.init.primer.length(
  template.df,
  allowed.region.definition = c("within", "any"),
  primer.lengths,
  mode.directionality = c("fw", "rev", "both")
)
```

Arguments

template.df	Template data frame.
allowed.region.definition	Definition of allowed binding regions.
primer.lengths	The desired lengths of the primers.
mode.directionality	The primer directionality.

Value

TRUE, if primers of the desired length can be constructed,

```
check.init.primer.length.single
```

Primer Length Check.

Description

Checks whether it is possible to construct primers of the desired length.

Usage

```
check.init.primer.length.single(
  allowed,
  allowed.region.definition = c("within", "any"),
  min.len
)
```

Arguments

allowed	String containing the allowed binding sequence.
allowed.region.definition	Definition of allowed binding regions.
min.len	Minimal desired primer lengths.

Value

TRUE if primers of the desired length can be constructed, FALSE otherwise.

```
check.mutations
```

Identification of Mismatch Mutations.

Description

Identifies primers that induce mutations due to mismatch binding.

Usage

```
check.mutations(
  primer.seq,
  pos.start,
  pos.end,
  template.df,
  covered.seqs,
  ORF.data,
  mode.directionality = c("fw", "rev"),
  mutation.types = c("stop_codon", "substitution")
)
```

Arguments

primer.seq	Primer sequence string.
pos.start	Binding position of primer (start).
pos.end	Binding position of primer (end).
template.df	Template data frame.
covered.seqs	Identifiers of covered templates.
ORF.data	Reading frame information of templates.
mode.directionality	Directionality of primers.
mutation.types	Character vector of the mutation types to be checked for.

Details

Checks for one primer and all covered templates whether any templates are bound with mismatches such that a forbidden mutation is induced. A boolean vector indicating which binding events induce a forbidden mutation is returned.

Value

TRUE if the primer.seq induces a mutation that is forbidden according to the provided mutation.types.

check.template.constraints

Check Constraints on Templates

Description

Transforms the comma-separated input strings to a boolean representation.

Usage

```
check.template.constraints(template.constraints)
```

Arguments

template.constraints	Strings with comma-separated values to be turned to logical.
----------------------	--

Value

List with boolean values

check.tool.function	<i>Check Functionality of Third-Party Tools.</i>
---------------------	--

Description

Checks whether all required tools should work.

Usage

```
check.tool.function(frontend = FALSE)
```

Arguments

frontend	Whether tool functionality shall be checked for the frontend.
----------	---

Value

TRUE for each functioning tool, FALSE for non-functioning tools.

check.tool.installation	<i>Check Tool Installation</i>
-------------------------	--------------------------------

Description

Checks whether all required tools are installed.

Usage

```
check.tool.installation(frontend = FALSE)
```

Arguments

frontend	Whether tool installation shall be checked for the frontend. If TRUE, dependencies that are required only by the frontend are considered additionally.
----------	--

Value

TRUE for each installed tool, FALSE otherwise.

`check_constraints_comparison`*Batch Procedure for Evaluating Primer Sets.*

Description

Batch Procedure for Evaluating Primer Sets.

Usage

```
check_constraints_comparison(  
  primer.data,  
  template.data,  
  settings,  
  active.constraints = names(constraints(settings)),  
  to.compute.constraints = active.constraints,  
  for.shiny = FALSE,  
  updateProgress = NULL  
)
```

Arguments

<code>primer.data</code>	A list of objects of class <code>Primers</code> .
<code>template.data</code>	A list of objects of class <code>Templates</code> corresponding to <code>primer.data</code> .
<code>settings</code>	An object of class <code>DesignSettings</code> .
<code>active.constraints</code>	A character vector providing identifiers of constraints to be considered.
<code>to.compute.constraints</code>	A character vector providing identifiers of constraints to be computed.
<code>for.shiny</code>	A logical indicating whether the results are indicated for the Shiny app or not.
<code>updateProgress</code>	A callback function to track progress in the Shiny app.

Value

A list with objects of class `Primers`.

Examples

```
## Not run:  
data(Comparison)  
eval.data <- check_constraints_comparison(primer.data[1:2], template.data[1:2], settings)  
  
## End(Not run)
```

`check_constraint_settings_validity`*Check the Validity of the Constraint Settings.*

Description

Checks whether the status and the active constraints match. Determines whether the constraints are allowed/known.

Usage

```
check_constraint_settings_validity(object)
```

Arguments

`object` An AbstractConstraintSettings object.

Value

TRUE if the constraint settings are valid, FALSE otherwise.

`check_correspondence` *Check of Primer and Template Correspondence.*

Description

Checks whether the primers relate to the correct templates.

Usage

```
check_correspondence(primer.df, template.df)
```

Arguments

`primer.df` An object of class Primers.

`template.df` An object of class Templates.

Value

TRUE if the primers and templates seem to correspond, FALSE otherwise.

check_cvg_constraints *Evaluation of Coverage Constraints.*

Description

Computes the biochemical properties specified in the settings object and determines whether the primers fulfill the required constraints.

Usage

```
check_cvg_constraints(  
  primer.df,  
  template.df,  
  settings,  
  active.constraints = names(cvg_constraints(settings)),  
  to.compute.constraints = active.constraints,  
  for.shiny = FALSE,  
  updateProgress = NULL  
)
```

Arguments

primer.df	A Primers object containing the primers to be checked.
template.df	A Templates object containing the template sequences corresponding to the primers.
settings	A DesignSettings object containing the coverage constraints to be checked and their settings.
active.constraints	Identifiers of constraints that are to be checked.
to.compute.constraints	Constraints that are to be computed.
for.shiny	Whether to format output for HTML.
updateProgress	Progress callback function for shiny.

Value

A Primers object with with columns for each constraint in active.constraints.

Note

Please note that some constraints can only be computed if additional software is installed, please see [DesignSettings](#) for an overview.

check_interval	<i>Check Constraint Intervals</i>
----------------	-----------------------------------

Description

Checks the validity of constraint intervals.

Usage

```
check_interval(constraints)
```

Arguments

constraints A list with constraint settings.

Value

TRUE, if all constraints specify valid intervals, FALSE otherwise.

check_limits	<i>Validity Check for Limits.</i>
--------------	-----------------------------------

Description

Checks whether the constraint limits are at least as general as the constraint settings. This ensures that the relaxation works in the proper direction.

Usage

```
check_limits(constraint.settings, constraint.limits)
```

Arguments

constraint.settings
 A list with the constraint settings.
constraint.limits
 A list with the constraint relaxation limits.

Value

TRUE if the limits are at least as wide as the constraints, FALSE otherwise.

check_limit_value	<i>Check of limit correctness.</i>
-------------------	------------------------------------

Description

Checks whether a constraint limit is more general than the setting.

Usage

```
check_limit_value(setting, limit)
```

Arguments

setting	A single constraint setting.
limit	A single constraint limit.

Value

A vector containing TRUE if the limit is more general than the constraint setting and FALSE otherwise.

check_names	<i>Check Setting Names.</i>
-------------	-----------------------------

Description

Checks whether the specified settings have the correct names.

Usage

```
check_names(known.options, input.options)
```

Arguments

known.options	Allowed setting names.
input.options	Input setting names

Value

Mapping of input.options to known.options or NULL if invalid.

check_report_deps	<i>Check for Report Dependencies.</i>
-------------------	---------------------------------------

Description

Checks whether the dependencies for `rmarkdown::render()` are fulfilled.

Usage

```
check_report_deps()
```

Value

A logical vector giving the dependency availability status.

check_restriction_sites_single	<i>Identification of Sequence Restriction Sites.</i>
--------------------------------	--

Description

Checks the input sequences `seqs` for the presence of restriction sites. By removing the restriction sites from a primer set, it is possible to identify the coverage of the primers (e.g. using [check_constraints](#)) discounting for the impact of the mismatching bases caused by the insert.

Usage

```
check_restriction_sites_single(
  primer.seqs,
  template.seqs,
  adapter.action,
  direction = c("fw", "rev"),
  selected = NULL,
  only.confident.calls = TRUE,
  updateProgress = NULL
)
```

Arguments

<code>primer.seqs</code>	Nucleotide sequences of primers to be checked for restriction sites in terms of a <code>DNAStrngSet</code> object.
<code>template.seqs</code>	A <code>DNAStrngSet</code> object with nucleotide sequences containing the templates corresponding to <code>seqs</code> .

`adapter.action` The action to be performed when adapter sequences are found. Either "warn" to issue warning about adapter sequences or "rm" to remove identified adapter sequences.

`selected` Names of restriction sites that are to be checked. By default selected is NULL in which case all REBASE restriction sites are checked.

`only.confident.calls` Only output confident calls of restriction sites.

`updateProgress` A Shiny progress callback function.

`The` primer direction that is checked.

Value

A data frame with restriction sites, if any could be found.

References

Roberts, R.J., Vincze, T., Posfai, J., Macelis, D. (2010) REBASE—a database for DNA restriction and modification: enzymes, genes and genomes. Nucl. Acids Res. 38: D234-D236. <http://rebase.neb.com>

check_setting	<i>Check Setting Validity.</i>
---------------	--------------------------------

Description

Checks whether the input settings are valid or not.

Usage

```
check_setting(known.options, options, mandatory.options = NULL)
```

Arguments

`known.options` Vector with names and classes of allowed options.

`options` Active options to be checked.

`mandatory.options` Fields that have to be present.

Value

TRUE if the setting is valid, FALSE otherwise.

`check_settings_validity`*Validity Check for DesignSettings.*

Description

Validates whether a DesignSettings object has the correct structure.

Usage

```
check_settings_validity(object)
```

Arguments

`object` A DesignSettings object to be checked for validity.

Value

TRUE if object is valid, FALSE otherwise.

`combine.binding.events`*Combination of Binding Events.*

Description

Appends all binding events.

Usage

```
combine.binding.events(my.binding.fw, my.binding.rev, fw.m, rev.m)
```

Arguments

`my.binding.fw` Forward binding events of individual primers.

`my.binding.rev` Reverse binding events of individual primers.

`fw.m` Forward binding events of paired primers.

`rev.m` Reverse binding events of paired primers.

Value

IRanges of all binding events.

combine.strings	<i>Combination of OligoArrayAux Structure Sequences.</i>
-----------------	--

Description

Combines the input strings.

Usage

```
combine.strings(s1, s2)
```

Arguments

s1	A character vector to be combined with s2.
s2	A character vector to be included into s1.

Value

A character vector.

comp	<i>Sequence complement</i>
------	----------------------------

Description

Complements the input sequence (re-write of seqinr comp function for gap support)

Usage

```
comp(seq, forceToLower = TRUE, ambiguous = FALSE)
```

Arguments

seq	Input char vector.
forceToLower	if TRUE the input is transformed to lower case.
ambiguous	if TRUE ambiguous IUPAC nucleotides are complemented.

Value

The complement of seq.

compare.constraints	<i>Constraint list comparison</i>
---------------------	-----------------------------------

Description

Determines whether two list with constraints are identical.

Usage

```
compare.constraints(A, B)
```

Arguments

A	First constraint list.
B	Second constraint list.

Value

TRUE if the constraints are identical, FALSE else.

comparison.cvg	<i>Comparison Coverage Stats.</i>
----------------	-----------------------------------

Description

Computes coverage stats for primer comparison.

Usage

```
comparison.cvg(primer.data, template.data)
```

Arguments

primer.data	List with primer data frames.
template.data	List with template data frames.

Value

Coverage statistics for comparing primers.

comparison.stats.raw	<i>Computation of Raw Stats for Primer Comparison</i>
----------------------	---

Description

Computes raw stats for primer comparison.

Usage

```
comparison.stats.raw(primer.data, template.data)
```

Arguments

primer.data	List with primer data frames.
template.data	List with template data frames.

Value

Raw statistics for primer comparison.

complement.sequence	<i>Sequence complement</i>
---------------------	----------------------------

Description

Computes the complement of the input sequence.

Usage

```
complement.sequence(seq)
```

Arguments

seq	The input sequence strings.
-----	-----------------------------

Value

The complements of the input sequences.

`compute.all.cross.dimers`*Cross dimerization*

Description

Compute worst-case DeltaG data frame with all possible primer cross-dimers.

Usage

```
compute.all.cross.dimers(  
  primer.df,  
  primer_conc,  
  na_salt_conc,  
  mg_salt_conc,  
  k_salt_conc,  
  tris_salt_conc,  
  annealing.temp,  
  results = NULL,  
  check.idx = NULL,  
  for.shiny = FALSE,  
  no.structures = FALSE  
)
```

Arguments

<code>primer.df</code>	Input primers data frame.
<code>primer_conc</code>	Primer concentration.
<code>na_salt_conc</code>	Sodium ion concentration.
<code>mg_salt_conc</code>	Magnesium ion concentration.
<code>k_salt_conc</code>	Potassium ion concentration.
<code>tris_salt_conc</code>	Tris buffer concentration.
<code>annealing.temp</code>	The PCR annealing temperature.
<code>results</code>	(optional) Cross dimer data frame (unfiltered)
<code>check.idx</code>	Indices of primers for checking cross-dimerization.
<code>for.shiny</code>	Whether the table is intended for HTML display.
<code>no.structures</code>	Whether dimerization structures shall not be outputted.

Value

Worst-case cross dimers.

```
compute.all.cross.dimers.frontend
```

Cross Dimerization.

Description

Computes all cross dimers in a user-formatted way.

Usage

```
compute.all.cross.dimers.frontend(  
  primer.df,  
  primer_conc,  
  na_salt_conc,  
  mg_salt_conc,  
  k_salt_conc,  
  tris_salt_conc,  
  annealing.temp,  
  for.shiny = FALSE,  
  no.structures = FALSE  
)
```

Arguments

primer.df	Input primer data frame.
primer_conc	Primer concentration.
na_salt_conc	Sodium ion concentration.
mg_salt_conc	Magensium ion concentration.
k_salt_conc	Potassium ion concentration.
tris_salt_conc	Tris buffer concentration.
annealing.temp	The PCR annealing temperature.
for.shiny	Whether to format the table for HTML output.
no.structures	Whether to compute structures of dimers.

Value

A formatted data frame with cross-dimerization infos

```
compute.all.cross.dimers.unfiltered
```

Cross dimerization

Description

Compute DeltaG data frame for possible primer cross-dimers.

Usage

```
compute.all.cross.dimers.unfiltered(  
  primer.df,  
  primer_conc,  
  na_salt_conc,  
  mg_salt_conc,  
  k_salt_conc,  
  tris_salt_conc,  
  annealing.temp,  
  check.idx = NULL,  
  for.shiny = FALSE,  
  no.structures = FALSE  
)
```

Arguments

<code>primer.df</code>	Input primers data frame.
<code>primer_conc</code>	Primer concentration.
<code>na_salt_conc</code>	Sodium ion concentration.
<code>mg_salt_conc</code>	Magensium ion concentration.
<code>k_salt_conc</code>	Potassium ion concentration.
<code>tris_salt_conc</code>	Tris buffer concentration.
<code>annealing.temp</code>	The PCR annealing temperature.
<code>check.idx</code>	Indices of primers for checking cross-dimerization.
<code>for.shiny</code>	Whether to format for HTML output.
<code>no.structures</code>	Whether dimer structures shall not be determined. If TRUE, structures are not computed resulting in faster runtimes.

Value

All cross dimers.

```
compute.all.primer.subsets.ILP
```

Computation of Primer Subsets

Description

Computes all optimal primer subsets and stores their plots.

Usage

```
compute.all.primer.subsets.ILP(  
  primer.df,  
  template.df,  
  k,  
  groups,  
  cur.results.loc,  
  required.cvg = 1  
)
```

Arguments

primer.df	Primer data frame.
template.df	Template data frame.
k	Subset size-increment.
groups	Identifiers of template groups in order to limit coverage to certain groups of template sequences.
cur.results.loc	Location for storing the results.
required.cvg	The required coverage ratio.

Value

Write-out of results.

```
compute.all.self.dimers
```

Self dimers

Description

Computes all possible self dimers for the primers in the input data frame.

Usage

```
compute.all.self.dimers(  
  primer.df,  
  primer_conc,  
  na_salt_conc,  
  mg_salt_conc,  
  k_salt_conc,  
  tris_salt_conc,  
  annealing.temp,  
  for.shiny = FALSE,  
  no.structures = FALSE  
)
```

Arguments

primer.df	Input primer data frame.
primer_conc	Primer concentration.
na_salt_conc	Sodium ion concentration.
mg_salt_conc	Magnesium ion concentration.
k_salt_conc	Potassium ion concentration.
tris_salt_conc	Tris buffer concentration.
annealing.temp	The PCR annealing temperature.
for.shiny	Whether the output is to be formatted for HTML.
no.structures	Whether dimerization structures shall be outputted.

Value

Data frame with thermodynamic information on all self dimers.

compute.all.self.dimers.frontend
Self Dimerization.

Description

Computes all self dimers in a user-formatted way.

Usage

```
compute.all.self.dimers.frontend(  
  primer.df,  
  primer_conc,  
  na_salt_conc,  
  mg_salt_conc,
```

```

    k_salt_conc,
    tris_salt_conc,
    annealing.temp,
    for.shiny = FALSE,
    no.structures = FALSE
  )

```

Arguments

primer.df	Input primer data frame.
primer_conc	Primer concentration.
na_salt_conc	Sodium ion concentration.
mg_salt_conc	Magnesium ion concentration.
k_salt_conc	Potassium ion concentration.
tris_salt_conc	Tris buffer concentration.
annealing.temp	The PCR annealing temperature.
for.shiny	Whether to format the table for HTML output.
no.structures	Whether dimerization structures shall be outputted.

Value

A formatted data frame with self-dimerization infos

compute.basic.details *Computation of Coverage Details*

Description

Determines binding properties of primers.

Usage

```

compute.basic.details(
  binding,
  mode = c("on_target", "off_target"),
  template.df,
  primers,
  mode.directionality = c("fw", "rev", "both"),
  allowed.mismatches,
  allowed.other.binding.ratio,
  allowed.region.definition = c("within", "any"),
  updateProgress = NULL
)

```

Arguments

binding	An IRanges object with primer binding information.
mode	Either on_target for on-target binding or off_target for off-target binding.
template.df	Template data frame.
primers	Primer data frame.
mode.directionality	Primer directionality.
allowed.mismatches	The number of allowed mismatches per binding event.
allowed.other.binding.ratio	Ratio of primers that are allowed to bind to non-allowed regions. If allowed.other.binding.ratio >0 primers are allowed to bind at any location within the templates. However, a warning is given if the ratio of primers binding to non-target regions exceeds the allowed.other.binding.ratio.
allowed.region.definition	Definition of the target binding sites used for evaluating the coverage. If allowed.region.definition is within, primers have to lie within the allowed binding region. If allowed.region.definition is any, primers have to overlap with the allowed binding region. The default is that primers have to bind within the target binding region.
updateProgress	Progress callback function for shiny.

Value

Primer data frame with information on the covered template sequences.

compute.constraints *Computation of Constraints.*

Description

Computes the specified constraints for the input primers.

Usage

```
compute.constraints(
  primer.df,
  mode.directionality = c("fw", "rev", "both"),
  template.df,
  settings,
  active.constraints = c("primer_coverage", "primer_length", "primer_specificity",
    "gc_clamp", "gc_ratio", "no_runs", "no_repeats", "self_dimerization",
    "cross_dimerization", "melting_temp_range", "melting_temp_diff",
    "secondary_structure", "primer_efficiency", "annealing_DeltaG", "stop_codon",
    "terminal_mismatch_pos", "substitution", "hexamer_coverage", "coverage_model",
    "off_primer_efficiency", "off_annealing_DeltaG", "off_coverage_model"),
```



```
    no.structures = FALSE,  
    for.shiny = FALSE,  
    updateProgress = NULL  
  )
```

Arguments

primer.df	Primer data frame.
mode.directionality	Primer directionality.
template.df	Template data frame.
settings	A DesignSettings object.
active.constraints	Strings giving the constraints that are to be computed.
no.structures	Whether dimer structures shall be computed.
for.shiny	Whether to format output for HTML.
updateProgress	Progress callback function for shiny.

Value

A data frame with columns for each constraint in active.constraints.

compute.covered.Ta	<i>Annealing temperature</i>
--------------------	------------------------------

Description

Computes the annealing temperature using all binding events.

Usage

```
compute.covered.Ta(  
  primer.df,  
  mode.directionality = c("fw", "rev", "both"),  
  template.df,  
  na_salt_conc,  
  mg_salt_conc,  
  k_salt_conc,  
  tris_salt_conc,  
  primer_conc  
)
```

Arguments

primer.df	Primer data frame.
mode.directionality	Primer directionality.
template.df	Template data frame
na_salt_conc	Sodium ion concentration.
mg_salt_conc	Magensium ion concentration.
k_salt_conc	Potassium ion concentration.
tris_salt_conc	Tris buffer concentration.
primer_conc	Primer concentration.

Value

The recommended annealing temperature.

compute.dimer.matrix	<i>Dimerization matrix</i>
----------------------	----------------------------

Description

Computes a matrix indicating all dimerizing primers according to a DeltaG cutoff.

Usage

```
compute.dimer.matrix(G, deltaG.cutoff = -7)
```

Arguments

G	Matrix with free energies of all considered primer pairs.
deltaG.cutoff	Primers with free energies below the cutoff are considered dimerizing.

Value

Binary matrix with dimerization events according to the deltaG.cutoff. Contains '1' if primers (i,j) dimerize and '0' else.

compute.ency	<i>Primer Efficiency.</i>
--------------	---------------------------

Description

Computes the efficiency of primer binding events for Taq polymerase.

Usage

```
compute.ency(  
  fw.primer,  
  fw.start,  
  fw.end,  
  covered,  
  taqEfficiency,  
  annealing.temp,  
  primer_conc,  
  sodium.eq.concentration,  
  mode.directionality = c("fw", "rev"),  
  seqs  
)
```

Arguments

fw.primer	Primer sequence strings.
fw.start	Binding position (start).
fw.end	Binding position (end).
covered	List of covered template indices per primer.
taqEfficiency	Whether the efficiency shall be computed using a mismatch-model developed for Taq polymerases. The default setting is TRUE. Set taqEfficiency to FALSE if you are using another polymerase than Taq.
annealing.temp	Annealing temperature for which to evaluate efficiency.
primer_conc	Primer concentration.
sodium.eq.concentration	The sodium-equivalent concentration of ions.
mode.directionality	Primer directionality.
seqs	Template sequence strings.

Details

This function uses DECIPHER's [CalculateEfficiencyPCR](#).

Value

The efficiencies of primer binding events.

References

Wright, Erik S., et al. "Exploiting extension bias in polymerase chain reaction to improve primer specificity in ensembles of nearly identical DNA templates." *Environmental microbiology* 16.5 (2014): 1354-1365.

compute.empiric.melting.temp

Non-Thermodynamic Computation of Melting Temperatures.

Description

Computes the melting temperature of primers from an empiric formula.

Usage

```
compute.empiric.melting.temp(primer.df)
```

Arguments

primer.df A Primers object.

Value

A data frame with melting temperature information for the primers.

compute.gc.ratio

GC ratio

Description

Computes the ratio of G/Cs in a sequence.

Usage

```
compute.gc.ratio(x)
```

Arguments

x Input sequence.

Details

In case of ambiguities, the mean GC ratio of all possible sequences is computed.

Value

The fraction of G/Cs in x.

compute.melting.temps *Computation of Melting Temperatures.*

Description

Use nearest-neighbor thermodynamic computations to find melting temperatures.

Usage

```
compute.melting.temps(  
  primer.df,  
  primer_conc,  
  na_salt_conc,  
  mg_salt_conc,  
  k_salt_conc,  
  tris_salt_conc,  
  mode.directionality = c("fw", "rev", "both")  
)
```

Arguments

primer.df	Primer data frame.
primer_conc	Primer concentration.
na_salt_conc	Sodium ion concentration.
mg_salt_conc	Magensium ion concentration.
k_salt_conc	Potassium ion concentration.
tris_salt_conc	Tris buffer concentration.
mode.directionality	Direction of primers

Value

Data frame with melting temperature info for the input primers.

compute.melting.temps.thermo
 Computation of Thermodynamic Melting Temperatures.

Description

Use nearest-neighbor thermodynamic computations to find melting temperatures.

Usage

```
compute.melting.temps.thermo(  
  primer.df,  
  primer_conc,  
  na_salt_conc,  
  mg_salt_conc,  
  k_salt_conc,  
  tris_salt_conc,  
  mode.directionality = c("fw", "rev", "both")  
)
```

Arguments

primer.df	Primer data frame.
primer_conc	Primer concentration.
na_salt_conc	Sodium ion concentration.
mg_salt_conc	Magensium ion concentration.
k_salt_conc	Potassium ion concentration.
tris_salt_conc	Tris buffer concentration.
mode.directionality	Direction of primers

Value

Data frame with melting temperature info for the input primers.

compute.mismatch.table
<i>Mismatch overview table</i>

Description

Computes a table summarizing all of the mismatches caused by the primers in the input data frame.

Usage

```
compute.mismatch.table(  
  primer.df,  
  template.df,  
  mode.directionality = c("fw", "rev")  
)
```

Arguments

primer.df	Primer data frame.
template.df	Template data.
mode.directionality	Direction of primers.

Value

: A data frame summarizing all mismatches of the input primers with the input templates.

```
compute.primer.efficiencies
```

Primer Efficiency.

Description

Computes the efficiency of primer binding events for Taq polymerase.

Usage

```
compute.primer.efficiencies(
  primer.df,
  template.df,
  annealing.temp,
  taqEfficiency,
  primer_conc,
  na_salt_conc,
  mg_salt_conc,
  k_salt_conc,
  tris_salt_conc,
  mode = c("on_target", "off_target")
)
```

Arguments

primer.df	Primer data frame.
template.df	Template data frame.
annealing.temp	Annealing temperature for which to evaluate efficiency.
taqEfficiency	Whether the efficiency shall be computed using a mismatch-model developed for Taq polymerases. The default setting is TRUE. Set taqEfficiency to FALSE if you are using another polymerase than Taq.
primer_conc	Primer concentration.
na_salt_conc	Sodium ion concentration.
mg_salt_conc	Magensium ion concentration.

k_salt_conc	Potassium ion concentration.
tris_salt_conc	Tris ion concentration.
mode	Compute efficiencies for on-target coverage events (on_target) or off-target coverage events (off_target).

Details

This function uses DECIPHER's [CalculateEfficiencyPCR](#).

Value

A list with the efficiency of every primer binding event.

Examples

```
data(Ippolito)
p <- PCR(settings)
# Requires OligoArrayAux software:
## Not run:
eff.df <- compute.primers.efficiencies(primer.df, template.df, 55,
                                     p$primer_concentration, p$Na_concentration,
                                     p$Mg_concentration, p$K_concentration, p$Tris_concentration)

## End(Not run)
```

```
compute.secondary.structures
```

Secondary Structure Computations.

Description

Computes the secondary structures of the input primers using ViennaRNA.

Usage

```
compute.secondary.structures(
  primer.df,
  mode.directionality = c("fw", "rev", "both"),
  annealing.temperature
)
```

Arguments

primer.df	Primer data frame.
mode.directionality	Direction of primers.
annealing.temperature	Temperatures at which to compute secondary structures for every primer

Value

Data frame with secondary structure information.

References

Lorenz, Ronny and Bernhart, Stephan H. and Höner zu Siederdisen, Christian and Tafer, Hakim and Flamm, Christoph and Stadler, Peter F. and Hofacker, Ivo L. ViennaRNA Package 2.0 Algorithms for Molecular Biology, 6:1 26, 2011, doi:10.1186/1748-7188-6-26

`compute.sodium.equivalent.conc`*Sodium-equivalent Concentration*

Description

Computes the sodium-equivalent concentration for the input ion concentrations.

Usage

```
compute.sodium.equivalent.conc(  
  na_salt_conc,  
  mg_salt_conc,  
  k_salt_conc,  
  tris_salt_conc  
)
```

Arguments

na_salt_conc	Sodium ion concentration.
mg_salt_conc	Magnesium ion concentration.
k_salt_conc	Potassium ion concentration.
tris_salt_conc	Tris buffer concentration.

Value

The sodium-equivalent concentration of the input ion concentrations.

References

Record, M. Thomas. "Effects of Na⁺ and Mg⁺⁺ ions on the helix-coil transition of DNA." Biopolymers 14.10 (1975): 2137-2158.

Owczarzy, Richard, et al. "Predicting stability of DNA duplexes in solutions containing magnesium and monovalent cations." Biochemistry 47.19 (2008): 5336-5353.

Peyret, Nicolas. Prediction of nucleic acid hybridization: parameters and algorithms. Detroit: Wayne State University, 2000.

compute.structure.vienna	<i>Computation of Secondary Structures with ViennaRNA.</i>
--------------------------	--

Description

Computes secondary structures using ViennaRNA.

Usage

```
compute.structure.vienna(  
  seqs,  
  annealing.temperature,  
  folding.constraints = NULL,  
  id = ""  
)
```

Arguments

- seqs The input sequences for which structures shall be computed.
- annealing.temperature The temperature in degree Celsius at which to compute secondary structures.
- folding.constraints Character vector specifying the folding conditions for every input sequence. For example the constraint xxxxxx... would forbid folding in the first 6 bases and allow folding in the last 3 bases.
- id An identifier for storing the files
- constraints If provide

Value

A data frame with secondary structures.

compute.Ta	<i>Annealing temperature</i>
------------	------------------------------

Description

Computes the annealing temperature using all binding events.

Usage

```
compute.Ta(  
  primer.df,  
  template.df,  
  mode.directionality = c("fw", "rev", "both"),  
  na_salt_conc,  
  mg_salt_conc,  
  k_salt_conc,  
  tris_salt_conc,  
  primer_conc  
)
```

Arguments

primer.df	Primer data frame.
template.df	Template data frame
mode.directionality	Primer directionality.
na_salt_conc	Sodium ion concentration.
mg_salt_conc	Magensium ion concentration.
k_salt_conc	Potassium ion concentration.
tris_salt_conc	Tris buffer concentration.
primer_conc	Primer concentration.

Value

All annealing temperatures for given binding events.

References

Rychlik, W. J. S. W., W. J. Spencer, and R. E. Rhoads. "Optimization of the annealing temperature for DNA amplification in vitro." *Nucleic acids research* 18.21 (1990): 6409-6412.

compute.template.secondary.structures
Template Secondary Structures

Description

Computes template secondary structures.

Usage

```
compute.template.secondary.structures(
  template.df,
  annealing.temperature,
  regions = NULL,
  constraints = NULL
)
```

Arguments

template.df	Template data frame.
annealing.temperature	Temperature [C] at which to compute secondary structures.
regions	List containing the positional intervals for which the template secondary structure should be computed.
constraints	String giving secondary structure constraints. For example xxxxxx... would forbid folding in the first 6 bases of a template with length 9 and allow folding in its last 3 bases.

Value

Data frame with info on template secondary structures.

compute.Tm.baldino	<i>Baldino Formula</i>
--------------------	------------------------

Description

Computes the melting temperature using the formulation by Baldino.

Usage

```
compute.Tm.baldino(
  sequences,
  na_salt_conc,
  mg_salt_conc,
  k_salt_conc,
  tris_salt_conc,
  primer_conc
)
```

Arguments

sequences	Input sequence strings.
na_salt_conc	Sodium ion concentration.
mg_salt_conc	Magensium ion concentration.
k_salt_conc	Potassium ion concentration.
tris_salt_conc	Tris buffer concentration.
primer_conc	Primer concentration.

Value

The melting temperature for the input sequences.

References

Rychlik, W. J. S. W., W. J. Spencer, and R. E. Rhoads. "Optimization of the annealing temperature for DNA amplification in vitro." Nucleic acids research 18.21 (1990): 6409-6412.

compute.Tm.sets	<i>Cross-Dimerization Filtering</i>
-----------------	-------------------------------------

Description

Removes cross-dimerizing primers from the input data.

Usage

```
compute.Tm.sets(  
  primer.df,  
  template.df,  
  Tm.brackets,  
  settings,  
  mode.directionality = c("fw", "rev"),  
  primer_conc,  
  template_conc,  
  na_salt_conc,  
  mg_salt_conc,  
  k_salt_conc,  
  tris_salt_conc,  
  allowed.mismatches,  
  allowed.other.binding.ratio,  
  allowed.stop.codons,  
  allowed.region.definition,  
  disallowed.mismatch.pos,  
  opti.mode = FALSE,  
  required.cvg = NULL,
```

```

    primers.fw = NULL,
    diagnostic.location = NULL,
    updateProgress = NULL
)

```

Arguments

<code>primer.df</code>	Primer data frame.
<code>template.df</code>	Template data frame.
<code>Tm.brackets</code>	Data frame with target primer melting temperatures.
<code>settings</code>	A DesignSettings object.
<code>mode.directionality</code>	Identifier of strand for which primers shall be designed.
<code>primer_conc</code>	Primer concentration.
<code>template_conc</code>	Template concentration.
<code>na_salt_conc</code>	Sodium ion concentration.
<code>mg_salt_conc</code>	Magnesium ion concentration.
<code>k_salt_conc</code>	Potassium ion concentration.
<code>tris_salt_conc</code>	Tris ion concentration.
<code>allowed.mismatches</code>	The number of mismatches primers are allowed to have with the templates.
<code>allowed.other.binding.ratio</code>	Ratio of primers allowed to bind to non-target regions.
<code>allowed.stop.codons</code>	Consider mismatch binding events that induce stop codons.
<code>allowed.region.definition</code>	Definition of the allowed region.
<code>disallowed.mismatch.pos</code>	The number of positions from the primer 3' end where mismatches should not be allowed. All primers binding templates with mismatches within <code>disallowed.mismatch.pos</code> from the 3' end are disregarded.
<code>opti.mode</code>	Compute optimization constraints and relax delta Tm if necessary.
<code>required.cvg</code>	Target coverage ratio.
<code>primers.fw</code>	Already designed primer sets for the target temperatures given in <code>Tm.brackets</code> . Used to determine cross-dimerization.
<code>diagnostic.location</code>	Directory for storing results.
<code>updateProgress</code>	Shiny progress callback function.
<code>primers.rev</code>	The primer data set to be filtered for cross-dimers.
<code>opti.constraints</code>	List with optimization constraint settings.
<code>annealing.temp</code>	The PCR annealing temperature.

Value

primers.rev with removed cross-dimerizing primers.
Primer data frames for every target temperature.

compute.unique.covered.idx	<i>Unique Coverage Indices Computes the indices of templates that are covered uniquely covered by an individual primer.</i>
----------------------------	---

Description

Unique Coverage Indices Computes the indices of templates that are covered uniquely covered by an individual primer.

Usage

compute.unique.covered.idx(primer.df, template.df)

Arguments

primer.df	Primer data frame.
template.df	Template data frame.

Value

Index of templates uniquely covered per input primer.

compute_annealing_temp	<i>Annealing temperature.</i>
------------------------	-------------------------------

Description

Identifies the optimal annealing temperature of a set of primers. If primers cover template sequences, the annealing temperature is computed using Rychlik’s formula. Otherwise, the annealing temperature is determined using the rule of thumb based on the melting temperatures of the primers.

Usage

```
compute_annealing_temp(  
  primer.df,  
  mode.directionality,  
  template.df,  
  na_salt_conc,  
  mg_salt_conc,  
  k_salt_conc,  
  tris_salt_conc,  
  primer_conc  
)
```

Arguments

primer.df	Primer data frame.
mode.directionality	Primer directionality.
template.df	Template data frame
na_salt_conc	Sodium ion concentration.
mg_salt_conc	Magensium ion concentration.
k_salt_conc	Potassium ion concentration.
tris_salt_conc	Tris buffer concentration.
primer_conc	Primer concentration.

Value

The optimal annealing temperature.

condition	<i>Condition Constructor</i>
-----------	------------------------------

Description

Constructs a condition for custom errors.

Usage

```
condition(subclass, message, call = sys.call(-1), ...)
```

Arguments

subclass	String giving the specific error.
message	String giving the user message.
call	Environment object.
...	Other arguments for the output structure.

Value

A condition structure.

consecutive.GC.count	<i>Consecutive GCs</i>
----------------------	------------------------

Description

Determines the maximum number of consecutive G/Cs

Usage

```
consecutive.GC.count(y, len)
```

Arguments

y	Positions where G/C occurs. Positions are numbered from 1 to 5 where 5 is the end of the primer.
len	Is the number of bases from the primer end considered.

Value

The maximal number of consecutive G/Cs.

constraints.to.df	<i>Conversion of Constraints List to Data Frame.</i>
-------------------	--

Description

Converts the input constraints to a data frame representation.

Usage

```
constraints.to.df(
  limit.constraints,
  out.names,
  format.type = c("backend", "shiny", "report")
)
```

Arguments

limit.constraints	A list with constraints.
out.names	The desired column names.
format.type	The type of formatting to be performed on the table

Value

A data frame giving an overview of the constraints.

```
constraints.xml.format
```

Constraint XML Format.

Description

Format constraint settings for XML output.

Usage

```
constraints.xml.format(constraints, set.name)
```

Arguments

constraints	List with constraint settings.
set.name	Identifier for the constraint settings.

Value

XML string containing the constraint settings.

```
constraints_to_unit
```

Mapping of Constraints to Units.

Description

Maps constraints to units for plotting.

Usage

```
constraints_to_unit(
  constraint,
  use.unit = TRUE,
  format.type = c("backend", "HTML", "report")
)
```

Arguments

constraint	The names of the constraints to convert to their plot identifiers (units).
use.unit	Whether constraint names should be annotated with their units.
use.HTML	Whether constraint units should be annotated with HTML units.

Value

A list of constraint names.

convert.from.iupac	<i>Conversion from IUPAC nucleotides</i>
--------------------	--

Description

Convert sequences with IUPAC ambiguity codes to all possible sequences without ambiguities.

Usage

```
convert.from.iupac(seqs)
```

Arguments

seqs	A vector of strings.
------	----------------------

Value

A list containing the disambiguated input sequences.

convert.PCR.units	<i>Conversion of PCR Units</i>
-------------------	--------------------------------

Description

Converts frontend PCR concentration units to the units used for the backend.

Usage

```
convert.PCR.units(pcr.settings, to.mol = TRUE)
```

Arguments

pcr.settings	List with several PCR settings (concentrations).
to.mol	If TRUE, convert to the molar concentration. If FALSE convert to the unit representation in the XML.

Value

List with concentrations for usage in the backend.

convert.temperature	<i>Conversion between Celsius and Kelvin</i>
---------------------	--

Description

Converts the input from Kelvin to Celsius or from Celsius to Kelvin.

Usage

```
convert.temperature(temp, temp.scale = c("K", "C"))
```

Arguments

temp	The input temperature.
temp.scale	The desired unit of the output temperature.

Details

If temp.scale is 'K', T_m is transformed from Celsius to Kelvin. If temp.scale is 'C', T_m is transformed from Kelvin to Celsius. The default is to transform from Celsius to Kelvin.

Value

Transforms the input temperature to the specified temp.scale.

convert.to.iupac	<i>Merge sequences.</i>
------------------	-------------------------

Description

Merges the input sequences to one sequence containing IUPAC ambiguity codes.

Usage

```
convert.to.iupac(seqs)
```

Arguments

seqs	Vector of strings.
------	--------------------

Value

Consensus sequence of seqs.

con_select	<i>Quick Selection of Constraints.</i>
------------	--

Description

Select constraints that can be used according to third-party tools quickly.

Usage

```
con_select(active.constraints)
```

Arguments

active.constraints
Identifiers of constraints.

Value

The identifiers of constraints that can be computed.

copy.melt.config	<i>Copy MELTING Config File</i>
------------------	---------------------------------

Description

Copies modified MELTING tandem mismatch file to the MELTING data folder.

Usage

```
copy.melt.config(melt.bin = NULL)
```

Value

TRUE if the file is available in the MELTING folder, FALSE otherwise.

`covered.primers.to.ID.string`*Conversion of Primer Indices to ID string*

Description

Converts the input coverage indices to a comma-separated string with the template IDs.

Usage

```
covered.primers.to.ID.string(covered.primers, primer.df)
```

Arguments

<code>covered.primers</code>	Identifiers of primers covering sequences.
<code>primer.df</code>	Primer data frame.

Value

String containing the covered template IDs.
A string containing the IDs of covering primers.

`covered.seqs.to.ID.string`*Conversion of Template Coverage Indices to ID string*

Description

Converts the input coverage indices to a comma-separated string with the template IDs.

Usage

```
covered.seqs.to.ID.string(covered.seqs, template.df)
```

Arguments

<code>covered.seqs</code>	Indices of covered template sequences.
<code>template.df</code>	Template data frame.

Value

A string containing the covered template IDs.

covered.seqs.to.idx	<i>Conversion of Coverage Strings to Indices.</i>
---------------------	---

Description

Converts the input coverage strings (comma separated template Identifiers) into indices.

Usage

```
covered.seqs.to.idx(covered.seqs, template.df)
```

Arguments

covered.seqs	Strings of covered sequences to be converted.
template.df	Template data frame containing the identifiers of templates

Value

Indices of covered templates.

create.constraint.table	<i>Output a Constraint Overview Table</i>
-------------------------	---

Description

Outputs a table showing the values of constraints.

Usage

```
create.constraint.table(
  constraints,
  constraint.limits = NULL,
  constraints.used.fw = NULL,
  constraints.used.rev = NULL,
  format.type = c("backend", "shiny", "report")
)
```

Arguments

constraints	List with constraint settings.
constraint.limits	List with constraint limits.
constraints.used.fw	Constraints used for forward primer design.
constraints.used.rev	Constraints used for reverse primer design.
format.type	The type of formatting to be performed on entries.

Value

Data frame with summary of constraints.

create.constraint.XML *XML Output of Constraints*

Description

Creates an XML summarizing all settings.

Usage

```
create.constraint.XML(  
  filtering.constraints,  
  c.f.lim,  
  cvg.constraints,  
  PCR.settings,  
  constraint.settings  
)
```

Arguments

filtering.constraints	List with constraint settings for filtering.
c.f.lim	Relaxation limits for the filtering constraints.
cvg.constraints	List with constraints for coverage computations.
PCR.settings	Settings for the PCR.
constraint.settings	Other settings of constraints (e.g. coverage).

Value

String in XML format containing all constraint settings.

create.cvg.text	<i>Coverage Info Text</i>
-----------------	---------------------------

Description

Creates a string with information on the coverage

Usage

```
create.cvg.text(stats, selected.group = NULL, ident = NULL)
```

Arguments

stats	Data frame with coverage statistics.
selected.group	Retrieve information for a subgroup of templates only.
ident	An identifier for the coverage.

Value

A string with information on the coverage.

create.G.matrix	<i>Create free energy matrix</i>
-----------------	----------------------------------

Description

Creates a matrix giving the deltaG values of all primers.

Usage

```
create.G.matrix(primer.df, G.df, primer.df.2 = NULL)
```

Arguments

primer.df	Primer data frame.
G.df	Free energy data for the primers.
primer.df.2	Optional second primer data frame

Value

Matrix with the smallest free dimerization energy for every primer pair.

`create.initial.primer.set`*Creation of an Initial Primer Set.*

Description

Creates an initial set of candidate primers for primer design.

Usage

```
create.initial.primer.set(  
  template.df,  
  primer.lengths,  
  mode.directionality = c("fw", "rev"),  
  sample,  
  allowed.region.definition = c("within", "any"),  
  init.algo = c("naive", "tree"),  
  max.degen,  
  conservation,  
  updateProgress = NULL  
)
```

Arguments

<code>template.df</code>	Template data frame.
<code>primer.lengths</code>	Vector containing the permissible primer lengths.
<code>mode.directionality</code>	Direction of primers to be created.
<code>sample</code>	Name of the template sample.
<code>allowed.region.definition</code>	Definition of the allowed binding region.
<code>init.algo</code>	Algorithm for initializing primers.
<code>max.degen</code>	Maximal allowed degeneration of created primers.
<code>conservation</code>	Required conservation of primers. The value of conservation should be in the range[0,1].
<code>updateProgress</code>	Shiny progress object.

Value

An initialized data frame of candidate primers.

create.k.mers	<i>Creation of k-mers for multiple sequences.</i>
---------------	---

Description

Creation of k-mers for multiple sequences.

Usage

```
create.k.mers(seqs, k)
```

Arguments

k	The size of the k-mer.
seq	A character vector.

Value

A list with named character vectors, containing the k-mers.

create.kmer	<i>Creation of k-mers of a single sequence.</i>
-------------	---

Description

Creation of k-mers of a single sequence.

Usage

```
create.kmer(seq, k)
```

Arguments

seq	A character vector.
k	The size of the k-mer.

Value

A names character vector, where the names are the relative positions of the k-mers and the values give the character vector of the k-mer.

`create.options.table` *Creation of a Table for Constraint Options.*

Description

Creation of a Table for Constraint Options.

Usage

```
create.options.table(  
  other.settings,  
  format.type = c("backend", "shiny", "report")  
)
```

Arguments

`other.settings` List with constraint options
`format.type` How the table shall be formatted.

Value

A data frame.

`create.other.table` *Creation of a Table for Other Constraint Settings.*

Description

Creation of a Table for Other Constraint Settings.

Usage

```
create.other.table(other.settings, col.names, format.type)
```

Arguments

`other.settings` List with other constraint settings.
`format.type` How the table shall be formatted.

Value

A data frame.

create.PCR.table	<i>Creation of a Table for PCR Conditions</i>
------------------	---

Description

Creation of a Table for PCR Conditions

Usage

```
create.PCR.table(other.settings, format.type = c("backend", "shiny", "report"))
```

Arguments

other.settings List with PCR settings.
 format.tyep How the table shall be formatted.

Value

A data frame.

create.primer.ranges	<i>Ranges for Initial Primers.</i>
----------------------	------------------------------------

Description

Creates a data frame indicating primer starts and ends.

Usage

```
create.primer.ranges(  
  end.position,  
  p.lens,  
  start.position,  
  step.size = 1,  
  groups = NULL  
)
```

Arguments

end.position End positions of primers.
 p.lens Desired primer lengths.
 step.size A numeric giving the steps with which start positions are cycled. Should be 1 for primer design (evaluate all positions) and higher values can be used for windowing.
 groups Character vector with group annotation.
 start.posiion The start positions of primers.

Value

Data frame with ranges for initial primers.

create.primers.naive *Naive Initialization of Primers.*

Description

Initialize primers by extracting substrings from all templates.

Usage

```
create.primers.naive(
  seqs,
  seq.IDs,
  seq.groups,
  l.s,
  e.s,
  primer.lengths,
  allowed.region.definition,
  max.degen,
  sample = "",
  identifier = "",
  updateProgress = NULL
)
```

Arguments

seqs	The template sequence strings.
seq.IDs	The identifiers of the templates.
seq.groups	The group identifiers of the templates.
l.s	The positions where the allowed region starts for each template.
e.s	The positions where the allowed region ends for each template.
primer.lengths	Vector of desired primer lengths.
allowed.region.definition	Definition of the allowed region.
max.degen	Maximum allowed degeneracy of primers.
sample	Template sample identifier.
updateProgress	Shiny progress object.

Value

Data frame with initialized primer candidates.

create.primers.tree *Tree-based Initialization of Primers.*

Description

Creates a set of candidate primers using a tree-based algorithm.

Usage

```
create.primers.tree(  
  seqs,  
  seq.IDs,  
  seq.groups,  
  start,  
  end,  
  primer.lengths,  
  allowed.region.definition,  
  max.degen,  
  conservation,  
  sample = "",  
  identifier = "",  
  updateProgress = NULL  
)
```

Arguments

seqs	Template sequences.
seq.IDs	Identifiers of template sequences.
seq.groups	Group identifiers of template sequences.
start	For each template the start of the interval where primers should be created.
end	For each template the end of the interval where primers should be created.
primer.lengths	Vector of desired primer lengths.
allowed.region.definition	Definition of allowed regions.
max.degen	Maximal degeneracy of primers.
conservation	Required conservation of template regions considered for the generation of primers. Conservation identifies the top conserved percentile of possible primers.
sample	Sample name for the analysis.
identifier	Identifier (e.g. for directionality).
updateProgress	Shiny progress object.

Details

First, primers are aligned and their sequence similarity is determined to compute a phylogenetic tree using hierarchical clustering. Next, the tree is traversed from leaves to top in order to identify groups of primers that can be merged (consensus) without exceeding the maximum degeneracy of primers.

Value

A vector with initialized primers.

<code>create.Tm.brackets</code>	<i>Creation of Melting Temperature Groups</i>
---------------------------------	---

Description

Creates a data frame identifying target melting temperatures of individual primer sets.

Usage

```
create.Tm.brackets(primers, template.df, settings, target.temps = NULL)
```

Arguments

<code>primers</code>	An object of class <code>Primers</code> for which to create groups based on melting temperatures.
<code>template.df</code>	An object of class <code>Templates</code> corresponding to the primers.
<code>settings</code>	A <code>DesignSettings</code> objects.
<code>target.temps</code>	Pre-defined target melting temperatures to use instead of automatically determining groups from the primers.

Value

Data frame with target melting temperatures for individual primer sets.

`create.uniform.leaders`*Uniform Binding Ranges.*

Description

Creates uniform binding regions for all templates.

Usage

```
create.uniform.leaders(fw.interval, rev.interval, template.df, gap.char)
```

Arguments

<code>fw.interval</code>	Binding region for forward templates.
<code>rev.interval</code>	Binding region for reverse templates.
<code>template.df</code>	Template data frame.
<code>gap.char</code>	The character for gaps in alignments.

Value

Data frame with binding region information.

`create_fulfilled_counts`*Creation of Fulfilled/Failed Constraint Counts.*

Description

Creates counts of fulfilled/failed constraints.

Usage

```
create_fulfilled_counts(primer.df, eval.cols = NULL)
```

Arguments

<code>primer.df</code>	An evaluated Primers object.
<code>eval.cols</code>	Evaluation columns in <code>primer.df</code> to consider. By default (NULL) all evaluation columns are considered.

Value

A data frame with the number of fulfilled/failed constraints for `primer.df`.

`create_report,list,list-method`*Creation of a PDF Report for Primer Comparison.*

Description

Creates a PDF report for comparing multiple primers.

Usage

```
## S4 method for signature 'list,list'
create_report(
  primers,
  templates,
  fname,
  settings,
  sample.name = NULL,
  used.settings = NULL
)
```

Arguments

<code>primers</code>	A list with evaluated Primers objects.
<code>templates</code>	A list with Templates objects.
<code>fname</code>	A character vector giving the file to store the report in.
<code>settings</code>	A DesignSettings object.
<code>sample.name</code>	An identifier for your analysis.
<code>used.settings</code>	A named list (with fields "fw" and "rev") containing the forward/reverse used design settings.

Value

Creates a PDF file giving a report on the comparison of the input primers.

Note

Creating the report requires the external programs Pandoc (<http://pandoc.org>) and LaTeX (<http://latex-project.org>).

create_report,Primers,Templates-method
Creation of a PDF report.

Description

Creates a PDF report for a set of primers.

Usage

```
## S4 method for signature 'Primers,Templates'
create_report(
  primers,
  templates,
  fname,
  settings,
  sample.name,
  used.settings,
  required.cvg = 1
)
```

Arguments

primers	An evaluated Primers object.
templates	A Templates object.
fname	A character vector giving the file to store the report in.
settings	A DesignSettings object.
sample.name	An identifier for your analysis.
used.settings	A named list (with fields "fw" and "rev") containing the forward/reverse used design settings.
required.cvg	The required coverage ratio.

Value

Creates a PDF file reporting on the input primers.

Note

Creating the report requires the external programs Pandoc (<http://pandoc.org>) and LaTeX (<http://latex-project.org>).

Data	Data Sets.
Description	
Ippolito	IGHV primer data from Ippolito et al.
Tiller	IGHV primer data from Tiller et al.
Comparison	Evaluated primer sets targeting the functional human IGH immunoglobulin genes. The sets were generated using the default evaluation settings of openPrimeR. The primer sets were gathered from IMGT and the literature.
RefCoverage	Experimental results of multiplex PCR.
Usage	
<code>data(Comparison)</code>	
<code>data(Ippolito)</code>	
<code>data(RefCoverage)</code>	
<code>data(Tiller)</code>	
Format	
For the RefCoverage data set, the <code>feature.matrix</code> data frame contains the properties of the primer set from Tiller et al. as well as a primer set that was designed by openPrimeR. The column <code>Experimental_Coverage</code> indicates the experimentally determined coverage, while the other columns relate to properties of the primers that were computed with openPrimeR. The <code>ref.data</code> list contains the raw experimental coverage of individual primers from the primer sets from Tiller and openPrimeR, which both target templates from the IGH locus. The rows of the data frames indicate primers and the columns indicate IGH templates for which experimental coverage was determined. The cell entries are hex codes. Each hex code represents a color indicating a certain experimental coverage status. Hex codes representing red shades indicate no or little amplification, while hex codes for green shades indicate high yields. For the Ippolito data set, <code>primer.df</code> provides a <code>Primers</code> object containing the evaluated set of primers from Tiller et al. <code>template.df</code> provides a <code>Templates</code> object containing functional, human IGHV templates for, and <code>settings</code> provides a <code>DesignSettings</code> object providing the used analysis settings. For the Comparison data set, <code>primer.data</code> and <code>template.data</code> are lists of <code>Primers</code> and <code>Templates</code> objects, respectively. For the Tiller data set, <code>tiller.primer.df</code> provides a <code>Primers</code> object, <code>tiller.template.df</code> provides the corresponding <code>Templates</code> object, and <code>tiller.settings</code> provides the <code>DesignSettings</code> object that was used for evaluating <code>tiller.primer.df</code>.	

References

IMGT®, the international ImMunoGeneTics information system® <http://www.imgt.org> (founder and director: Marie-Paule Lefranc, Montpellier, France).

Ippolito GC, Hoi KH, Reddy ST, Carroll SM, Ge X, Rogosch T, Zemlin M, Shultz LD, Ellington AD, VanDenBerg CL, Georgiou G. 2012. Antibody Repertoires in Humanized NOD-scid-IL2R gamma null Mice and Human B Cells Reveals Human-Like Diversification and Tolerance Check-points in the Mouse. PLoS One 7:e35497.

Tiller, Thomas, et al. "Efficient generation of monoclonal antibodies from single human B cells by single cell RT-PCR and expression vector cloning." Journal of immunological methods 329.1 (2008): 112-124.

Examples

```
# Load the comparison data
data(Comparison)
# Explore the first entry of the primer and template data:
primer.data[[1]]
template.data[[1]]
# Summarize the primer properties:
get_comparison_table(template.data, primer.data)

# Load the data from Ippolito et al.
data(Ippolito)
primer.df
template.df
constraints(settings)

# Load experimental PCR results
data(RefCoverage)

# Load the data from Tiller et al.
data(Tiller)
tiller.primer.df
tiller.template.df
constraints(tiller.settings)
```

design_primers.single *Design Primers for a Single Direction*

Description

Designs primers for a single direction.

Usage

```
design_primers.single(
  template.df,
  sample.name,
```

```

mode.directionality = c("fw", "rev"),
settings,
timeout,
opti.algo,
allowed.region.definition,
init.algo,
max.degen,
conservation,
target.temps,
required.cvg,
fw.primers = NULL,
cur.results.loc = NULL,
primer.df = NULL,
updateProgress = NULL
)

```

Arguments

template.df	Template data frame with sequences for which primers shall be designed.
sample.name	Identifier for the templates.
mode.directionality	Template strands for which primers shall be designed. Primers can be designed either only for forward strands, only for reverse strands, or both strand directions.
settings	A DesignSettings object specifying the criteria for designing primers.
timeout	Timeout in seconds for the optimization with ILPs.
opti.algo	The algorithm to be used for solving the primer set covering problem.
allowed.region.definition	Definition of the target binding sites used for evaluating the coverage. If allowed.region.definition is "within", primers have to lie within the allowed binding region. If allowed.region.definition is "any", primers have to overlap with the allowed binding region. The default is that primers have to bind within the target binding region.
init.algo	The algorithm to be used for initializing primers. If init.algo is naive, then primers are constructed from substrings of the input template sequences. If init.algo is tree, phylogenetic trees are used to form degenerate primers whose degeneracy is bounded by max.degen.
max.degen	Maximal degeneracy of merged primers.
conservation	When using the tree-based primer initialization, consider only the conservation percentile of regions with the highest conservation.
target.temps	Target melting temperatures for optimized primer sets in Celsius. Only required when optimizing primers for both strand directions and one optimization was already performed.
required.cvg	The target ratio of covered template sequences. If the target ratio cannot be reached, the constraint settings are relaxed up to the relaxation limits.

fw.primers	List with optimized primer data frames corresponding to target.temps. Only required for optimizing both strand directions and only in the second optimization run in order to check for cross dimerization.
cur.results.loc	Directory for storing results of the primer design procedure.
primer.df	A data frame of evaluated primer candidates that can be optimized directly.
updateProgress	Shiny progress callback function.

Value

A list containing the results of the primer design procedure:

opti: A Primers object representing the set of optimized primers.

all_results: A list containing the optimal results for each sampled melting temperature range in terms of a Primers object in case that the melting_temp_diff constraint was active. Otherwise, all_results only has a single entry representing a primer set relating to an undefined melting temperature.

used_constraints: A DesignSettings object with the (adjusted) analysis settings.

filtered: A Primers object containing the primer candidates that passed the filtering procedure and which gave rise to the final optimal set.

detect.gap.columns	<i>Identification of Gappy Columns in Alignments.</i>
--------------------	---

Description

Identification of Gappy Columns in Alignments.

Usage

```
detect.gap.columns(bins, gap.cutoff = 0.95, gap.char = "-")
```

Arguments

bins	A list of DNABin alignments.
gap.cutoff	The required percentage of gaps for consideration as a gap column.
gap.char	The gap character in the alignments.

Value

A list with indices giving the gap columns for every alignment in bins.

dimerization.table	<i>Dimerization Table.</i>
--------------------	----------------------------

Description

Summarizes how often individual primers dimerize according to the deltaG.cutoff.

Usage

```
dimerization.table(  
  dimer.data,  
  deltaG.cutoff,  
  dimer.type = c("Self-Dimerization", "Cross-Dimerization")  
)
```

Arguments

dimer.data	Data frame with dimerization data.
deltaG.cutoff	Free energy cutoff for dimerization.
dimer.type	String identifying whether dimer.data refers to cross-dimers or self-dimers?

Value

Data frame with dimer counts.

dir.copy	<i>Copy Directories.</i>
----------	--------------------------

Description

Copies a directory to another location.

Usage

```
dir.copy(src.dir, dest.dir, overwrite)
```

Arguments

src.dir	The directory to be copied.
dest.dir	The target directory.
overwrite	Overwrite existing files in dest.dir.

Value

TRUE if copying was successful, FALSE otherwise.

disambiguate.primers	<i>Disambiguation of Primers.</i>
----------------------	-----------------------------------

Description

Disambiguates ambiguous primer sequences into all possible sequences.

Usage

```
disambiguate.primers(p.df)
```

Arguments

p.df	Primer data frame.
------	--------------------

Value

Data frame with disambiguated primers.

estimate.cvg	<i>Estimation of Primer Coverage.</i>
--------------	---------------------------------------

Description

Estimates the possible coverage of primers using probes of size k and only considering perfect matches without consideration of ambiguities.

Usage

```
estimate.cvg(lex.df, k = 18, mode.directionality, sample = "")
```

Arguments

k	A numeric giving the size of the primers.
mode.directionality	Estimation of coverage for forward/reverse/both?
sample	An optional identifier for the sample.
seqs	A character vector of sequences to evaluate coverage for.

Value

A list with entries fw and rev giving data frames for forward/reverse binding.

estimate.cvg.dir	<i>Estimation of Primer Coverage.</i>
------------------	---------------------------------------

Description

Estimates the possible coverage of primers using probes of size k and only considering perfect matches without consideration of ambiguities.

Usage

```
estimate.cvg.dir(seqs, k, id = "")
```

Arguments

seqs	A character vector of sequences to evaluate coverage for.
k	A numeric giving the size of the primers.
id	An optional identifier for the primers.

Value

A data frame with binding information.

eval.comparison.primers	<i>Evaluation of Primers for Comparison</i>
-------------------------	---

Description

Evaluate multiple primer sets according to the input constraint settings.

Usage

```
eval.comparison.primers(primer.data, constraint.settings)
```

Arguments

primer.data	List with primer data frames.
constraint.settings	List with constraint.settings.

Value

List with evaluated primer data frames.

eval.constraints	<i>Evaluation of Constraints'</i>
------------------	-----------------------------------

Description

Evaluates whether the given primer data frame fulfills the required conditions.

Usage

```
eval.constraints(  
  constraint.df,  
  constraint.settings,  
  active.constraints,  
  mode.directionality = c("fw", "rev", "both"),  
  primer.df  
)
```

Arguments

`constraint.df` Primer data frame with computed constraints.
`constraint.settings`
List with allowed values pers constraint.
`active.constraints`
Names of constraints to be evaluated.
`mode.directionality`
Directionality of primers
`primer.df` Primer data frame corresponding to `constraint.df`.

Details

Constraint values should be contained in `constraint.df`. For each constraint in `active.constraints`, a boolean column with the name `EVAL_<constraint_name>` is generated, which indicates whether a primer in a given rows fulfills a constraint or not.

Value

Augments the `constraint.df` data frame with evaluation columns.

evaluate.basic.cvg	<i>Evaluation of Primer Coverage.</i>
--------------------	---------------------------------------

Description

Evaluates the coverage of a set of primers.

Usage

```
evaluate.basic.cvg(
  template.df,
  primers,
  mode.directionality = c("fw", "rev", "both"),
  allowed.mismatches,
  allowed.other.binding.ratio,
  allowed.region.definition = c("within", "any"),
  updateProgress = NULL
)
```

Arguments

template.df	Template data frame.
primers	Primer data frame.
mode.directionality	Primer directionality.
allowed.mismatches	The number of allowed mismatches per binding event.
allowed.other.binding.ratio	Ratio of primers that are allowed to bind to non-allowed regions. If allowed.other.binding.ratio >0 primers are allowed to bind at any location within the templates. However, a warning is given if the ratio of primers binding to non-target regions exceeds the allowed.other.binding.ratio.
allowed.region.definition	Definition of the target binding sites used for evaluating the coverage. If allowed.region.definition is within, primers have to lie within the allowed binding region. If allowed.region.definition is any, primers have to overlap with the allowed binding region. The default is that primers have to bind within the target binding region.
updateProgress	Progress callback function for shiny.

Value

Primer data frame with information on the covered template sequences.

`evaluate.constrained.cvg`*Evaluation of Primer Coverage.*

Description

Evaluates the coverage of a set of primers.

Usage

```
evaluate.constrained.cvg(  
  template.df,  
  primer.df,  
  cvg.df,  
  mode.directionality = c("fw", "rev", "both"),  
  settings,  
  updateProgress = NULL  
)
```

Arguments

<code>template.df</code>	Template data frame.
<code>primer.df</code>	Primer data frame.
<code>cvg.df</code>	Data frame with basic coverage entries.
<code>mode.directionality</code>	Primer directionality.
<code>settings</code>	A DesignSettings object.
<code>updateProgress</code>	Progress callback function for shiny.

Value

Primer data frame with information on the covered template sequences.

`evaluate.cvg`*Evaluation of Coverage.*

Description

Evaluates primer coverage.

Usage

```
evaluate.cvg(
  template.seqs,
  primers,
  mode.directionality = c("fw", "rev"),
  allowed.mismatches,
  updateProgress = NULL
)
```

Arguments

template.seqs Template sequences as a DNASTringSet.
 primers Primer sequences as a DNASTringSet.
 mode.directionality Directionality of primers
 allowed.mismatches Allowed number of mismatches between a primer and a template.
 updateProgress Progress function for shiny

Value

IRanges object with primer coverage information.

evaluate.diff.primer.cvg
Evaluation of Coverage.

Description

Re-evaluates the coverage of primers under exclusion of certain templates.

Usage

```
evaluate.diff.primer.cvg(primers, excluded.seqs, template.df)
```

Arguments

primers Primer data frame.
 excluded.seqs Identifiers of templates to be excluded.
 template.df Template data frame

Details

This function requires that primers was already annotated with primer coverage before.

Value

Primer data frame with updated coverage under the exclusion of excluded.seqs.

`evaluate.fw.rev.combinations`*Evaluation of Set Combinations*

Description

Evaluates the combinations of forward and reverse primer sets.

Usage

```
evaluate.fw.rev.combinations(opti.fw, opti.rev, compatible.df, template.df)
```

Arguments

<code>opti.fw</code>	List with forward optimal primer sets.
<code>opti.rev</code>	List with reverse optimal primer sets.
<code>compatible.df</code>	Data frame containing the indices of temperature-compatible forward and reverse primers sets.
<code>template.df</code>	Template data frame for which primers were designed.
<code>opti.rev.indices</code>	Indices for accessing <code>opti.rev</code> .

Value

List with information on the combinations of forward and reverse primers as well as the combined data frames themselves.

`evaluate.GC.clamp` *GC clamp*

Description

Determines the number of consecutive G/Cs at the 3' end.

Usage

```
evaluate.GC.clamp(y)
```

Arguments

<code>y</code>	Primer sequence from 5' to 3'.
----------------	--------------------------------

Value

The length of the GC clamp.

evaluate.primer.cvg *Evaluation of Primer Coverage.*

Description

Evaluates the coverage of a set of primers.

Usage

```
evaluate.primer.cvg(  
  template.df,  
  primers,  
  mode.directionality = c("fw", "rev", "both"),  
  settings,  
  updateProgress = NULL  
)
```

Arguments

template.df	Template data frame.
primers	Primer data frame.
mode.directionality	Primer directionality.
settings	A DesignSettings object.
updateProgress	Progress callback function for shiny.

Value

Primer data frame with information on the covered template sequences.

evaluate.template.constraints
 Evaluation of Template Constraints.

Description

Evaluates the input template constraints.

Usage

```
evaluate.template.constraints(  
  constraint.values,  
  constraint.settings,  
  active.constraints,  
  mode.directionality = c("fw", "rev", "both")  
)
```


Arguments

- constraint.values
Data frame with template constraints
- constraint.settings
List specifying the allowed values for constraint evaluation.
- active.constraints
Strings specifying the constraints to check.
- mode.directionality
Direction of primers.

Value

List indicating which template constraints where fulfilled or not (TRUE/FALSE).

exclude.cols	<i>Exclusion of Columns</i>
--------------	-----------------------------

Description

Removes columns from a data frame.

Usage

exclude.cols(excl.col, template.df)

Arguments

- excl.col
Names of columns in template.df to be removed.
- template.df
Data frame for which columns in excl.col should be removed.

Value

template.df with removed columns as specified in excl.col.

`filter.by.constraints` *Filter By Constraints*

Description

Remove primers that do not fulfill the current constraints (evaluate all primers).

Usage

```
filter.by.constraints(  
  filtered.df,  
  constraint.df,  
  current.constraints,  
  active.constraints,  
  mode.directionality = c("fw", "rev", "both"),  
  template.df  
)
```

Arguments

<code>filtered.df</code>	Primer data frame.
<code>constraint.df</code>	Data frame with constraint values.
<code>current.constraints</code>	List with constraint settings.
<code>active.constraints</code>	Strings giving the names of active constraints.
<code>mode.directionality</code>	Direction of primers
<code>template.df</code>	Template data frame.

Value

A list containing the filtered primer data frame, as well as a data frame of the excluded primers and the used filtering settings.

`filter.comparison.primers`
Filter Multiple Primer Sets.

Description

Filters multiple primer sets at once.

Usage

```
filter.comparison.primers(  
  primers,  
  templates,  
  active.constraints,  
  settings,  
  updateProgress = NULL  
)
```

Arguments

primers	List with primer data frames.
templates	List with template data frames.
active.constraints	Strings giving the constraints that are to be checked.
settings	List with settings.
updateProgress	Progress callback function for shiny.

Value

A list with filtered primer data frames.

filter.primer.candidates

Filtering of Primer Candidates

Description

Filters primer candidates according to length and duplications.

Usage

```
filter.primer.candidates(primer.candidates, min.len)
```

Arguments

primer.candidates	Alignment of candidate primers.
min.len	Minimal required length of primers.

Value

Filtered alignment of candidate primers.

`filter.primer.set.opti`*Filtering of Primers*

Description

Filters a primer set during the optimization procedure.

Usage

```
filter.primer.set.opti(  
  primer.df,  
  sample,  
  template.df,  
  settings,  
  mode.directionality,  
  required.cvg,  
  results.loc,  
  target.temps  
)
```

Arguments

<code>primer.df</code>	Primer data frame.
<code>sample</code>	Name of the current template sample.
<code>template.df</code>	Template data frame.
<code>settings</code>	List with settings for the constraints to be used for filtering.
<code>mode.directionality</code>	Primer direction.
<code>required.cvg</code>	Required ratio of covered templates. If <code>required.cvg</code> is set to 0, the constraints are not relaxed.
<code>results.loc</code>	Path to a directory where the results should be written.
<code>target.temps</code>	Target melting temperature of the primers in Celsius. This argument is only required if we try to match the melting temperatures of another primer set, e.g. when first optimizing forward and then optimizing reverse primers.

Value

The filtered primer data frame with respect to `required.cvg`.

filterLimits	<i>Getter for Filtering Constraint Limits.</i>
--------------	--

Description

Gets the limits on the constraints that are used for the filtering procedure when designing primers using the Input_Constraint_Boundaries slot of the provided DesignSettings object x.

Usage

```
filterLimits(x)

## S4 method for signature 'DesignSettings'
filterLimits(x)
```

Arguments

x A DesignSettings object.

Value

Gets the list of filtering limits.

filters	<i>Getter for Filtering Constraints.</i>
---------	--

Description

Gets the constraints on the physicochemical properties that are used for the filtering procedure when designing primers using the Input_Constraints slot of the provided DesignSettings object x.

Usage

```
filters(x)

## S4 method for signature 'DesignSettings'
filters(x)
```

Arguments

x A DesignSettings object.

Value

Gets the list of filtering constraints.

<code>filter_primers.by.Tm.delta</code>
<i>Filter by Melting Temperature Difference</i>

Description

Filters primers by melting temperature differences.

Usage

```
filter_primers.by.Tm.delta(target.temp, selected.primers, max.Tm.delta)
```

Arguments

<code>target.temp</code>	Target melting temperature in Celsius.
<code>selected.primers</code>	Current candidate primer data frame.
<code>max.Tm.delta</code>	Maximum allowed difference of primer melting temperatures to target temperature.

Value

Filtered primer data frame.

<code>fix_constraint_boundaries</code>
<i>Correction of Constraint Boundaries.</i>

Description

Fixes the constraint boundaries if they are more narrow than the current settings.

Usage

```
fix_constraint_boundaries(constraints, constraint.limits, fix.limit = TRUE)
```

Arguments

<code>constraints</code>	A list with constraint settings.
<code>constraint.limits</code>	A list with constraint limits.
<code>fix.limit</code>	Whether the constraint limits should be adjusted. If FALSE, the constraint settings are adjusted.

Value

The corrected constraint limits.

format.constraints	<i>Format Constraint Names.</i>
--------------------	---------------------------------

Description

Formats constraint names for frontend output.

Usage

```
## S3 method for class 'constraints'  
format(constraints)
```

Arguments

constraints The character vector of constraints to transform.

Value

A character vector with formatted constraint names.

format.seq.ali	<i>Format mismatches</i>
----------------	--------------------------

Description

Formats a sequence for highlighting mismatches in an alignment.

Usage

```
## S3 method for class 'seq.ali'  
format(seq, pos, format.type)
```

Arguments

seq The input sequence.
pos The mismatch positions to be formatted.
format.type Vector of giving the style (bold/italics) for each pos.

Value

The input sequence with highlighted mismatch positions.

format.seqs.tex	<i>Format a Sequence for LaTeX output.</i>
-----------------	--

Description

Formats a sequence for LaTeX report output.

Usage

```
## S3 method for class 'seqs.tex'
format(seqs)
```

Arguments

seqs	Character vector of sequences.
------	--------------------------------

Value

Formatted sequences.

get.3prime.mismatch.pos	<i>Identification of 3' Mismatches.</i>
-------------------------	---

Description

Computes the lastmost position of a 3' mismatches of a primer with a template.

Usage

```
get.3prime.mismatch.pos(primers, mismatches)
```

Arguments

primers	Primer sequence strings.
mismatches	Comma-separated strings containing the primer mismatch positions.

Value

The closest position of a mismatch relative to the 3' end of the primer. Here, 1 indicates the terminal position, 2 the penultimate position, and so on. No mismatch is indicated by an infinite value.

get.analysis.mode	<i>Direction of Primers.</i>
-------------------	------------------------------

Description

Identifies the directionality of the input primers.

Usage

```
get.analysis.mode(primers)
```

Arguments

primers	A primer data frame.
---------	----------------------

Value

both if both, forward and reverse primers exist in primers. Otherwise, if either only forward primers or reverse primers exist, returns fw or rev, respectively.

get.consensus.seq	<i>Computation of Consensus.</i>
-------------------	----------------------------------

Description

Computes the consensus of the sequences in the input alignment.

Usage

```
get.consensus.seq(ali)
```

Arguments

ali	An alignment object.
-----	----------------------

Value

A consensus sequence without gap characters.

```
get.constraint.value.idx
```

Retrive Constraint Indices.

Description

Gets the index of the required constraint columns in the primer data frame.

Usage

```
get.constraint.value.idx(active.constraints, constraint.df)
```

Arguments

`active.constraints`

The names of the constraints for which to find the indices in `constraint.df`.

`constraint.df` The primer data frame where the `active.constraints` should be found.

Value

Indices of `active.constraints` in `constraint.df`.

```
get.constraint.values
```

Get the Values of a Constraint.

Description

Get the Values of a Constraint.

Usage

```
get.constraint.values(con.name, cur.candidates, mode.directionality)
```

Arguments

`con.name` The name of the constraint.

`cur.candidates` The Primers data frame where the values should be retrieved.

`mode.directionality`

The direction for which values should be retrieved.

Value

The constraint values corresponding to `con.name` for the primers `cur.candidates`.

get.coverage.matrix	<i>Coverage Matrix</i>
---------------------	------------------------

Description

Constructs a coverage matrix where rows indicate templates and columns indicate primers.

Usage

```
get.coverage.matrix(primer.df, template.df, constraints = NULL)
```

Arguments

primer.df	Primer data frame.
template.df	Template data frame.
constraints	A character vector of coverage constraints to be used as entries for the coverage matrix instead of the 0/1 encoding. At its default setting (NULL), the 0/1 encoding is used.

Details

Entry (i,j) in the matrix is equal to 1 if primer j covers template i and otherwise 0.

Value

The binary coverage matrix.

get.covered.templates	<i>Covered Templates</i>
-----------------------	--------------------------

Description

Get the indices of covered templates.

Usage

```
get.covered.templates(Tm.set, template.df)
```

Arguments

Tm.set	Primer data frame.
template.df	Template data set.

Value

Index of templates that are covered by the primers in Tm.set.

get.cross.dimers	<i>Cross dimers</i>
------------------	---------------------

Description

Computes all possible primer cross-dimers.

Usage

```
get.cross.dimers(
  primers.1,
  primers.2,
  ions,
  annealing.temp,
  check.idx = NULL,
  no.structures = FALSE,
  mode = c("symmetric", "asymmetric")
)
```

Arguments

primers.1	Input primers.
primers.2	Input primers.
ions	Sodium-equivalent ionic concentration.
annealing.temp	The PCR annealing temperature.
check.idx	indices of primers for checking cross-dimerization
no.structures	Whether to compute structures of dimers.
mode	'symmetric', if primers.1 and primers.2 carry the same information (i.e. fw-fw, rev-rev, fw-rev), 'asymmetric' else.

Value

Data frame with potential cross dimers.

get.cvg.constraint.settings	<i>Gather all Coverage Constraints.</i>
-----------------------------	---

Description

Constructor for coverage constraint settings.

Usage

```
get.cvg.constraint.settings(
  allowed.stop.codons,
  allowed.efficiency,
  disallowed.mismatch.pos,
  allowed.anneal.deltaG,
  allowed.substitutions,
  allowed.coverage.model
)
```

Arguments

`allowed.stop.codons`
Whether mismatch binding events inducing stop codons in the amino acid sequence are allowed.

`allowed.efficiency`
Min/max for primer efficiency.

`disallowed.mismatch.pos`
The positions from the 3' terminal end of primers where mismatches shall be prevented.

`allowed.anneal.deltaG`
Maximal allowed free energy of template-primer annealing.

`allowed.substitutions`
Whether mismatch binding events inducing substitutions in the amino acid sequence are allowed.

Value

List with all coverage constraint settings.

get.cvg.gain	<i>Computation of Coverage Gain.</i>
--------------	--------------------------------------

Description

Computes the coverage gain from `covered.seqs`.

Usage

```
get.cvg.gain(
  covered.seqs,
  template.df,
  missing.df,
  candidate.df,
  con.names,
  constraint.limits,
  feasible.only = FALSE
)
```

Arguments

covered.seqs	List with covered sequences.
template.df	A Templates data frame.
missing.df	A Templates data frame containing only the templates that still need to be covered.
candidate.df	A Primers data frame containing candidate primers.
con.names	The constraint to evaluate the coverage gain for upon being relaxed.
constraint.limits	A list with constraint limits.
feasible.only	Whether only feasible coverage gains are to be outtputed. Here, <i>feasible</i> relates to coverage gains that can be obtained directly with the next relaxation.

Value

The number of covered sequences to be gained.

get.delta.G	<i>Change in Free Energy.</i>
-------------	-------------------------------

Description

Computes the change in free energy.

Usage

```
get.delta.G(delta.H, delta.S, temp = 37)
```

Arguments

delta.H	Change in enthalpy in cal/mol.
delta.S	Change in entropy cal/mol*K.
temp	Temperature in Celsius for which to compute free energy change.

Value

The change in free energy in kcal/mol.

get.dimer.data	<i>Retrieval of dimerization energies.</i>
----------------	--

Description

Uses OligoArrayAux to compute dimerization candidates.

Usage

```
get.dimer.data(s1, s2, annealing.temp, ions, no.structures)
```

Arguments

s1	Nucleotide character vectors (5' to 3')
s2	Nucleotide character vectors (5' to 3')
annealing.temp	The PCR annealing temperature in Celsius.
ions	The sodium-equivalent ions used in the PCR.
no.structures	Whether to compute structures of dimers.

Value

A data frame containing free energies in the field `DeltaG` and the dimerization structure in `Structure`.

get.duplex.energies	<i>Determination of the Free Binding Energy.</i>
---------------------	--

Description

Computest the free energy of annealing between primers and templates. If the mode is set to "on_target", the free energies of binding events in the allowed region are computed, while if the mode is set to "off_target", the free energies of off-target events are computed.

Usage

```
get.duplex.energies(  
  primer.df,  
  template.df,  
  annealing.temp,  
  settings,  
  mode = c("on_target", "off_target")  
)
```

Arguments

primer.df	A Primers object.
template.df	A Templates object.
annealing.temp	The vector of optimal annealing temperatures of the primers.
settings	A DesignSettings object.
mode	If the mode is set to "on_target", the free energies of binding events in the allowed region are computed, while if the mode is set to "off_target", the free energies of off-target events are computed.

Value

A list of lists containing the numeric free energies of the annealing events for every primer.

get.eval.cols	<i>Retrieval of Evaluation Columns.</i>
---------------	---

Description

Retrieves the evaluation columns by intersecting the already evaluated constraints in primer.data as well as the constraints specified in input constraint settings.

Usage

```
get.eval.cols(primer.data, constraint.settings)
```

Arguments

primer.data	A list with Primers objects.
constraint.settings	A list with constraint settings.

Value

A character vector with EVAL-columns.

get.extension	<i>Identification of File extension.</i>
---------------	--

Description

Identifies the file extension of x.

Usage

```
get.extension(x)
```

Arguments

x	A string for a filename.
---	--------------------------

Value

The extension of x.

get.ILP.vars	<i>Retrieval of ILP Decisions</i>
--------------	-----------------------------------

Description

Retrieves ILP decision variables.

Usage

```
get.ILP.vars(ILP, original.dim = NULL)
```

Arguments

ILP	A solved ILP instance.
original.dim	Dimension of ILP before using presolve.

Details

The original dimension of the ILP is required to determine the correct decisions when presolve has been active and dimensions of the ILP might have changed.

Value

The ILP decision variables.

get.init.file.name	<i>File Name for Initialized Primers.</i>
--------------------	---

Description

Constructs a filename for initialized primers.

Usage

```
get.init.file.name(  
    cur.results.loc,  
    GROUP,  
    primer.lengths,  
    mode.directionality,  
    allowed.region.definition,  
    init.algo,  
    max.degen,  
    conservation  
)
```

Arguments

cur.results.loc	Directory where the file should be stored.
GROUP	Sample name of templates.
primer.lengths	Interval of desired primer lengths.
mode.directionality	Directionality of the primers
allowed.region.definition	Definition of the allowed region.
init.algo	Initialization algorithm identifier.
max.degen	Maximum degeneracy of primers.
conservation	Required ratio of primer conservation.

Value

A filename for the initialized primers.

`get.leader.exon.regions`*Assign Binding Regions*

Description

Augments a template data frame with individual binding regions.

Usage

```
get.leader.exon.regions(lex.seqs, uni.leaders)
```

Arguments

<code>lex.seqs</code>	Data frame with template sequences.
<code>uni.leaders</code>	Data frame with individual allowed binding regions.

Value

Template data frame with annotated binding regions.

`get.leader.exon.regions.single`*Individual Binding Annotation*

Description

Annotate individual binding regions.

Usage

```
get.leader.exon.regions.single(  
  l.seq,  
  lex.seq,  
  direction = c("fw", "rev"),  
  gap.char  
)
```

Arguments

<code>l.seq</code>	Data frame with individual binding regions.
<code>lex.seq</code>	Template data frame.
<code>direction</code>	The primer direction for which the binding info is valid.
<code>gap.char</code>	The character for gaps in alignments.

Value

Template data frame with annotated binding regions.

<code>get.matches</code>	<i>Identification of Sequence Matches.</i>
--------------------------	--

Description

Identifies matches between two strings provided by OligoArrayAux.

Usage

`get.matches(s1, s2)`

Arguments

- `s1` The aligned nucleotide sequence character vector.
- `s2` The aligned, matching substring of `s1`.

Value

A match vector (M for matches, X for mismatches).

<code>get.melting.temp.diff</code>	<i>Computation of Maximal Melting Temperature Differences.</i>
------------------------------------	--

Description

Computation of Maximal Melting Temperature Differences.

Usage

`get.melting.temp.diff(Tm.fw, Tm.rev)`

Arguments

- `Tm.fw` The melting temperatures of forward primers.
- `Tmr.rev` The melting temperatures of reverse primers.

Value

The worst-case melting temperature difference, for every primer.

get.merge.idx	<i>Indices for merging sequences</i>
---------------	--------------------------------------

Description

Identifies the indices of similar input sequences to be merged.

Usage

```
get.merge.idx(seqs, max.degeneracy)
```

Arguments

seqs	The input sequence strings.
max.degeneracy	The maximal allowed degeneracy of a merged seq.

Value

A list of lists containing the indices of seqs to be merged. For example `[[1,2,3]]` would indicate to merge primers 1, 2, and 3.

get.missing.df	<i>Uncovered Templates.</i>
----------------	-----------------------------

Description

Computes a data frame containing the templates that are not yet covered.

Usage

```
get.missing.df(  
  filtered.df,  
  template.df,  
  Tm.brackets,  
  settings,  
  mode.directionality  
)
```

Arguments

filtered.df	An object of class Primers.
template.df	An object of class Templates.

Value

A Templates data frame containing the missing templates.

get.ORFs

Identification of ORFs.

Description

Given a template data frame, identify the exon reading frames in the sequences.

Usage

```
get.ORFs(template.df)
```

Arguments

template.df template data frame.

Value

Returns a data frame containing the shift of the ORF (either 0,1, or 2) for every sequence, as well as a comment in case of problems.

get.other.constraint.settings

Gather all Other Constraints (for Shiny frontend).

Description

Constructor for other constraint settings (non-PCR, non-filtering, non-optimization).

Usage

```
get.other.constraint.settings(
  allowed_mismatches,
  allowed_other_binding_ratio,
  allowed_region_definition
)
```

Arguments

allowed_mismatches
 Allowed mismatches for primers binding events.

allowed_other_binding_ratio
 Ratio of primers allowed to bind to non-target regions.

allowed_region_definition
 The definition of the allowed region.

Value

List with all other constraint settings.

get.PCR.settings	<i>Gather all PCR settings.</i>
------------------	---------------------------------

Description

Gathers all PCR settings (e.g. for XML output).

Usage

```
get.PCR.settings(  
  use_taq_polymerase,  
  annealing_temp,  
  Na_concentration,  
  Mg_concentration,  
  K_concentration,  
  Tris_concentration,  
  primer_concentration,  
  template_concentration,  
  nbr_cycles  
)
```

Arguments

annealing_temp	Annealing temperature in Celsius.
Na_concentration	Sodium ion concentration.
Mg_concentration	Magensium ion concentration.
K_concentration	Potassium ion concentration.
Tris_concentration	Tris buffer concentration.
primer_concentration	Primer concentration.
template_concentration	Template concentration.

Value

List with all PCR settings.

get.plot.height	<i>Plot Extent</i>
-----------------	--------------------

Description

Returns the extent of a plot.

Usage

```
get.plot.height(N, px.per.n = 50, min.size = 300, max.size = 1500000)
```

Arguments

N	Number of observations to plot.
px.per.n	Pixels required per observations.
min.size	Minimal extent of plot in pixels.
max.size	Maximal extent of plot in pixels.

Value

The extent of the plot.

get.primer.binding.idx	<i>Retrieval of Allowed Binding Indices.</i>
------------------------	--

Description

Retrieves the indices of allowed binding events in binding for the primer with index x and type primer.type.

Usage

```
get.primer.binding.idx(
  binding,
  primer.type = c("fw", "rev", "both"),
  x,
  allowed.other.binding.ratio
)
```

Arguments

binding	IRanges binding information.
primer.type	Direction of primer.
x	Index of primer in the primer data frame.
allowed.other.binding.ratio	The ratio of allowed off-target binding events.

Value

Indices in binding for primer with index codex that are allowed.

<code>get.primer.identifier.string</code>
<i>Primer Identifier Creation.</i>

Description

Creates identifiers for generated primers.

Usage

```
get.primer.identifier.string(  
  sample,  
  seq.IDs,  
  seq.identifier,  
  all.starts,  
  all.ends,  
  identifier,  
  seq.primers  
)
```

Arguments

<code>sample</code>	Sample name of the templates.
<code>seq.IDs</code>	Identifiers of the templates.
<code>all.starts</code>	Primer positions (start).
<code>all.ends</code>	Primer positions (end).
<code>identifier</code>	Direction keyword.
<code>seq.primers</code>	The primer sequences as strings.
<code>seq.identifiers</code>	The index of the seq.

Value

Identifiers for each primer.

get.redundant.cols *Identification of Redudant Primers.*

Description

Identifies primers that are redundant.

Usage

```
get.redundant.cols(cvg.matrix)
```

Arguments

cvg.matrix Binary matrix of coverage events.

Details

Redundant primers do not reduce the coverage when removed.

Value

TRUE for redundant primers, FALSE otherwise.

get.relative.binding.pos
 Retrieval of Relative Binding Positions.

Description

Retrieves primer binding position relative to allowed regions of either forward or reverse primers, as specified by direction.

Usage

```
get.relative.binding.pos(allowed, primer.pos, direction, covered.seqs.idx)
```

Arguments

allowed Positions where binding is allowed in the templates.
 primer.pos Binding position of primer (absolute).
 direction Direction (either fw/rev).
 covered.seqs.idx Indices of covered templates.

Value

Numeric of relative binding position to allowed region.

get.run.names	<i>Getter for Run Names.</i>
---------------	------------------------------

Description

Retrieves the run names of the input data.

Usage

```
get.run.names(primer.data)
```

Arguments

primer.data A list with Primers or Templates.

Value

A vector with identifiers for every set.

get.self.dimers	<i>Self dimerization</i>
-----------------	--------------------------

Description

Computes possible self-dimers.

Usage

```
get.self.dimers(  
  primers.1,  
  primers.2,  
  ions,  
  annealing.temp,  
  no.structures = FALSE  
)
```

Arguments

primers.1	Input primers
primers.2	(Copy/reverse) of the input primers
ions	Sodium-equivalent ionic concentration.
annealing.temp	The annealing temperature.
no.structures	Whether the dimerization structure shall be computed.

Value

Possible self-dimer conformations.

`get.sets.from.decisions`*Optimal Sets from Decision Variables*

Description

Determines primer sets from decision variables from ILP.

Usage

```
get.sets.from.decisions(ILP.df, Tm.sets)
```

Arguments

ILP.df	Data frame with ILP optimization results.
Tm.sets	List with primer data frames for every target melting temperature.

Value

A list with optimal primer data sets for every target temperature.

`get.static.tool.info` *Retrieval of Tool Information.*

Description

Constructs a data frame containing information about the tools.

Usage

```
get.static.tool.info()
```

Value

A data frame with information about the required tools.

get.tree.seqs	<i>Determine Tree Consensus Sequences</i>
---------------	---

Description

Creates all possible consensus sequences from a phylogenetic tree.

Usage

```
get.tree.seqs(tree, max.degen, primer.candidates)
```

Arguments

tree	The phylogenetic tree.
max.degen	The maximal degeneration of consensus primers.
primer.candidates	Alignment of primers.

Details

Ambiguous sequences are only generated with a degeneracy of at most max.degen. The tree is iterated from leaves to the top, i.e., starting from least degeneracy to most degeneracy. Merges only take place when the degeneracy of the resulting sequence would be at most max.degen. Gaps are removed from the alignments.

Value

Data frame with consensus primers extracted from the tree.

get.unlist.idx	<i>Index for Unlisting.</i>
----------------	-----------------------------

Description

Determines indices for unlisting.

Usage

```
get.unlist.idx(primer.start, primer.data.idx)
```

Arguments

primer.start	Numeric vector.
primer.data.idx	Selection indices.

Value

Indices.

<code>get_constraint_deviation_data</code>
<i>Retrieve data for Constraint Deviations.</i>

Description

Retrieve data for Constraint Deviations.

Usage

```
get_constraint_deviation_data(constraint.df, constraint.settings)
```

Arguments

- `constraint.df` An evaluated object of class Primers.
- `constraint.settings`
 A list with settings for the constraints that are to be evaluated.

Value

A data frame providing primer-specific information on deviations of primer properties from the desired properties.

<code>get_covered.vanilla</code>	<i>Determination of the Covered Sequences.</i>
----------------------------------	--

Description

Determines the covered template sequences given by `template.df` that are covered by the primers given by `primers`.

Usage

```
get_covered.vanilla(primers, template.df, mode.directionality = NULL)
```

Arguments

- `primers` A Primers object containing the primers for which the coverage should be evaluated.
- `template.df` A Templates object containing the template sequences corresponding to primers.
- `mode.directionality`
 If `mode.directionality` is provided, the coverage of templates is computed for a specific direction of primers. Either "fw" (forward coverage only), "rev" (reverse coverage only), or "both" for both directions. If `mode.directionality` is not provided the direction is determined by the input primers.

Details

The manner in which the coverage ratio is evaluated depends on the directionality of the input primers. If either only forward or reverse primers are inputted, the individual coverage of each primer is used to determine the overall coverage. If, however, forward and reverse primers are inputted at the same time, the coverage is defined by the intersection of binding events from both, forward and reverse primers.

Value

The IDs of all covered templates.

get_cvg_stats,list-method
<i>Coverage Statistics for Multiple Primer Sets.</i>

Description

Retrieve statistics on covered templates for multiple primer sets.

Usage

```
## S4 method for signature 'list'
get_cvg_stats(
  primers,
  templates,
  for.viewing = FALSE,
  total.percentages = FALSE,
  allowed.mismatches = Inf,
  cvg.definition = c("constrained", "basic")
)
```

Arguments

primers	A list with objects of class Primers containing primers with evaluated coverage.
templates	A list with objects of class Templates containing templates with evaluated coverage.
for.viewing	Whether the table should be formatted for viewing rather than processing.
total.percentages	Whether group coverage percentages should relate to all template sequences or just those templates belonging to a specific group.
allowed.mismatches	The maximal allowed number of mismatches. By default, the number of mismatches is not restricted.
cvg.definition	If cvg.definition is set to "constrained", the statistics for the expected coverage (after applying the coverage constraints) are retrieved. If cvg.definition is set to "basic", the coverage is determined solely by string matching (i.e. without applying the coverage constraints). By default, cvg.definition is set to "constrained".

Value

Data frame with coverage statistics.

get_cvg_stats,Primers-method
<i>Coverage Statistics of a Primer Set.</i>

Description

Retrieve statistics on the templates that are covered by a primer set.

Usage

```
## S4 method for signature 'Primers'
get_cvg_stats(
  primers,
  templates,
  for.viewing = FALSE,
  total.percentages = FALSE,
  allowed.mismatches = Inf,
  cvg.definition = c("constrained", "basic")
)
```

Arguments

- for.viewing Whether the table should be formatted for viewing rather than processing.
- total.percentages Whether group coverage percentages should relate to all template sequences or just those templates belonging to a specific group.
- allowed.mismatches The maximal allowed number of mismatches. By default, the number of mismatches is not restricted.
- cvg.definition If cvg.definition is set to "constrained", the statistics for the expected coverage (after applying the coverage constraints) are retrieved. If cvg.definition is set to "basic", the coverage is determined solely by string matching (i.e. without applying the coverage constraints). By default, cvg.definition is set to "constrained".
- primer.df An object of class Primers containing primers with evaluated coverage.
- template.df An object of class Templates containing templates with evaluated coverage.

Value

Data frame with coverage statistics.

get_max_set_coverage *Determination of Maximal Coverage.*

Description

Determines the maximal coverage ratio of a set of primers for primer subsets valid for a certain temperature range. a certain melting temperature range.

Usage

```
get_max_set_coverage(  
  primer.df,  
  template.df,  
  Tm.brackets,  
  settings,  
  mode.directionality,  
  max.only = TRUE  
)
```

Arguments

primer.df	An object of class Primers.
template.df	An object of class Templates.
Tm.brackets	A data frame with temperature information.
settings	A DesignSettings object.
mode.directionality	The direction of the primers.
max.only	Whether only the maximum coverage shall be returned. If max.only is FALSE, the coverage ratios of all melting temperature sets according to Tm.brackets are returned.

Value

The maximal coverage ratio of a primer set if max.only is TRUE or the coverages of all melting temperature sets if max.only is FALSE.

get_plot_primer_data *Data for Primer Plot.*

Description

Constructs a data frame containing information about primer binding events.

Usage

```
get_plot_primer_data(  
  primer.df,  
  template.df,  
  identifier = NULL,  
  relation = c("fw", "rev")  
)
```

Arguments

- `primer.df` An object of class `Primers` containing primers with evaluated primer coverage.
- `template.df` An object of class `Templates` with template sequences corresponding to `primer.df`.
- `identifier` Identifiers of primers that are to be considered. If `identifier` is set to `NULL` (the default), all primers are considered.
- `relation` Compute binding positions relative to forward (`fw`) or reverse (`rev`) binding regions. The default is `"fw"`.

Value

Data frame with primer binding data.

<code>get_primer_cvg_mm_plot_df</code>
<i>Data for Mismatch Primer Coverage Plot.</i>

Description

Ensures that there's an entry for every possible mismatch setting.

Usage

```
get_primer_cvg_mm_plot_df(primer.df, template.df)
```

Arguments

- `primer.df` A `Primers` object.
- `template.df` A `Templates` object.

Value

A data frame for plotting mismatch primer coverage.

`get_report_fname`*Creation of a Filename for Reports.*

Description

Creates the filename for reports.

Usage

```
get_report_fname(report.name, sample.name)
```

Arguments

<code>report.name</code>	The identifier for the report type.
<code>sample.name</code>	The identifier of the sample that was analyzed.

Value

A character vector.

`get_template_cvg_data`*Retrieval of Template Coverage Data.*

Description

Determines the coverage of the templates for individual allowed mismatch settings and coverage definitions.

Usage

```
get_template_cvg_data(primer.df, template.df)
```

Arguments

<code>primer.df</code>	A Primers object.
<code>template.df</code>	A Templates object.

Value

Computes a data frame providing the coverage of the templates for the basic as well as expected (constrained) coverage.

hclust.tree	<i>Hierarchical Clustering.</i>
-------------	---------------------------------

Description

Performs hierarchical clustering on aligned primer sequences.

Usage

```
hclust.tree(primer.candidates)
```

Arguments

primer.candidates
Alignment of primer candidates.

Details

The clustering is performed to identify similar groups of primer candidates that can be merged to form degenerate primers.

Value

Phylogeny of the input primer.candidates.

highlight.mismatch	<i>Highlight mismatches</i>
--------------------	-----------------------------

Description

Collects information on the mutations present in the input and highlights the mutations in the sequence.

Usage

```
highlight.mismatch(seq, mm.seq)
```

Arguments

seq character vector of the original sequence
mm.seq character vector of the mutated sequence

Value

A list highlighting the mutations and additional information (mutation type, number, etc.)

html.format.structure *Formats a Dimerization Structure for HTML.*

Description

Formats a Dimerization Structure for HTML.

Usage

```
html.format.structure(structures)
```

Arguments

structures A character vector of dimerization structures.

Value

HTML-formatted character vectors.

I.cvg *Primer Coverage.*

Description

Determines the indices of covered templates for every primer.

Usage

```
I.cvg(cvg.matrix)
```

Arguments

cvg.matrix Binary matrix of covering events.

Value

A list with covered templates for every primer.

ILPConstrained	<i>Construct Coverage ILP.</i>
----------------	--------------------------------

Description

Constructs an ILP modeling the primer set cover problem.

Usage

```
ILPConstrained(D, cvg.matrix, time.limit = NULL, presolve.active = FALSE)
```

Arguments

- D Binary dimerization matrix.
- cvg.matrix Binary coverage matrix.
- time.limit Time limit for ILP optimization in seconds.
- presolve.active Whether the ILP presolver should be used. This is set to FALSE by default, since presolving may lead to inferior solutions. However, for large problems presolving might be useful.

Value

An instance of the set cover ILP.

initialize.primers.set	<i>Creation of Initial Primers</i>
------------------------	------------------------------------

Description

Creates a set of candidate primers.

Usage

```
initialize.primers.set(  
  template.df,  
  sample.name,  
  primer.lengths,  
  allowed.region.definition,  
  mode.directionality,  
  init.algo,  
  max.degen,  
  conservation,  
  cur.results.loc  
)
```

Arguments

<code>template.df</code>	Template data frame.
<code>sample.name</code>	Name of the template sample.
<code>primer.lengths</code>	Interval of minimal and maximal desired primer length.
<code>allowed.region.definition</code>	Definition of the allowed binding region.
<code>mode.directionality</code>	Direction of primers to be created.
<code>init.algo</code>	Algorithm for initializing primers.
<code>max.degen</code>	Maximal allowed degeneration of created primers.
<code>conservation</code>	Required conservation of primers. The value of conservation should be in the range[0,1].
<code>cur.results.loc</code>	Location for writing the primers as csv.

Value

An initial primer data frame.

Input	<i>Input Functionalities.</i>
-------	-------------------------------

Description

`read_primers` Reads one or multiple input files with primer sequences. The input can either be in FASTA or in CSV format.

`read_templates` Read one or multiple files with template sequences in FASTA or CSV format.

`read_settings` Loads primer analysis settings from an XML file.

`Templates` The `Templates` class encapsulates a data frame containing the sequences of the templates, their binding regions, as well as additional information (e.g. template coverage).

`Primers` The `Primers` class encapsulates a data frame representing a set of primers. Objects of this class store all properties associated with a set of primers, for example the results from evaluating the properties of a primer set or from determining its coverage.

Usage

```
Templates(...)
```

```
read_templates(
  fname,
  hdr.structure = NULL,
  delim = NULL,
  id.column = NULL,
```

```

    rm.keywords = NULL,
    remove.duplicates = FALSE,
    fw.region = c(1, 30),
    rev.region = c(1, 30),
    gap.char = "-",
    run = NULL
)

Primers(...)

read_primers(
  fname,
  fw.id = "_fw",
  rev.id = "_rev",
  merge.ambig = c("none", "merge", "unmerge"),
  max.degen = 16,
  template.df = NULL,
  adapter.action = c("warn", "rm"),
  sample.name = NULL,
  updateProgress = NULL
)

read_settings(
  filename = list.files(system.file("extdata", "settings", package = "openPrimeR"),
    pattern = "*.xml", full.names = TRUE),
  frontend = FALSE
)

```

Arguments

<code>...</code>	A data frame fulfilling the structural requirements for initializing a <code>Templates</code> or <code>Primers</code> object.
<code>fname</code>	Character vector providing either a single or multiple paths to FASTA or CSV files.
<code>hdr.structure</code>	A character vector describing the information contained in the FASTA headers. In case that the headers of <code>fasta.file</code> contain template group information, please include the keyword "GROUP" in <code>hdr.structure</code> . If the number of elements provided via <code>hdr.structure</code> is shorter than the actual header structure, the missing fields are ignored.
<code>delim</code>	Delimiter for the information in the FASTA headers.
<code>id.column</code>	Field in the header to be used as the identifier of individual template sequences.
<code>rm.keywords</code>	A vector of keywords that are used to remove templates whose headers contain any of the keywords.
<code>remove.duplicates</code>	Whether duplicate sequence shall be removed.
<code>fw.region</code>	The positional interval from the template 5' end specifying the binding sites for forward primers. The default <code>fw.region</code> is set to the first 30 bases of the templates.

<code>rev.region</code>	The positional interval from the template 3' end specifying the binding sites for reverse primers. The default <code>rev.region</code> is set to the last 30 bases of the templates.
<code>gap.char</code>	The character in the input file representing gaps. Gaps are automatically removed upon input and the default character is "-".
<code>run</code>	An identifier for the set of template sequences. By default, <code>run</code> is NULL and its value is set via <code>template.file</code> .
<code>fw.id</code>	For FASTA input, the identifier for forward primers in the FASTA headers.
<code>rev.id</code>	For FASTA input, the identifier for reverse primers in the FASTA headers.
<code>merge.ambig</code>	Indicates whether similar primers should be merged ("merge") using IUPAC ambiguity codes or whether primers should be disambiguated ("unmerge"). By default <code>merge.ambig</code> is set to "none", leaving primers as they are.
<code>max.degen</code>	A scalar numeric providing the maximum allowed degeneracy for merging primers if <code>merge.ambig</code> is set to "merge". Degeneracy is defined by the number of disambiguated sequences that are represented by a degenerate primer.
<code>template.df</code>	An object of class <code>Templates</code> . If <code>template.df</code> is provided for <code>read_primers</code> then the primers are checked for restriction sites upon input; otherwise they are not checked.
<code>adapter.action</code>	The action to be performed when <code>template.df</code> is provided for identifying adapter sequences. Either "warn" to issue warning about adapter sequences or "rm" to remove identified adapter sequences. The default is "warn".
<code>sample.name</code>	An identifier for the input primers.
<code>updateProgress</code>	A Shiny progress callback function. This is NULL by default such that no progress is tracked.
<code>filename</code>	Path to a valid XML file containing the primer analysis settings. By default, <code>filename</code> is set to all settings that are shipped with <code>openPrimeR</code> and the lexicographically first file is loaded.
<code>frontend</code>	Indicates whether settings shall be loaded for the Shiny frontend. In this case no unit conversions for the PCR settings are performed. The default setting is FALSE such that the correct units are used.

Details

In the following you can find a description of the most important columns that can be found in an object of class `Templates`. Note that angle brackets in the column names indicate the existence of multiple possibilities.

ID The identifiers of the templates.

Identifier The internal identifiers of the templates.

Group The identifiers of the groups that the templates belong to.

Allowed_Start_<fw|rev> The start of the interval in the templates where binding is allowed for forward and reverse primers, respectively.

Allowed_End_<fw|rev> The end of the interval in the templates where binding is allowed for forward and reverse primers, respectively.

`Allowed_<fw|rev>` The template sequence where binding is allowed for forward and reverse primers, respectively.

`Run` An identifier for the set of template sequences.

`Covered_By_Primers` The identifiers of primers covering the templates, when the template coverage has been annotated.

`primer_coverage` The number of primers covering the templates, when the template coverage has been annotated.

When loading a FASTA file with `read_templates`, the input arguments `hdr.structure`, `delim`, `id.column`, `rm.keywords`, `remove.duplicates`, `fw.region`, `rev.region`, `gap.character`, and `run` are utilized. Most importantly, `hdr.structure` and `delim` should match the FASTA header structure. To learn more about setting the primer binding regions, consider the [assign_binding_regions](#) function. In contrast, when a CSV file is loaded with `read_templates`, the data are loaded without performing any modifications because the CSV file should represent an object of class `Templates`, which can be stored using the [write_templates](#) function.

When loading primers via `read_primers`, the input arguments `fw.id`, `rev.id`, `merge.ambig`, and `max.degen` are only used for loading primers from a FASTA file. In this case, please ensure that `fw.id` and `rev.id` are set according to the keywords indicating the primer directionalities in the FASTA file. When loading primers from a CSV file, the format of the file should adhere to the structure defined by the `Primers` class.

When loading a settings file with `read_settings`, if `filename` is not provided, a default XML settings file is loaded. Please review the function's examples to learn more about the default settings. If you want to load custom settings, you can store a modified `DesignSettings` object as an XML file using [write_settings](#).

Value

The `Templates` constructor returns a `Templates` object, an instance of a data frame.

`read_templates` returns a single object of class `Templates` if a single filename was provided or a list of such objects if multiple file names were provided.

The `Primers` constructor returns an object of class `Primers`.

`read_primers` returns a single object of class `Primers` if a single input file is provided or a list of such objects if multiple files are provided.

`read_settings` returns an object of class `DesignSettings`.

Basic columns

In the following you can find a description of the most important columns that can be found in objects of class `Primers`. Note that angular brackets indicate the existence of multiple possibilities. The following columns are present when a set of primers is loaded from a FASTA file using [read_primers](#):

`ID` The identifiers of the primers.

`Identifier` The internal identifiers of the primers.

`Forward` The sequences of forward primers.

`Reverse` The sequences of reverse primers.

`primer_length<fw|rev>` The lengths of forward and reverse primer sequences, respectively.
`Direction` Either 'fw' for forward primers, 'rev' for reverse primers, or 'both' for a primer pair.
`Degeneracy_<fw|rev>` The degeneracy (ambiguity) of forward and reverse primers, respectively.
`Run` An identifier describing the primer set.

Coverage-related columns

The following columns are only available in an object of class `Primers` after primer coverage has been computed, that is after `check_constraints` has been called with the active `primer_coverage` constraint. Computed coverage values relating solely to string matching are indicated by the prefix `Basic_`, while columns without this prefix relate to the coverage after applying the constraints formulated via `CoverageConstraints`. Information on off-target coverage events are indicated by the `Off_` prefix, while on-target coverage events do not carry this prefix.

`primer_coverage` The number of templates that are covered by the primers. Note that if a primer set contains primers of both directions, a template is only considered covered if it is covered by primers of both directions.

`Coverage_Ratio` The ratio of templates that are covered by the primers.

`Binding_Position_Start_<fw|rev>` The upstream position in the templates where forward and reverse primers respectively bind.

`Binding_Position_End_<fw|rev>` The downstream position in the templates where forward and reverse primers respectively bind.

`Relative_<Forward|Reverse>_Binding_Position_<Start|End>_<fw|rev>` The binding upstream (Start) or downstream (End) positions of the primers relative to the forward (Forward) or reverse (Reverse) binding regions, either for forward (fw) or reverse primers (rev).

`Binding_Region_Allowed` Whether a coverage event occurred in the target binding region or not. If the allowed off-target ratio was set to 0 only coverage events within the the target region are reported.

`Nbr_of_mismatches_<fw|rev>` The number of mismatches of forward and reverse primer coverage events, respectively.

`Mismatch_pos_<fw|rev>` The position of mismatches for forward and reverse coverage events, respectively. Mismatch positions are reported relative to the 3' end, that is, position 1 indicates a mismatch in the last base of a primer.

`primer_specificity` The specificity of a primer as determined by its ratio of off-target binding events.

Constraint-related columns

Each constraint that is considered when calling `check_constraints` gives rise to at least one column in the provided `Primers` object. Due to the large number of possible constraints, we will limit our description to the `gc_clamp` constraint. Once the GC clamp property has been computed, the `gc_clamp_fw` column contains the length of the GC clamp for forward primers and `gc_clamp_rev` the corresponding length for reverse primers. Whether the desired extent of the GC clamp was obtained by a primer is indicated by the `EVAL_gc_clamp` column. It contains `TRUE` when the GC clamp constraint was fulfilled and `FALSE` when it was broken. To identify whether all required constraints were fulfilled by a primer, the `constraints_passed` column can be used. It contains `TRUE` if all active constraints used by `check_constraints` were fulfilled and `FALSE` otherwise.

Examples

```
# Load a set of templates:
fasta.file <- system.file("extdata", "IMGT_data", "templates",
  "Homo_sapiens_IGH_functional_exon.fasta", package = "openPrimerR")
hdr.structure <- c("ACCESSION", "GROUP", "SPECIES", "FUNCTION")
template.df <- read_templates(fasta.file, hdr.structure, "|", "GROUP")
# Load templates from a FASTA file
fasta.file <- system.file("extdata", "IMGT_data", "templates",
  "Homo_sapiens_IGH_functional_exon.fasta", package = "openPrimerR")
hdr.structure <- c("ACCESSION", "GROUP", "SPECIES", "FUNCTION")
template.df.fasta <- read_templates(fasta.file, hdr.structure, "|", "GROUP")
# Load multiple FASTA files
fasta.files <- c(fasta.file, fasta.file)
template.df.fastas <- read_templates(fasta.files, hdr.structure, "|", "GROUP")
# Load templates from a previously stored CSV file
csv.file <- system.file("extdata", "IMGT_data", "comparison",
  "templates", "IGH_templates.csv", package = "openPrimerR")
template.df.csv <- read_templates(csv.file)
# Load multiple CSV files:
csv.files <- c(csv.file, csv.file)
template.df.csvs <- read_templates(csv.files)
# Load a mixture of FASTA/CSV files:
mixed.files <- c(csv.file, fasta.file)
template.data <- read_templates(mixed.files)

# Load a set of primers
primer.location <- system.file("extdata", "IMGT_data", "primers", "IGHV",
  "Ippolito2012.fasta", package = "openPrimerR")
primer.df <- read_primers(primer.location, "_fw", "_rev")

primer.fasta <- system.file("extdata", "IMGT_data", "primers", "IGHV",
  "Ippolito2012.fasta", package = "openPrimerR")
primer.df <- read_primers(primer.fasta, "_fw", "_rev")
# Read multiple FASTA files
fasta.files <- list.files(system.file("extdata", "IMGT_data", "primers",
  "IGHV", package = "openPrimerR"), pattern = "*\\*.fasta",
  full.names = TRUE)[1:3]
primer.data <- read_primers(fasta.files)
# Read primers from a CSV file
primer.csv <- system.file("extdata", "IMGT_data", "comparison",
  "primer_sets", "IGL", "IGL_openPrimerR2017.csv", package = "openPrimerR")
primer.df <- read_primers(primer.csv)
# Read multiple primer CSV files
primer.files <- list.files(path = system.file("extdata", "IMGT_data", "comparison",
  "primer_sets", "IGH", package = "openPrimerR"),
  pattern = "*\\*.csv", full.names = TRUE)[1:3]
primer.data <- read_primers(primer.files)
# Read a mixture of FASTA/CSV files:
mixed.primers <- c(primer.fasta, primer.csv)
primer.data <- read_primers(mixed.primers)

# Select available settings
```

```

available.settings <- list.files(
  system.file("extdata", "settings", package = "openPrimeR"),
  pattern = "*.xml", full.names = TRUE)
# Select one of the settings and load them
filename <- available.settings[1]
settings <- read_settings(filename)

```

insert_str	<i>String Insertion.</i>
------------	--------------------------

Description

Inserts a string into another string at the specified position.

Usage

```
insert_str(target, insert, index)
```

Arguments

target	The string to be modified.
insert	The string to be inserted.
index	The position where the insertion should take place.

Value

A string where insert is inserted into target at position index.

interleave	<i>Interleave strings Combines the input vectors in an interleaved fashion.</i>
------------	---

Description

Interleave strings Combines the input vectors in an interleaved fashion.

Usage

```
interleave(v1, v2)
```

Arguments

v1	Input string.
v2	Input string.

Value

The interleaved combination of v1 and v2.

`J.cvg`*Template Coverage.*

Description

Determines the indices of covering primers for every template.

Usage

```
J.cvg(cvg.matrix)
```

Arguments

`cvg.matrix` Binary matrix of covering events.

Value

A list with covering primers for every template.

`joule.to.cal`*Conversion from J to cal*

Description

Converts the input from Joule to calories.

Usage

```
joule.to.cal(val.J)
```

Arguments

`val.J` Numeric Joule value.

Value

The value corresponding to `val.J` in calories.

listToXml	<i>List to XML</i>
-----------	--------------------

Description

Convert List to XML.

Usage

```
listToXml(item, tag)
```

Arguments

item	
tag	xml tag

Details

Can convert list or other object to an xml object using xmlNode.

Value

xmlNode

Author(s)

David LeBauer, Carl Davidson, Rob Kooper

merge.ambig.primers	<i>Merge similar primers</i>
---------------------	------------------------------

Description

Merges similar primers contained in the input primer data frame.

Usage

```
## S3 method for class 'ambig.primers'  
merge(primer.df, mode.directionality = c("fw", "rev", "both"), max.degeneracy)
```

Arguments

primer.df	Primer data frame.
mode.directionality	Analysis direction.
max.degeneracy	Maximal degeneracy of merged primers.

Value

A primer data frame where similar primers are merged into one entry.

merge.binding.information
<i>Merge of Forward/Reverse Binding Information.</i>

Description

Determines binding events of individual and pairs of primers.

Usage

```
## S3 method for class 'binding.information'
merge(
  primers,
  fw.binding.filtered,
  rev.binding.filtered,
  mode.directionality = c("fw", "rev", "both"),
  idx.fw,
  idx.rev
)
```

Arguments

primers	The primer data frame.
mode.directionality	Primer directionality.
idx.fw	Index of fw primers.
idx.rev	Index of rev primers.
fw.binding	IRanges object with binding events of fw primers.
rev.binding	IRanges object with binding events of rev primers.

Value

IRanges with correct binding events.

merge.primer.entries *Merge similar primers*

Description

Merges the entries of similar entries in the input primer data frame, given a list with merge indices.

Usage

```
## S3 method for class 'primer.entries'  
merge(opti.result, merge.idx, mode.directionality = c("fw", "rev", "both"))
```

Arguments

opti.result Input primer data frame.
merge.idx List of lists with merge indices (get.merge.idx).
mode.directionality
 Direction of primers.

Value

A primer data frame where entries of similar primers are merged.

merge.primer.entries.single
 Merge input sequences

Description

Merges the input sequences given a list with merge indices.

Usage

```
## S3 method for class 'primer.entries.single'  
merge(seqs, merge.idx)
```

Arguments

seqs The input sequences.
merge.idx List of list with merge indices.

Value

Merged input sequences according to the input merge indices.

merge.select	Select merge indices
--------------	----------------------

Description

Greedly identifies the smallest number of possible sequences merges that can be performed.

Usage

```
## S3 method for class 'select'  
merge(merge.idx)
```

Arguments

merge.idx list of lists containing the indices of possible merges

Value

The smallest number of possible merge operations as an index list.

merge.template.decisions	Merge Template Decisions.
--------------------------	---------------------------

Description

Merges the results for multiple template evaluations.

Usage

```
## S3 method for class 'template.decisions'  
merge(eval.t)
```

Arguments

eval.t List with evaluated template constraints

Value

List with merged boolean decisions.

mismatch.info	<i>Information about Mismatches.</i>
---------------	--------------------------------------

Description

Computes information about mismatch binding events.

Usage

```
mismatch.info(primer, seqs)
```

Arguments

primer	Primer character vector.
seqs	Template binding sequences of primers as a XStringsView object.

Value

List with positions and number of mismatches of the primer in the seqs. The list contains the field `mm.pos` containing a list with the positions of the mismatches and the field `Nbr` containing a numeric vector with the number of mismatches per template binding event.

mismatch.mutation.check	<i>Identification of Mutations Induced by Mismatch Binding Events.</i>
-------------------------	--

Description

Identifies whether mutations are induced by mismatch binding events.

Usage

```
mismatch.mutation.check(  
  primer.df,  
  template.df,  
  mutation.types = c("stop_codon", "substitution")  
)
```

Arguments

primer.df	A Primers object.
template.df	A Template object.
mutation.types	Character vector of the mutation types to be checked for.

Details

Checks for one primer and all covered templates whether any templates are bound with mismatches such that mismatches are induced. A numeric vector indicating which binding events induce a forbidden mismatch according to `mutation.types` is returned such that 1 indicates forbidden events and 0 allowed events.

Value

A list containing data frames where an entry of 1 is present if the `primer.seq` induces a mutation that is forbidden according to the provided `mutation.types`, otherwise 0.

<code>mismatch.string.to.list</code>	<i>Conversion of Mismatch Postions String to List.</i>
--------------------------------------	--

Description

Conversion of Mismatch Postions String to List.

Usage

```
mismatch.string.to.list(mismatches)
```

Arguments

<code>mismatches</code>	A character vector where parenthesis give mismatches for a template binding event.
-------------------------	--

Value

A list with the mismatches for every template for every primer.

<code>modify.col.rep</code>	<i>Modification of Column Names.</i>
-----------------------------	--------------------------------------

Description

Modifies column names for frontend output.

Usage

```
modify.col.rep(template.df, for.shiny = TRUE)
```

Arguments

template.df	The data frame whose column names are to be modified.
for.shiny	Whether formatting should be for shiny.

Value

template.df with modified column names.

my.disambiguate	<i>Disambiguation of Sequences.</i>
-----------------	-------------------------------------

Description

Disambiguates the input sequences, but does not disambiguate highly generate sequences.

Usage

```
my.disambiguate(template.seqs, gap.char = "-", degen.cutoff = 2^10)
```

Arguments

template.seqs	A DNASTringSet object with sequences to disambiguate.
gap.char	The character indicating gaps in alignments.
degen.cutoff	The maximal degeneration of sequences to be disambiguated.

Value

A DNASTringSetList object with disambiguated sequences.

my.error	<i>Custom Error</i>
----------	---------------------

Description

Creates an error with a custom class.

Usage

```
my.error(subclass, message, call = sys.call(-1), ...)
```

Arguments

subclass	String giving the specific type of error.
message	Message to be displayed to the user.
call	Environment where the error occurred.
...	Other arguments to be passed to the condition function.

Value

Generates a custom error.

<code>my.read.fasta</code>	<i>Read FASTA File.</i>
----------------------------	-------------------------

Description

Reads the input FASTA file.

Usage

```
my.read.fasta(fasta.file, NTs)
```

Arguments

<code>fasta.file</code>	The path to a FASTA file.
<code>NTs</code>	The allowed set of nucleotides.

Value

List with vectors of chars.

<code>my.warning</code>	<i>Custom Warning.</i>
-------------------------	------------------------

Description

Creates a warning with a custom class.

Usage

```
my.warning(subclass, message, call = sys.call(-1), ...)
```

Arguments

<code>subclass</code>	String giving the specific type of error.
<code>message</code>	Message to be displayed to the user.
<code>call</code>	Environment where the error occurred.
<code>...</code>	Other arguments to the condition function.

Value

Generates a custom warning.

my_ggsave	<i>Wrapper for the ggplot2::ggsave function.</i>
-----------	--

Description

Saves a plot using ggplot2's ggsave function.

Usage

```
my_ggsave(filename, plot = ggplot2::last_plot(), ...)
```

Arguments

filename	The filename to store the plot.
plot	The ggplot object.
...	Further arguments to the ggplot2 ggsave function.

Value

Stores p in fname.

my_rbind	<i>Smartbind preserving classes.</i>
----------	--------------------------------------

Description

Rbind allowing for column mismatch, retains the classes of the data frames. Motivation: smart-bind/rbind.fill only keep the data.frame class but not additional classes.

Usage

```
my_rbind(...)
```

Arguments

...	Data frames.
-----	--------------

Value

A data frame resulting from row binding of ...

nbr.of.repeats	<i>Number of Repeats</i>
----------------	--------------------------

Description

Computes the number of dinucleotide repeats in the input sequences.

Usage

nbr.of.repeats(x)

Arguments

x Input sequence strings.

Value

The maximal number of dinucleotide repeats in x.

nbr.of.runs	<i>Number of Runs</i>
-------------	-----------------------

Description

Computes the longest run of a single character in the input sequence.

Usage

nbr.of.runs(x)

Arguments

x Primer character sequences.

Value

The longest repeat of a single character in x.

opti	<i>Getter for Optimization Constraints.</i>
------	---

Description

Gets the constraints on the physicochemical properties that are applied just before the optimization procedure using the Input_Constraints slot of the provided DesignSettings object x.

Usage

```
opti(x)

## S4 method for signature 'DesignSettings'
opti(x)
```

Arguments

x A DesignSettings object.

Value

Gets the list of optimization constraints.

optiLimits	<i>Getter for Optimization Constraint Limits.</i>
------------	---

Description

Gets the limits for the constraints that are applied just before the optimization procedure using the Input_Constraint_Boundaries slot of the provided DesignSettings object x.

Usage

```
optiLimits(x)

## S4 method for signature 'DesignSettings'
optiLimits(x)
```

Arguments

x A DesignSettings object.

Value

Gets the optimization constraint limits.

optimize.ILP	<i>Solver for ILP Set Cover</i>
--------------	---------------------------------

Description

Solves the primer set cover problem using an ILP formulation.

Usage

```
optimize.ILP(
  primer.df,
  template.df,
  settings,
  primer_conc,
  template_conc,
  na_salt_conc,
  mg_salt_conc,
  k_salt_conc,
  tris_salt_conc,
  allowed.mismatches,
  allowed.other.binding.ratio,
  allowed.stop.codons,
  allowed.region.definition,
  disallowed.mismatch.pos,
  target.temps,
  required.cvg,
  fw.primers = NULL,
  diagnostic.location = NULL,
  timeout = Inf,
  updateProgress = NULL
)
```

Arguments

primer.df	Primer data frame to be optimized.
template.df	Template data frame with sequences.
settings	A DesignSettings object.
primer_conc	Primer concentration.
template_conc	Template concentration.
na_salt_conc	Sodium ion concentration.
mg_salt_conc	Magensium ion concentration.
k_salt_conc	Potassium ion concentration.
tris_salt_conc	Tris ion concentration.
allowed.mismatches	The number of mismatches primers are allowed to have with the templates.

allowed.other.binding.ratio	Ratio of primers allowed to bind to non-target regions.
allowed.stop.codons	Consider mismatch binding events that induce stop codons.
allowed.region.definition	Definition of the target binding sites used for evaluating the coverage. If allowed.region.definition is within, primers have to lie within the allowed binding region. If allowed.region.definition is any, primers have to overlap with the allowed binding region. The default is that primers have to bind within the target binding region.
disallowed.mismatch.pos	The number of positions from the primer 3' end where mismatches should not be allowed. All primers binding templates with mismatches within disallowed.mismatch.pos from the 3' end are disregarded.
target.temps	Target melting temperatures for primer sets in Celsius.
required.cvg	Target coverage ratio of the templates by the primers.
fw.primers	List with optimized primer data frames corresponding to target.temps. Only required for optimizing both strand directions and only in the second optimization run in order to check for cross dimerization.
diagnostic.location	Directory for storing results.
timeout	Timeout in seconds for the optimization with ILPs.
updateProgress	Shiny progress callback function.

Value

List with optimization results.

optimize.primer.cvg	<i>Greedy Optimization</i>
---------------------	----------------------------

Description

Greedy approach for solving the primer set coverage problem.

Usage

```
optimize.primer.cvg(
  primers,
  template.df,
  mode.directionality,
  cur.opti.constraints,
  target.temp,
  allowed.mismatches,
  opti.limits,
  primer_conc,
```

```

    na_salt_conc,
    mg_salt_conc,
    k_salt_conc,
    tris_salt_conc,
    updateProgress = NULL
  )

```

Arguments

<code>primers</code>	Primer data frame to be optimized.
<code>template.df</code>	Template data frame.
<code>mode.directionality</code>	Primer direction.
<code>cur.opti.constraints</code>	List with optimization constraint settings.
<code>target.temp</code>	Target annealing temperature of the optimized primer set in Celsius.
<code>allowed.mismatches</code>	The number of mismatches primers are allowed to have with the templates.
<code>opti.limits</code>	List with optimization limits.
<code>primer_conc</code>	Primer concentration.
<code>na_salt_conc</code>	Sodium ion concentration.
<code>mg_salt_conc</code>	Magnesium ion concentration.
<code>k_salt_conc</code>	Potassium ion concentration.
<code>tris_salt_conc</code>	Tris ion concentration.
<code>updateProgress</code>	Shiny progress callback function.
<code>template_conc</code>	Template concentration.

Value

List with optimization data.

```
optimize.template.binding.regions.dir
```

Optimization of Binding Regions

Description

Optimizes the template binding regions.

Usage

```

optimize.template.binding.regions.dir(
  template.df,
  annealing.temperature = NULL,
  primer.lengths,
  mode.directionality = c("fw", "rev", "both")
)

```

Arguments

template.df Template data frame.
annealing.temperature Temperature at which to compute secondary structures.
primer.lengths Target length of primers that are to be used.
mode.directionality Direction of primers.

Value

List with intervals indicating improved primer binding regions.

optimize.template.binding.regions.single
Optimization of Template Binding

Description

Optimizes template binding regions according to secondary structures.

Usage

```
optimize.template.binding.regions.single(  
  template.df,  
  annealing.temperature,  
  primer.lengths,  
  mode.directionality = c("fw", "rev")  
)
```

Arguments

template.df Template data frame.
annealing.temperature Temperature at which to compute secondary structures.
primer.lengths Target length of primers that are to be used.
mode.directionality Direction of primers.

Value

List with new binding intervals for every template.

Output

*Output Functionalities.***Description**

`write_primers` Writes a set of primers to disk, either as a FASTA or CSV file.

`write_settings` Stores primer analysis settings to a file in XML format.

`write_templates` Stores a set of templates as a FASTA or CSV file.

`create_report` Creates a PDF report for analyzed primer sets.

`create_coverage_xls` Creation of an XLS spreadsheet providing an overview of the covered template sequences for each primer. Each cell in the spreadsheet indicates a coverage event between a primer and template using color codes. Identified coverage events are indicated by green, while primer-template pairs without coverage are indicated by red. In case that a primer binding condition (see [CoverageConstraints](#)) was active when computing the coverage, the numeric value of the coverage condition is annotated for each cell.

Usage

```
write_templates(template.df, fname, ftype = c("FASTA", "CSV"))
```

```
write_primers(primer.df, fname, ftype = c("FASTA", "CSV"))
```

```
create_coverage_xls(primer.df, template.df, fname, settings)
```

```
create_report(
  primers,
  templates,
  fname,
  settings,
  sample.name = NULL,
  used.settings = NULL,
  ...
)
```

```
write_settings(settings, fname)
```

Arguments

<code>template.df</code>	An object of class <code>Templates</code> .
<code>fname</code>	The path to the output file.
<code>ftype</code>	A character vector giving the type of the file. This can either be "FASTA" or "CSV" (default: "FASTA").
<code>primer.df</code>	An object of class <code>Primers</code> .
<code>settings</code>	A <code>DesignSettings</code> object to be stored to disk.

<code>primers</code>	To create a report for a single primer set, please provide an evaluated <code>Primers</code> object. For creating a report comparing multiple primer sets, please provide a list of <code>Primers</code> objects.
<code>templates</code>	If <code>primers</code> is a <code>Primers</code> object, <code>templates</code> should be a <code>Templates</code> object. If <code>primers</code> is a list of <code>Primers</code> objects, <code>templates</code> should be a list of <code>Templates</code> objects of the same length as <code>primers</code> .
<code>sample.name</code>	An identifier for your analysis. By default (<code>NULL</code>), the sample identifier is selected from the <code>Run</code> column of the input templates.
<code>used.settings</code>	A named list (with fields <code>fw</code> and <code>rev</code>) containing the relaxed settings for designing forward/reverse primers. By default (<code>NULL</code>), the relaxed settings are not shown in the report.
<code>...</code>	<code>required.cvg</code> (optional, default: 1), the desired coverage ratio if <code>primers</code> is a single primer set.

Value

`write_templates` stores templates to `fname`.

`write_primers` stores primers to disk.

`create_coverage_xls` stores information on the primer coverage in a spreadsheet.

`create_report` Creates a PDF file summarizing the results from analyzing one or multiple sets of primers.

`write_settings` returns the status from closing the connection to the output file.

Note

Creating the report requires the external programs Pandoc (<http://pandoc.org>) and LaTeX (<http://latex-project.org>).

Examples

```
data(Ippolito)
# Store templates as FASTA
fname.fasta <- tempfile("my_templates", fileext = ".fasta")
write_templates(template.df, fname.fasta)
# Store templates as CSV
fname.csv <- tempfile("my_templates", fileext = ".csv")
write_templates(template.df, fname.csv, "CSV")
```

```
data(Ippolito)
# Store primers as FASTA
fname.fasta <- tempfile("my_primers", fileext = ".fasta")
write_primers(primer.df, fname.fasta)
# Store primers as CSV
fname.csv <- tempfile("my_primers", fileext = ".csv")
write_primers(primer.df, fname.csv, "CSV")
```

```
data(Ippolito)
filename <- tempfile("cvg_overview", fileext = ".xls")
```

```

# Store coverage of a single primer in an XLS file:
my.primers <- primer.df[,]
cvd <- unique(unlist(strsplit(my.primers$Covered_Seqs, split = ",")))
m <- match(cvd, template.df$Identifier)
my.templates <- template.df[m,]
create_coverage_xls(my.primers, my.templates, filename, settings)

setting.xml <- system.file("extdata", "settings",
                           "C_Taq_PCR_high_stringency.xml", package = "openPrimerR")
settings <- read_settings(setting.xml)
# Creation of a report for a single primer set
data(Ippolito)
out.file.single <- tempfile("evaluation_report", fileext = ".pdf")
create_report(primer.df, template.df, out.file.single, settings)
# Creation of a report for multiple primer sets
data(Comparison)
set.sizes <- sapply(primer.data, nrow)
sel.sets <- order(set.sizes)[1:2]
out.file.comp <- tempfile("comparison_report", fileext = ".pdf")
create_report(primer.data[sel.sets], template.data[sel.sets], out.file.comp, settings)

# Store settings to disk
xml <- system.file("extdata", "settings",
                   "C_Taq_PCR_high_stringency.xml", package = "openPrimerR")
settings <- read_settings(xml)
out.file <- tempfile("my_settings", fileext = ".xml")
write_settings(settings, out.file)

```

pair_primers

Pairing of Forward and Reverse Primers.

Description

Pairs forward and reverse primers such that coverage is maximized for every pair.

Usage

```
pair_primers(primer.df, template.df)
```

Arguments

primer.df An object of class Primers.

Value

An object of class Primers containing the paired primers.

parse.constraints	<i>Parse XML Constraint Data.</i>
-------------------	-----------------------------------

Description

Parses the constraint settings contained in an XML object.

Usage

```
parse.constraints(xml_data)
```

Arguments

xml_data	XML object from a parsed XML file.
----------	------------------------------------

Value

List with constraint settings.

parse.header	<i>Parse FASTA headers</i>
--------------	----------------------------

Description

Parses the headers of a FASTA file.

Usage

```
parse.header(hdr, delim, hdr.str, id.column)
```

Arguments

hdr	The headers (> entries) of a FASTA File.
delim	The delimiter used to separate distinct fields in the headers. For example, for headers such as > E.coli GeneX ...
hdr.str	Names of the fields appearing in the header.
id.column	Field in the header to be used used as an identifier for the sequences.

Value

Data frame with structured information from the headers.

parse.IMG.T.gene.groups

Parser for IMG.T Groups.

Description

Parses IMG.T group information contained in FASTA headers.

Usage

```
parse.IMG.T.gene.groups(IDs)
```

Arguments

IDs	Group information strings to be parsed.
-----	---

Value

Data frame with structured group information.

parse.oligo.results

Parser for OligoArrayAux Dimerization Data.

Description

Parses the free energies and structures of OligoArrayAux.

Usage

```
parse.oligo.results(deltaG.file, struct.file)
```

Arguments

deltaG.file	A path to a file with OligoArrayAux energies.
struct.file	A path to a file with OligoArrayAux structures.

Value

A data frame with structures and free energies.

plot.all.cvg.info *Plots Coverage Information*

Description

Visualizes all coverage-related data.

Usage

```
## S3 method for class 'all.cvg.info'
plot(
  sample,
  results.loc,
  primers,
  template.df,
  mode.directionality,
  identifier = c("filtering", "optimized"),
  primer_conc,
  na_salt_conc,
  mg_salt_conc,
  k_salt_conc,
  tris_salt_conc,
  settings,
  required.cvg,
  used.settings = NULL
)
```

Arguments

sample	Primer design run identifier.
results.loc	Location where the filtering results are stored.
primers	Primer data frame.
template.df	Template data frame.
mode.directionality	Design direction.
identifier	Identifies whether filtering or optimization info should be displayed.
primer_conc	Primer concentration.
na_salt_conc	Sodium ion concentration.
mg_salt_conc	Magnesium ion concentration.
k_salt_conc	Potassium ion concentration.
tris_salt_conc	Tris ion concentration.
settings	The DesignSettings object.
required.cvg	The required coverage.
used.settings	A list containing DesignSettings objects for the 'fw' and 'rev' optimization.

Value

Writes plots to files.

plot.all.filtering.stats

Plot Filtering Stats.

Description

Plots filtering statistics.

Usage

```
## S3 method for class 'all.filtering.stats'
plot(
  results.loc,
  sample,
  excluded.df,
  filtered.stats,
  stats.relax,
  template.df
)
```

Arguments

results.loc	Location where the filtering results are stored.
sample	Primer design run identifier.
excluded.df	Data frame with excluded primers.
filtered.stats	Filtering statistics data frame.
stats.relax	Filtering statistics after relaxation.
template.df	Template data frame.

Value

Write-out of filtering results.

plot.Delta.DeltaG	<i>Delta DeltaG Plot</i>
-------------------	--------------------------

Description

Plots the difference between the free energy of constrained and unconstrained foldings.

Usage

```
## S3 method for class 'Delta.DeltaG'  
plot(constrained.foldings, stratify = FALSE)
```

Arguments

constrained.foldings	
	Data frame with info from constrained foldings.
stratify	Stratify according to template groups?

Value

Plot of Delta DeltaG.

plot.dimer.dist	<i>Plot Dimer DeltaG</i>
-----------------	--------------------------

Description

Plot the distribution of dimerization free energies.

Usage

```
## S3 method for class 'dimer.dist'  
plot(dimer.data, deltaG.cutoff)
```

Arguments

dimer.data	Data frame with dimerization information.
deltaG.cutoff	Free energy cutoff for dimerization.

Value

A plot of dimerization free energies.

plot.excluded.hist *Plot of Excluded Primers*

Description

Plots histogram of excluded primers.

Usage

```
## S3 method for class 'excluded.hist'  
plot(excluded.df, filtered.stats, template.df)
```

Arguments

excluded.df Data frame with excluded primers.
filtered.stats Data frame with statistics of the filtering procedure.
template.df Template data frame.

Value

A plot of excluded primers.

plot.filtering.runtime
 Plot Filtering Runtimes

Description

Plots the runtimes of individual evaluation steps in the filtering procedure.

Usage

```
## S3 method for class 'filtering.runtime'  
plot(filtered.stats)
```

Arguments

filtered.stats Stats from filtering.

Value

A plot of the runtime for each filtering step.

plot.filtering.stats *Plot of Overall Filtering Stats.*

Description

Plots the number of primers remaining after each filtering step.

Usage

```
## S3 method for class 'filtering.stats'  
plot(stats, stats.relax = NULL)
```

Arguments

stats	Statistics on the filtering procedure
stats.relax	Statistic on the filtering procedure after relaxation.

Value

A plot for the number of primers after filtering.

plot.filtering.stats.cvg
 Plot of Filtering Stats for Coverage.

Description

Plots the remaining coverage after each filtering step.

Usage

```
## S3 method for class 'filtering.stats.cvg'  
plot(stats, stats.relax = NULL)
```

Arguments

stats	Statistics of the filtering procedure.
stats.relax	Statistic of the relaxation procedure.

Value

A plot showing the possible coverage after each filtering step.

Plots

*Plotting Functions.***Description**

- `plot_cvg_vs_set_size` Plots the coverage ratios of the input primer sets against the size of the sets.
- `plot_penalty_vs_set_size` Plots the penalties of the input primer sets against the number of primers contained in each set. The penalties are computed using `score_primers` where more information is provided on how to set alpha.
- `plot_primer_subsets` Visualizes the coverage of optimized primer subsets.
- `plot_primer` Visualizes the binding positions of every primer relative to the target binding region in the corresponding template sequences.
- `plot_template_cvg` Creates a bar plot visualizing the covered templates.
- `plot_primer_cvg` Shows which groups of templates are covered by individual primers.
- `plot_constraint` Shows the distribution of the primer properties. The current constraint settings are indicated with dashed lines.
- `plot_constraint_fulfillment` Visualizes which primers pass the constraints and which primers break the constraints
- `plot_cvg_constraints` Plots the distribution of the coverage constraint values.
- `plot_constraint_deviation` Plots the deviation of primer properties from the target ranges.
- `plot_primer_binding_regions` Visualizes the number of binding events of the primers with respect to the allowed binding regions in the templates.
- `plot_conservation` Plots the template sequence conservation (range [0,1]) according to the Shannon entropy of the sequences.

Usage

```
plot_conservation(entropy.df, alignments, template.df, gap.char = "-")

plot_primer_binding_regions(
  primers,
  templates,
  direction = c("both", "fw", "rev"),
  group = NULL,
  relation = c("fw", "rev"),
  region.names = c("Binding region", "Amplification region"),
  ...
)

plot_constraint(
  primers,
  settings,
```



```
    active.constraints = names(constraints(settings)),
    ...
)

plot_constraint_fulfillment(
  primers,
  settings,
  active.constraints = names(constraints(settings)),
  plot.p.vals = FALSE,
  ...
)

plot_cvg_constraints(
  primers,
  settings,
  active.constraints = names(cvg_constraints(settings)),
  ...
)

plot_constraint_deviation(
  primers,
  settings,
  active.constraints = names(constraints(settings)),
  ...
)

plot_cvg_vs_set_size(
  primer.data,
  template.data,
  show.labels = TRUE,
  highlight.set = NULL
)

plot_penalty_vs_set_size(
  primer.data,
  settings,
  active.constraints = names(constraints(settings)),
  alpha = 0
)

plot_primer_subsets(primer.subsets, template.df, required.cvg = 1)

plot_primer(
  primer.df,
  template.df,
  identifier = NULL,
  relation = c("fw", "rev"),
  region.names = c("Binding region", "Amplification region")
)
```

)

```
plot_template_cvg(primers, templates, per.mismatch = FALSE, ...)
```

```
plot_primer_cvg(primers, templates, per.mismatch = FALSE, ...)
```

Arguments

<code>entropy.df</code>	A data frame with entropies. Each row gives the entropies of a group of related template sequences for all columns of the alignment.
<code>alignments</code>	A list with DNABin alignment objects corresponding to the groups (rows) in the alignment.
<code>template.df</code>	An object of class <code>Templates</code> containing the template sequences.
<code>gap.char</code>	The gap char in the alignments. By default, <code>gap.char</code> is set to "-".
<code>primers</code>	Either a single <code>Primers</code> object with evaluated primer coverage or a list containing such <code>Primers</code> objects.
<code>templates</code>	If <code>primers</code> is a <code>Primers</code> object, <code>templates</code> should be a <code>Templates</code> object. If <code>primers</code> is a list, then <code>templates</code> should be a list of <code>Templates</code> objects.
<code>direction</code>	The directionality of primers to be plotted. This can either be "both" to plot primers of both directions (the default), "fw" to plot only forward primers, or "rev" to plot only reverse primers.
<code>group</code>	Optional identifiers of template groups for which binding events should be determined. By default, <code>group</code> is set to <code>NULL</code> such that all templates are considered.
<code>relation</code>	Whether binding positions are computed relative to forward ("fw") or reverse ("rev") binding regions. The default is "fw".
<code>region.names</code>	Character vector of length 2 providing the names of the binding and amplification region.
<code>...</code>	Optional arguments <code>groups</code> (a character vector of groups to be plotted when <code>primers</code> is a single primer set), <code>highlight.set</code> (the identifier of a primer set to be highlighted when <code>primers</code> is a list), <code>ncol</code> (a numeric indicating the number of facet columns if <code>primers</code> is a list), <code>deviation.per.primer</code> (a boolean indicating whether constraint deviations should be plotted per primer rather than per constraint if <code>primers</code> is a list)
<code>settings</code>	An object of class <code>DesignSettings</code> containing the constraints to be considered.
<code>active.constraints</code>	A character vector containing the identifiers to be considered for plotting. By default, <code>active.constraints</code> is <code>NULL</code> such that all computed constraints found in <code>settings</code> are plotted.
<code>plot.p.vals</code>	An optional logical argument indicating whether p-values computed via primer_significance should be annotated in the plot. The default is <code>FALSE</code> .
<code>primer.data</code>	List with objects of class <code>Primers</code> containing the primer sets that are to be compared.
<code>template.data</code>	List with objects of class <code>Templates</code> containing the templates corresponding to <code>primer.data</code> .

<code>show.labels</code>	Whether the identifiers of the primer sets should be annotated in the plot. The default is TRUE.
<code>highlight.set</code>	A character vector providing the identifiers of primer sets to highlight. By default, <code>highlight.set</code> is NULL such that no highlighting takes place.
<code>alpha</code>	A numeric in the range [0,1] defining the trade-off between the maximal deviation of a constraint (large alpha) and all constraint deviations (large alpha). By default, alpha is set to 0 such that the absolute deviation across all constraints is considered.
<code>primer.subsets</code>	A list with optimal primer subsets, each of class <code>Primers</code> . The k-th list entry should correspond to an object of class <code>Primers</code> representing the primer subset of size k whose coverage ratio is the largest among all possible subsets of size k.
<code>required.cvg</code>	The required coverage ratio. The default is 100%; this value is plotted as a horizontal line.
<code>primer.df</code>	An object of class <code>Primers</code> containing primers with evaluated primer coverage.
<code>identifier</code>	Identifiers of primers that are to be considered. If <code>identifier</code> is set to NULL (the default), all primers are considered.
<code>per.mismatch</code>	A logical specifying whether the visualization should be stratified according to the allowed number of mismatches. By default, <code>per.mismatch</code> is set to FALSE such that the overall coverage is plotted.

Details

The deviations for `plot_constraint_deviation` are computed in the following way. Let the minimum and maximum allowed constraint values be given by the interval $[s, e]$ and the observed value be p . Then, if $p < s$, we output $-p/|s|$, if $p > e$ we output $p/|e|$, and otherwise, i.e. if $s \leq p \leq e$, we output 0.

The `primer.subsets` argument for `plot_primer_subsets` can be computed using [subset_primer_set](#). The line plot indicates the ratio of covered templates when considering all primers in a primer set of a given size. The bar plots indicate the coverage ratios of individual primers in a set. The target coverage ratio is indicated by a horizontal line. Bars exceeding the target ratio possibly indicate the existence of redundant coverage events.

Value

`plot_conseration` returns a plot showing the degree of sequence conservation in the templates.

`plot_primer_binding_regions` returns a plot of the primer binding regions.

`plot_constraint` returns a plot showing the distribution of primer properties.

`plot_constraint_fulfillment` returns a plot indicating the constraints that are fulfilled by the input primers.

`plot_cvg_constraints` returns a plot showing the distribution of the coverage constraint values.

`plot_constraint_deviation` returns a plot showing the deviations of the primer properties from the target constraints.

`plot_cvg_vs_set_size` returns a plot of coverage vs set size.

`plot_penalty_vs_set_size` returns a plot of constraint penalties vs primer set sizes.
`plot_primer_subsets` plots the coverages of the primer subsets provided via `primer.subsets`.
`plot_primer` plots the primer binding sites in the templates.
`plot_template_cvg` creates a plot showing the number of covered template sequences.
`plot_primer_cvg` creates a plot showing the coverage of individual primers.

Note

Computing the conservation scores for using `plot_conservation` requires the MAFFT software for multiple alignments (<http://mafft.cbrc.jp/alignment/software/>).

Examples

```
data(Ippolito)
# Select binding regions for every group of templates and plot:
template.df <- select_regions_by_conservation(template.df, win.len = 30)
if (length(template.df) != 0) {
  p1 <- plot_conservation(attr(template.df, "entropies"),
                        attr(template.df, "alignments"), template.df)
}
# Select binding regions for all templates and plot:
data(Ippolito)
template.df <- select_regions_by_conservation(template.df, by.group = FALSE)
if (length(template.df) != 0) {
  p2 <- plot_conservation(attr(template.df, "entropies"),
                        attr(template.df, "alignments"), template.df)
}

# Primer binding regions of a single primer set
data(Ippolito)
p <- plot_primer_binding_regions(primer.df, template.df)
# Primer binding regions of multiple primer sets
data(Comparison)
p.comp <- plot_primer_binding_regions(primer.data[1:3], template.data[1:3])

# Plot histogram of constraints for a single primer set
data(Ippolito)
p <- plot_constraint(primer.df, settings,
                    active.constraints = c("gc_clamp", "gc_ratio"))
# Compare constraints across multiple primer sets
data(Comparison)
p.comp <- plot_constraint(primer.data[1:3], settings,
                        active.constraints = c("gc_clamp", "gc_ratio"))

# Plot fulfillment for a single primer set:
data(Ippolito)
p <- plot_constraint_fulfillment(primer.df, settings)
# Plot fulfillment for multiple primer sets:
data(Comparison)
p.comp <- plot_constraint_fulfillment(primer.data[1:5], settings)
```

```
# Plot coverage constraints of a single primer set
data(Ippolito)
p <- plot_cvg_constraints(primer.df, settings)
# Plot coverage constraints for multiple primer sets
data(Comparison)
p.cmp <- plot_cvg_constraints(primer.data[1:2], settings)

# Deviations for a single primer set
data(Ippolito)
p.dev <- plot_constraint_deviation(primer.df, settings)
# Deviations for multiple primer sets
data(Comparison)
p.dev.cmp <- plot_constraint_deviation(primer.data, settings)

# Plot coverage vs primer set size
data(Comparison)
p <- plot_cvg_vs_set_size(primer.data, template.data)

# Plot penalties vs number of primers
data(Comparison)
p <- plot_penalty_vs_set_size(primer.data, settings)

# Plot the coverage of optimal primer subsets
data(Ippolito)
primer.subsets <- subset_primer_set(primer.df, template.df, k = 3)
p <- plot_primer_subsets(primer.subsets, template.df)

# Plot of individual primer binding positions
data(Ippolito)
p <- plot_primer(primer.df[1,], template.df[1:30,])

# Visualize the template coverage of a single primer set
data(Ippolito)
p.cvg <- plot_template_cvg(primer.df, template.df)
# Stratify by allowed mismatches:
p.mm.cvg <- plot_template_cvg(primer.df, template.df, per.mismatch = TRUE)
# Compare the coverage of multiple primer sets
data(Comparison)
p.cmp.cvg <- plot_template_cvg(primer.data[1:2], template.data[1:2])
# Stratify by allowed mismatches:
p.cmp.cvg.mm <- plot_template_cvg(primer.data[1:2], template.data[1:2],
                                per.mismatch = TRUE)

# Plot expected coverage per primer
data(Ippolito)
p.cvg <- plot_primer_cvg(primer.df, template.df)
# Plot coverage stratified by allowed mismatches:
p.cvg.mm <- plot_primer_cvg(primer.df, template.df, per.mismatch = TRUE)
# Plot coverage of multiple primer sets
data(Comparison)
p.cvg.cmp <- plot_primer_cvg(primer.data[1:3], template.data[1:3])
```

 plot_constraint, list-method

Boxplot for Comparing Constraints.

Description

Creates a boxplot visualizing the physicochemical properties of multiple primer sets.

Usage

```
## S4 method for signature 'list'
plot_constraint(
  primers,
  settings,
  active.constraints,
  highlight.set = NULL,
  nfacets = NULL
)
```

Arguments

primers	List with evaluated objects of class Primers. Each list element corresponds to a single primer set.
settings	A DesignSettings object containing the constraints to be plotted.
active.constraints	The names of the constraints to be plotted.
highlight.set	Identifiers of primer sets to be highlighted.
nfacets	A numeric providing the number of facet columns to show. By default nfacets is NULL such that the number of facet columns is chosen automatically.
constraint.settings	List with settings for each constraint.

Value

Boxplot comparing the values of the properties specified by constraints.

 plot_constraint, Primers-method

Histogram of Constraint Values.

Description

Plots a histogram of constraint values.

Usage

```
## S4 method for signature 'Primers'
plot_constraint(primers, settings, active.constraints)
```

Arguments

primers	An evaluated object of class Primers.
settings	A DesignSettings object containing the settings for the constraints to be plotted.
active.constraints	Identifiers of constraints to be plotted. provided settings are used to visualize the desired ranges of constraints. If active.constraints is not provided, the plotting method will automatically try to plot all constraints defined in settings.

Value

A histogram of constraint values for the properties specified by constraints.

```
plot_constraint.histogram
```

Histogram of Constraints.

Description

Plots a histogram of constraint values.

Usage

```
plot_constraint.histogram(
  primer.df,
  con.cols,
  con.identifier,
  boundaries = NULL,
  x.limits = NULL
)
```

Arguments

primer.df	Primer data frame, not necessarily a Primers object.
con.cols	Constraint identifiers in primer.df to plot.
con.identifier	Name of the constraint to plot.
boundaries	List with constraint settings.
x.limits	Interval limiting the extent of the x-axis.

Value

A constraint histogram plot.

```
plot_constraint.histogram.nbr.mismatches
```

Histogram of Number of Mismatches.

Description

Plots a histogram of mismatches.

Usage

```
plot_constraint.histogram.nbr.mismatches(primer.df, allowed.mismatches)
```

Arguments

`primer.df` Primer data frame.
`allowed.mismatches` Number of allowed mismatches.

Value

A plot of the number of primer mismatches.

```
plot_constraint.histogram.primer.efficienc
```

Histogram of Efficiencies

Description

Plots a histogram of primer efficiencies.

Usage

```
plot_constraint.histogram.primer.efficienc(primer.df, opti.constraints)
```

Arguments

`primer.df` Primer data frame.
`opti.constraints` List with constraint settings.

Value

A plot of primer efficiencies.

plot_constraint_deviation,list-method

Plot of Constraint Deviations for Multiple Primer Sets.

Description

Plots a box plot of the absolute mean deviation of each primer for comparing multiple primer sets.

Usage

```
## S4 method for signature 'list'
plot_constraint_deviation(
  primers,
  settings,
  active.constraints,
  deviation.per.primer = FALSE
)
```

Arguments

`settings` A DesignSettings object containing the target ranges for the primer properties.

`active.constraints` Constraint identifiers to be plotted.

`deviation.per.primer` Whether to show the deviation per primer or per constraint.

`constraint.df` An evaluated object of class Primers.

Value

A boxplot of deviations

plot_constraint_deviation,Primers-method

Plot of Constraint Deviations for a Single Primer Set.

Description

Plots a box plot of deviations of primer properties from the target ranges.

Usage

```
## S4 method for signature 'Primers'
plot_constraint_deviation(primers, settings, active.constraints)
```

Arguments

primers	An evaluated object of class Primers.
settings	A DesignSettings object containing the target ranges for the primer properties.
active.constraints	Constraint identifiers to be plotted.

Value

A boxplot of deviations

plot_constraint_fulfillment,list-method
Comparison of Evaluation Results.

Description

Plots the percentage of primers fulfilling the specified constraints for multiple primer sets.

Usage

```
## S4 method for signature 'list'
plot_constraint_fulfillment(
  primers,
  settings,
  active.constraints,
  plot.p.vals = FALSE,
  ncol = 2,
  highlight.set = NULL
)
```

Arguments

primers	A list of Primers objects.
settings	A DesignSettings object.
active.constraints	The identifiers of constraints to be plotted for fulfillment.
plot.p.vals	Whether p-values from Fisher's exact test should be annotated for every primer set.
ncol	The number of columns for facet wrap.
highlight.set	Identifiers of primer sets to be highlighted.

Value

Plot indicating the ratio of primers fulfilling the constraints specified in constraint.settings for each primer set in primers.

```
plot_constraint_fulfillment,Primers-method
```

Overview of Constraint Fulfillment.

Description

Plots an overview of which primers passed the filtering constraints and which primers did not.

Usage

```
## S4 method for signature 'Primers'
plot_constraint_fulfillment(
  primers,
  settings,
  active.constraints,
  plot.p.vals = TRUE
)
```

Arguments

primers	A Primers object.
settings	A DesignSettings object.
active.constraints	The identifiers of constraints to be plotted for fulfillment.
plot.p.vals	Show p-value from Fisher's exact test for the significance of primer constraint fulfillment in comparison to reference primer sets.

Value

A data frame with statistics on fulfilled constraints.

```
plot_cvg_constraints,list-method
```

Plot for Comparing Primer Coverage Constraints.

Description

Plot for Comparing Primer Coverage Constraints.

Usage

```
## S4 method for signature 'list'
plot_cvg_constraints(
  primers,
  settings,
  active.constraints,
  highlight.set = NULL
)
```

Arguments

`primers` List with objects of class `Primers`.
`settings` A `DesignSettings` object.
`active.constraints` Names of the coverage constraints to be plotted.
`highlight.set` Primer sets to highlight in the plot.

Value

Plot of primer coverage constraints for multiple sets.

plot_cvg_constraints, Primers-method
Histogram of Coverage Constraints.

Description

Plots a histogram of coverage constraint values.

Usage

```
## S4 method for signature 'Primers'
plot_cvg_constraints(primers, settings, active.constraints)
```

Arguments

`primers` A `Primers` object.
`settings` A `DesignSettings` object.
`active.constraints` Names of coverage constraints to be plotted.

Value

A plot of coverage constraints.

`plot_primer.comparison.box`*Boxplot for Primer Comparison*

Description

Constructs a box plot showing constraint values for each primer set.

Usage

```
plot_primer.comparison.box(  
  primer.data,  
  con.identifier,  
  con.cols,  
  boundaries,  
  y.limits = NULL,  
  show.points = TRUE,  
  highlight.set = NULL,  
  nfacets = NULL  
)
```

Arguments

<code>primer.data</code>	List with primer data frames.
<code>con.identifier</code>	Identifier of constraint to be plotted.
<code>con.cols</code>	Column names with the constraint values in the primer data frames.
<code>boundaries</code>	List with constraint settings.
<code>y.limits</code>	Limits for the extent of the y-axis.
<code>show.points</code>	If TRUE (the default), individual data points are visualized in the boxplot, otherwise they are not shown.
<code>highlight.set</code>	The identifier of a primer set to highlight in the plot.
<code>nfacets</code>	A numeric providing the number of facet columns to show. By default <code>nfacets</code> is NULL such that the number of facet columns is chosen automatically.

Value

A boxplot for primer comparison.

```
plot_primer.comparison.mismatches
```

Plot Primer Mismatches

Description

Plots primer mismatches for every set.

Usage

```
plot_primer.comparison.mismatches(
  primer.data,
  template.data,
  allowed.mismatches,
  highlight.set = NULL
)
```

Arguments

```
primer.data      List with primer data frames.
template.data    List with template data frames.
allowed.mismatches
                  Allowed mismatches.
highlight.set    Primer sets to highlight in the plot.
```

Value

Plot of mismatches for comparison.

```
plot_primer_binding_regions,list,list-method
```

Plot of Primer Binding Regions for Multiple Sets.

Description

Plots the primer binding regions for every primer set.

Usage

```
## S4 method for signature 'list,list'
plot_primer_binding_regions(
  primers,
  templates,
  direction = c("both", "fw", "rev"),
  group = NULL,
```

```

    relation = c("fw", "rev"),
    region.names = c("Binding region", "Amplification region"),
    highlight.set = NULL
  )

```

Arguments

primers	List with primer data frames.
templates	List with template data frames.
direction	Direction of primers.
group	Template groups to plot. This defaults to plotting all groups.
relation	Plot binding region relative to forward binding region or reverse?
region.names	Names for the primer binding region and the amplified region.
highlight.set	Primer sets to highlight in the plot.

Value

A plot for primer binding region comparison.

plot_primer_binding_regions,Primers,Templates-method

Plot of Primer Binding Regions for a Single Primer Set.

Description

Plots the primer binding regions in the templates.

Usage

```

## S4 method for signature 'Primers,Templates'
plot_primer_binding_regions(
  primers,
  templates,
  direction = c("both", "fw", "rev"),
  group = NULL,
  relation = c("fw", "rev"),
  region.names = c("Binding region", "Amplification region")
)

```

Arguments

primers	An object of class Primers with annotated primer coverage.
templates	An object of class Templates providing the template sequences corresponding to primers.
direction	Primer direction

group	The template groups for which binding events should be determined. By default, group is set to NULL such that all templates are considered.
relation	A character vector specifying whether binding region data shall be plotted relative to the forward (fw) or reverse (rev) target binding regions.
region.names	Names for the primer binding region and the amplified region.

Value

A histogram of primer binding regions.

plot_primer_cvg,list,list-method
<i>Plot Multiple Primer Coverages.</i>

Description

Plots the coverage of individual primers for multiple sets.

Usage

```
## S4 method for signature 'list,list'
plot_primer_cvg(primers, templates, per.mismatch = FALSE)
```

Arguments

primers	List with Primers objects.
templates	List with Templates objects.
per.mismatch	Whether the coverage should be broken down for individual settings of allowed mismatches.

Value

A bar plot showing the coverage of individual primers.

```
plot_primer_cvg,Primers,Templates-method
```

Plot Individual Primer Coverage.

Description

Shows which templates are covered by individual primers.

Usage

```
## S4 method for signature 'Primers,Templates'
plot_primer_cvg(primers, templates, per.mismatch = FALSE, groups = NULL)
```

Arguments

per.mismatch	Whether the coverage should be broken down for individual settings of allowed mismatches.
p.df	Primer data frame.
template.df	Template data frame.
excluded.seqs	Identifiers of templates that should not be considered.

Value

A bar plot showing the coverage of individual primers.

```
plot_primer_cvg_mismatches
```

Plot of Individual Primer Coverage and Mismatches.

Description

Plots the coverage of individual primers for different mismatch settings.

Usage

```
plot_primer_cvg_mismatches(
  primer.df,
  template.df,
  groups = NULL,
  nfacets = NULL
)
```

Arguments

<code>primer.df</code>	A Primers object.
<code>template.df</code>	A Templates object.
<code>groups</code>	Optional identifiers of template groups to be considered. If not provided, all template groups are considered.
<code>nfacets</code>	A numeric providing the number of facet columns to use. By default, <code>nfacets</code> is set to NULL such that a suitable number of columns is chosen automatically.

Value

A bar plot showing the coverage of individual primers for different mismatch settings.

<code>plot_primer_cvg_unstratified</code>
<i>Plot Individual Primer Coverage.</i>

Description

Plots the coverage of individual primers.

Usage

```
plot_primer_cvg_unstratified(p.df, template.df, groups = NULL)
```

Arguments

<code>p.df</code>	Primer data frame.
<code>template.df</code>	Template data frame.
<code>groups</code>	Optional identifiers of template groups to be considered. If not provided, all template groups are considered.

Value

A bar plot showing the coverage of individual primers.

```
plot_template_cvg,list,list-method
```

Templates Coverage for Multiple Primer Sets.

Description

Plots the coverage of multiple primer sets.

Usage

```
## S4 method for signature 'list,list'
plot_template_cvg(primers, templates, per.mismatch, highlight.set = NULL)
```

Arguments

primers	List with primer data frames.
templates	List with template data frames.
highlight.set	Primer sets to be highlighted.
colors	Color for every primer set.

Value

A plot for comparing primer coverage.

```
plot_template_cvg,Primers,Templates-method
```

Bar Plot of Template Coverage.

Description

Creates a bar plot showing the coverage for every group of template sequences.

Usage

```
## S4 method for signature 'Primers,Templates'
plot_template_cvg(primers, templates, per.mismatch, groups = NULL)
```

Arguments

primers	A Primers object with evaluated primer coverage.
templates	A Templates object containing the template sequences.
per.mismatch	Whether to stratify by mismatches.
groups	Identifiers of template groups for which plot should be created. By default, groups is set to NULL such that all templates are considered. according to the number of mismatches between primer-template pairs.

Value

A plot showing the number of covered template sequences.

```
plot_template_cvg_comparison_mismatch
```

Templates Coverage for Multiple Primer Sets.

Description

Plots the coverage of multiple primer sets.

Usage

```
plot_template_cvg_comparison_mismatch(primers, templates, highlight.set = NULL)
```

Arguments

primers	List with primer data frames.
templates	List with template data frames.
highlight.set	Primer sets to be highlighted.

Value

A plot for comparing primer coverage.

```
plot_template_cvg_comparison_unstratified
```

Templates Coverage for Multiple Primer Sets.

Description

Plots the coverage of multiple primer sets.

Usage

```
plot_template_cvg_comparison_unstratified(
  primers,
  templates,
  highlight.set = NULL
)
```

Arguments

primers	List with primer data frames.
templates	List with template data frames.
highlight.set	Primer sets to be highlighted.

Value

A plot for comparing primer coverage.

plot_template_cvg_mismatches

Bar Plot of Template Coverage for Mismatches.

Description

Creates a bar plot showing the coverage for every group of template sequences.

Usage

```
plot_template_cvg_mismatches(
  primer.df,
  template.df,
  groups = NULL,
  nfacets = 2
)
```

Arguments

primer.df	A Primers object.
template.df	A Templates object.
groups	Identifiers of template groups for which plot should be created. By default, groups is set to NULL such that all templates are considered.
nfacets	The number of facets columns to plot. By default, nfacets is set to 2.

Value

A plot showing the number of covered template sequences.

plot_template_cvg_unstratified

Bar Plot of Template Coverage.

Description

Creates a bar plot showing the coverage for every group of template sequences.

Usage

```
plot_template_cvg_unstratified(primers, templates, groups = NULL)
```

Arguments

primers	A Primers object with evaluated primer coverage.
templates	A Templates object containing the template sequences.
groups	Identifiers of template groups for which plot should be created. By default, groups is set to NULL such that all templates are considered. according to the number of mismatches between primer-template pairs.

Value

A plot showing the number of covered template sequences.

plot_template_structure

Plot of Template Folding Energies.

Description

Plots the DeltaDeltaG of template folding, which is the difference between the free energy change of the unconstrained folding and the free energy change of the constrained folding.

Usage

```
plot_template_structure(fold.df)
```

Arguments

fold.df	A data frame with free energies for the template regions.
---------	---

Value

A plot of DeltaDeltaG.

pos.to.range

Conversion of Positions to Ranges.

Description

Converts two numeric values to a range.

Usage

```
pos.to.range(pos1, pos2)
```

Arguments

pos1	The first value.
pos2	The second value.

Value

A character vector range.

predict_coverage	<i>Prediction of Primer Coveragee.</i>
------------------	--

Description

Predicts primer coverage using a logistic regression model. Converts coverage probabilities to expected false positive rate for a given probability.

Usage

```
predict_coverage(  
  primer.df,  
  template.df,  
  settings,  
  mode = c("on_target", "off_target"),  
  updateProgress = NULL  
)
```

Arguments

primer.df	A Primers data frame.
template.df	A Templates data frame.
settings	A DesignSettings object.
mode	Whether on-target or off-target events shall be considered.

Value

The predictions for primer coverage

```
prefilter.primers.candidates
```

Identification of Short Primers.

Description

Identify initial primers that are too short.

Usage

```
prefilter.primers.candidates(primer.candidates, min.len)
```

Arguments

primer.candidates	Primer alignment.
min.len	Minimal primer length.

Value

The index of proposed primers that are shorter than min.len.

```
prepare.constraint.plot
```

Preparation of Comparison Plot for Evaluation.

Description

Preparation of Comparison Plot for Evaluation.

Usage

```
prepare.constraint.plot(primer.data, constraint.settings, plot.p.vals = FALSE)
```

Arguments

primer.data	List with objects of class Primers. Each list entry corresponds to a single primer set.
constraint.settings	List with settings for each constraint. If NULL (the default), use the available evaluation results in primer.data.
plot.p.vals	Whether p-values from Fisher's exact test should be annotated for every primer set.

Value

Plot indicating the ratio of primers fulfilling the constraints specified in `constraint.settings` for each primer set in `primer.data`.

prepare.dimer.seqs	<i>Preparation of Input for Dimerization.</i>
--------------------	---

Description

Preparation of Input for Dimerization.

Usage

```
prepare.dimer.seqs(s1, s2)
```

Arguments

s1	Nucleotide character vectors (5' to 3')
s2	Nucleotide character vectors (5' to 3')

Value

A list with two fields containing character vectors.

prepare_mm_plot	<i>Data Preparation for Mismatch Plot.</i>
-----------------	--

Description

Data Preparation for Mismatch Plot.

Usage

```
prepare_mm_plot(primer.df, template.df, mode = c("on_target", "off_target"))
```

Arguments

primer.df	A Primers object.
template.df	A Templates object.
mode	Whether to compute for on-target or off-target events.

Value

A data frame with binding information for every primer.

```
prepare_template_cvg_mm_data
```

Preparation of Data for Plotting Mismatch Template Coverage.

Description

Creates a data frame for plotting a bar plot for the covered templates per allowed mismatches.

Usage

```
prepare_template_cvg_mm_data(primer.df, template.df, allowed.mismatches = NULL)
```

Arguments

`primer.df` A Primers object.

`template.df` A Templates object.

`allowed.mismatches`

An optional numeric specifying the number of mismatches to be considered at most for plotting. If not provided, the maximal number of mismatches found for the input primer set is used.

Value

A data frame for creating a plot.

```
primer.binding.regions.data
```

Primer Binding Region Data

Description

Collects all data concerning primer binding regions.

Usage

```
primer.binding.regions.data(
  primer.df,
  template.df,
  direction = c("both", "fw", "rev"),
  group = NULL,
  relation = c("fw", "rev")
)
```

Arguments

primer.df	Primer data frame.
template.df	Template data frame.
direction	Primer direction
group	The groups for which binding data shall be retrieved.
relation	Binding region data relative to forward/reverse binding region?

Value

Data frame with primer binding data.

`primer.coverage.for.groups`

Determination of Primer Coverage for Groups.

Description

Modifies a primer data frame to retain only coverage events relating to the selected groups of templates.

Usage

```
primer.coverage.for.groups(primer.df, template.df, groups)
```

Arguments

primer.df	Primer data frame.
template.df	Template data frame.
groups	Template groups for which coverage should be determined.

Value

primer.df with coverage considered only for groups.

`primer.set.parameter.stats`

Primer Set Statistics

Description

Creates an overview of all primer set constraint values.

Usage

```
primer.set.parameter.stats(primer.df, mode.directionality, lex.seq)
```

Arguments

<code>primer.df</code>	Primer data frame.
<code>mode.directionality</code>	Direction of primers.
<code>lex.seq</code>	Template data frame.

Value

A data frame with statistics.

PrimerDesign

Primer Design Functionalities.

Description

`design_primers` Designs a primer set maximizing the number of covered templates using the smallest possible number of primers. The algorithm tries to ensure that the designed set of primers achieves a coverage ratio not lower than `required.cvg`. To this end, the constraints for designing primers may be relaxed.

`get_initial_primers` Creates a set of primer candidates based on the input template sequences. This set of primers can be used to create custom primer design algorithms.

Usage

```
classify_design_problem(  
  template.df,  
  mode.directionality = c("both", "fw", "rev"),  
  primer.length = 18,  
  primer.estimate = FALSE,  
  required.cvg = 1  
)
```

```

get_initial_primers(
  sample,
  template.df,
  primer.lengths,
  mode.directionality = c("fw", "rev"),
  allowed.region.definition = c("within", "any"),
  init.algo = c("naive", "tree"),
  max.degen = 16,
  conservation = 1,
  updateProgress = NULL
)

design_primers(
  template.df,
  mode.directionality = c("both", "fw", "rev"),
  settings,
  init.algo = c("naive", "tree"),
  opti.algo = c("Greedy", "ILP"),
  required.cvg = 1,
  timeout = Inf,
  max.degen = 16,
  conservation = 1,
  sample.name = NULL,
  cur.results.loc = NULL,
  primer.df = NULL,
  updateProgress = NULL
)

```

Arguments

<code>template.df</code>	A Templates object containing the template sequences with annotated primer target binding regions.
<code>mode.directionality</code>	The template strand for which primers shall be designed. Primers can be designed either for forward strands ("fw"), for reverse strands ("rev"), or for both strands ("both"). The default setting is "both".
<code>primer.length</code>	A scalar numeric providing the target length of the designed primers. The default length of generated primers is set to 18.
<code>primer.estimate</code>	Whether the number of required primers shall be estimated. By default (FALSE), the number of required primers is not estimated.
<code>required.cvg</code>	The desired ratio of covered template sequences. If the target coverage ratio cannot be reached, the constraint settings are relaxed according to the constraint limits in order to reach the target coverage. The default <code>required.cvg</code> is set to 1, indicating that 100% of the templates are to be covered.
<code>sample</code>	Character vector providing an identifier for the templates.
<code>primer.lengths</code>	Numeric vector of length 2 providing the minimal and maximal allowed lengths for generated primers.

<code>allowed.region.definition</code>	A character vector providing the definition of region where primers are to be constructed. If <code>allowed.region.definition</code> is "within", constructed primers lie within the allowed binding region. If <code>allowed.region.definition</code> is "any", primers overlap with the allowed binding region. The default is "within".
<code>init.algo</code>	The algorithm to be used for initializing primers. If <code>init.algo</code> is "naive", then primers are constructed from substrings of the input template sequences. If <code>init.algo</code> is "tree", phylogenetic trees are used to form degenerate primers whose degeneracy is bounded by <code>max.degen</code> . This option requires an installation of MAFFT (see notes). The default <code>init.algo</code> is "naive".
<code>max.degen</code>	The maximal degeneracy of primer candidates. This setting is particularly relevant when <code>init.algo</code> is set to "tree". The default setting is 16, which means that at most 4 maximally degenerate positions are allowed per primer.
<code>conservation</code>	Restrict the percentile of considered regions according to their conservation. Only applicable for the tree-based primer initialization. At the default of 1, all available binding regions are considered.
<code>updateProgress</code>	Shiny progress callback function. The default is NULL such that no progress is logged.
<code>settings</code>	A <code>DesignSettings</code> object specifying the constraint settings for designing primers.
<code>opti.algo</code>	The algorithm to be used for solving the primer set covering problem. If <code>opti.algo</code> is "Greedy" a greedy algorithm is used to solve the set cover problem. If <code>opti.algo</code> is "ILP" an integer linear programming formulation is used. The default <code>opti.algo</code> is "Greedy".
<code>timeout</code>	Timeout in seconds. Only applicable when <code>opti.algo</code> is "ILP". The default is Inf, which does not limit the runtime.
<code>sample.name</code>	An identifier for the primer design task. The default setting is NULL, which means that the run identifier provided in <code>template.df</code> is used.
<code>cur.results.loc</code>	Directory for storing the results of the primer design procedure. The default setting is NULL such that no output is stored.
<code>primer.df</code>	An optional <code>Primers</code> object. If an evaluated <code>primer.df</code> is provided, the primer design procedure only optimizes <code>primer.df</code> and does not perform the initialization and filtering steps. The default is NULL such that primers are initialized and filtered from scratch.

Details

`classify_design_problem` determines the difficulty of a primer design task by estimating the distribution of coverage ratios per primer by performing exact string matching with primers of length `primer.length`, which are constructed by extracting template subsequences. Next, a beta distribution is fitted to the estimated coverage distribution, which is then compared to reference distributions representing primer design problems of different difficulties via the total variance distance. The difficulty of the input primer design problem is found by selecting the class of the reference distributions that has the smallest distance to the estimated coverage distribution. An estimate of the required number of primers to reach a given `required.cvg` can be computed by setting

`primer.estimate` to `TRUE`. Since this estimate is based solely on perfect matching primers, the number of primers that would actually be required is typically less.

The primer design algorithm used by `design_primers` consists of three steps: primer initialization, filtering, and optimization. The method for initializing a set of candidate primers is determined via `init.algo`. If `init.algo` is set to *naive*, primers are created by extracting substrings from all input template sequences. If `init.algo` is set to *tree*, degenerate primers are created by merging similar subsequences by forming their consensus sequence up to a degeneracy of at most `max.degen`. The tree-based initialization is recommended for related sequences.

The candidate primer set is filtered according to the constraints specified in the `settings` object. In some cases, it is necessary to relax the constraints in order to reach the desired `required.cvg`. In these cases, primers that fail the input constraints may be selected. If you would like to skip the initialization and filtering stages, you can provide an evaluated `Primers` object via `primer.df`.

Optimizing a primer set entails finding the smallest subset of primers maximizing the coverage, which is done by solving the set cover problem. If melting temperature differences are a constraint, the optimization procedure automatically samples ranges of melting temperatures to find optimal sets for all possible temperatures. You can select the used optimization algorithm via `optia.algo`, where you can set "Greedy" for a greedy algorithm or "ILP" for an integer linear program formulation (ILP). While the worst-case runtime of the greedy algorithm is shorter than the worst-case runtime of the ILP, the greedy solution may yield larger primer sets than the ILP solution.

Value

`classify_design_problem` returns a list with the following fields:

Classification The estimated difficulty of the primer design task.

Class-Distances The total variance distance of the fitted beta distribution to the reference distribution.

Confidence The confidence in the estimate of the design tasks' difficulty as based on the class distances.

Uncertain Whether the classification is highly uncertain, that is low-confidence.

Nbr_primers_fw and Nbr_primers_rev The respective number of required forward and reverse primers if `primer.estimate` was set to `TRUE`.

`get_initial_primers` returns a data frame with candidate primers for optimization.

`design_primers` returns a list with the following fields:

opti: A `Primers` object providing the designed primer set.

used_constraints: A list with `DesignSettings` objects for each primer direction providing the (possibly relaxed) constraints used for designing the optimal primers.

all_results: A list containing objects of class `Primers`. Each list entry corresponds to an optimal primer set for a given melting temperature.

all_used_constraints: A list containing `DesignSettings` object for each optimized set in `all_results`.

filtered: A list with data providing information on the results of the filtering procedure.

Note

Some constraints can only be computed if additional software is installed, please see the documentation of [DesignSettings](#) for more information. The usage of `init.algo = "tree"` requires an installation of the multiple alignment program MAFFT (<http://mafft.cbrc.jp/alignment/software/>).

Examples

```
data(Ippolito)
# Naive primer initialization
init.primers <- get_initial_primers("InitialPrimers", template.df,
                                   c(18,18), "fw", init.algo = "naive")
# Tree-based primer initialization (requires MAFFT)
## Not run:
init.primers <- get_initial_primers("InitialPrimers", template.df,
                                   c(18,18), "fw", init.algo = "tree")

## End(Not run)

# Define PCR settings and primer criteria
data(Ippolito)
# design only with minimal set of constraints
constraints(settings)$primer_length <- c("min" = 18, "max" = 18)
constraints(settings) <- constraints(settings)[c("primer_length", "primer_coverage")]
# Design only forward primers using a greedy algorithm
optimal.primers.greedy <- design_primers(template.df[1:2,], "both", settings, init.algo = "naive")
# Usage of the tree-based initialization strategy (requires MAFFT)
## Not run:
out.dir <- tempdir()
optimal.primers.tree <- design_primers(template.df[1:2,], "both", settings,
                                       init.algo = "tree", opti.algo = "ILP",
                                       max.degen = 16,
                                       cur.results.loc = out.dir)

## End(Not run)
```

PrimerEval

Primer Evaluation.

Description

`check_constraints` Determines whether a set of primers fulfills the constraints on the properties of the primers.

`check_restriction_sites` Checks a set of primers for the presence of restriction sites. To reduce the number of possible restriction sites, only unambiguous restriction sites are taken into account and only common (typically used) restriction sites are checked if a common restriction site can be found in a sequence.

`filter_primers` Filters a primer set according to the specified constraints such that all primers that do not fulfill the constraints are removed from the primer set.

`primer_significance` Uses Fisher's exact test to determine the significance of a primer set according to its ratio of fulfilled constraints.

`subset_primer_set` Determines subsets of the input primer set that are optimal with regard to the number of covered template sequences.

Usage

```
check_restriction_sites(  
  primer.df,  
  template.df,  
  adapter.action = c("warn", "rm"),  
  selected = NULL,  
  only.confident.calls = TRUE,  
  updateProgress = NULL  
)  
  
check_constraints(  
  primer.df,  
  template.df,  
  settings,  
  active.constraints = names(constraints(settings)),  
  to.compute.constraints = active.constraints,  
  for.shiny = FALSE,  
  updateProgress = NULL  
)  
  
filter_primers(  
  primer.df,  
  template.df,  
  settings,  
  active.constraints = names(constraints(settings))  
)  
  
subset_primer_set(  
  primer.df,  
  template.df,  
  k = 1,  
  groups = NULL,  
  identifier = NULL,  
  cur.results.loc = NULL  
)  
  
primer_significance(primer.df, set.name = NULL, active.constraints = NULL)
```

Arguments

<code>primer.df</code>	A Primers object containing the primers whose properties are to be checked.
<code>template.df</code>	A Templates object containing the template sequences corresponding to <code>primer.df</code> .

<code>adapter.action</code>	The action to be performed when adapter sequences are found. Either "warn" to issue a warning about adapter sequences or "rm" to remove identified adapter sequences. Currently, only the default setting ("warn") is supported.
<code>selected</code>	Names of restriction sites that are to be checked. By default <code>selected</code> is NULL in which case all REBASE restriction sites are taken into account.
<code>only.confident.calls</code>	Whether only confident calls of restriction sites are returned. All restriction site call is considered <i>confident</i> if the restriction site is located in a region that does not match the template sequences. Note that this classification requires that the provided primers are somehow complementary to the provided templates. In contrast, non-confident restriction site calls are based solely on the primer sequences and do not take the templates into account, resulting in more false positive calls of restriction sites.
<code>updateProgress</code>	Progress callback function for shiny. The default is NULL meaning that no progress is monitored via the Shiny interface.
<code>settings</code>	A <code>DesignSettings</code> object containing the constraints that are to be considered.
<code>active.constraints</code>	A subset of the constraint identifiers provided by <code>settings</code> that are to be checked for fulfillment. By default <code>active.constraints</code> is NULL such that all constraints found in <code>settings</code> are evaluated. Otherwise, only the constraints specified via <code>active.constraints</code> that are available in <code>settings</code> are considered.
<code>to.compute.constraints</code>	Constraints that are to be computed. By default, <code>to.compute.constraints</code> is set to NULL such that all <code>active.constraints</code> are computed. If <code>to.compute.constraints</code> is a subset of <code>active.constraints</code> , all constraints specified via <code>active.constraints</code> are evaluated for fulfillment, but only the constraints in <code>to.compute.constraints</code> are newly calculated.
<code>for.shiny</code>	Whether the output of the function shall be formatted as HTML. The default setting is FALSE.
<code>k</code>	The spacing between generated primer subset sizes. By default, <code>k</code> is set to 1 such that all primer subsets are constructed.
<code>groups</code>	The identifiers of template groups according to which coverage should be determined. By default, <code>groups</code> is set to NULL such that all covered templates are considered.
<code>identifier</code>	An identifier for storing the primer set. By default, <code>identifier</code> is set to NULL.
<code>cur.results.loc</code>	Directory for storing the results. By default, <code>cur.results.loc</code> is set to NULL, which means that no results are stored.
<code>set.name</code>	An identifier for the input primers. If NULL, the run identifier is used.

Details

When the optional argument `active.constraints` is supplied to `check_constraints`, only a subset of the constraints provided in `settings` is evaluated. Only constraints that are defined in `settings` can be computed. For a detailed description of all possible constraints and their options, please consider the [ConstraintSettings](#) documentation.

`subset_primer_set` determines optimal subsets of the input primer set by solving an integer-linear program. Since the quality of the primers (in terms of properties) is not taken into account when creating the subsets, this method should only be used for primer sets that are already of high quality.

`primer_significance` computes the significance by comparing the total count of fulfilled and failed constraints with the corresponding counts of primer sets from the literature. Significant p-values indicate primer sets whose rate of constraint fulfillment is higher compared to the reference sets.

Value

`check_restriction_sites` returns a data frame with possible restriction sites found in the primers.

`check_constraints` returns a `Primers` object that is augmented with columns providing the results for the evaluated constraints. The `constraints_passed` column indicates whether all `active.constraints` were fulfilled. The `EVAL_*` columns indicate the fulfillment of primer-specific constraints. The `T_EVAL_*` columns indicate the fulfillment of template-specific (e.g. coverage-based) constraints. For the coverage computations, columns prefixed by `Basic_`, indicate the results from string matching, while all other results (e.g. `primer_coverage`) indicate the expected coverage after applying the coverage constraints specified in settings. Columns prefixed by `Off_` indicate off-target binding results.

`filter_primers` returns a `Primers` object containing only those primers fulfilling all specified constraints.

`subset_primer_set` returns a list with optimal primer subsets, each of class `Primers`.

`primer_significance` returns a numeric providing the p-value of the primer set according to Fisher's exact test. The returned value has the following attributes:

`test` The results of the significance test

`tab` The confusion matrix for Fisher's exact test

`constraints` The names of the considered constraints

Note

Please note that some constraint computations may require the installation of additional programs; for more information please view the documentation of [DesignSettings](#).

References

Roberts, R.J., Vincze, T., Posfai, J., Macelis, D. (2010) REBASE—a database for DNA restriction and modification: enzymes, genes and genomes. *Nucl. Acids Res.* 38: D234-D236. <http://rebase.neb.com>

Examples

```
data(Ippolito)
# Check the first primer for restriction sites with respect to the first 10 templates
site.df <- check_restriction_sites(primer.df[1,], template.df[1:10])
```

```
data(Ippolito)
settings.xml <- system.file("extdata", "settings",
                             "C_Taq_PCR_high_stringency.xml", package = "openPrimer")
```

```

settings <- read_settings(settings.xml)
# Check GC clamp and number of runs for all primers:
constraint.df <- check_constraints(primer.df, template.df,
                                settings, active.constraints = c("gc_clamp", "no_runs"))
# Summarize the evaluation results
summary(constraint.df)

data(Ippolito)
filename <- system.file("extdata", "settings",
                        "C_Taq_PCR_high_stringency.xml", package = "openPrimerR")
settings <- read_settings(filename)
# Only retain the primers fulfilling the GC clamp constraint:
filtered.df <- filter_primers(primer.df, template.df, settings,
                             active.constraints = c("gc_ratio"))

# Determine optimal primer subsets
data(Ippolito)
primer.subsets <- subset_primer_set(primer.df, template.df, k = 3)

# Determine the significance of a primer set
data(Ippolito)
p.data <- primer_significance(primer.df, "Ippolito")
attr(p.data, "tab") # the confusion matrix
attr(p.data, "test") # results from Fisher's test
attr(p.data, "constraints") # considered constraints for the test

```

rbind.primer.data	<i>Rbind for Primer Data Frames.</i>
-------------------	--------------------------------------

Description

Merges all primer data frames in `primer.data` into one data frame.

Usage

```
## S3 method for class 'primer.data'
rbind(primer.data)
```

Arguments

`primer.data` List with primer data frames.

Value

A data frame containing all data in `primer.data`.

rbind.Primers	<i>rbind for Primers class.</i>
---------------	---------------------------------

Description

Ensures that the rbind result has the appropriate class.

Usage

```
## S3 method for class 'Primers'  
rbind(...)
```

Arguments

... Parameters for rbind function.

Value

Row-binded Primers data frame.

Examples

```
data(Ippolito)  
primer.df <- rbind(primer.df, primer.df)
```

rbind.Templates	<i>rbind for Template class.</i>
-----------------	----------------------------------

Description

Ensures that the rbind result has the appropriate class.

Usage

```
## S3 method for class 'Templates'  
rbind(...)
```

Arguments

... Parameters for rbind function.

Value

Row-binded Templates data frame.

Examples

```
data(Ippolito)  
template.df <- rbind(template.df, template.df)
```

<code>read.leaders</code>	<i>Read Individual Binding Regions</i>
---------------------------	--

Description

Reads individual binding regions into a data frame.

Usage

```
read.leaders(  
  fasta.file,  
  direction = c("fw", "rev"),  
  rm.keywords = NULL,  
  gap.character  
)
```

Arguments

- | | |
|----------------------------|--|
| <code>fasta.file</code> | Path to a FASTA file with binding regions. |
| <code>direction</code> | String identifying whether the FASTA file contains information pertaining to the binding region of forward or reverse primers. |
| <code>rm.keywords</code> | A vector of keywords that are used to remove templates whose headers contain any of the keywords. |
| <code>gap.character</code> | The character for indicating gaps in sequences. |

Value

A data frame with individual binding regions.

<code>read.secondary.structure.raw</code>	<i>Read a Secondary Structure</i>
---	-----------------------------------

Description

Reads the secondary structure output of ViennaRNA.

Usage

```
read.secondary.structure.raw(fw.out)
```

Arguments

- | | |
|---------------------|--|
| <code>fw.out</code> | Path to a ViennaRNA secondary structure output file. |
|---------------------|--|

Value

Data frame with information on secondary structures.

read.sequences	<i>Read Sequences.</i>
----------------	------------------------

Description

Reads an input FASTA file.

Usage

```
read.sequences(fasta.file, gap.character)
```

Arguments

fasta.file	The path to a FASTA file.
The	character indicating gaps in sequences.

Value

A data frame with sequences.

read_primers.internal	<i>Internal Function for Reading Primers</i>
-----------------------	--

Description

Reads the given primer sequences into a data frame.

Usage

```
read_primers.internal(  
  primer.seqs,  
  headers,  
  fw.id,  
  rev.id,  
  merge.ambig = c("none", "merge", "unmerge"),  
  max.degen,  
  sample.name  
)
```

Arguments

<code>primer.seqs</code>	Primer sequences.
<code>headers</code>	Headers of the primer FASTA file.
<code>fw.id</code>	Identifier of forward primers in the headers.
<code>rev.id</code>	Identifier of reverse primers in the headers.
<code>merge.ambig</code>	Should ambiguous primers be merged?
<code>max.degen</code>	Maximum allowed degeneracy

Value

A data frame with primer sequences.

<code>read_primers_csv</code>	<i>Read Primer CSV File.</i>
-------------------------------	------------------------------

Description

Reads a primer data frame stored in a CSV file.

Usage

```
read_primers_csv(file)
```

Arguments

<code>file</code>	The path to a csv file containing the primer data.
-------------------	--

Value

A Primers object, an instance of a data frame.

<code>read_primers_multiple</code>	<i>Input of Multiple Primer Sets.</i>
------------------------------------	---------------------------------------

Description

Reads multiple CSV files representing stored objects of class Primers.

Usage

```
read_primers_multiple(  
  filenames,  
  fw.id,  
  rev.id,  
  merge.ambig,  
  max.degen,  
  template.df,  
  adapter.action,  
  sample.name,  
  updateProgress  
)
```

Arguments

filenames The paths to multiple primer CSV/FASTA files.

Value

A list containing objects of class Primers.

read_templates_csv	<i>Read Template CSV File</i>
--------------------	-------------------------------

Description

Reads an input template CSV file.

Usage

```
read_templates_csv(fname)
```

Arguments

fname The filename of the input template CSV file.

Value

A template data frame.

read_templates_fasta *Input of Template Sequences.*

Description

Read template sequences from a FASTA file.

Usage

```
read_templates_fasta(
  fasta.file,
  hdr.structure = NULL,
  delim = NULL,
  id.column = NULL,
  rm.keywords = NULL,
  remove.duplicates = FALSE,
  fw.region = c(1, 30),
  rev.region = c(1, 30),
  gap.character = "-",
  run = NULL
)
```

Arguments

fasta.file	Path to a FASTA file containing the template sequences.
hdr.structure	Names describing the information contained in the FASTA headers. In case that the headers of fasta.file contain template group information, please include the keyword "GROUP" in hdr.structure.
delim	Delimiter for the information in the FASTA headers.
id.column	Field in the header to be used as the identifier.
rm.keywords	A vector of keywords that are used to remove templates whose headers contain any of the keywords.
remove.duplicates	Whether duplicate sequence shall be removed.
fw.region	The positional interval from the template 5' end specifying the binding sites for forward primers.
rev.region	The positional interval from the template 3' end specifying the binding sites for reverse primers.
gap.character	The character in the input file representing gaps. Gaps are automatically removed upon input.
run	An identifier for the template sequences.

Value

An object of class Templates.

Examples

```

fasta.file <- system.file("extdata", "IMGT_data", "templates",
                          "Homo_sapiens_IGH_functional_exon.fasta", package = "openPrimeR")
hdr.structure <- c("ACCESSION", "GROUP", "SPECIES", "FUNCTION")
template.df <- read_templates(fasta.file, hdr.structure, "|", "GROUP")

```

```
read_templates_multiple
```

Input of Multiple Templates.

Description

Reads multiple template CSV/FASTA files.

Usage

```

read_templates_multiple(
  filenames,
  hdr.structure = NULL,
  delim = NULL,
  id.column = NULL,
  rm.keywords = NULL,
  remove.duplicates = FALSE,
  fw.region = c(1, 30),
  rev.region = c(1, 30),
  gap.character = "-",
  run = NULL
)

```

Arguments

<code>filenames</code>	Names of FASTA/CSV files containing template data.
<code>hdr.structure</code>	A character vector describing the information contained in the FASTA headers. In case that the headers of <code>fasta.file</code> contain template group information, please include the keyword "GROUP" in <code>hdr.structure</code> .
<code>delim</code>	Delimiter for the information in the FASTA headers.
<code>id.column</code>	Field in the header to be used as the identifier.
<code>rm.keywords</code>	A vector of keywords that are used to remove templates whose headers contain any of the keywords.
<code>remove.duplicates</code>	Whether duplicate sequence shall be removed.
<code>fw.region</code>	The positional interval from the template 5' end specifying the binding sites for forward primers.
<code>rev.region</code>	The positional interval from the template 3' end specifying the binding sites for reverse primers.

gap.character	The character in the input file representing gaps. Gaps are automatically removed upon input.
run	An identifier for the template sequences.

Value

A list containing objects of class Templates.

read_templates_single *Input of a Single Template File.*

Description

Read template sequences from a FASTA or CSV file.

Usage

```
read_templates_single(
  template.file,
  hdr.structure = NULL,
  delim = NULL,
  id.column = NULL,
  rm.keywords = NULL,
  remove.duplicates = FALSE,
  fw.region = c(1, 30),
  rev.region = c(1, 30),
  gap.character = "-",
  run = NULL
)
```

Arguments

template.file	Path to a FASTA or CSV file containing the template sequences.
hdr.structure	A character vector describing the information contained in the FASTA headers. In case that the headers of fasta.file contain template group information, please include the keyword "GROUP" in hdr.structure.
delim	Delimiter for the information in the FASTA headers.
id.column	Field in the header to be used as the identifier.
rm.keywords	A vector of keywords that are used to remove templates whose headers contain any of the keywords.
remove.duplicates	Whether duplicate sequence shall be removed.
fw.region	The positional interval from the template 5' end specifying the binding sites for forward primers.

rev.region	The positional interval from the template 3' end specifying the binding sites for reverse primers.
gap.character	The character in the input file representing gaps. Gaps are automatically removed upon input.
run	An identifier for the template sequences.

Details

When supplying a FASTA file with template sequences, the input arguments `hdr.structure`, `delim`, `id.column`, `rm.keywords`, `remove.duplicates`, `fw.region`, `rev.region`, `gap.character`, and `run` are utilized. Most importantly, `hdr.structure` and `delim` should match the FASTA header structure. When supplying a CSV file with template sequences, the data are loaded without any modification and the CSV file should represent an object of class [Templates](#), which can be stored using the [write_templates](#) function.

Value

An object of class `Templates`.

relax.constraints	<i>Relaxation of Constraints</i>
-------------------	----------------------------------

Description

Relax constraints trying to reach the target coverage ratio.

Usage

```
relax.constraints(
  settings,
  filtered.df,
  excluded.df,
  stat.df,
  template.df,
  mode.directionality = c("fw", "rev"),
  required.cvg,
  target.temps = NULL,
  results.loc = NULL
)
```

Arguments

settings	A <code>DesignSettings</code> object.
filtered.df	Data set of primers that fulfilled all constraints of the filtering procedure.
excluded.df	Data frame with excluded primers from the first filtering round.
stat.df	Data frame with statistics from filtering.

template.df	Template data frame.
mode.directionality	Primer direction.
required.cvg	Required ratio of covered templates.
target.temps	Target melting temperature values.
results.loc	The location where intermediary results should be stored.

Value

A list containing information about the relaxation as well as the filtered primers.

relax.opti.constraints

Relaxation of Optimization Constraints

Description

Relax optimization constraints.

Usage

```
relax.opti.constraints(
  cur.opti.constraints,
  initial.opti.limits,
  initial.opti.constraints
)
```

Arguments

cur.opti.constraints
List with optimization constraint settings.

initial.opti.limits
Initial optimization limits.

initial.opti.constraints
Initial optimization constraints.

Value

Relaxed optimization constraints.

remove.redundant.cols *Removal of Redundant Primers.*

Description

Removes redundant primers from an optimal solution.

Usage

```
remove.redundant.cols(S, cvg.matrix)
```

Arguments

S	Indices of primers that are selected in an optimal solution.
cvg.matrix	Binary matrix of coverage events.

Details

An optimal solution can contain primers with redundant coverage when using presolve or greedy optimization.

Value

Updated indices of selected primers S such that indices representing primers with redundant coverage are removed.

remove.seqs.by.keyword
Removal of Partial Sequences.

Description

Removes partial template sequences.

Usage

```
remove.seqs.by.keyword(template.df, keyword = "partial")
```

Arguments

template.df	Template data frame.
Header	keywords indicating templates that should be excluded.

Value

Template data frame with partial sequences removed.

```
rename.constraint.options
```

Renaming of Constraint Options.

Description

Renames the input list with constraint options.

Usage

```
rename.constraint.options(constraint.options)
```

Arguments

```
constraint.options
```

A list with constraint options.

Value

A list with renamed constraint options.

```
render_report
```

Renders an rmarkdown file using Pandoc.

Description

Creates a PDF report using rmarkdown and Pandoc by passing the specified params to the mark-down file given by report_template and storing the PDF in out.file.

Usage

```
render_report(params, report_template, out.file)
```

Arguments

```
params
```

A list with parameters for the R markdown parser.

```
report_template
```

A character vector giving the basename of the Rmarkdown template to use for report creation.

```
out.file
```

The filename of the report PDF to be created.

Value

Creates a PDF in out.file if successful.

reorder.primer.table	<i>Reorder Primers</i>
----------------------	------------------------

Description

Reorders a primer set according to the IDs of primers.

Usage

```
## S3 method for class 'primer.table'
reorder(filtered.primers, primer.ID.order)
```

Arguments

filtered.primers	Primer data frame.
primer.ID.order	new ordering of IDs in the data frame.

Value

Reordered primer data frame.

restriction_ali	<i>Identification of Badly Fitting Regions.</i>
-----------------	---

Description

Identify regions in the templates where the primers are not very complementary. These regions indicate possible restriction enzyme adapters.

Usage

```
restriction_ali(primer.seqs, template.seqs, search.hits)
```

Arguments

primer.seqs	Primer sequences.
template.seqs	Template sequences.
search.hits	Template substrings that agree well with the input primers.

Value

A list with putative restriction sites for every primer.

restriction_hits	<i>Identification of Restriction Sites.</i>
------------------	---

Description

Identifies restriction sites in a list with putative restriction sites provided by `bad.regions` using a data frame of restriction sites given by `DB`.

Usage

```
restriction_hits(bad.regions, DB)
```

Arguments

<code>DB</code>	A data frame with restriction enzyme sites.
<code>bad.region</code>	<code>IRanges</code> with possible adapter sites.

Value

A boolean data frame indicating the presence of adapters for all considered restriction sites.

restriction_match	<i>Identification of Sequence Matches.</i>
-------------------	--

Description

Determines the most similar template sequence for every input primer sequence. Used to identify regions for alignment for the identification of restriction sites.

Usage

```
restriction_match(primer.seqs, template.seqs)
```

Arguments

<code>primer.seqs</code>	Primer sequences.
<code>template.seqs</code>	Template sequences.

Value

A vector with the template regions matching the `primer.seqs` best.

`retrieve.leader.region`*Retrieval of Binding Regions*

Description

Retrieves information about individual binding regions.

Usage

```
retrieve.leader.region(  
  template.df,  
  direction = c("fw", "rev"),  
  start,  
  end,  
  gap.char,  
  init.from.leader  
)
```

Arguments

<code>template.df</code>	Template data frame.
<code>direction</code>	Identify forward and reverse.
<code>start</code>	Start positions.
<code>end</code>	End positions.
<code>gap.char</code>	The character for gaps in alignments.
<code>init.from.leader</code>	Whether the binding regions are initialized from leader sequences.

Value

Data frame with information on allowed binding regions.

`rev.comp.sequence` *Reverse complement of a sequence*

Description

Computes the reverse complement of the input sequences.

Usage

```
## S3 method for class 'comp.sequence'  
rev(seq)
```

Arguments

seq the input strings

Value

The reverse complement of the input sequences.

rev.sequence	<i>Reversion of a sequence</i>
--------------	--------------------------------

Description

Reverses the input sequences.

Usage

```
## S3 method for class 'sequence'  
rev(seq)
```

Arguments

seq the input sequence.

Value

The input sequence in reverse order.

runTutorial	<i>The openPrimeR Tutorial.</i>
-------------	---------------------------------

Description

Starts a Shiny app containing the openPrimeR tutorial, which was built using the learnr package. The application starts locally and should open a new tab in your default browser. If no browser is opened, please consider the console output to identify the local port on which the server is running.

Usage

```
runTutorial(dev = FALSE)
```

Arguments

dev A logical indicating whether to start the development version of the tutorial (default: FALSE).

Value

Opens the openPrimeR tutorial in a web browser.

Note

The Shiny app can be started only if you fulfill all of the suggested package dependencies for the Shiny framework, so please ensure that you've installed openPrimeR including all suggested dependencies.

Examples

```
## Not run:  
# Open the tutorial  
if (interactive()) {  
  runTutorial()  
}  
  
## End(Not run)
```

sanitize_path

Sanitization of Filename.

Description

Ensures that a filename is valid for the file system.

Usage

```
sanitize_path(path, suffix = "", sub.char = "_")
```

Arguments

path	The path to the file to be sanitized, without file extension.
suffix	The suffix (e.g. ".png") of a file.
sub_char	The character used to replacing disallowed chars.

Value

The sanitized filename

score.conservation	<i>Conservation Scores</i>
--------------------	----------------------------

Description

Scores the conservation of alignment regions.

Usage

```
score.conservation(primer.range, ali.entropy)
```

Arguments

primer.range	A data frame with starts/ends of primers.
ali.entropy	Entropies corresponding to the alignment

Value

Entropies indicating conservation (similarity) of regions.

Scoring	<i>Scoring Functions.</i>
---------	---------------------------

Description

score_degen	Determines the degeneration score of a sequence.
score_conservation	Determines the sequence conservation scores of a set of templates using Shannon entropy.
score_primers	Computes scores for a set of primers based on the deviations of the primers from the constraints.

Usage

```
score_conservation(template.df, gap.char = "-", win.len = 30, by.group = TRUE)

score_degen(seq, gap.char = "-")

score_primers(
  primer.df,
  settings,
  active.constraints = names(constraints(settings)),
  alpha = 0.5
)
```

Arguments

<code>template.df</code>	A Templates object providing the set of templates.
<code>gap.char</code>	The gap character in the sequences. The default is "-".
<code>win.len</code>	The size of a window for evaluating conservation. The default window size is set to 30.
<code>by.group</code>	Whether the determination of binding regions should be stratified according to the groups defined in <code>template.df</code> . The default is TRUE.
<code>seq</code>	A list of vectors containing individual characters of a nucleotide sequence.
<code>primer.df</code>	A Primers object containing the primers.
<code>settings</code>	A DesignSettings object containing the analysis settings.
<code>active.constraints</code>	A character vector of constraint identifiers that are considered for scoring the primers.
<code>alpha</code>	A numeric that is used to determine the trade-off between the impact of the maximal observed deviation and the total deviation. At its default alpha is set to 0.5 such that the maximal deviation and the total deviation have an equal weight when computing the penalties.

Details

`score_degen` computes the degeneration of an ambiguous sequence by considering the number of unambiguous sequences that are represented by the the ambiguous sequence. Let a sequence S of length n be represented by a collection of sets such that

$$S = s_1, s_2, \dots, s_n$$

where s_i indicates the set of unambiguous bases found at position i of the primer. Then the degeneracy D of a primer can be defined as

$$D = \prod_i |s_i|$$

where $|s_i|$ provides the number of disambiguated bases at position i .

`score_primers` determines the penalty of a primer in the following way. Let d be a vector indicating the absolute deviations from individual constraints and let p be the scalar penalty that is assigned to a primer. We define

$$p = \alpha \cdot \max_i d_i + \sum_i (1 - \alpha) \cdot d_i$$

such that for large values of alpha the maximal deviation dominates giving rise to a local penalty (reflecting the largest absolute deviation) and for small alpha the total deviation dominates giving rise to a global penalty (reflecting the sum of constraint deviations). When alpha is 1 only the most extreme absolute deviation is considered and when alpha is 0 the sum of all absolute deviations is computed.

Value

A list containing Entropies and Alignments. Entropies is a data frame with conservation scores. Each column indicates a position in the alignment of template sequences and each row gives the entropies of the sequences belonging to a specific group of template sequences. Alignments is a list of DNABin objects, where each object gives the alignment corresponding to one group of template sequences.

score_degen finds the number of unambiguous sequences that are represented by seq.

score_primers returns a data frame containing scores for individual primers.

Note

score_conservation requires the MAFFT software for multiple alignments (<http://mafft.cbrc.jp/alignment/software/>).

Examples

```
## Not run:
data(Ippolito)
entropy.data <- score_conservation(template.df, gap.char = "-", win.len = 18, by.group = TRUE)

## End(Not run)
# Compute degeneration for sequences with differing number of ambiguous bases
seq <- strsplit(c("ctggaattacggtacc", "taggaaccggrtaagc", "rtaasrygtar"), split = "")
degen <- score_degen(seq)

# Score the primers
data(Ippolito)
primer.scores <- score_primers(primer.df, settings)
```

select.allowed.binding.events
Selection of Binding Events

Description

Selects primer binding events that are within the allowed binding regions.

Usage

```
select.allowed.binding.events(
  bound.fw,
  bound.to.allowed.region.fw,
  allowed.other.binding.ratio
)
```


Arguments

- `bound.fw` Indices of covered templates of a single primer.
- `bound.to.allowed.region.fw` Corresponding allowed binding regions.
- `allowed.other.binding.ratio` The ratio of other binding events. If this is different from 0, disallowed binding events will also be reported.

Value

The indices of the allowed binding events.

<code>select.best.ILP</code>	<i>Selection of Best ILP</i>
------------------------------	------------------------------

Description

Selects the best solution from multiple solved ILP instances.

Usage

`select.best.ILP(ILP.df)`

Arguments

- `ILP.df` Data frame with ILP result properties.

Value

The index of the best solution.

<code>select.best.opti.result</code>	<i>Selection of Best Greedy Result</i>
--------------------------------------	--

Description

Selects best greedy primer data set.

Usage

`select.best.opti.result(opti.results, template.df)`

Arguments

opti.results	List with primer data frames for different target melting temperatures.
template.df	Template data frame.

Value

The index of the best primer data set.

```
select.best.primer.idx
```

Greedy Choice

Description

Selects the currently best primer for Greedy primer selection.

Usage

```
select.best.primer.idx(
  result,
  primers,
  deltaG.cutoff,
  target.temp,
  primer_conc,
  na_salt_conc,
  mg_salt_conc,
  k_salt_conc,
  tris_salt_conc
)
```

Arguments

result	Data frame of current optimized primer data set that is to be augmented.
primers	Data frame of candidate primers for addition to result.
deltaG.cutoff	Free energy cutoff for cross-dimerization.
target.temp	Target annealing temperature in Celsius.
primer_conc	Primer concentration.
na_salt_conc	Sodium ion concentration.
mg_salt_conc	Magnesium ion concentration.
k_salt_conc	Potassium ion concentration.
tris_salt_conc	Tris ion concentration.

Value

The index of a suitable primer according to Greedy selection.

`select.best.primer.set`*Selection of Best Primer Set.*

Description

Selects the best primer set according to coverage and melting temperature differences among primers in the set.

Usage

```
select.best.primer.set(stats)
```

Arguments

stats	Statistics of the primer sets to be evaluated.
-------	--

Value

The index of the best primer set.

`select.binding.events` *Selection of Individual Binding Events*

Description

Selects only binding events of interest.

Usage

```
select.binding.events(fw.binding.filtered, p.idx)
```

Arguments

fw.binding.filtered	IRanges with binding events.
p.idx	Index of binding events to keep.

Value

An IRanges object containing only the selected binding events.

select.constraints	<i>Selection of Constraints.</i>
--------------------	----------------------------------

Description

Selects constraints that can be computed according to installed third-party software. This function is only used for initializing the 'constraint_order' option.

Usage

```
select.constraints(active.constraints)
```

Arguments

active.constraints	A vector whose names give the constraints to be checked.
--------------------	--

Value

A vector of useable constraint identifiers.

select.min.cross.idx	<i>Selection of cross dimer index</i>
----------------------	---------------------------------------

Description

Select the index with the smallest DeltaG value.

Usage

```
select.min.cross.idx(deltaG, primers)
```

Arguments

deltaG	Data frame with thermodynamic info.
primers	The corresponding primers.

Value

The indices with smallest DeltaG for every primer.

```
select.primer.region.by.conservation
```

Selection by Conservation

Description

Selects primer regions for initialization of primers according to their conservation scores.

Usage

```
select.primer.region.by.conservation(  
  primer.range,  
  ali.entropy,  
  conservation,  
  bin,  
  gap.char = "-"  
)
```

Arguments

<code>primer.range</code>	Data frame with primer starts/stops.
<code>ali.entropy</code>	Entropy values for the alignment.
<code>conservation</code>	Desired ratio of primer conservation. Only regions with a conservation of at least conservation are considered for the initialization of primers.
<code>bin</code>	DNABin alignment of templates.
<code>gap.char</code>	The character for alignment gaps.

Details

The conservation scores are computed using the entropies computed from the alignment of the template sequence regions of interests.

Value

Updated primer regions according to the desired conservation.

select.primers.by.cvg *Greedy Optimization.*

Description

Greedy approach for solving the primer set coverage problem.

Usage

```
select.primers.by.cvg(
  primers,
  settings,
  template.df,
  mode.directionality = c("fw", "rev"),
  required.cvg = 1,
  allowed.mismatches,
  primer_conc,
  na_salt_conc,
  mg_salt_conc,
  k_salt_conc,
  tris_salt_conc,
  template_conc,
  allowed.other.binding.ratio,
  allowed.stop.codons,
  allowed.region.definition = c("within", "any"),
  disallowed.mismatch.pos,
  target.temps = NULL,
  fw.primers = NULL,
  updateProgress = NULL
)
```

Arguments

primers	Primer data frame to be optimized.
settings	A DesignSettings object.
template.df	Template data frame.
mode.directionality	Primer direction.
required.cvg	Target coverage ratio.
allowed.mismatches	The number of mismatches primers are allowed to have with the templates.
primer_conc	Primer concentration.
na_salt_conc	Sodium ion concentration.
mg_salt_conc	Magensium ion concentration.

k_salt_conc	Potassium ion concentration.
tris_salt_conc	Tris ion concentration.
template_conc	Template data frame.
allowed.other.binding.ratio	Ratio of primers allowed to bind to non-target regions.
allowed.stop.codons	Consider mismatch binding events that induce stop codons.
allowed.region.definition	Definition of the target binding sites used for evaluating the coverage. If allowed.region.definition is within, primers have to lie within the allowed binding region. If allowed.region.definition is any, primers have to overlap with the allowed binding region. The default is that primers have to bind within the target binding region.
disallowed.mismatch.pos	The number of positions from the primer 3' end where mismatches should not be allowed. All primers binding templates with mismatches within disallowed.mismatch.pos from the 3' end are disregarded.
target.temps	Target melting temperatures for optimized sets in Celsius.
fw.primers	List with already optimized primer data frames corresponding to target.temps.
updateProgress	Shiny progress callback function.

Value

List with optimization data.

select_best_binding	<i>Selection of Best (smallest number of mismatches) Binding Event per Template Coverage Event.</i>
---------------------	---

Description

Selection of Best (smallest number of mismatches) Binding Event per Template Coverage Event.

Usage

```
select_best_binding(binding, fw.mm.info)
```

Arguments

binding	Binding information.
fw.mm.info	Info about mismatches.

Value

A list with entries 'fw' and 'rev' giving the best indices of primers.

selenium.installed	<i>Determination if Selenium is installed.</i>
--------------------	--

Description

Checks whether selenium module for python is installed on the system.

Usage

```
selenium.installed()
```

Value

TRUE is selenium for python is available, FALSE otherwise.

set.new.constraint.value	<i>Update Constraint Settings.</i>
--------------------------	------------------------------------

Description

Updates the constraint settings with new values. Sets to the maximal observed values within the limits or less if relax.speed is less than 1.

Usage

```
set.new.constraint.value(values, relax.speed, cur.limits, cur.setting)
```

Arguments

values	Observed constraint values considered for the update.
relax.speed	The speed at which the constraints should be relaxed. This value should be in the interval [0,1].
cur.limits	List with current relaxation limits.
cur.setting	List with current constraint settings.

Value

Relaxed constraint settings according to the given values and cur.limits.

set.new.limits	<i>Relaxation of Constraint Limits.</i>
----------------	---

Description

Relaxes the constraint limits by moving according to the difference between the initial.limits and initial.constraints.

Usage

```
set.new.limits(  
  cur.limits,  
  initial.limits,  
  initial.constraints,  
  con.name = NULL  
)
```

Arguments

- cur.limits List with current constraint settings.
- initial.limits List with initial coonstraint limits.
- initial.constraints List with initial constraint settings before relaxing.
- con.name The constraint for which the settings are to be changed.

Value

A list with relaxed constraint limits.

Settings	<i>Settings Functionalities.</i>
----------	----------------------------------

Description

DesignSettings The DesignSettings class encapsulates all settings for designing and evaluating primer sets. Upon loading an XML file, the DesignSettings class checks whether the defined constraints can be applied by identifying whether the requirements for external programs are fulfilled. If the requirements are not fulfilled, the affected constraints are removed from the loaded DesignSettings object and a warning is issued. The loaded constraints are automatically ordered according to the option openPrimeR.constraint_order such that the runtime of the [design_primers](#) and [filter_primers](#) functions is optimized.

constraints Gets the active constraints of the provided DesignSettings object.

constraints<- Sets the active constraints of the provided DesignSettings object.

cvg_constraints Gets the coverage constraints of the provided DesignSettings object.

`cvg_constraints<-` Sets the coverage constraints of the provided `DesignSettings` object.
`conOptions` Gets the constraint settings of the provided `DesignSettings` object.
`conOptions<-` Sets the constraint settings of the provided `DesignSettings` object.
`constraintLimits` Gets the constraint limits that are defined in the provided `DesignSettings` object.
`constraintLimits<-` Sets the constraint limits of the provided `DesignSettings` object.
`PCR` Gets the PCR conditions that are defined in the provided `DesignSettings` object.
`PCR<-` Sets the PCR conditions that are defined in the provided `DesignSettings` object.
`ConstraintSettings` The `ConstraintSettings` class encapsulates the constraints on the physicochemical properties of primers.
`CoverageConstraints` The `CoverageConstraints` class encapsulates the conditions under which the coverage of primers is evaluated.
`PCR_Conditions` The `PCR_Conditions` class encapsulates the PCR conditions for the computation of primer properties.
`ConstraintOptions` The `ConstraintOptions` class encapsulates the options for constraint computations.
`parallel_setup` Registers the specified number of cores with the parallel backend.

Usage

```

constraints(x)

## S4 method for signature 'DesignSettings'
constraints(x)

## S4 method for signature 'AbstractConstraintSettings'
constraints(x)

cvg_constraints(x)

## S4 method for signature 'DesignSettings'
cvg_constraints(x)

PCR(x)

## S4 method for signature 'DesignSettings'
PCR(x)

conOptions(x)

## S4 method for signature 'DesignSettings'
conOptions(x)

constraintLimits(x)
  
```

```

## S4 method for signature 'DesignSettings'
constraintLimits(x)

constraints(x) <- value

## S4 replacement method for signature 'DesignSettings,list'
constraints(x) <- value

## S4 replacement method for signature 'AbstractConstraintSettings,list'
constraints(x) <- value

cvg_constraints(x) <- value

## S4 replacement method for signature 'DesignSettings'
cvg_constraints(x) <- value

constraintLimits(x) <- value

## S4 replacement method for signature 'DesignSettings'
constraintLimits(x) <- value

PCR(x) <- value

## S4 replacement method for signature 'DesignSettings'
PCR(x) <- value

conOptions(x) <- value

## S4 replacement method for signature 'DesignSettings'
conOptions(x) <- value

parallel_setup(cores = NULL)

```

Arguments

x	A DesignSettings object.
value	An object to be used in one of the setters. For <code>constraints<-</code> and <code>constraintLimits<-</code>, a list with constraint settings or boundaries. Each list entry should have a permissible name and consist of at most two values providing the minimal and/or maximal allowed values, which have to be denominated via <code>min</code> and <code>max</code>. For <code>conOptions<-</code>, a list with constraint options. The permissible fields of the list and their types are documented in the ConstraintOptions class. For <code>cvg_constraints<-</code>, a list with coverage constraints. Each list entry must have a permissible name and contain a numeric vector with at most two components describing the minimal and/or maximal required values that are to be indicated via <code>min</code> and <code>max</code>. The permissible constraint identifiers are documented in the CoverageConstraints class. For <code>PCR<-</code>, a named list providing PCR conditions The permissible fields of the

	list and their types are documented in the PCR_Conditions class.
cores	A numeric providing the number of cores to use. The default is NULL such that half the number of available cores are used.

Details

Note that for the `DesignSettings` class, the fields `Input_Constraints`, `Input_Constraint_Boundaries`, and `Coverage_Constraints` should contain entries with at most two components using the fields `min` and/or `max`. The `Input_Constraint_Boundaries` should always be at least as general as the specified `Input_Constraints`.

For an overview of permissible constraints, please consider the [ConstraintSettings](#) documentation.

Value

The `ConstraintSettings` constructor defines a new `ConstraintSettings` object.

The `CoverageConstraints` constructor initializes a new `CoverageConstraints` object.

The `ConstraintOptions` constructor returns a new `ConstraintOptions` object.

The `PCR_Conditions` constructor defines a new `PCR_Conditions` object.

The `DesignSettings` constructor defines a `DesignSettings` object.

`constraints` gets a list with the active constraint settings.

`cvg_constraints` returns the list of active coverage constraints.

`PCR` gets the list of PCR conditions defined in the provided `DesignSettings` object.

`conOptions` returns a list with constraint options.

`constraintLimits` gets the list of constraint limits.

`constraints<-` sets the list of constraints in a `DesignSettings` object.

`cvg_constraints<-` sets the list of coverage constraints in the provided `DesignSettings` object.

`constraintLimits<-` sets the list of constraint limits in the provided `DesignSettings` object.

`PCR<-` sets the constraint options in the provided `DesignSettings` object.

`conOptions<-` sets the specified list of constraint options in the provided `DesignSettings` object.

`parallel_setup` returns NULL.

Slots

`Input_Constraints` A [ConstraintSettings](#) object specifying the desired target value ranges for primer properties.

`Input_Constraint_Boundaries` A [ConstraintSettings](#) object specifying the limits for relaxing the constraints during the primer design procedure. This slot may contain the same fields as the `Input_Constraints` slot, but the specified desired ranges should be at least as general as those specified in the `Input_Constraints` slot.

`Coverage_Constraints` A [CoverageConstraints](#) object specifying the constraints for computing the primer coverage.

`PCR_conditions` A [PCR_Conditions](#) object specifying the PCR-related settings.

constraint_settings A [ConstraintSettings](#) object providing options for the computation of individual physicochemical properties.

status Named boolean vector indicating which of the possible constraints are active (TRUE) and which are not (FALSE).

settings For [ConstraintSettings](#), a named list containing the settings for the active constraints. The list may contain the following fields:

primer_coverage: The required number of covered template sequences per primer.

primer_specificity: The required required specificity of primers in terms of a ratio in the interval [0,1].

primer_length: The required lengths of primer sequences.

gc_clamp: The desired number of GCs at primer 3' termini.

gc_ratio: The desired ratio of GCs in primers in terms of numbers in the interval [0,1].

no_runs: The accepted length homopolymer runs in a primer.

no_repeats: The accepted length of dinucleotide repeats in a primer.

self_dimerization: The lowest acceptable free energy [kcal/mol] for the interaction of a primer with itself. The identification of self dimers requires the software *OligoArrayAux* (see notes).

melting_temp_range: The desired melting temperature (Celsius) of primers. The accurate computation of melting temperatures requires the software *MELTING* (see notes).

melting_temp_diff: The maximal allowed difference between the melting temperatures (Celsius) of primers contained in the same set. The accurate computation of melting temperatures requires the software *MELTING* (see notes).

cross_dimerization: The lowest acceptable free energy [kcal/mol] for the interaction of a primer with another primer. The identification of cross dimers requires the software *OligoArrayAux* (see notes).

secondary_structure: The lowest acceptable free energy [kcal/mol] for the formation of primer secondary structures. Secondary structures are determined using the software *ViennaRNA* (see notes).

For [PCR_Conditions](#), a named list with PCR conditions. The following fields are possible:

use_taq_polymerase: A logical identifying whether you are performing PCR with a Taq polymerase (TRUE) or not (FALSE).

annealing_temp: The annealing temperature in Celsius that is to be used for evaluating the constraints defined in the [ConstraintSettings](#) object. If the annealing temperature field is not provided, a suitable annealing temperature is automatically computed using a rule of thumb (i.e. subtracting 5 from the melting temperature).

Na_concentration: The molar concentration of monovalent sodium ions.

Mg_concentration: The molar concentration of divalent magnesium ions.

K_concentration: The molar concentration of monovalent potassium ions.

Tris_concentration: The molar concentration of the Tris(hydroxymethyl)-aminomethan buffer.

primer_concentration: The molar concentration of the PCR primers.

template_concentration: The molar concentration of the PCR templates.

For [CoverageConstraints](#), a named list with constraint options. Each list entry should have an entry **min** and/or **max** in order to indicate the minimal and maximal allowed values, respectively. The following identifiers can be used as coverage constraints:

primer_efficiency: The desired efficiencies of primer-template amplification events in order to be considered as *covered*. `primer_efficiency` provides a value in the interval [0,1], which is based on **DECIPHER**'s thermodynamic model, which considers the impact of 3' terminal mismatches.

annealing_DeltaG: The desired free energies of annealing for putative coverage events between primers and templates. Typically, one would limit the maximally allowed free energy.

stop_codon: Whether coverage events introducing stop codons into the amplicons should be allowed or discarded. Here, a value of 1 indicates coverage events that induce stop codons. As such, setting both minimum and maximum to zero will disregard coverage events inducing stop codons, while setting the minimum to zero and the maximum to 1 will allow coverage events that induce stop codons.

substitution: Whether coverage events introducing substitutions into the amino acid sequence are considered or discarded. The same encoding as for `stop_codon` is used, that is, the value 1 indicates coverage events inducing substitutions. Hence, to prevent substitutions, the maximal value of `substitution` can be set to zero.

terminal_mismatch_pos: The position relative to the primer 3' terminal end for which mismatch binding events should be allowed, where the last base in a primer is indicated by position 1. For example, setting the minimal value of `terminal_mismatch_pos` to 7 means that only coverage events that do not have a terminal mismatch within the last 6 bases of the primer are allowed.

coverage_model: Use a logistic regression model combining the free energy of annealing and 3' terminal mismatch positions to determine the expected rate of false positive coverage calls. Using `coverage_model`, you can specify the allowed ratio of falsely predicted coverage events. Typically, one would limit the maximal allowed rate of false positives. Note that setting a small false positive rate will reduce the sensitivity of the coverage calls (i.e. true positives will be missed).

For `ConstraintOptions`, a named list with constraint options. The following fields are permissible:

allowed_mismatches: The maximal number of allowed mismatches between a primer and a template sequence. If the number of mismatches of a primer with a template exceeds the specified value, the primer is not considered to cover the corresponding template when the coverage is being computed.

allowed_other_binding_ratio: Ratio of allowed binding events outside the target binding ratio. This value should be in the interval [0,1]. If the specified value is greater than zero, all coverage events outside the primer binding region are reported. If, however, the identified ratio of off-target events should exceed the allowed ratio, a warning is issued. If `allowed_other_binding_ratio` is set to 0, only on-target primer binding events are reported. The setting of `allowed_other_binding_ratio` is ignored when designing primers, which always uses a value of 0.

allowed_region_definition: The definition of the target binding regions that is used for evaluating the coverage. In case that `allowed_region_definition` is `within`, primers have to lie within the allowed binding region. If `allowed_region_definition` is `any`, primers only have to overlap with the target binding region.

hexamer_coverage: If `hexamer_coverage` is set to "active", primers whose 3' hexamer (the last 6 bases) is fully complementary to the corresponding template region are automat-

ically considered to cover the template. If `hexamer_coverage` is set to `inactive`, hexamer complementarity does not guarantee template coverage.

primer_coverage

Computing the primer coverage involves identifying which templates are expected to be amplified (covered) by which primers. The `primer_coverage` constraint determines the minimal and maximal number of coverage events per primer that are required. The computation of primer coverage is governed by the coverage constraints postulated via [CoverageConstraints](#) and the constraint options defined via [ConstraintOptions](#).

primer_specificity

Primer specificity is automatically determined during the primer coverage computations but the constraint is only checked when the `primer_specificity` field is available. The specificity of a primer is defined as its ratio of on-target vs total coverage events (including off-target coverage). Low-specificity primers should be excluded as they may not amplify the target region effectively.

primer_length

The length of a primer is defined by its number of bases. Typical primers have lengths between 18 and 22. Longer primers may guarantee higher specificities.

gc_clamp

The GC clamp refers to the presence of GCs at the 3' end of a primer. For the `gc_clamp` constraint, we consider the number of 3' terminal GCs. For example, the primer *actgaaatttcaccg* has a GC clamp of length 3. The presence of a GC clamp is supposed to aid the stability of the polymerase complex. At the same time, long GC clamps should be avoided.

no_runs

Homopolymer runs (e.g. the primer *aaaaa* has a run of 5 A's) may lead to secondary structure formation and unspecific binding and should therefore be avoided.

no_repeats

Dinucleotide repeats (e.g. the primer *tatata* has 3 TA repeats) should be avoided for the same reason a long homopolymer runs.

self_dimerization

Self dimerization refers to a primer that binds to itself rather than to one of the templates. Primers exhibiting self dimers should be avoided as they may prevent the primer from amplifying the templates. Therefore primers with small free energies of dimerization should be avoided.

melting_temp_range

The melting temperature is the temperature at which 50 are in duplex with templates and 50 Hence, primers exhibiting high melting temperatures have high affinities to the templates, while primers with small melting temperatures have small affinities. The melting temperatures of the primers determine the annealing temperature of the PCR, which is why the melting temperatures of the primers should not deviate too much (see `melting_temp_diff`).

melting_temp_diff

The differences between the melting temperatures of primers in a set of primers should not deviate too much as the annealing temperature of a PCR should be based on the smallest melting temperature of a primer in the set. If there are other primers in the set exhibiting considerably higher melting temperatures, these primers may bind inspecifically due to the low annealing temperature.

cross_dimerization

When two different primers bind to each other rather than to the templates, this is called cross dimerization. Cross dimerization should be prevent at all costs because such primers cannot effectively amplify their target templates. Cross dimerizing primers can be excluding primers exhibiting small free energies of cross dimerization.

secondary_structure

When a primer exhibits secondary structure, this may prevent it from binding to the templates. To prevent this, primers with low free energies of secondary structure formation can be excluded.

Note

The following external programs are required for constraint computations:

MELTING (<http://www.ebi.ac.uk/biomodels/tools/melting/>): Thermodynamic computations (optional) for determining melting temperatures for the constraints `melting_temp_diff` and `melting_temp_range`

OligoArrayAux (<http://unafold.rna.albany.edu/OligoArrayAux.php>): Thermodynamic computations used for computing `self_dimerization` and `cross_dimerization`. Also required for computing `primer_coverage` when a constraint based on the free energy of annealing is active.

ViennaRNA (<http://www.tbi.univie.ac.at/RNA/>): Secondary structure predictions used for the constraint `secondary_structure`

The following external programs are required for computing the coverage constraints:

OligoArrayAux (<http://unafold.rna.albany.edu/OligoArrayAux.php>): Thermodynamic computations used for computing the coverage constraints `annealing_DeltaG`, `primer_efficiency`, and `coverage_model`

See Also

[read_settings](#) for reading settings from XML files, [write_settings](#) for storing settings as XML files, [constraints](#) for accessing constraints, [constraintLimits](#) for accessing constraint boundaries, [cvg_constraints](#) for accessing coverage constraints, [conOptions](#) for accessing constraint options, [PCR](#) for accessing the PCR conditions.

Examples

```
# Initializing a new 'ConstraintSettings' object:
constraint.settings <- new("ConstraintSettings")
# Retrieving the constraint settings from a 'DesignSettings' object:
data(Ippolito) # loads a 'DesignSettings' object into 'settings'
constraints(settings)
# Modifying the constraint settings:
constraints(settings)$no_runs["max"] <- 10
constraints(settings) <- constraints(settings)[names(constraints(settings)) != "gc_clamp"]

# Initialize a new 'CoverageConstraints' object:
cvg.constraints <- new("CoverageConstraints")
# Retrieving the coverage constraints from a 'DesignSettings' object:
data(Ippolito) # loads a 'DesignSettings' object into 'settings'
cvg_constraints(settings)
# Modifying the coverage constraints
cvg_constraints(settings)$primer_efficiency["min"] <- 0.001

# Initialize a new 'ConstraintOptions' object:
constraint.options <- new("ConstraintOptions")
# Retrieve the constraint options from a 'DesignSettings' object:
data(Ippolito) # loads a 'DesignSettings' object into 'settings'
conOptions(settings)
# Prevent off-target binding:
conOptions(settings)$allowed_other_binding_ratio <- 0

# Initialize a new 'PCR_Conditions' object:
PCR.conditions <- new("PCR_Conditions")
# Retrieving the PCR conditions from a 'DesignSettings' object:
data(Ippolito) # loads a 'DesignSettings' object into 'settings'
PCR(settings)
# Modifying the PCR conditions:
PCR(settings)$use_taq_polymerase <- FALSE

# Load a settings object
filename <- system.file("extdata", "settings",
                        "C_Taq_PCR_high_stringency.xml", package = "openPrimerR")
settings <- read_settings(filename)
# Modify the constraints
constraints(settings)$gc_clamp["min"] <- 0
# Modify the constraint limits for designing primers
constraintLimits(settings)$gc_clamp["max"] <- 6
# Modify the coverage constraints
cvg_constraints(settings)$primer_efficiency["min"] <- 0.001
# Modify the PCR conditions
```

```
PCR(settings)$Na_concentration <- 0.0001
# Modify the constraint options
conOptions(settings)$allowed_mismatches <- 0

# Load some settings
data(Ippolito)
# View the active constraints
constraints(settings)
# Require a minimal GC clamp extent of 0
constraints(settings)$gc_clamp["min"] <- 0
# View available constraints
settings

# Load some settings
data(Ippolito)
# View all active coverage constraints
cvg_constraints(settings)
# Increase the maximal false positive rate to increase the sensitivity of coverage predictions
cvg_constraints(settings)$coverage_model <- c("max" = 0.1)
# View available coverage constraints:
settings

# Load some settings
data(Ippolito)
# View the active constraint limits
constraintLimits(settings)
# Extend the GC relaxation limit
constraintLimits(settings)$gc_clamp <- c("min" = 0, "max" = 6)
# View available constraints
settings

# Load some settings
data(Ippolito)
# View the active PCR conditions
PCR(settings)
# Evaluate primers with a fixed annealing temperature
PCR(settings)$annealing_temperature <- 50 # celsius
# View available PCR conditions
settings

# Load some settings
data(Ippolito)
# View the active constraint options
conOptions(settings)
# Prevent mismatch binding events
conOptions(settings)$allowed_mismatches <- 0
# View available constraint options
settings
# Use two cores for parallel processing:
parallel_setup(2)
```

shannon.entropy	<i>Shannon Entropy</i>
-----------------	------------------------

Description

Computation of Shannon entropy for an alignment.

Usage

```
shannon.entropy(ali)
```

Arguments

ali	An alignment of primer sequences.
-----	-----------------------------------

Value

The Shannon entropy for the alignment.

solve.ILP	<i>Solve an ILP</i>
-----------	---------------------

Description

Constructs and solves an ILP and outputs a list with the results.

Usage

```
## S3 method for class 'ILP'
solve(
  cur.D,
  cur.G,
  cur.settings,
  cur.cvg.matrix,
  time.limit,
  required.cvg,
  primer.df,
  template.df
)
```

Arguments

<code>cur.D</code>	Binary dimerization matrix.
<code>cur.G</code>	Free energy matrix for cross-dimerization.
<code>cur.settings</code>	Current DesignSettings object.
<code>cur.cvg.matrix</code>	Binary coverage matrix.
<code>time.limit</code>	Time limit for solving the ILP in seconds.
<code>required.cvg</code>	The target coverage of the designed primer set.
<code>primer.df</code>	A Primers object.
<code>template.df</code>	A Templates object.
<code>deltaG.cutoff</code>	Cutoff for dimerization free energy.
<code>deltaG.limit</code>	Relaxation limit for free energy cutoff.

Value

List with ILP solution data.

<code>split_str_by_index</code>	<i>Split a sequence</i>
---------------------------------	-------------------------

Description

Splits a sequence at a specified positions

Usage

`split_str_by_index(target, index)`

Arguments

<code>target</code>	The target string.
<code>index</code>	The position for the split.

Value

List with splitted strings

stats_plot_data	<i>Combination of Filtering Stats.</i>
-----------------	--

Description

Summarizes filtering/relaxation statistics for plotting.

Usage

```
stats_plot_data(stats, stats.relax)
```

Arguments

stats	Statistics of the filtering procedure.
stats.relax	Statistic of the relaxation procedure.

Value

A data frame combinin filtering/relaxation stats.

store.filtering.sets	<i>Writes Filtering Data Sets to Disk.</i>
----------------------	--

Description

Writes Filtering Data Sets to Disk.

Usage

```
store.filtering.sets(  
  filtered.df,  
  excluded.df,  
  results.loc,  
  tag = "",  
  stat.df = NULL,  
  settings = NULL  
)
```

Arguments

filtered.df	A filtered Primers set.
excluded.df	A set of Primers that were excluded.
results.loc	The location where to store the data.
tag	A tag for the output files.
stat.df	Data frame with statistics of the filtering procedure.
settings	A DesignSettings object.

Value

No return value, writes output to disk.

<code>string.list.format</code>	<i>Format a String List.</i>
---------------------------------	------------------------------

Description

Formats a string list, summarizing values with percentages.

Usage

```
string.list.format(values, order.mode = c("percentage", "value"))
```

Arguments

- | | |
|-------------------------|---|
| <code>values</code> | The string list to format. |
| <code>order.mode</code> | How the result should be ordered. For "percentage", the strings are ordered by their percentages, while for "value", the strings are ordered by their values. |

Value

A formatted string with percentage annotations.

<code>string.list.format.total</code>
<i>Format Strings</i>

Description

Changes the representation of the comma-separated string input.

Usage

```
string.list.format.total(values)
```

Arguments

- | | |
|---------------------|---------------------------------------|
| <code>values</code> | A comma-separated string with values. |
|---------------------|---------------------------------------|

Value

A percentage-formatted representation of the input string.

string.to.IQR	<i>Conversion of Comma-Separated String to IQR String</i>
---------------	---

Description

Conversion of Comma-Separated String to IQR String

Usage

```
string.to.IQR(string.values)
```

Arguments

string.values A vector of comma-separated numeric strings.

Value

The IQR corresponding to the input string.

subset.ILP	<i>Subset ILP Constructor</i>
------------	-------------------------------

Description

Constructs an ILP for selecting optimal primer subsets.

Usage

```
## S3 method for class 'ILP'  
subset(primer.df, template.df, k)
```

Arguments

primer.df Primer data frame to be subsetted.
template.df Template data frame.
k Required number of primers to be selected.

Details

Here, "optimal" refers to a subset of a certain size that maximizes the coverage.

Value

An ILP for choosing the primer subset of size k with the largest coverage.

TemplatesFunctions	<i>Template Functionalities.</i>
--------------------	----------------------------------

Description

`adjust_binding_regions` Adjusts the existing annotation of binding regions by specifying a new binding interval relative to the existing binding region.

`assign_binding_regions` Assigns the primer target binding regions to a set of template sequences.

`update_template_cvg` Annotates the template coverage.

`select_regions_by_conservation` Computes Shannon entropy for the defined binding regions and determines the most conserved regions.

Usage

```
update_template_cvg(template.df, primer.df, mode.directionality = NULL)
```

```
adjust_binding_regions(template.df, region.fw, region.rev)
```

```
assign_binding_regions(
  template.df,
  fw = NULL,
  rev = NULL,
  optimize.region = FALSE,
  primer.length = 20,
  gap.char = "-"
)
```

```
select_regions_by_conservation(
  template.df,
  gap.char = "-",
  win.len = 30,
  by.group = TRUE,
  mode.directionality = c("both", "fw", "rev")
)
```

Arguments

<code>template.df</code>	An object of class <code>Templates</code> .
<code>primer.df</code>	An object of class <code>Primers</code> containing primers with annotated coverage that are to be used to update the template coverage in <code>template.df</code> .
<code>mode.directionality</code>	The directionality of primers/templates.
<code>region.fw</code>	Interval of new binding regions relative to the forward binding region defined in <code>template.df</code> .

<code>region.rev</code>	Interval of new binding regions relative to the reverse binding region defined in <code>template.df</code>
<code>fw</code>	Binding regions for forward primers. Either a numeric interval indicating a uniform binding range relative to the template 5' end or a path to a FASTA file providing binding sequences for every template. If <code>fw</code> is missing, only <code>rev</code> is considered.
<code>rev</code>	Binding regions for reverse primers. Either a numeric interval indicating a uniform binding range relative to the template 3' end or the path to a FASTA file providing binding sequences for every template. If <code>rev</code> is missing, only <code>fw</code> is considered.
<code>optimize.region</code>	If TRUE, the binding regions specified via <code>fw</code> and <code>rev</code> are adjusted such that binding regions that may form secondary structures are avoided. This feature requires ViennaRNA (see notes). If FALSE (the default), the input binding regions are not modified.
<code>primer.length</code>	A numeric scalar providing the probe length that is used for adjusting the primer binding regions when <code>optimize.region</code> is TRUE.
<code>gap.char</code>	The character in the input file representing gaps.
<code>win.len</code>	The extent of the desired primer binding region. This should be smaller than the <code>allowed.region</code> . The default is 30.
<code>by.group</code>	Shall the determination of binding regions be stratified according to the groups defined in <code>template.df</code> . By default, this is set to TRUE.

Details

When modifying binding regions with `adjust_binding_regions`, new binding intervals can be specified via `fw` and `rev` for forward and reverse primers, respectively. The new regions should be provided relative to the existing definition of binding regions in `template.df`. For specifying the new binding regions, position 0 refers to the first position after the end of the existing binding region. Hence, negative positions relate to regions within the existing binding region, while non-negative values relate to positions outside the defined binding region.

Binding regions are defined using `assign_binding_regions`, where the arguments `fw` and `rev` provide data describing the binding regions of the forward and reverse primers, respectively. To specify binding regions for each template individually, `fw` and `rev` should provide the paths to FASTA files. The headers of these FASTA file should match the headers of the loaded `template.df` and the sequences in the files specified by `fw` and `rev` should indicate the target binding regions.

To specify uniform binding regions, `fw` and `rev` should be numeric intervals indicating the allowed binding range for primers in the templates. Setting the forward interval to (1,30) indicates that the first 30 bases should be used for forward primers and specifying the reverse interval to (1,30) indicates that the last 30 bases should be used for reverse primer binding.

If `optimize.region` is TRUE, the input binding region is adjusted such that regions forming secondary structures are avoided.

Value

`update_template_cvg` returns an object of class `Templates` with updated coverage columns.

`adjust_binding_regions` returns a `Templates` object with updated binding regions.

`assign_binding_regions` returns an object of class `Templates` with newly assigned binding regions.

`select_regions_by_conservation` returns a `Templates` object with adjusted binding regions. The attribute `entropies` gives a data frame with positional entropies and the attribute `alignments` gives the alignments of the templates.

Note

`assign_binding_regions` requires the program ViennaRNA (<https://www.tbi.univie.ac.at/RNA/>) for adjusting the binding regions when `optimize.region` is set to `TRUE`.

`select_regions_by_conservation` requires the MAFFT software for multiple alignments (<http://mafft.cbrc.jp/alignment/s>)

Examples

```
# Annotate the coverage of the templates
data(Ippolito)
template.df <- update_template_cvg(template.df, primer.df)
data(Ippolito)
# Extend the binding region by one position
relative.interval <- c(-max(template.df$Allowed_End_fw), 0)
template.df.adj <- adjust_binding_regions(template.df, relative.interval)
# compare old and new annotations:
head(cbind(template.df$Allowed_Start_fw, template.df$Allowed_End_fw))
head(cbind(template.df.adj$Allowed_Start_fw, template.df.adj$Allowed_End_fw))
data(Ippolito)
# Assignment of individual binding regions
l.fasta.file <- system.file("extdata", "IMGT_data", "templates",
  "Homo_sapiens_IGH_functional_leader.fasta", package = "openPrimeR")
template.df.individual <- assign_binding_regions(template.df, l.fasta.file, NULL)
# Assign the first/last 30 bases as forward/reverse binding regions
template.df.uniform <- assign_binding_regions(template.df, c(1,30), c(1,30))
# Optimization of binding regions (requires ViennaRNA)
## Not run: template.df.opti <- assign_binding_regions(template.df, c(1,30), c(1,30),
  optimize.region = TRUE, primer.length = 20)

## End(Not run)
data(Ippolito)
new.template.df <- select_regions_by_conservation(template.df)
```

ungap_sequence

Ungapping of Sequences.

Description

Removes gaps from the input sequences.

Usage

```
ungap_sequence(seqs, gap.char = "-")
```

Arguments

- seqs The input character vector with sequences
- gap.char The character used to represent gaps.

Value

seqs with gaps removed.

unify.leaders	<i>Unification of Leaders</i>
---------------	-------------------------------

Description

Unifies individual binding regions for forward and reverse primers.

Usage

unify.leaders(l.seq.fw, l.seq.rev, lex.seq, gap.char)

Arguments

- l.seq.fw Data frame with binding information for forward primers.
- l.seq.rev Data frame with binding information for reverse primers.
- lex.seq Template data frame.
- gap.char The character for indicating alignment gaps.

Value

Template data frame with annotated binding regions.

update.binding.ranges.by.conservation	<i>Updates Binding Region in the Alignment by conservation.</i>
---------------------------------------	---

Description

Updates Binding Region in the Alignment by conservation.

Usage

```
## S3 method for class 'binding.ranges.by.conservation'
update(
  template.df,
  bins,
  entropy.df,
  gap.char = "-",
  win.len = 30,
  direction = c("fw", "rev")
)
```

Arguments

template.df	A Templates object.
bins	A list with DNABin alignments, one for each group of template sequences.
entropy.df	A data frame with entropy information.
gap.char	The gap character for alignments.
win.len	The desired length of the new binding region.
direction	The direction for which the binding range shall be adjusted.

Value

A Templates object with modified binding regions.

update.binding.regions

Update of Binding Regions.

Description

Updates the binding regions in the templates by providing new intervals for forward and reverse binding regions.

Usage

```
## S3 method for class 'binding.regions'
update(template.df, opti.regions)
```

Arguments

template.df	An object of class Templates.
opti.regions	List with new binding intervals. The list can contain the components fw and rev providing numeric vectors of length 2 providing the start and end of the binding regions in the templates, for forward and reverse binding regions, respectively.

Value

A Templates object with updated binding regions.

update.constraint.values

Update of Primer Constraints.

Description

Updates the input primer data frame with the computed constraint values.

Usage

```
## S3 method for class 'constraint.values'
update(constraint.df, constraint.values)
```

Arguments

constraint.df Primer data frame.
constraint.values
 Data frame with computed constraint values.

Value

A primer data frame with updated columns.

update.cvg.data

Update Coverage Information.

Description

Updates the coverage-related columns in the input primer data frame. Does not modify the entries of template-specific coverage columns such as primer efficiency (comma-separated values).

Usage

```
## S3 method for class 'cvg.data'
update(
  filtered.df,
  sel,
  template.df,
  mode = c("on_target", "off_target"),
  active.constraints
)
```

Arguments

filtered.df	Primer data frame.
sel	List with indices of covered templates to be retained, one list with template indices to keep per primer.
template.df	Template data frame.
mode	Either on_target to filter on-target binding events or off_target to filter off-target binding events. The corresponding sel argument should be different.
active.constraints	The active coverage constraints.

Details

Removes all coverage events of templates whose index is not in sel.

Value

A primer data frame with updated coverage information.

update.individual.binding.region

Adjustment of Existing Binding Regions for one Direction.

Description

Adjusts the existing annotation of binding regions by specifying an interval relative to the existing binding region.

Usage

```
## S3 method for class 'individual.binding.region'
update(min, max, template.df, mode.directionality)
```

Arguments

min	Position where binding should start.
max	End position of binding.
mode.directionality	Directionality of primers.
Template	data frame.

Details

Position 0 indicates the first position after the existing binding region. Hence, negative positions adjust the binding region towards the existing binding regions and non-negative positions extend the existing binding region definition away from the existing target region.

Value

Template data frame with updated binding regions.

update.opti.results	<i>Augmentation of Optimized Primer Data.</i>
---------------------	---

Description

Adds melting_temp_diff and cross_dimerization info to optimized sets.

Usage

```
## S3 method for class 'opti.results'
update(primer.df, settings, template.df)
```

Arguments

primer.df	A primer data frame.
settings	A DesignSettings object.

Value

An updated primer data frame.

update_primer_binding_regions	<i>Update of Primer Binding Regions.</i>
-------------------------------	--

Description

Updates the relative primer binding sites in the templates when the template binding regions have changed since the last coverage computation.

Usage

```
update_primer_binding_regions(primer.df, template.df, old.template.df)
```

Arguments

primer.df	A Primers data frame.
template.df	Templates with the new binding regions.
old.template.df	Templates with the old binding regions.

Value

A Primers object with updated relative binding positions.

update_primer_cvg	<i>Updates the Primer Coverage.</i>
-------------------	-------------------------------------

Description

Updates the most important columns in a primer data frame according to the selected coverage definition. Only coverage events with less or equal than the allowed number of mismatches according to the selected coverage definition will be retained.

Usage

```
update_primer_cvg(  
  primer.df,  
  template.df,  
  allowed.mismatches,  
  cvg.definition = c("constrained", "basic")  
)
```

Arguments

primer.df	A Primers object.
template.df	A Templates object.
allowed.mismatches	A numeric giving the maximal number of allowed mismatches.
cvg.definition	The definition of coverage to be used, either "constrained" or "basic".

Value

A primer data frame with modified coverage information.

validate_primers	<i>Validates a Primers Object.</i>
------------------	------------------------------------

Description

Checks whether a Primers object is valid or not.

Usage

```
validate_primers(object)
```

Arguments

object	An input data frame to be checked for being a primer data frame.
--------	--

Value

TRUE, if the object is valid, FALSE otherwise.

validate_templates	<i>Validates a Template Object.</i>
--------------------	-------------------------------------

Description

Checks whether a Templates object is valid or not.

Usage

```
validate_templates(object)
```

Arguments

object An input data frame to be checked for being a template data frame.

Value

TRUE, if the object is valid, FALSE otherwise.

view.cvg.primers	<i>View the Evaluated Primers.</i>
------------------	------------------------------------

Description

Creates a formatted primers table.

Usage

```
view.cvg.primers(  
  primer.df,  
  template.df,  
  mode.directionality,  
  view.cvg.individual = c("active", "inactive"),  
  for.shiny = TRUE  
)
```

Arguments

primer.df A Primers object.
template.df A Templates object.
mode.directionality The direction of the primers.
view.cvg.individual Whether information on individual coverage events should be retrained.
for.shiny Whether the table is intended for Shiny (HTML) or not.

Value

A formatted primer table.

view.dimer.df	<i>Formatted dimerization data.</i>
---------------	-------------------------------------

Description

Format a dimerization data frame for frontend output.

Usage

```
view.dimer.df(dimers, type = c("Self", "Cross"))
```

Arguments

dimers	Dimerization data frame.
type	Type of dimerization.

Value

A data frame whose columns are formatted in a user-readable way.

view.input.primers	<i>View the Input Primers.</i>
--------------------	--------------------------------

Description

Creates a formatted primers table.

Usage

```
view.input.primers(primer.df, mode.directionality, for.shiny = TRUE)
```

Arguments

primer.df	A Primers object.
mode.directionality	The direction of the primers.
for.shiny	Whether output is intended for Shiny.

Value

A formatted primer table.

view.primers	<i>View the Evaluated Primers.</i>
--------------	------------------------------------

Description

Creates a formatted primers table.

Usage

```
view.primers(primer.df, template.df)
```

Arguments

- primer.df A Primers object.
- template.df A Templates object.

Value

A formatted primer table.

view.primers.report	<i>View the Evaluated Primers in the Report.</i>
---------------------	--

Description

Creates a formatted primers table for the report PDF.

Usage

```
view.primers.report(primer.df, template.df)
```

Arguments

- primer.df A Primers object.
- template.df A Templates object.

Value

A formatted primer table.

visualize.all.results *Visualization of Design Results.*

Description

Visualizes all results from designing primers.

Usage

```
visualize.all.results(  
  sample,  
  filtering.results.loc,  
  opti.results.loc,  
  primer_conc,  
  na_salt_conc,  
  mg_salt_conc,  
  k_salt_conc,  
  tris_salt_conc,  
  settings,  
  mode.directionality,  
  used.settings,  
  required.cvg  
)
```

Arguments

sample	Identifier of the design run.
filtering.results.loc	
	Location of filtering results.
opti.results.loc	
	Location of optimization results.
primer_conc	Primer concentration.
na_salt_conc	Sodium ion concentration.
mg_salt_conc	Magensium ion concentration.
k_salt_conc	Potassium ion concentration.
tris_salt_conc	Tris ion concentration.
settings	The DesignSettings object.
mode.directionality	
	Strand direction for which primers were designed.
used.settings	A list with the used settings for optimization (fields "fw" and "rev").
required.cvg	The required coverage.
template_conc	Template concentration.

Value

Writes visualizations to files in.

`visualize.filtering.results`*Visualization of Filtering Results.*

Description

Visualizes the filtering results.

Usage

```
visualize.filtering.results(  
    sample,  
    results.loc,  
    mode.directionality,  
    excluded.df,  
    template.df,  
    filtered.df,  
    filtered.stats,  
    stats.relax,  
    primer_conc,  
    na_salt_conc,  
    mg_salt_conc,  
    k_salt_conc,  
    tris_salt_conc,  
    settings,  
    required.cvg  
)
```

Arguments

<code>sample</code>	Primer design run identifier.
<code>results.loc</code>	Location where the filtering results are stored.
<code>mode.directionality</code>	Design direction.
<code>excluded.df</code>	Data frame with excluded primers.
<code>template.df</code>	Template data frame.
<code>filtered.df</code>	Primer data frame containing the primers that passed the constraints.
<code>stats.relax</code>	Filtering statistics after relaxation.
<code>primer_conc</code>	Primer concentration.
<code>na_salt_conc</code>	Sodium ion concentration.
<code>mg_salt_conc</code>	Magensium ion concentration.
<code>k_salt_conc</code>	Potassium ion concentration.
<code>tris_salt_conc</code>	Tris ion concentration.

<code>settings</code>	A DesignSettings object.
<code>required.cvg</code>	The required coverage.
<code>template_conc</code>	Template concentration.

Value

Write-out of filtering results.

<code>were.constraints.relaxed</code>
<i>Check for Relaxation</i>

Description

Determines whether constraints where relaxed or not.

Usage

```
were.constraints.relaxed(used.constraints, input.constraints)
```

Arguments

<code>used.constraints</code>	The constraints that were used during the optimization.
<code>input.constraints</code>	The user-specified constraints.

Value

If `input.constraints` was relaxed TRUE is returned, otherwise FALSE.

<code>write.out.primer.info</code>	<i>Write Out Optimization Data</i>
------------------------------------	------------------------------------

Description

Writes out all data relating to the optimization of primers.

Usage

```
write.out.primer.info(  
  opti.results.loc,  
  optimal.primers.data,  
  mode.directionality,  
  settings,  
  sample.name,  
  template.df,  
  max.degen  
)
```

Arguments

opti.results.loc	Folder where optimization data reside.
optimal.primers.data	List with optimization results.
mode.directionality	Direction of primers.
settings	Settings used in the optimization procedure. List containing fw, rev settings.
sample.name	Name of template sample.
template.df	Template data frame.
max.degen	Maximal degeneracy of primers.

Value

Write-out of primer information to `opti.results.loc`.

xmlToChar	<i>Conversion of XML to Character.</i>
-----------	--

Description

Converts an XML object to a character string.

Usage

`xmlToChar(xml)`

Arguments

xml	An xml object to be converted to character.
-----	---

Value

A character vector.

Index

- * **Creation**
 - compute.Tm.sets, [69](#)
- * **Cross-dimerization**
 - compute.Tm.sets, [69](#)
- * **FALSE**
 - check.init.primer.length, [35](#)
- * **Melting**
 - compute.Tm.sets, [69](#)
- * **Sets.**
 - compute.Tm.sets, [69](#)
- * **Settings**
 - Settings, [241](#)
- * **Stratifies**
 - compute.Tm.sets, [69](#)
- * **Temperature**
 - compute.Tm.sets, [69](#)
- * **according**
 - compute.Tm.sets, [69](#)
- * **and**
 - compute.Tm.sets, [69](#)
- * **a**
 - compute.Tm.sets, [69](#)
- * **between**
 - compute.Tm.sets, [69](#)
- * **case**
 - compute.Tm.sets, [69](#)
- * **checked**
 - compute.Tm.sets, [69](#)
- * **checks**
 - compute.Tm.sets, [69](#)
- * **constraints.**
 - compute.Tm.sets, [69](#)
- * **datasets**
 - Data, [92](#)
- * **data**
 - compute.Tm.sets, [69](#)
- * **forward**
 - compute.Tm.sets, [69](#)
- * **frames**
 - compute.Tm.sets, [69](#)
- * **here,**
 - compute.Tm.sets, [69](#)
- * **internal**
 - AbstractConstraintSettings-class, [11](#)
 - add.coverage.constraints, [11](#)
 - add.dimerization.constraints, [12](#)
 - add.uniform.leaders.to.seqs, [12](#)
 - adjust.ORF.start, [13](#)
 - align.seqs, [13](#)
 - align.structures, [14](#)
 - ancestor_of, [17](#)
 - annealing.temp.rule.of.thumb, [17](#)
 - annotate.binding.events, [18](#)
 - apply.constraint, [18](#)
 - apply.constraint.list, [19](#)
 - assign_binding_regions.character, [20](#)
 - assign_binding_regions.numeric, [21](#)
 - augment.primer.cvg, [22](#)
 - batchify, [22](#)
 - batchify.simple, [23](#)
 - batchify.temp, [23](#)
 - build.gain.df, [24](#)
 - build.ILP.df, [24](#)
 - build.tool.overview, [25](#)
 - build_leader_df, [26](#)
 - call.melt, [26](#)
 - call.melt.single, [27](#)
 - cascaded.filter, [28](#)
 - cascaded.filter.quick, [29](#)
 - cbind.Primers, [30](#)
 - cbind.Templates, [31](#)
 - cbind2,Primers,ANY-method, [31](#)
 - cbind2,Templates,ANY-method, [32](#)
 - check.3prime.hexamers, [34](#)
 - check.3prime.mismatches, [34](#)
 - check.init.primer.length, [35](#)

- check.init.primer.length.single,
36
- check.mutations, 36
- check.template.constraints, 37
- check.tool.function, 38
- check.tool.installation, 38
- check_constraint_settings_validity,
40
- check_constraints_comparison, 39
- check_correspondence, 40
- check_cvg_constraints, 41
- check_interval, 42
- check_limit_value, 43
- check_limits, 42
- check_names, 43
- check_report_deps, 44
- check_restriction_sites_single, 44
- check_setting, 45
- check_settings_validity, 46
- combine.binding.events, 46
- combine.strings, 47
- comp, 47
- compare.constraints, 48
- comparison.cvg, 48
- comparison.stats.raw, 49
- complement.sequence, 49
- compute.all.cross.dimers, 50
- compute.all.cross.dimers.frontend,
51
- compute.all.cross.dimers.unfiltered,
52
- compute.all.primer.subsets.ILP, 53
- compute.all.self.dimers, 53
- compute.all.self.dimers.frontend,
54
- compute.basic.details, 55
- compute.constraints, 56
- compute.covered.Ta, 57
- compute.dimer.matrix, 58
- compute.efficiency, 59
- compute.empiric.melting.temp, 60
- compute.gc.ratio, 60
- compute.melting.temps, 61
- compute.melting.temps.thermo, 61
- compute.mismatch.table, 62
- compute.primer.efficiencies, 63
- compute.secondary.structures, 64
- compute.sodium.equivalent.conc, 65
- compute.structure.vienna, 66
- compute.Ta, 66
- compute.template.secondary.structures,
67
- compute.Tm.baldino, 68
- compute.Tm.sets, 69
- compute.unique.covered.idx, 71
- compute_annealing_temp, 71
- con_select, 77
- condition, 72
- consecutive.GC.count, 73
- constraints.to.df, 73
- constraints.xml.format, 74
- constraints_to_unit, 74
- convert.from.iupac, 75
- convert.PCR.units, 75
- convert.temperature, 76
- convert.to.iupac, 76
- copy.melt.config, 77
- covered.primers.to.ID.string, 78
- covered.seqs.to.ID.string, 78
- covered.seqs.to.idx, 79
- create.constraint.table, 79
- create.constraint.XML, 80
- create.cvg.text, 81
- create.G.matrix, 81
- create.initial.primer.set, 82
- create.k.mers, 83
- create.kmer, 83
- create.options.table, 84
- create.other.table, 84
- create.PCR.table, 85
- create.primer.ranges, 85
- create.primers.naive, 86
- create.primers.tree, 87
- create.Tm.brackets, 88
- create.uniform.leaders, 89
- create_fulfilled_counts, 89
- create_report,list,list-method, 90
- create_report,Primers,Templates-method,
91
- design_primers.single, 93
- detect.gap.columns, 95
- dimerization.table, 96
- dir.copy, 96
- disambiguate.primers, 97
- estimate.cvg, 97
- estimate.cvg.dir, 98

eval.comparison.primers, 98
eval.constraints, 99
evaluate.basic.cvg, 100
evaluate.constrained.cvg, 101
evaluate.cvg, 101
evaluate.diff.primer.cvg, 102
evaluate.fw.rev.combinations, 103
evaluate.GC.clamp, 103
evaluate.primer.cvg, 104
evaluate.template.constraints, 104
exclude.cols, 105
filter.by.constraints, 106
filter.comparison.primers, 106
filter.primer.candidates, 107
filter.primer.set.opti, 108
filter_primers.by.Tm.delta, 110
filterLimits, 109
filters, 109
fix_constraint_boundaries, 110
format.constraints, 111
format.seq.ali, 111
format.seqs.tex, 112
get.3prime.mismatch.pos, 112
get.analysis.mode, 113
get.consensus.seq, 113
get.constraint.value.idx, 114
get.constraint.values, 114
get.coverage.matrix, 115
get.covered.templates, 115
get.cross.dimers, 116
get.cvg.constraint.settings, 116
get.cvg.gain, 117
get.delta.G, 118
get.dimer.data, 119
get.duplex.energies, 119
get.eval.cols, 120
get.extension, 121
get.ILP.vars, 121
get.init.file.name, 122
get.leader.exon.regions, 123
get.leader.exon.regions.single,
123
get.matches, 124
get.melting.temp.diff, 124
get.merge.idx, 125
get.missing.df, 125
get.ORFs, 126
get.other.constraint.settings, 126
get.PCR.settings, 127
get.plot.height, 128
get.primer.binding.idx, 128
get.primer.identifier.string, 129
get.redundant.cols, 130
get.relative.binding.pos, 130
get.run.names, 131
get.self.dimers, 131
get.sets.from.decisions, 132
get.static.tool.info, 132
get.tree.seqs, 133
get.unlist.idx, 133
get_constraint_deviation_data, 134
get_covered.vanilla, 134
get_cvg_stats,list-method, 135
get_cvg_stats,Primers-method, 136
get_max_set_coverage, 137
get_plot_primer_data, 137
get_primer_cvg_mm_plot_df, 138
get_report_fname, 139
get_template_cvg_data, 139
hclust.tree, 140
highlight.mismatch, 140
html.format.structure, 141
I.cvg, 141
ILPConstrained, 142
initialize.primer.set, 142
insert_str, 149
interleave, 149
J.cvg, 150
joule.to.cal, 150
listToXml, 151
merge.ambig.primers, 151
merge.binding.information, 152
merge.primer.entries, 153
merge.primer.entries.single, 153
merge.select, 154
merge.template.decisions, 154
mismatch.info, 155
mismatch.mutation.check, 155
mismatch.string.to.list, 156
modify.col.rep, 156
my.disambiguate, 157
my.error, 157
my.read.fasta, 158
my.warning, 158
my_ggsave, 159
my_rbind, 159

- nbr.of.repeats, [160](#)
- nbr.of.runs, [160](#)
- opti, [161](#)
- optilimits, [161](#)
- optimize.ILP, [162](#)
- optimize.primer.cvg, [163](#)
- optimize.template.binding.regions.dir, [164](#)
- optimize.template.binding.regions.single, [165](#)
- pair_primers, [168](#)
- parse.constraints, [169](#)
- parse.header, [169](#)
- parse.IMG.T.gene.groups, [170](#)
- parse.oligo.results, [170](#)
- plot.all.cvg.info, [171](#)
- plot.all.filtering.stats, [172](#)
- plot.Delta.DeltaG, [173](#)
- plot.dimer.dist, [173](#)
- plot.excluded.hist, [174](#)
- plot.filtering.runtime, [174](#)
- plot.filtering.stats, [175](#)
- plot.filtering.stats.cvg, [175](#)
- plot_constraint,list-method, [182](#)
- plot_constraint,Primers-method, [182](#)
- plot_constraint.histogram, [183](#)
- plot_constraint.histogram.nbr.mismatches, [184](#)
- plot_constraint.histogram.primer.efficienciers, [184](#)
- plot_constraint_deviation,list-method, [185](#)
- plot_constraint_deviation,Primers-method, [185](#)
- plot_constraint_fulfillment,list-method, [186](#)
- plot_constraint_fulfillment,Primers-method, [187](#)
- plot_cvg_constraints,list-method, [187](#)
- plot_cvg_constraints,Primers-method, [188](#)
- plot_primer.comparison.box, [189](#)
- plot_primer.comparison.mismatches, [190](#)
- plot_primer_binding_regions,list,list-method, [190](#)
- plot_primer_binding_regions,Primers,Templates-method, [191](#)
- plot_primer_cvg,list,list-method, [192](#)
- plot_primer_cvg,Primers,Templates-method, [193](#)
- plot_primer_cvg_mismatches, [193](#)
- plot_primer_cvg_unstratified, [194](#)
- plot_template_cvg,list,list-method, [195](#)
- plot_template_cvg,Primers,Templates-method, [195](#)
- plot_template_cvg_comparison_mismatch, [196](#)
- plot_template_cvg_comparison_unstratified, [196](#)
- plot_template_cvg_mismatches, [197](#)
- plot_template_cvg_unstratified, [197](#)
- plot_template_structure, [198](#)
- pos.to.range, [198](#)
- predict_coverage, [199](#)
- prefilter.primer.candidates, [200](#)
- prepare.constraint.plot, [200](#)
- prepare.dimer.seqs, [201](#)
- prepare_mm_plot, [201](#)
- prepare_template_cvg_mm_data, [202](#)
- primer.binding.regions.data, [202](#)
- primer.coverage.for.groups, [203](#)
- primer.set.parameter.stats, [204](#)
- rbind.primer.data, [212](#)
- rbind.Primers, [213](#)
- rbind.Templates, [213](#)
- read.leaders, [214](#)
- read.secondary.structure.raw, [214](#)
- read.sequences, [215](#)
- read_primers.internal, [215](#)
- read_primers_csv, [216](#)
- read_primers_multiple, [216](#)
- read_templates_csv, [217](#)
- read_templates_fasta, [218](#)
- read_templates_multiple, [219](#)
- read_templates_single, [220](#)
- relax.constraints, [221](#)
- relax.opti.constraints, [222](#)
- remove.redundant.cols, [223](#)
- remove.seqs.by.keyword, [223](#)
- rename.constraint.options, [224](#)

- render_report, 224
- reorder.primer.table, 225
- restriction_ali, 225
- restriction_hits, 226
- restriction_match, 226
- retrieve.leader.region, 227
- rev.comp.sequence, 227
- rev.sequence, 228
- sanitize_path, 229
- score.conservations, 230
- select.allowed.binding.events, 232
- select.best.ILP, 233
- select.best.opti.result, 233
- select.best.primer.idx, 234
- select.best.primer.set, 235
- select.binding.events, 235
- select.constraints, 236
- select.min.cross.idx, 236
- select.primer.region.by.conservations, 237
- select.primers.by.cvg, 238
- select_best_binding, 239
- selenium.installed, 240
- set.new.constraint.value, 240
- set.new.limits, 241
- shannon.entropy, 251
- solve.ILP, 251
- split_str_by_index, 252
- stats_plot_data, 253
- store.filtering.sets, 253
- string.list.format, 254
- string.list.format.total, 254
- string.to.IQR, 255
- subset.ILP, 255
- ungap_sequence, 258
- unify.leaders, 259
- update.binding.ranges.by.conservations, 259
- update.binding.regions, 260
- update.constraint.values, 261
- update.cvg.data, 261
- update.individual.binding.region, 262
- update.opti.results, 263
- update_primer_binding_regions, 263
- update_primer_cvg, 264
- validate_primers, 264
- validate_templates, 265
- view.cvg.primers, 265
- view.dimer.df, 266
- view.input.primers, 266
- view.primers, 267
- view.primers.report, 267
- visualize.all.results, 268
- visualize.filtering.results, 269
- were.constraints.relaxed, 270
- write.out.primer.info, 270
- xmlToChar, 271
- * **in**
compute.Tm.sets, 69
- * **is**
compute.Tm.sets, 69
- * **list(primers.fw)**
compute.Tm.sets, 69
- * **list**
compute.Tm.sets, 69
- * **melting**
compute.Tm.sets, 69
- * **of**
compute.Tm.sets, 69
- * **optimization**
compute.Tm.sets, 69
- * **otherwise.**
check.init.primer.length, 35
- * **primers**
compute.Tm.sets, 69
- * **primer**
compute.Tm.sets, 69
- * **provided.**
compute.Tm.sets, 69
- * **reverse**
compute.Tm.sets, 69
- * **run**
compute.Tm.sets, 69
- * **second**
compute.Tm.sets, 69
- * **settings functions**
Settings, 241
- * **temperature-dependent**
compute.Tm.sets, 69
- * **temperatures**
compute.Tm.sets, 69
- * **templates**
Plots, 176
- * **their**
compute.Tm.sets, 69

- * **this**
 - compute.Tm.sets, 69
- * **to**
 - compute.Tm.sets, 69
- * **with**
 - compute.Tm.sets, 69
- [,Primers,ANY-method
 - (cbind2,Primers,ANY-method), 31
- [,Primers-method
 - (cbind2,Primers,ANY-method), 31
- [,Templates,ANY-method
 - (cbind2,Templates,ANY-method), 32
- [,Templates-method
 - (cbind2,Templates,ANY-method), 32
- \$<-,Primers-method
 - (cbind2,Primers,ANY-method), 31
- \$<-,Templates-method
 - (cbind2,Templates,ANY-method), 32
- AbstractConstraintSettings
 - (AbstractConstraintSettings-class), 11
- AbstractConstraintSettings-class, 11
- add.coverage.constraints, 11
- add.dimerization.constraints, 12
- add.uniform.leaders.to.seqs, 12
- adjust.ORF.start, 13
- adjust_binding_regions
 - (TemplatesFunctions), 256
- align.seqs, 13
- align.structures, 14
- AnalysisStats, 14
- ancestor_of, 17
- annealing.temp.rule.of.thumb, 17
- annotate.binding.events, 18
- apply.constraint, 18
- apply.constraint.list, 19
- assign_binding_regions, 146
- assign_binding_regions
 - (TemplatesFunctions), 256
- assign_binding_regions.character, 20
- assign_binding_regions.numeric, 21
- augment.primers.cvg, 22
- batchify, 22
- batchify.simple, 23
- batchify.temp, 23
- build.gain.df, 24
- build.ILP.df, 24
- build.tool.overview, 25
- build_leader_df, 26
- CalculateEfficiencyPCR, 59, 64
- call.melt, 26
- call.melt.single, 27
- cascaded.filter, 28
- cascaded.filter.quick, 29
- cbind.Primers, 30
- cbind.Templates, 31
- cbind2,Primers,ANY-method, 31
- cbind2,Templates,ANY-method, 32
- check.3prime.hexamers, 34
- check.3prime.mismatches, 34
- check.init.primers.length, 35
- check.init.primers.length.single, 36
- check.mutations, 36
- check.template.constraints, 37
- check.tool.function, 38
- check.tool.installation, 38
- check_constraint_settings_validity, 40
- check_constraints, 10, 44, 147
- check_constraints (PrimerEval), 208
- check_constraints_comparison, 39
- check_correspondence, 40
- check_cvg_constraints, 41
- check_interval, 42
- check_limit_value, 43
- check_limits, 42
- check_names, 43
- check_report_deps, 44
- check_restriction_sites (PrimerEval), 208
- check_restriction_sites_single, 44
- check_setting, 45
- check_settings_validity, 46
- classify_design_problem (PrimerDesign), 204
- combine.binding.events, 46
- combine.strings, 47
- comp, 47
- compare.constraints, 48
- comparison.cvg, 48
- comparison.stats.raw, 49
- complement.sequence, 49
- compute.all.cross.dimers, 50

- compute.all.cross.dimers.frontend, 51
- compute.all.cross.dimers.unfiltered, 52
- compute.all.primer.subsets.ILP, 53
- compute.all.self.dimers, 53
- compute.all.self.dimers.frontend, 54
- compute.basic.details, 55
- compute.constraints, 56
- compute.covered.Ta, 57
- compute.dimer.matrix, 58
- compute.efficiency, 59
- compute.empiric.melting.temp, 60
- compute.gc.ratio, 60
- compute.melting.temps, 61
- compute.melting.temps.thermo, 61
- compute.mismatch.table, 62
- compute.primer.efficiencies, 63
- compute.secondary.structures, 64
- compute.sodium.equivalent.conc, 65
- compute.structure.vienna, 66
- compute.Ta, 66
- compute.template.secondary.structures, 67
- compute.Tm.baldino, 68
- compute.Tm.sets, 69
- compute.unique.covered.idx, 71
- compute_annealing_temp, 71
- con_select, 77
- condition, 72
- conOptions, 10, 249
- conOptions (Settings), 241
- conOptions, DesignSettings-method (Settings), 241
- conOptions<- (Settings), 241
- conOptions<-, DesignSettings-method (Settings), 241
- consecutive.GC.count, 73
- constraintLimits, 10, 249
- constraintLimits (Settings), 241
- constraintLimits, DesignSettings-method (Settings), 241
- constraintLimits<- (Settings), 241
- constraintLimits<-, DesignSettings-method (Settings), 241
- ConstraintOptions, 243, 247
- ConstraintOptions (Settings), 241
- ConstraintOptions-class (Settings), 241
- constraints, 10, 249
- constraints (Settings), 241
- constraints, AbstractConstraintSettings-method (Settings), 241
- constraints, DesignSettings-method (Settings), 241
- constraints.to.df, 73
- constraints.xml.format, 74
- constraints<- (Settings), 241
- constraints<-, AbstractConstraintSettings, list-method (Settings), 241
- constraints<-, DesignSettings, list-method (Settings), 241
- constraints_to_unit, 74
- ConstraintSettings, 210, 244, 245
- ConstraintSettings (Settings), 241
- ConstraintSettings-class (Settings), 241
- convert.from.iupac, 75
- convert.PCR.units, 75
- convert.temperature, 76
- convert.to.iupac, 76
- copy.melt.config, 77
- CoverageConstraints, 166, 243, 244, 247
- CoverageConstraints (Settings), 241
- CoverageConstraints-class (Settings), 241
- covered.primers.to.ID.string, 78
- covered.seqs.to.ID.string, 78
- covered.seqs.to.idx, 79
- create.constraint.table, 79
- create.constraint.XML, 80
- create.cvg.text, 81
- create.G.matrix, 81
- create.initial.primer.set, 82
- create.k.mers, 83
- create.kmer, 83
- create.options.table, 84
- create.other.table, 84
- create.PCR.table, 85
- create.primer.ranges, 85
- create.primers.naive, 86
- create.primers.tree, 87
- create.Tm.brackets, 88
- create.uniform.leaders, 89
- create_coverage_xls (Output), 166
- create_fulfilled_counts, 89
- create_report, 10
- create_report (Output), 166
- create_report, list, list-method, 90

- create_report, Primers, Templates-method, 91
- cvg_constraints, 10, 249
- cvg_constraints (Settings), 241
- cvg_constraints, DesignSettings-method (Settings), 241
- cvg_constraints<- (Settings), 241
- cvg_constraints<- , DesignSettings-method (Settings), 241
- Data, 92
- design_primers, 10, 241
- design_primers (PrimerDesign), 204
- design_primers.single, 93
- DesignSettings, 10, 41, 208, 211
- DesignSettings (Settings), 241
- DesignSettings-class (Settings), 241
- detect.gap.columns, 95
- dimerization.table, 96
- dir.copy, 96
- disambiguate.primers, 97
- estimate.cvg, 97
- estimate.cvg.dir, 98
- eval.comparison.primers, 98
- eval.constraints, 99
- evaluate.basic.cvg, 100
- evaluate.constrained.cvg, 101
- evaluate.cvg, 101
- evaluate.diff.primer.cvg, 102
- evaluate.fw.rev.combinations, 103
- evaluate.GC.clamp, 103
- evaluate.primer.cvg, 104
- evaluate.template.constraints, 104
- exclude.cols, 105
- feature.matrix (Data), 92
- filter.by.constraints, 106
- filter.comparison.primers, 106
- filter.primer.candidates, 107
- filter.primer.set.opti, 108
- filter_primers, 241
- filter_primers (PrimerEval), 208
- filter_primers.by.Tm.delta, 110
- filterLimits, 109
- filterLimits, DesignSettings-method (filterLimits), 109
- filters, 109
- filters, DesignSettings-method (filters), 109
- fix_constraint_boundaries, 110
- format.constraints, 111
- format.seq.ali, 111
- format.seqs.tex, 112
- get.3prime.mismatch.pos, 112
- get.analysis.mode, 113
- get.consensus.seq, 113
- get.constraint.value.idx, 114
- get.constraint.values, 114
- get.coverage.matrix, 115
- get.covered.templates, 115
- get.cross.dimers, 116
- get.cvg.constraint.settings, 116
- get.cvg.gain, 117
- get.delta.G, 118
- get.dimer.data, 119
- get.duplex.energies, 119
- get.eval.cols, 120
- get.extension, 121
- get.ILP.vars, 121
- get.init.file.name, 122
- get.leader.exon.regions, 123
- get.leader.exon.regions.single, 123
- get.matches, 124
- get.melting.temp.diff, 124
- get.merge.idx, 125
- get.missing.df, 125
- get.ORFs, 126
- get.other.constraint.settings, 126
- get.PCR.settings, 127
- get.plot.height, 128
- get.primer.binding.idx, 128
- get.primer.identifier.string, 129
- get.redundant.cols, 130
- get.relative.binding.pos, 130
- get.run.names, 131
- get.self.dimers, 131
- get.sets.from.decisions, 132
- get.static.tool.info, 132
- get.tree.seqs, 133
- get.unlist.idx, 133
- get_comparison_table (AnalysisStats), 14
- get_constraint_deviation_data, 134
- get_covered.vanilla, 134
- get_cvg_ratio (AnalysisStats), 14
- get_cvg_stats, 10

- get_cvg_stats (AnalysisStats), 14
- get_cvg_stats, list-method, 135
- get_cvg_stats, Primers-method, 136
- get_cvg_stats_primer (AnalysisStats), 14
- get_initial_primers (PrimerDesign), 204
- get_max_set_coverage, 137
- get_plot_primer_data, 137
- get_primer_cvg_mm_plot_df, 138
- get_report_fname, 139
- get_template_cvg_data, 139

- hclust.tree, 140
- highlight.mismatch, 140
- html.format.structure, 141

- I.cvg, 141
- ILPConstrained, 142
- initialize.primer.set, 142
- Input, 143
- insert_str, 149
- interleave, 149

- J.cvg, 150
- joule.to.cal, 150

- listToXml, 151

- merge.ambig.primers, 151
- merge.binding.information, 152
- merge.primer.entries, 153
- merge.primer.entries.single, 153
- merge.select, 154
- merge.template.decisions, 154
- mismatch.info, 155
- mismatch.mutation.check, 155
- mismatch.string.to.list, 156
- modify.col.rep, 156
- my.disambiguate, 157
- my.error, 157
- my.read.fasta, 158
- my.warning, 158
- my_ggsave, 159
- my_rbind, 159

- nbr.of.repeats, 160
- nbr.of.runs, 160

- openPrimerR (openPrimerR-package), 10
- openPrimerR-package, 10
- opti, 161
 - opti, DesignSettings-method (opti), 161
 - optiLimits, 161
 - optiLimits, DesignSettings-method (optiLimits), 161
 - optimize.ILP, 162
 - optimize.primer.cvg, 163
 - optimize.template.binding.regions.dir, 164
 - optimize.template.binding.regions.single, 165
 - Output, 166
 - pair_primers, 168
 - parallel_setup (Settings), 241
 - parse.constraints, 169
 - parse.header, 169
 - parse.IMGT.gene.groups, 170
 - parse.oligo.results, 170
 - PCR, 10, 249
 - PCR (Settings), 241
 - PCR, DesignSettings-method (Settings), 241
 - PCR<- (Settings), 241
 - PCR<- , DesignSettings-method (Settings), 241
 - PCR_Conditions, 244
 - PCR_Conditions (Settings), 241
 - PCR_Conditions-class (Settings), 241
 - plot.all.cvg.info, 171
 - plot.all.filtering.stats, 172
 - plot.Delta.DeltaG, 173
 - plot.dimer.dist, 173
 - plot.excluded.hist, 174
 - plot.filtering.runtime, 174
 - plot.filtering.stats, 175
 - plot.filtering.stats.cvg, 175
 - plot_conservation (Plots), 176
 - plot_constraint (Plots), 176
 - plot_constraint, list-method, 182
 - plot_constraint, Primers-method, 182
 - plot_constraint.histogram, 183
 - plot_constraint.histogram.nbr.mismatches, 184
 - plot_constraint.histogram.primer efficiencies, 184
 - plot_constraint_deviation, 10
 - plot_constraint_deviation (Plots), 176
 - plot_constraint_deviation, list-method, 185

- `plot_constraint_deviation`, Primers-method, 185
- `plot_constraint_fulfillment` (Plots), 176
- `plot_constraint_fulfillment`, list-method, 186
- `plot_constraint_fulfillment`, Primers-method, 187
- `plot_cvg_constraints` (Plots), 176
- `plot_cvg_constraints`, list-method, 187
- `plot_cvg_constraints`, Primers-method, 188
- `plot_cvg_vs_set_size` (Plots), 176
- `plot_penalty_vs_set_size` (Plots), 176
- `plot_primer` (Plots), 176
- `plot_primer.comparison.box`, 189
- `plot_primer.comparison.mismatches`, 190
- `plot_primer_binding_regions` (Plots), 176
- `plot_primer_binding_regions`, list, list-method, 190
- `plot_primer_binding_regions`, Primers, Templates-method, 191
- `plot_primer_cvg` (Plots), 176
- `plot_primer_cvg`, list, list-method, 192
- `plot_primer_cvg`, Primers, Templates-method, 193
- `plot_primer_cvg_mismatches`, 193
- `plot_primer_cvg_unstratified`, 194
- `plot_primer_subsets` (Plots), 176
- `plot_template_cvg` (Plots), 176
- `plot_template_cvg`, list, list-method, 195
- `plot_template_cvg`, Primers, Templates-method, 195
- `plot_template_cvg_comparison_mismatch`, 196
- `plot_template_cvg_comparison_unstratified`, 196
- `plot_template_cvg_mismatches`, 197
- `plot_template_cvg_unstratified`, 197
- `plot_template_structure`, 198
- Plots, 176
- `pos.to.range`, 198
- `predict_coverage`, 199
- `prefilter.primer.candidates`, 200
- `prepare.constraint.plot`, 200
- `prepare.dimer.seqs`, 201
- `prepare_mm_plot`, 201
- `prepare_template_cvg_mm_data`, 202
- `primer.binding.regions.data`, 202
- `primer.coverage.for.groups`, 203
- `primer.data` (Data), 92
- `primer.df` (Data), 92
- `primer.set.parameter.stats`, 204
- `primer_significance`, 178
- `primer_significance` (PrimerEval), 208
- PrimerDesign, 204
- PrimerEval, 208
- Primers, 146
- Primers (Input), 143
- Primers-class (Input), 143
- `rbind.primer.data`, 212
- `rbind.Primers`, 213
- `rbind.Templates`, 213
- `rbind2`, Primers, ANY-method (cbind2, Primers, ANY-method), 31
- `rbind2`, Templates, ANY-method (cbind2, Templates, ANY-method), 32
- `read.leaders`, 214
- `read.secondary.structure.raw`, 214
- `read.sequences`, 215
- `read_primers`, 10, 146
- `read_primers` (Input), 143
- `read_primers.internal`, 215
- `read_primers_csv`, 216
- `read_primers_multiple`, 216
- `read_settings`, 10, 249
- `read_settings` (Input), 143
- `read_templates`, 10
- `read_templates` (Input), 143
- `read_templates_csv`, 217
- `read_templates_fasta`, 218
- `read_templates_multiple`, 219
- `read_templates_single`, 220
- `ref.data` (Data), 92
- `RefCoverage` (Data), 92
- `relax.constraints`, 221
- `relax.opti.constraints`, 222
- `remove.redundant.cols`, 223
- `remove.seqs.by.keyword`, 223
- `rename.constraint.options`, 224
- `render_report`, 224
- `reorder.primer.table`, 225
- `restriction_ali`, 225
- `restriction_hits`, 226
- `restriction_match`, 226

retrieve.leader.region, 227
rev.comp.sequence, 227
rev.sequence, 228
runTutorial, 228

sanitize_path, 229
score.conservations, 230
score_conservation (Scoring), 230
score_degen (Scoring), 230
score_primers, 176
score_primers (Scoring), 230
Scoring, 230
select.allowed.binding.events, 232
select.best.ILP, 233
select.best.opti.result, 233
select.best.primer.idx, 234
select.best.primer.set, 235
select.binding.events, 235
select.constraints, 236
select.min.cross.idx, 236
select.primer.region.by.conservations, 237
select.primers.by.cvg, 238
select_best_binding, 239
select_regions_by_conservation (TemplatesFunctions), 256
selenium.installed, 240
set.new.constraint.value, 240
set.new.limits, 241
Settings, 241
settings (Data), 92
shannon.entropy, 251
solve.ILP, 251
split_str_by_index, 252
stats_plot_data, 253
store.filtering.sets, 253
string.list.format, 254
string.list.format.total, 254
string.to.IQR, 255
subset.ILP, 255
subset_primer_set, 179
subset_primer_set (PrimerEval), 208

template.data (Data), 92
template.df (Data), 92
Templates, 10, 146, 221
Templates (Input), 143
Templates-class (Input), 143
TemplatesFunctions, 256

Tiller (Data), 92
tiller.primer.df (Data), 92
tiller.settings (Data), 92
tiller.template.df (Data), 92

ungap_sequence, 258
unify.leaders, 259
update.binding.ranges.by.conservations, 259
update.binding.regions, 260
update.constraint.values, 261
update.cvg.data, 261
update.individual.binding.region, 262
update.opti.results, 263
update_primer_binding_regions, 263
update_primer_cvg, 264
update_template_cvg (TemplatesFunctions), 256

validate_primers, 264
validate_templates, 265
view.cvg.primers, 265
view.dimer.df, 266
view.input.primers, 266
view.primers, 267
view.primers.report, 267
visualize.all.results, 268
visualize.filtering.results, 269

were.constraints.relaxed, 270
write.out.primer.info, 270
write_primers (Output), 166
write_settings, 146, 249
write_settings (Output), 166
write_templates, 146, 221
write_templates (Output), 166

xmlToChar, 271