

# Package ‘ROI.plugin.optimx’

July 7, 2023

**Version** 1.0-1

**Title** 'optimx' Plug-in for the 'R' Optimization Infrastructure

**Description** Enhances the R Optimization Infrastructure ('ROI') package with the 'optimx' package.

**Imports** methods, stats, utils, ROI (>= 1.0-0), optimx

**Suggests** BB, ucminf, minqa, dfoptim, lbfgsb3c, lbfgs, subplex

**License** GPL-3

**URL** <https://roigrp.gitlab.io>,  
<https://gitlab.com/roigrp/solver/ROI.plugin.optimx>

**NeedsCompilation** no

**Author** Florian Schwendinger [aut, cre]

**Maintainer** Florian Schwendinger <FlorianSchwendinger@gmx.at>

**Repository** CRAN

**Date/Publication** 2023-07-06 23:30:06 UTC

## R topics documented:

Example-1 . . . . .	1
<b>Index</b>	<b>3</b>

---

Example-1	<i>Banana</i>
-----------	---------------

---

### Description

The following example is also known as Rosenbrock’s banana function ([https://en.wikipedia.org/wiki/Rosenbrock\\_function](https://en.wikipedia.org/wiki/Rosenbrock_function)).

$$\text{minimize } f(x) = 100(x_2 - x_1^2)^2 + (1 - x_1)^2$$

Solution: c(1, 1)

**Examples**

```
library(ROI)

f <- function(x) {
  return( 100 * (x[2] - x[1]^2)^2 + (1 - x[1])^2 )
}

f.gradient <- function(x) {
  return( c( -400 * x[1] * (x[2] - x[1] * x[1]) - 2 * (1 - x[1]),
            200 * (x[2] - x[1] * x[1])) )
}

x <- OP( objective = F_objective(f, n = 2L, G = f.gradient),
        bounds = V_bound(ld = -3, ud = 3, nobj = 2L) )

nlp <- ROI_solve(x, solver="optimx", start=c(-1.2, 1), method = "Rvmmin")
nlp
## Optimal solution found.
## The objective value is: 4.979684e-30
solution(nlp)
## [1] 1 1
```

# Index

Example-1, 1