

Package ‘box.linters’

June 7, 2024

Title Linters for 'box' Modules

Version 0.9.1

Description Static code analysis of 'box' modules.

The package enhances code quality by providing linters that check for common issues, enforce best practices, and ensure consistent coding standards.

URL <https://appslon.github.io/box.linters/>,

<https://github.com/Appslon/box.linters>

License LGPL-3

Encoding UTF-8

RoxygenNote 7.3.1

Depends R (>= 2.10)

Imports cli, fs, glue, lintr (>= 3.0.0), rlang, stringr, xml2,
xmlparsedata

Suggests box, covr, dplyr, knitr, rcmdcheck, rmarkdown, R6, rex,
rhino, shiny, spelling, testthat (>= 3.0.0), withr,

Config/testthat/edition 3

Config/testthat/parallel true

Language en-US

NeedsCompilation no

Author Ricardo Rodrigo Basa [aut, cre],
Jakub Nowicki [aut],
Appslon Sp. z o.o. [cph]

Maintainer Ricardo Rodrigo Basa <opensource+rodrigo@appslon.com>

Repository CRAN

Date/Publication 2024-06-04 09:50:39 UTC

Contents

box_alpha alphabetical_calls_linter	2
box_default_linters	4
box_func_import_count_linter	4
box_mod_fun_exists_linter	5
box_pkg_fun_exists_linter	6
box_separate_calls_linter	7
box_trailing_commas_linter	8
box_universal_import_linter	9
box_unused_attached_mod_linter	10
box_unused_attached_pkg_linter	11
box_unused_att_mod_obj_linter	13
box_unused_att_pkg_fun_linter	14
box_usage_linter	15
r6_usage_linter	16
rhino_default_linters	18
unused_declared_object_linter	19
use_box_lintr	20

Index

21

box_alpha alphabetical_calls_linter

box library alphabetical module and function imports linter

Description

Checks that module and function imports are sorted alphabetically. Aliases are ignored. The sort check is on package/module names and attached function names.

Usage

```
box_alpha alphabetical_calls_linter()
```

Details

For use in rhino, see the [Explanation: Rhino style guide](#) to learn about the details.

Value

A custom linter function for use with r-lib/lintr.

Examples

```
# will produce lints
lintr::lint(
  text = "box::use(packageB, packageA)",
  linters = box_alpha_betical_calls_linter()
)

lintr::lint(
  text = "box::use(package,functionB, functionA)",
  linters = box_alpha_betical_calls_linter()
)

lintr::lint(
  text = "box::use(path/to/B, path/to/A)",
  linters = box_alpha_betical_calls_linter()
)

lintr::lint(
  text = "box::use(path/to/A,functionB, functionA)",
  linters = box_alpha_betical_calls_linter()
)

lintr::lint(
  text = "box::use(path/to/A[alias = functionB, functionA])",
  linters = box_alpha_betical_calls_linter()
)

# okay
lintr::lint(
  text = "box::use(packageA, packageB)",
  linters = box_alpha_betical_calls_linter()
)

lintr::lint(
  text = "box::use(package,functionA, functionB)",
  linters = box_alpha_betical_calls_linter()
)

lintr::lint(
  text = "box::use(path/to/A, path/to/B)",
  linters = box_alpha_betical_calls_linter()
)

lintr::lint(
  text = "box::use(path/to/A,functionA, functionB)",
  linters = box_alpha_betical_calls_linter()
)

lintr::lint(
  text = "box::use(path/to/A,functionA, alias = functionB)",
  linters = box_alpha_betical_calls_linter()
)
```

`box_default_linters` *Box-compatible default linters*

Description

A replacement for `lintr::object_usage_linter()` that works with box modules.

Usage

```
box_default_linters
```

Format

An object of class `list` of length 33.

Examples

```
linters <- lintr::linters_with_defaults(defaults = box.linters::box_default_linters)  
names(linters)
```

`box_func_import_count_linter`
 box library function import count linter

Description

Checks that function imports do not exceed the defined `max`.

Usage

```
box_func_import_count_linter(max = 8L)
```

Arguments

`max` Maximum function imports allowed between [and]. Defaults to 8.

Details

For use in rhino, see the [Explanation: Rhino style guide](#) to learn about the details.

Value

A custom linter function for use with `r-lib/lintr`.

Examples

```
# will produce lints
lintr::lint(
  text = "box::use(package[one, two, three, four, five, six, seven, eight, nine])",
  linters = box_func_import_count_linter()
)

lintr::lint(
  text = "box::use(package[one, two, three, four])",
  linters = box_func_import_count_linter(3)
)

# okay
lintr::lint(
  text = "box::use(package[one, two, three, four, five])",
  linters = box_func_import_count_linter()
)

lintr::lint(
  text = "box::use(package[one, two, three])",
  linters = box_func_import_count_linter(3)
)
```

box_mod_fun_exists_linter

*box library attached function exists and exported by called module
linter*

Description

Checks that functions being attached exist and are exported by the local module being called.

Usage

```
box_mod_fun_exists_linter()
```

Details

For use in rhino, see the [Explanation: Rhino style guide](#) to learn about the details.

Value

A custom linter function for use with r-lib/lintr

Examples

```
## Not run:
## will produce lint
lintr::lint(
  text = "box::use(path/to/module_a[function_not_exists],)",
  linter = box_mod_fun_exists_linter()
)

# okay
lintr::lint(
  text = "box::use(path/to/module_a[function_exists],)",
  linter = box_mod_fun_exists_linter()
)

## End(Not run)
```

box_pkg_fun_exists_linter

box library attached function exists and exported by package linter

Description

Checks that functions being attached exist and are exported by the package/library being called.

Usage

```
box_pkg_fun_exists_linter()
```

Details

For use in rhino, see the [Explanation: Rhino style guide](#) to learn about the details.

Value

A custom linter function for use with r-lib/lintr

Examples

```
# will produce lint
lintr::lint(
  text = "box::use(stringr,function_not_exists),",
  linter = box_pkg_fun_exists_linter()
)

# okay
lintr::lint(
  text = "box::use(stringr,str_pad),",
  linter = box_pkg_fun_exists_linter()
)
```

box_separate_calls_linter

box library separate packages and module imports linter

Description

Checks that packages and modules are imported in separate box::use() statements.

Usage

```
box_separate_calls_linter()
```

Details

For use in rhino, see the [Explanation: Rhino style guide](#) to learn about the details.

Value

A custom linter function for use with r-lib/lintr

Examples

```
# will produce lints
lintr::lint(
  text = "box::use(package, path/to/file)",
  linters = box_separate_calls_linter()
)

lintr::lint(
  text = "box::use(path/to/file, package)",
  linters = box_separate_calls_linter()
)

# okay
lintr::lint(
  text = "box::use(package1, package2)
        box::use(path/to/file1, path/to/file2)",
  linters = box_separate_calls_linter()
)
```

`box_trailing_commas_linter`
box library trailing commas linter

Description

Checks that all `box::use` imports have a trailing comma. This applies to package or module imports between `(` and `)`, and, optionally, function imports between `[` and `]`. Take note that `lintr::commas_linter()` may come into play.

Usage

```
box_trailing_commas_linter(check_functions = FALSE)
```

Arguments

`check_functions`
 Boolean flag to include function imports between `[` and `]`. Defaults to FALSE.

Details

For use in rhino, see the [Explanation: Rhino style guide](#) to learn about the details.

Value

A custom linter function for use with `r-lib/lintr`

Examples

```
# will produce lints
lintr::lint(
  text = "box::use(base, rlang)",
  linters = box_trailing_commas_linter()
)

lintr::lint(
  text = "box::use(
    dplyr[select, mutate]
  )",
  linters = box_trailing_commas_linter()
)

# okay
lintr::lint(
  text = "box::use(base, rlang, )",
  linters = box_trailing_commas_linter()
)

lintr::lint(
```

```
text = "box::use(  
  dplyr[select, mutate],  
)",  
linters = box_trailing_commas_linter()  
)
```

```
box_universal_import_linter  
  box library universal import linter
```

Description

Checks that all function imports are explicit. package[...] is not used.

Usage

```
box_universal_import_linter()
```

Details

For use in rhino, see the [Explanation: Rhino style guide](#) to learn about the details.

Value

A custom linter function for use with r-lib/lintr

Examples

```
# will produce lints  
lintr::lint(  
  text = "box::use(base[...])",  
  linters = box_universal_import_linter()  
)  
  
lintr::lint(  
  text = "box::use(path/to/file[...])",  
  linters = box_universal_import_linter()  
)  
  
# okay  
lintr::lint(  
  text = "box::use(base[print])",  
  linters = box_universal_import_linter()  
)  
  
lintr::lint(  
  text = "box::use(path/to/file[do_something])",  
  linters = box_universal_import_linter()  
)
```

```
box_unused_attached_mod_linter
    box library unused attached module linter
```

Description

Checks that all attached modules are used within the source file. This also covers modules attached using the

Usage

```
box_unused_attached_mod_linter()
```

Details

For use in rhino, see the [Explanation: Rhino style guide](#) to learn about the details.

Value

A custom linter function for use with `r-lib/lintr`.

Examples

```
## Not run:
# will produce lints
code <- "
box::use(
  path/to/module
)
"

lintr::lint(code, linters = box_unused_attached_mod_linter())

code <- "
box::use(
  alias = path/to/module
)
"

lintr::lint(code, linters = box_unused_attached_mod_linter())

code <- "
box::use(
  path/to/module[...]
)
"

lintr::lint(code, linters = box_unused_attached_mod_linter())

# okay
```

```

code <- "
box::use(
  path/to/module
)

module$some_function()
"

lintr::lint(code, linters = box_unused_attached_mod_linter())

code <- "
box::use(
  alias = path/to/module
)

alias$some_function()
"

lintr::lint(code, linters = box_unused_attached_mod_linter())

code <- "
box::use(
  path/to/module[...]      # module exports some_function()
)
some_function()
"

lintr::lint(code, linters = box_unused_attached_mod_linter())

## End(Not run)

```

box_unused_attached_pkg_linter
box library unused attached package linter

Description

Checks that all attached packages are used within the source file. This also covers packages attached using the . . .

Usage

```
box_unused_attached_pkg_linter()
```

Details

For use in `rhino`, see the [Explanation: Rhino style guide](#) to learn about the details.

Value

A custom linter function for use with *r-lib/lintr*.

Examples

```
# will produce lints
code <- "
box::use(
  stringr
)
"

lintr::lint(text = code, linters = box_unused_attached_pkg_linter())

code <- "
box::use(
  alias = stringr
)
"

lintr::lint(text = code, linters = box_unused_attached_pkg_linter())

code <- "
box::use(
  stringr[...]
)
"

lintr::lint(text = code, linters = box_unused_attached_pkg_linter())

# okay
code <- "
box::use(
  stringr
)

stringr$str_pad()
"

lintr::lint(text = code, linters = box_unused_attached_pkg_linter())

code <- "
box::use(
  alias = stringr
)

alias$str_pad()
"

lintr::lint(text = code, linters = box_unused_attached_pkg_linter())

code <- "
```

```
box::use(  
  stringr[...]  
)  
  
str_pad()  
"  
  
lintr::lint(text = code, linters = box_unused_attached_pkg_linter())
```

box_unused_att_mod_obj_linter

box library unused attached module object linter

Description

Checks that all attached module functions and data objects are used within the source file.

Usage

```
box_unused_att_mod_obj_linter()
```

Details

For use in rhino, see the [Explanation: Rhino style guide](#) to learn about the details.

Value

A custom linter function for use with r-lib/lintr.

Examples

```
## Not run:  
# will produce lints  
code <- "  
box::use(  
  path/to/module[some_function, some_object],  
)  
"  
  
lintr::lint(text = code, linters = box_unused_att_mod_obj_linter())  
  
code <- "  
box::use(  
  path/to/module[alias_func = some_function, alias_obj = some_object],  
)  
"  
  
lintr::lint(text = code, linters = box_unused_att_mod_obj_linter())
```

```

# okay
code <- "
box::use(
  path/to/module[some_function, some_object],
)

x <- sum(some_object)
some_function()
"

lintr::lint(text = code, linters = box_unused_att_mod_obj_linter())

code <- "
box::use(
  path/to/module[alias_func = some_function, alias_obj = some_object],
)

x <- sum(alias_obj)
alias_func()
"

lintr::lint(text = code, linters = box_unused_att_mod_obj_linter())

## End(Not run)

```

box_unused_att_pkg_fun_linter
box library unused attached package function linter

Description

Checks that all attached package functions are used within the source file.

Usage

```
box_unused_att_pkg_fun_linter()
```

Details

For use in `rhino`, see the [Explanation: Rhino style guide](#) to learn about the details.

Value

A custom linter function for use with `r-lib/lintr`.

Examples

```
# will produce lints
code <- "
box::use(
  stringr[str_pad],
)
"

lintr::lint(text = code, linters = box_unused_att_pkg_fun_linter())

code <- "
box::use(
  stringr[alias_func = str_pad],
)
"

lintr::lint(text = code, linters = box_unused_att_pkg_fun_linter())

# okay
code <- "
box::use(
  stringr[str_pad],
)
str_pad()
"

lintr::lint(text = code, linters = box_unused_att_pkg_fun_linter())

code <- "
box::use(
  stringr[alias_func = str_pad],
)
alias_func()
"

lintr::lint(text = code, linters = box_unused_att_pkg_fun_linter())
```

`box_usage_linter`

`box library-aware object usage linter`

Description

Checks that all function and data object calls made within a source file are valid. There are three ways for functions and data object calls to be come "valid". First is via base R packages. Second is via local declaration/definition. The third is via `box::use()` attachment.

Usage

```
box_usage_linter()
```

Details

For use in `rhino`, see the [Explanation: Rhino style guide](#) to learn about the details.

Value

A custom linter function for use with `r-lib/lintr`.

Examples

```
## Not run:
box::use(
  dplyr[`%>%`, filter, pull],
  stringr,
)

mpg <- mtcars %>%
  filter(mpg <= 10) %>%
  pull(mpg)

mpg <- mtcars %>%
  filter(mpg <= 10) %>%
  select(mpg)           # will lint

trimmed_string <- stringr$str_trim(" some string ")
trimmed_string <- stringr$strtrim(" some string ")      # will lint

existing_function <- function(x, y, z) {
  mean(c(x, y, z))
}

existing_function(1, 2, 3)
non_existing_function(1, 2, 3)    # will lint

average(1, 2, 3)      # will lint

## End(Not run)
```

Description

Checks method and attribute calls within an R6 class. Covers public, private, and active objects. All internal calls should exist. All private methods and attributes should be used.

Usage

```
r6_usage_linter()
```

Details

For use in `rhino`, see the [Explanation: Rhino style guide](#) to learn about the details.

Value

A custom linter function for use with `r-lib/lintr`.

Examples

```
# will produce lints
code = "
box::use(
  R6[R6Class],
)

badClass <- R6Class('badClass',
  public = list(
    initialize = function() {
      private$not_exists()
    }
  ),
  private = list(
    unused_attribute = 'private data',
    unused_method = function() {
      self$attribute_not_exists
      self$function_not_exists()
    }
  )
)
"

lintr::lint(
  text = code,
  linters = r6_usage_linter()
)

# okay
code = "
box::use(
  R6[R6Class],
)

goodClass <- R6Class('goodClass',
  public = list(
    public_attr = NULL,
    initialize = function() {
      private$private_func()
    },
  )
)"
```

```

some_function = function () {
  private$private_attr
}
),
private = list(
  private_attr = 'private data',
  private_func = function() {
    self$public_attr
  }
)
"
)

lintr::lint(
  text = code,
  linters = r6_usage_linter()
)

```

rhino_default_linters *Rhino default linters*

Description

See the [Explanation: Rhino style guide](#) to learn about the details.

Usage

```
rhino_default_linters
```

Format

An object of class list of length 38.

Examples

```

lintrs <- lintr::linters_with_defaults(defaults = box.linters::rhino_default_linters)

names(lintrs)
```

unused_declared_object_linter
Unused declared function and data objects linter

Description

Checks that all defined/declared functions and data objects are used within the source file. Functions and data objects that are marked with @export are ignored.

Usage

```
unused_declared_object_linter()
```

Details

For use in rhino, see the [Explanation: Rhino style guide](#) to learn about the details.

Value

A custom linter function for use with r-lib/lintr.

Examples

```
# will produce lint
code <- "
#' @export
public_function <- function() {

}

private_function <- function() {

}

local_data <- \"A\"
"

lintr::lint(text = code, linters = unused_declared_object_linter())

# okay
code <- "
#' @export
public_function <- function() {
  some_variable <- local_data
  private_function()
}

private_function <- function() {

}
```

```
local_data <- \"A\"
"
lintr::lint(text = code, linters = unused_declared_object_linter())
```

use_box_lintr*Use lintr with box.linters in your project***Description**

Create a minimal lintr config file with box modules support as a starting point for customization

Usage

```
use_box_lintr(path = ".", type = c("basic_box", "rhino"))
```

Arguments

path	Path to project root where a .lintr file should be created. If the .lintr file already exists, an error will be thrown.
type	The kind of configuration to create <ul style="list-style-type: none"> • basic_box creates a minimal lintr config based on the tidyverse configuration of lintr. This starts with lintr::linters_with_defaults() and is customized for box module compatibility • rhino creates a lintr config based on the Rhino style guide

Value

Path to the generated configuration, invisibly.

Examples

```
## Not run:
# use default box-compatible set of linters
box.linters::use_box_lintr()

# use `rhino` set of linters
box.linters::use_box_lintr(type = "rhino")

## End(Not run)
```

Index

* datasets

 box_default_linters, [4](#)
 rhino_default_linters, [18](#)

 box_alphabetical_calls_linter, [2](#)
 box_default_linters, [4](#)
 box_func_import_count_linter, [4](#)
 box_mod_fun_exists_linter, [5](#)
 box_pkg_fun_exists_linter, [6](#)
 box_separate_calls_linter, [7](#)
 box_trailing_commas_linter, [8](#)
 box_universal_import_linter, [9](#)
 box_unused_att_mod_obj_linter, [13](#)
 box_unused_att_pkg_fun_linter, [14](#)
 box_unused_attached_mod_linter, [10](#)
 box_unused_attached_pkg_linter, [11](#)
 box_usage_linter, [15](#)

 r6_usage_linter, [16](#)
 rhino_default_linters, [18](#)

 unused_declared_object_linter, [19](#)
 use_box_lintr, [20](#)