

# Package ‘shroomDK’

January 10, 2024

**Type** Package

**Title** Accessing the Flipside Crypto ShroomDK API

**Version** 0.3.0

**Author** Carlos Mercado

**Maintainer** Carlos Mercado <carlos.mercado@flipsidecrypto.com>

**Description** Programmatic access to Flipside Crypto data via the Compass RPC API: <<https://api-docs.flipsidecrypto.xyz/>>. As simple as `auto_paginate_query()` but with core functions as needed for troubleshooting. Note, 0.1.1 support deprecated 2023-05-31.

**Imports** jsonlite, httr

**License** MIT + file LICENSE

**Encoding** UTF-8

**RoxygenNote** 7.2.1

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2024-01-10 15:50:02 UTC

## R topics documented:

auto_paginate_query . . . . .	2
cancel_query . . . . .	3
clean_query . . . . .	4
create_query_token . . . . .	4
get_query_from_token . . . . .	6
get_query_status . . . . .	7
<b>Index</b>	<b>8</b>

---

auto\_paginate\_query    *Auto Paginate Queries*

---

### Description

Intelligently grab up to 1 Gigabyte of data from a SQL query including automatic pagination and cleaning.

### Usage

```
auto_paginate_query(
  query,
  api_key,
  page_size = 25000,
  page_count = NULL,
  data_source = "snowflake-default",
  data_provider = "flipside",
  api_url = "https://api-v2.flipsidecrypto.xyz/json-rpc"
)
```

### Arguments

query	The SQL query to pass to ShroomDK
api_key	ShroomDK API key.
page_size	Default 25,000. May return error if 'page_size' is too large (if page exceeds 30MB or entire query >1GB). Ignored if results fit on 1 page of < 15 Mb of data.
page_count	How many pages, of page_size rows each, to read. Default NULL calculates the ceiling (# rows in results / page_size). Ignored if results fit on 1 page of < 15 Mb of data.
data_source	Where data is sourced, including specific computation warehouse. Default "snowflake-default". Non default data sources may require registration of api_key to allowlist.
data_provider	Who provides data, Default "flipside". Non default data providers may require registration of api_key to allowlist.
api_url	default to https://api-v2.flipsidecrypto.xyz/json-rpc but upgradeable for user.

### Value

data frame of up to 'page\_size \* page\_count' rows, see ?clean\_query for more details on column classes.

**Examples**

```
## Not run:
pull_data <- auto_paginate_query("
SELECT * FROM ETHEREUM.CORE.FACT_TRANSACTIONS LIMIT 10001",
api_key = readLines("api_key.txt"),
page_size = 9000, # ends up ignored because results fit on 1 page.
page_count = NULL)

## End(Not run)
```

---

cancel_query	<i>Cancel Query</i>
--------------	---------------------

---

**Description**

Uses Flipside ShroomDK to CANCEL a query run id from 'create\_query\_token()', as the new API uses warehouse-seconds to charge users above the free tier, the ability to cancel is critical for cost management.

**Usage**

```
cancel_query(
  query_run_id,
  api_key,
  api_url = "https://api-v2.flipsidecrypto.xyz/json-rpc"
)
```

**Arguments**

query_run_id	queryRunId from 'create_query_token()', for token stored as 'x', use 'x\$result\$queryRequest\$queryRunId'
api_key	Flipside Crypto ShroomDK API Key
api_url	default to https://api-v2.flipsidecrypto.xyz/json-rpc but upgradeable for user.

**Value**

returns a list of the status\_canceled (TRUE or FALSE) and the cancel object (which includes related details).

**Examples**

```
## Not run:
query <- create_query_token("SELECT * FROM ETHEREUM.CORE.FACT_TRANSACTIONS LIMIT 1000000", api_key)
query_status <- get_query_status(query$result$queryRequest$queryRunId, api_key)
canceled <- cancel_query(query$result$queryRequest$queryRunId, api_key)

## End(Not run)
```

---

clean_query	<i>Clean Query</i>
-------------	--------------------

---

### Description

Converts query response to data frame while attempting to coerce classes intelligently.

### Usage

```
clean_query(request, try_simplify = TRUE)
```

### Arguments

request	The request output from <code>get_query_from_token()</code>
try_simplify	because requests can return JSON and may not have the same length across values, they may not be data frame compliant (all columns having the same number of rows). A key example would be TX_JSON in EVM FACT_TRANSACTION tables which include 50+ extra details from transaction logs. But other examples like NULLs in TO_ADDRESS can have similar issues. Default TRUE.

### Value

A data frame. If 'try\_simplify' is FALSE OR if 'try\_simplify' TRUE fails: the data frame is comprised of lists, where each column must be coerced to a desired class (e.g., with 'as.numeric()').

### Examples

```
## Not run:
query <- create_query_token("SELECT * FROM ETHEREUM.CORE.FACT_TRANSACTIONS LIMIT 1000", api_key)
request <- get_query_from_token(query$result$queryRequest$queryRunId, api_key)
df1 <- clean_query(request, try_simplify = TRUE)

## End(Not run)
```

---

create_query_token	<i>Create Query Token</i>
--------------------	---------------------------

---

### Description

Uses Flipside ShroomDK to create a Query Token to access Flipside Crypto data. The query token is kept 'ttl' hours and available for no-additional cost reads up to 'mam' minutes (i.e., cached to the same exact result). allowing for pagination and multiple requests before expending more daily request uses.

**Usage**

```

create_query_token(
  query,
  api_key,
  ttl = 1,
  mam = 10,
  data_source = "snowflake-default",
  data_provider = "flipside",
  api_url = "https://api-v2.flipsidecrypto.xyz/json-rpc"
)

```

**Arguments**

query	Flipside Crypto Snowflake SQL compatible query as a string.
api_key	Flipside Crypto ShroomDK API Key
ttl	time-to-live (in hours) to keep query results available. Default 1 hour.
mam	max-age-minutes, lifespan of cache. set to 0 to always re-execute. Default 10 minutes.
data_source	Where data is sourced, including specific computation warehouse. Default "snowflake-default". Non default data sources may require registration of api_key to allowlist.
data_provider	Who provides data, Default "flipside". Non default data providers may require registration of api_key to allowlist.
api_url	default to https://api-v2.flipsidecrypto.xyz/json-rpc but upgradeable for user.

**Value**

list of 'token' and 'cached' use 'token' in 'get\_query\_from\_token()'

**Examples**

```

## Not run:
create_query_token(
  query = "SELECT * FROM ethereum.core.fact_transactions LIMIT 33",
  api_key = readLines("api_key.txt"),
  ttl = 1,
  mam = 5
)

## End(Not run)

```

---

get\_query\_from\_token *Get Query From Token*

---

### Description

Uses Flipside ShroomDK to access a Query Token (Run ID). This function is for pagination and multiple requests. It is best suited for debugging and testing new queries. Consider `'auto_paginate_query()'` for queries already known to work as expected. Note: To reduce payload it returns a list of outputs (separating column names from rows). See `'clean_query()'` for converting result to a data frame.

### Usage

```
get_query_from_token(
  query_run_id,
  api_key,
  page_number = 1,
  page_size = 1000,
  result_format = "csv",
  api_url = "https://api-v2.flipsidecrypto.xyz/json-rpc"
)
```

### Arguments

query_run_id	queryRunId from <code>'create_query_token()'</code> , for token stored as 'x', use <code>'x\$result\$queryRequest\$queryRunId'</code>
api_key	Flipside Crypto ShroomDK API Key
page_number	Results are cached, max 30MB of data per page.
page_size	Default 1000. Paginate via page_number. May return error if page_size causes data to exceed 30MB.
result_format	Default to csv. Options: csv and json.
api_url	default to <code>https://api-v2.flipsidecrypto.xyz/json-rpc</code> but upgradeable for user.

### Value

returns a list of jsonrpc, id, and result. Within result are: columnNames, columnTypes, rows, page, sql, format, originalQueryRun, redirectedToQueryRun use `'clean_query()'` to transform this into a data frame.

### Examples

```
## Not run:
query <- create_query_token("SELECT * FROM ETHEREUM.CORE.FACT_TRANSACTIONS LIMIT 1000", api_key)
fact_transactions <- get_query_from_token(query$result$queryRequest$queryRunId, api_key, 1, 1000)

## End(Not run)
```

---

get_query_status	<i>Get Query ID Status</i>
------------------	----------------------------

---

### Description

Uses Flipside ShroomDK to access the status of a query run id from 'create\_query\_token()'

### Usage

```
get_query_status(  
  query_run_id,  
  api_key,  
  api_url = "https://api-v2.flipsidecrypto.xyz/json-rpc"  
)
```

### Arguments

query_run_id	queryRunId from 'create_query_token()', for token stored as 'x', use 'x\$result\$queryRequest\$queryRunId'
api_key	Flipside Crypto ShroomDK API Key
api_url	default to https://api-v2.flipsidecrypto.xyz/json-rpc but upgradeable for user.

### Value

returns request content; for content 'x', use 'x\$result\$queryRun\$state' and 'x\$result\$queryRun\$errorMessage'.  
Expect one of QUERY\_STATE\_READY, QUERY\_STATE\_RUNNING, QUERY\_STATE\_STREAMING\_RESULTS, QUERY\_STATE\_SUCCESS, QUERY\_STATE\_FAILED, QUERY\_STATE\_CANCELED

### Examples

```
## Not run:  
query = create_query_token("SELECT * FROM ETHEREUM.CORE.FACT_TRANSACTIONS LIMIT 10000", api_key)  
get_query_status(query$result$queryRequest$queryRunId, api_key)  
  
## End(Not run)
```

# Index

`auto_paginate_query`, 2

`cancel_query`, 3

`clean_query`, 4

`create_query_token`, 4

`get_query_from_token`, 6

`get_query_status`, 7