


Omni 56K USB *Lite*

Simple and Compact 56K Analog Modem with Powerful Data/Fax/Voice Features

Compact Lightning!!



ZyXEL's Omni 56K USB Lite is the ideal solution for dial-up Internet access. The Omni 56K USB Lite supports ITU V.90 protocol with the highest speed of 56Kbps and complies with most international standards. The "bus powered" feature eliminates the need of an external power supply, enhancing its compact and lightweight space saving design. With fast installation and easy configuration of the Omni 56K USB Lite, Internet access has never been easier than before.

Features

- ITU V.90 56Kbps downstream data transmission
- V.34 33.6Kbps data transmission rate
- Complies with USB 1.1 specification
- Automatic speed fall-back / fall-forward with fast rate negotiation
- Automatic Data / Fax call detection
- Voice digitization and compression
- Error correction & data compression
- Microsoft Windows 98 / 2000 / ME / XP compatible
- Distinctive Ring Detection

*USB hot plug and play for easy installation in Windows 98/2000/ME/XP environment.

ZyXEL
TOTAL INTERNET ACCESS SOLUTION

Corporate Headquarters
ZyXEL Communications Co.
Tel: +886-3-578-3942
Fax: +886-3-578-2439
Email: sales@zyxel.com.tw
support@zyxel.com.tw
http://www.zyxel.com
http://www.zyxel.com.tw

North America Headquarters
ZyXEL Communications, Inc.
Tel: +1-714-632-0882
Fax: +1-714-632-0858
Email: sales@zyxel.com
support@zyxel.com
http://www.zyxel.com

Denmark / Nordic Headquarters
ZyXEL Communications A/S
Tel: +45 39 55 07 00
Fax: +45 39 55 07 07
Email: sales@zyxel.dk
support@zyxel.dk
http://www.zyxel.dk

Germany
ZyXEL Deutschland GmbH.
Tel: +49 2405 6909-0
Fax: +49 2405 6909-99
Email: sales@zyxel.de
support@zyxel.de
http://www.zyxel.de

Austria
ZyXEL Communications Services GmbH.
Tel: +43-1-494 86 77-0
Fax: +43-1-494 86 78
Email: sales@zyxel.at
support@zyxel.at
http://www.zyxel.at

Malaysia
ZyXEL Communications Co. (M) Sdn Bhd
Tel: 603-795-44-688
Fax: 603-795-34-407
Email: sales@zyxel.com.my
support@zyxel.com.my
http://www.zyxel.com.my

Specifications

Technical Specifications

- Operation Modes: Auto-dial/Auto Answer, Originate/Answer
- Command Set: Full AT command set, Extended AT command set
- Dialing Type: Tone/Pulse dialing
- Flow Control: Software XON/XOFF, Hardware RTS/CTS
- Configuration Settings: Software programmable (with non-volatile memory storage, 2 user profiles)
- Line Type: twisted pair dial-up line
- Diagnostics: V.54 Loopback, Line Condition Reporting LED Status Indicators: USB, OH

USB Features

- Complies with USB 1.1 specification at 12Mbps full speed
- Power management: Bus-powered, suspend mode

Standards and Protocols supported

- Error Control: V.42/MNP 3-4
- Data Compression: V.42bis/MNP 5

Data Compatibility

- V.90 56K down-stream data transmission
- Modulation mode: V.90, V.34, V.32bis, V.32, V.23, V.22bis, V.22, V.21, Bell 212A, Bell 103
- On-line line condition monitoring

Fax Compatibility

- G3 Fax send/receive
- V.17 (7.2Kbps to 14.4Kbps)
- V.29 (7.2Kbps to 9.6Kbps)
- V.27ter (2.4Kbps to 4.8Kbps)

Physical Interface

- One RJ-11 interface for phone connection
- One RJ-11 interface for line connection
- One USB interface for computer connection
- Dimensions: 75mm(W) x 100mm(D) x 25mm(H)
- Weight: 102 g

System Requirements

- IBM compatible PC
- 56K compatible local analog phone line
- V.90 56K ITU standard capable service provider

Operating Environment

- Temperature: 0 °C to 40 °C
- Humidity: 5 to 90 %

2-Year Limited Warranty

